



STATE OF WASHINGTON
DEPARTMENT OF ECOLOGY

PO Box 47600 • Olympia, WA 98504-7600 • 360-407-6000
711 for Washington Relay Service • Persons with a speech disability can call 877-833-6341

July 23, 2020

Susan Poulosom, Manager
NPDES Permits Unit
United States Environmental Protection Agency - Region 10
1200 Sixth Avenue, Suite 155, OWW
Seattle, WA 98101

**RE: Clean Water Act Section 401 Final Certification for
EPA National Pollutant Discharge Elimination System
Multi-Sector General Permit**

Dear Susan Poulosom:

This letter is in response to the U.S. Environmental Protection Agency's (EPA) letter, received May 27, 2020, requesting Washington State Department of Ecology (Ecology) provide a Clean Water Act Section 401 Certification for the Final National Pollutant Discharge Elimination System (NPDES) Permit for EPA's Multi Sector General Permit.

With this Section 401 Water Quality Certification, Ecology certifies NPDES Permit with conditions as found in Order No.18218. The Enclosed Order may be appealed by following the procedures described in the Order.

If you have any questions or would like to discuss these matters further, please contact Travis Porter at travis.porter@ecy.wa.gov or (360) 407-6127.

Sincerely,

A handwritten signature in black ink, reading "Jeff Killelea".

Jeff Killelea
Program Development Services Section Manager (Acting)
Water Quality Program

Enclosure

cc: Margaret McCauley, Permit Writer, Region 10 EPA
Travis Porter, Department of Ecology, WQ Program
Loree' Randall, Department of Ecology, SEA Program
ecyrefedpermits@ecy.wa.gov

By Certified Mail: 9489 0090 0027 6066 2467 47

IN THE MATTER OF GRANTING A) ORDER # 18218
WATER QUALITY)
CERTIFICATION TO)
U.S. Environmental Protection Agency)
in accordance with 33 U.S.C. 1341)
(FWPCA § 401), RCW 90.48.120, RCW)
90.48.260 and chapter 173-201A WAC)
)

TO: UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 10
ATTN: Susan Poulsom
1200 Sixth Ave, Suite 155, OWW
SEATTLE, WA 98101

On May 27, 2020, the U.S. Environmental Protection Agency (EPA) requested a Section 401 Water Quality Certification for the NPDES Multi-Sector General Permit (MSGP) authorizing discharges to a water of the state (defined in chapter 90.48 RCW) from stormwater associated with industrial activities on federal lands. This Order and Section 401 Certification (Certification) imposes additional conditions, beyond the conditions of the draft NPDES permit, on the Applicant or Permittee.

The draft NPDES Multi-Sector General Permit covers the discharge of pollutants from the discharge of stormwater associated with industrial activity into waters of Washington State.

Material handling and storage, equipment maintenance and cleaning, and other activities at industrial facilities are often exposed to the weather. Runoff from rainfall or snowmelt that comes in contact with these activities can pick up pollutants, and transport them directly to a nearby river, lake, or coastal water or indirectly via a storm sewer and degrade water quality.

This Certification is based on the terms and conditions contained in the proposed draft NPDES MSGP. If EPA issues a final NPDES MSGP that contains any changes from the draft NPDES permit that do not include the requirements outlined in this Certification, Ecology reserves the right to either modify or revoke this Certification. In accordance with 40 CFR 124.53(e)(3), Ecology has determined that no condition in the draft NPDES permit may be made less stringent without violating requirements in Washington State law. Ecology reserves the right to modify or revoke this Certification if there is no longer reasonable assurance that there will be compliance with 33 U.S.C §§ 1311, 1312, 1313, 1316 and 1317 due to changes in the operation of the facility, changes in the characteristics of the waters into which discharges occur, changes in water quality criteria applicable to those waters, or changes to applicable effluent limits or other requirements.

AUTHORITIES:

In exercising authority under 33 U.S.C. § 1341, 16 U.S.C. § 1456, RCW 90.48.120, and RCW 90.48.260, Ecology has examined EPA's request for CWA 401 certification of the draft permit pursuant to the following:

1. Conformance with applicable water quality-based, technology-based, and toxic or pretreatment effluent limitations as provided under 33 U.S.C. § 1311, 1312, 1313, 1316, and 1317 (FWPCA § 301, 302, 303, 306 and 307);
2. Conformance with the state water quality standards contained in chapter 173-201A WAC and authorized by 33 U.S.C. § 1313 and by chapter 90.48 RCW, and with other applicable state laws; and
3. Conformance with the provision of using all known, available and reasonable methods to prevent and control pollution of state waters as required by RCW 90.48.010.
4. Conformance with Washington's prohibition on discharges that cause or tend to cause pollution of waters of the state of Washington. RCW 90.48.080.

WATER QUALITY CERTIFICATION CONDITIONS:

With this Certification and through issuance of this Order, Ecology certifies that it has reasonable assurance that the activity as proposed and conditioned by this Certification will be conducted in a manner that will not violate applicable water quality standards and other appropriate requirements of state law. In view of the foregoing and in accordance with 33 U.S.C. § 1341, RCW 90.48.120, RCW 90.48.260, chapter 173-200 WAC and chapter 173-201A WAC, water quality certification is granted to the Applicant subject to the conditions within this Order and the Multi-Sector General Permit.

Certification of the Applicant's proposed final permits does not authorize the Permittee to exceed applicable state surface water quality standards (chapter 173-201A WAC), ground water standards (chapter 173-200 WAC) or sediment quality standards (chapter 173-204 WAC), standards in the EPA's Revision of certain Federal water quality criteria applicable to Washington (40 CFR 131.45), and other appropriate requirements of State law.

A. General Conditions

1. For purposes of this Order, the term “Applicant” shall mean U.S. Environmental Protection Agency, and its agents, assignees and contractors.
2. For purposes of this Order, the permit “Permittee” shall mean any facility granted coverage under EPA’s Multi Sector General Permit.
3. The Applicant shall enforce the permit and ensure that the Permittee complies with the conditions of the permits at all times.
4. Nothing in this Certification waives Ecology’s authority to issue additional orders if Ecology determines that further actions are necessary to implement the water quality laws of the state. Further, Ecology retains continuing jurisdiction to make modifications hereto through supplemental orders, if additional impacts due to project construction or operation are identified (*e.g.*, violations of water quality standards, downstream erosion, etc.), or if additional conditions are necessary to further protect water quality.
5. In the event of changes or amendments to the state water quality, ground water quality, or sediment standards, or changes in or amendments to the state Water Pollution Control Act (RCW 90.48) or the federal Clean Water Act, Ecology may issue an amendment to this Certification to incorporate any such changes or amendments applicable to this project.
6. Failure of any person or entity to comply with this Certification may result in the issuance of civil penalties or other actions, whether administrative or judicial, to enforce the terms of this Certification.

B. Water Quality

1. This Certification does not authorize exceedances of water quality standards established in chapter 173-201A WAC.
2. Discharges shall not cause or contribute to a violation of surface water quality standards (chapter 173-201A WAC), ground water quality standards (chapter 173-200 WAC), sediment management standards (chapter 173-204 WAC), and human health-based criteria in the National Toxics Rule (40 CFR Part 131.36). Discharges that are not in compliance with these standards are not authorized.
3. Prior to the discharge of stormwater and non-stormwater to waters of the state, the Permittee shall apply all known, available, and reasonable methods of prevention, control, and treatment (AKART). This includes the preparation and implementation of an adequate Stormwater Pollution Prevention Plan (SWPPP), with all appropriate best management practices (BMPs) installed and maintained in accordance with the SWPPP and the terms and conditions of this permit. The Permittee shall include each of the following mandatory BMPs in the SWPPP and implement the BMPs. The Permittee may omit individual BMPs if site conditions render the BMP unnecessary or infeasible and the Permittee provides alternative and equally effective BMPs. The Permittee must justify each BMP omission in the SWPPP.

BMPs shall be consistent with:

- a. *2019 Stormwater Management Manual for Western Washington*, for sites west of the crest of the Cascade Mountains; **or**
 - b. *2019 Stormwater Management Manual for Eastern Washington*, for sites east of the crest of the Cascade Mountains; **or**
 - c. Revisions to the manuals in S3.A.3. a & b., or other stormwater management guidance documents or manuals which provide an equivalent level of ***pollution*** prevention, that are approved by Ecology and incorporated into this permit in accordance with the permit modification requirements of WAC 173-226-230. For purposes of this section, the documents listed in Appendix 10 of the August 1, 2019 Phase I Municipal Stormwater Permit are hereby incorporated into this permit; **or**
 - d. Documentation in the SWPPP that the BMPs selected are ***demonstrably equivalent*** to practices contained in stormwater technical manuals approved by Ecology, including the proper selection, implementation, and maintenance of all applicable and appropriate best management practices for on-site pollution control.
4. Additional Sampling Requirements and Effluent Limits for Discharges to Certain Impaired Waters and Puget Sound Sediment Cleanup Sites.
1. Permittees discharging to a 303(d)-listed waterbody (Category 5), either directly or indirectly through a stormwater drainage system, shall comply with the applicable sampling requirements and numeric effluent limits in Table 1.

For purposes of this condition, “applicable sampling requirements and effluent limits” means the sampling and effluent limits in Table 1 that correspond to the specific parameter(s) the receiving water is 303(d)-listed for at the time of permit coverage, or Total Suspended Solids (TSS) if the waterbody is 303(d)-listed (Category 5) for sediment quality at the time of MSGP coverage.

If a discharge point is subject to an impaired waterbody effluent limit for a parameter that also has a benchmark, the effluent limit supersedes the benchmark. All references to Category 5 pertain to the 2012 EPA-approved Water Quality Assessment.

The 2012 EPA-approved Water Quality Assessment may be viewed online at: http://www.ecy.wa.gov/programs/wq/links/wq_assessments.html

Table 1: Sampling and Effluent Limits Applicable to Discharges to 303(d)-listed Waters

Parameter	Units	Maximum Daily ^a		Analytical Method ^b	Laboratory Quantitation Level ^c	Sampling Frequency ^d
		Freshwater	Marine			
Turbidity	NTUs	25	25	EPA 180.1 Meter	0.5	1/quarter
pH	SU	j	Between 7.0 and 8.5	Meter	±0.1	1/quarter
Fecal Coliform Bacteria	# colonies/ 100 mL	i	i	SM 9222D	20 CFU/ 100 mL	1/quarter
TSS ^f	mg/L	30	30	SM2540-D	5	1/quarter
Phosphorus, Total	mg/L	g	g	EPA 365.1	0.01	1/quarter
Total Ammonia (as N)	mg/L	g	g	SM 4500 NH ³ -GH	0.3	1/quarter
Copper, Total	µg/L	g	g	EPA 200.8	2.0	1/quarter
Lead, Total	µg/L	g	g	EPA 200.8	0.5	1/quarter
Mercury, Total	µg/L	2.1	1.8	EPA1631E	0.0005	1/quarter
Zinc, Total	µg/L	g	g	EPA 200.8	2.5	1/quarter
Pentachlorophenol	µg/L	9 ^h	g	EPA 625	1.0	1/quarter

- ^a Maximum daily effluent limit means the highest allowable daily discharge. The daily discharge means the discharge of a pollutant measured during a calendar day. The daily discharge is the average measurement of the pollutant over the day; this does not apply to pH.
- ^b Or other equivalent method with the same reporting level.
- ^c The Permittee shall ensure laboratory results comply with the quantitation level (QL) specified in the table. However, if an alternate method from 40 CFR Part 136 is sufficient to produce measurable results in the sample, the Permittee may use that method for analysis. If the Permittee uses an alternative method it must report the test method and QL on the DMR. If the Permittee is unable to obtain the required QL due to matrix effects, the Permittee must report the matrix-specific method detection level (MDL) and QL on the DMR.
- ^d 1/quarter means at least one sample taken each quarter, e.g., Q1 = Jan 1 – March 31, Q2 = April 1 – June 30.
- ^e Permittees shall use either a calibrated pH meter consistent with EPA 9040 or an approved state method.
- ^f Permittees who discharge to a waterbody 303(d)-listed (Category 5) for sediment quality shall sample the discharge for TSS.
- ^g Site-specific effluent limitation will be assigned at the time of permit coverage.
- ^h Based on a pH of 7.0.
- ⁱ A numeric effluent limit does not apply, but Permittees must sample according to Table 1. In addition, the following mandatory BMPs shall be incorporated into the SWPPP and implemented; the Permittee must:
- 1) Use all known, available and reasonable methods to prevent rodents, birds, and other animals from feeding/nesting/roosting at the facility. Nothing in this section shall be construed as allowing violations of any applicable federal, state or local statutes, ordinances, or regulations including the Migratory Bird Treaty Act.
 - 2) Perform at least one annual dry weather inspection of the stormwater system to identify and eliminate sanitary sewer cross-connections.
 - 3) Install structural source control BMPs to address on-site activities and sources that could cause bacterial contamination (e.g., dumpsters, compost piles, food waste, and animal products).
 - 4) Implement operational source control BMPs to prevent bacterial contamination from any known sources of fecal coliform bacteria (e.g., animal waste).
 - 5) Conduct additional bacteria-related sampling and/or BMPs, if ordered by Ecology on a case-by-case basis.
- ^j The effluent limit for a Permittee who discharges to a freshwater body 303(d)-listed for pH is: Between 6.0 and 8.5, if the 303(d)-listing is for high pH only; Between 6.5 and 9.0, if the 303(d)-listing is for low pH only; and Between 6.5 and 8.5 if the 303(d)-listing is for both low and high pH. All pH effluent limits are applied end-of-pipe.

2. Permittees discharging to a Puget Sound Sediment Cleanup Site¹, either directly or indirectly through a stormwater drainage system, shall comply with this section:
 - a. Permittees shall sample the discharge for Total Suspended Solids (TSS) in accordance with Table 2.
 - b. If the waterbody is listed within Category 5 (sediment medium) where the *outfall* discharges to the waterbody, the discharge is subject to the TSS numeric effluent limit in Attachment A, Table 1.
 - c. If the waterbody is not listed within Category 5 (sediment medium) where the outfall discharges to the waterbody (*e.g.*, Category 4B, etc.), the discharge is subject to the TSS benchmark in Attachment A, Table 2. If the discharge is subject to more than one TSS benchmark value (*i.e.*, two different benchmarks), the lower benchmark supersedes the higher one. If a discharge exceeds the TSS benchmark, the Permittee shall implement corrective actions in accordance with the MSGP.
 - d. Permittees shall remove accumulated solids from storm drain lines (including inlets, catch basins, sumps, conveyance lines, and oil/water separators) owned or controlled by the Permittee at least once during the term of the MSGP.

Permittees shall conduct line cleaning operations (*e.g.*, jetting, vacuuming, removal, loading, storage, and/or transport) using BMPs to prevent discharges of storm drain solids to surface waters of the state.

Removed storm drain solids and liquids shall be disposed of in accordance with applicable laws and regulations and documented in the SWPPP.
 - e. Prior to removing storm drain solids according to Attachment A. Condition 2.D, Permittees shall sample and analyze storm drain solids in accordance with Table 3. Storm drain solids must be collected/sampled from a representative catch basin, sump, pipe, or other feature within the storm drain system that corresponds to the discharge point where Total Suspended Solids (TSS) samples are collected per Attachment A. Samples may be either a single grab sample or a composite sample. Samples must be representative of the storm drain solids generated and accumulated in the facility's drainage system. To the extent possible, sample locations must exclude portions of the drainage system affected by water from off-site sources (*e.g.*, run-on from off-site properties, tidal influence, backflow).

¹**Puget Sound Sediment Cleanup Site:** means Category 4B (Sediment) portions of Budd Inlet (Inner), Commencement Bay (Inner), Commencement Bay (Outer), Dalco Passage and East Passage, Duwamish Waterway (including East and West Waterway), Eagle Harbor, Elliot Bay, Hood Canal (North), Liberty Bay, Rosario Strait, Sinclair Inlet, and Thea Foss Waterway; Category 5 (Sediment) portions of the Duwamish Waterway; Category 4A (Sediment) portions of Bellingham Bay (Inner); and the Everett/Port Gardner, Oakland Bay/Shelton Harbor, and Port Angeles Harbor sediment cleanup areas, as mapped on Ecology's ISGP website. All references to Category 4A, 4B and 5 pertain to the 2012 EPA-approved Water Quality Assessment

All references to Category 4B and 5 pertain to the 2012 EPA-approved Water Quality Assessment, available online at: http://www.ecy.wa.gov/programs/wq/links/wq_assessments.html.

Table 2: Benchmarks and Sampling Requirements Applicable to Discharges to Puget Sound Sediment Cleanup Sites that are not Category 5 for Sediment Quality

Parameter	Units	Benchmark Value ^a	Analytical Method	Laboratory Quantitation Level ^b	Minimum Sampling Frequency ^c
TSS	mg/L	30	SM2540-D	5	1/quarter

- ^a. Permittees sampling more than once per quarter shall average the sample results and compare the average value to the benchmark to determine if the discharge has exceeded the benchmark value. However, if Permittees collect more than one sample during a 24-hour period, they must first calculate the daily average of the individual grab sample results collected during that 24-hour period; then use the daily average to calculate a quarterly average.
- ^b. The Permittee shall ensure laboratory results comply with the quantitation level (QL) specified in the table. However, if an alternate method from 40 CFR Part 136 is sufficient to produce measurable results in the sample, the Permittee may use that method for analysis. If the Permittee uses an alternative method it must report the test method and QL on the DMR. If the Permittee is unable to obtain the required QL due to matrix effects, the Permittee must report the matrix-specific method detection level (MDL) and QL on the DMR.
- ^c. 1/quarter means at least one sample taken each quarter, year-round.

Table 3: Sampling and Analytical Procedures for Storm Drain Solids

Analyte	Method in Sediment	Quantitation Level ^a
Conventional Parameters		
Percent total solids	SM 2540G, or ASTM Method D 2216	NA
Total organic carbon	Puget Sound Estuary Protocols (PSEP 1997), or EPA 9060	0.1%
Grain size	Ecology Method Sieve and Pipette (ASTM 1997), ASTM D422, or PSEP 1986/2003	NA
Metals		
Antimony, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw ^b
Arsenic, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.1 mg/kg dw
Beryllium, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw
Cadmium, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw
Chromium, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.5 mg/kg dw
Copper, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw
Lead, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw
Mercury, Total	EPA Method 1631E, or EPA Method 7471B	0.005 mg/kg dw
Nickel, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.1 mg/kg dw
Selenium, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.5 mg/kg dw
Silver, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.1 mg/kg dw
Thallium, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	0.2 mg/kg dw
Zinc, Total	EPA Method 200.8 (ICP/MS) , EPA Method 6010 or EPA Method 6020	5.0 mg/kg dw
Organics		
PAH compounds ^c	EPA Method 8270 D	70 µg/kg dw
PCBs (aroclor)s, Total ^d	EPA Method 8082	10 µg/kg dw
Petroleum Hydrocarbons		
NWTPH-Dx	NWTPH-Dx	25.0-100.0 mg/kg dw

^a The Permittee shall ensure laboratory results comply with the quantitation level (QL) specified in the table. However, if an alternate method is sufficient to produce measurable results in the sample, the Permittee may use that method for analysis. If the Permittee uses an alternative method, it must report the test method and QL on the sediment monitoring report. All results shall be reported. For values below the QL, or where a QL is not specified, report results at the method detection level (MDL) from the lab and the qualifier of "U" for undetected at that concentration. If the Permittee is unable to obtain the required QL due to matrix effects, the Permittee must report the matrix-specific MDL and QL on the DMR.

- b. dw = dry weight.
 - c. PAH compounds include: 1-methylnaphthalene, 2-methylnaphthalene, 2-chloronaphthalene, acenaphthylene, acenaphthene, anthracene, benzo(a)anthracene, benzo(a)pyrene, benzo(b,k)fluoranthene, benzo(ghi)perylene, dibenzo(a,h)anthracene, dibenzofuran, carbazole, chrysene, fluoranthene, fluorene, indeno(1,2,3-cd)pyrene, naphthalene, phenanthrene, and pyrene.
 - d. Total = sum of PCB aroclors 1016+1221+1232+1242+1248+1254+1260.
- f. All storm drain solids sampling data shall be reported to EPA no later than the DMR due date for the reporting period in which the solids were sampled. A copy of the lab report shall be submitted to EPA.

5. Requirements for Discharges to Waters with Applicable TMDLs

- a. The Permittee shall comply with applicable TMDL determinations. Applicable TMDLs or TMDL determinations are TMDLs which have been completed by the issuance date of this permit, or which have been completed prior to the date that the Permittee's NOI is received by EPA, whichever is later. EPA will list the Permittee's requirements to comply with this condition on the letter of permit coverage.
- b. TMDL requirements associated with TMDLs completed after the issuance date of this permit only become effective if they are imposed through an administrative order issued by EPA.
- c. Where Ecology has established a TMDL wasteload allocation and sampling requirements for the Permittee's discharge, the Permittee shall comply with all requirements of the TMDL.
 - a. If a discharge point is subject to a TMDL-related effluent limit for a parameter that also has a benchmark, the effluent limit supersedes the benchmark.
- d. Where Ecology has established a TMDL general wasteload allocation for industrial stormwater discharges for a parameter present in the Permittee's discharge, but has not identified specific requirements, EPA will assume the Permittee's compliance with the terms and conditions of the permit complies with the approved TMDL.
- e. Where Ecology has not established a TMDL wasteload allocation for industrial stormwater discharges for a parameter present in the Permittee's discharge, but has not excluded these discharges, EPA will assume the Permittee's compliance with the terms and conditions of this permit complies with the approved TMDL.
- f. Where a TMDL for a parameter present in the Permittee's discharge specifically precludes or prohibits discharges of stormwater associated with industrial activity, the Permittee is not eligible for coverage under the MSGP.

C. Timing Requirements

- 1. This Certification is valid until the expiration date including any administrative extension or termination date of EPA's NPDES Multi-Sector General Permit.

D. Notification Requirements

- 1. The Applicant shall enforce and the Permittee must comply with all the reporting and notification conditions of the NPDES permit, including conditions of the permit requiring the Permittee to report to Ecology.

YOUR RIGHT TO APPEAL

You have a right to appeal this Order to the Pollution Control Hearing Board (PCHB) within 30 days of the date of receipt of this Order. The appeal process is governed by chapter 43.21B RCW and chapter 371-08 WAC. "Date of receipt" is defined in RCW 43.21B.001(2).

To appeal you must do all of the following within 30 days of the date of receipt of this Order:

- File your appeal and a copy of this Order with the PCHB (see addresses below). Filing means actual receipt by the PCHB during regular business hours.
- Serve a copy of your appeal and this Order on Ecology in paper form - by mail or in person (see addresses below). E-mail is not accepted.

You must also comply with other applicable requirements in chapter 43.21B RCW and chapter 371-08 WAC.

ADDRESS AND LOCATION INFORMATION

Street Addresses	Mailing Addresses
Department of Ecology Attn: Appeals Processing Desk 300 Desmond Drive SE Lacey, WA 98503	Department of Ecology Attn: Appeals Processing Desk PO Box 47608 Olympia, WA 98504-7608
Pollution Control Hearings Board 1111 Israel RD SW STE 301 Tumwater, WA 98501	Pollution Control Hearings Board PO Box 40903 Olympia, WA 98504-0903

CONTACT INFORMATION

Please direct all questions about this Order to:

Travis Porter
Department of Ecology
P.O. Box 47600
Olympia, WA 98503-7600
(360) 407- 6127
Travis.Porter@ecy.wa.gov

MORE INFORMATION

- **Pollution Control Hearings Board Website**
<http://www.eluho.wa.gov/Board/PCHB>
- **Chapter 43.21B RCW - Environmental and Land Use Hearings Office – Pollution Control Hearings Board**
<http://apps.leg.wa.gov/RCW/default.aspx?cite=43.21B>
- **Chapter 371-08 WAC – Practice And Procedure**
<http://apps.leg.wa.gov/WAC/default.aspx?cite=371-08>
- **Chapter 34.05 RCW – Administrative Procedure Act**
<http://apps.leg.wa.gov/RCW/default.aspx?cite=34.05>
- **Chapter 90.48 RCW – Water Pollution Control**
<http://apps.leg.wa.gov/RCW/default.aspx?cite=90.48>
- **Chapter 173.204 Washington Administrative Code (WAC) Sediment Management Standards**
<https://apps.leg.wa.gov/WAC/default.aspx?cite=173-204>
- **Chapter 173-200 WAC Water Quality Standards for Ground Waters of the State of Washington**
<https://apps.leg.wa.gov/WAC/default.aspx?cite=173-200>
- **Chapter 173-201A WAC Water Quality Standards for Surface Waters of the State of Washington**
<https://apps.leg.wa.gov/WAC/default.aspx?cite=173-201A>

SIGNATURE



July 23, 2020

Jeff Killelea
Program Development Services Section Manager (Acting)
Water Quality Program
Washington State Department of Ecology

DATE