

Table 4
Groundwater Elevation Data, September 15, 2021
Rexam Beverage Can Company/Ball Corporation
Kent, WA

Well Number	Top of Casing Elevation (feet AMSL)	Depth to LNAPL (feet below top of casing)	Depth to Water (feet below top of casing)	PID Reading (response units)	Well Screen Interval (feet below ground surface)	Groundwater Elevation (feet AMSL)
MW-101	41.39	11.40	11.50	0.0	7-17	Not Calculated
MW-102	37.23	Not Encountered	8.15	104.3	7-17	29.08
MW-103	36.62	Not Encountered	6.77	0.0	4-14	29.85
MW-104	38.82	Not Encountered	7.62	0.0	5-15	31.20
MW-105R	36.62	Not Encountered	6.89	0.0	5-15	29.73
MW-106	40.34	Not Encountered	10.87	0.6	7-17	29.47
MW-107	36.74	Not Encountered	6.50	2.6 ⁽¹⁾	4.6-14.6	30.24
MW-108	40.92	Not Encountered	9.80	380	6-16	31.12
MW-113	36.72	Not Encountered	7.31	2.3	4-14	29.41
MW-201	37.22	Not Encountered	7.72	0.0	58.5-63.5	29.50
ETMW-2	38.59	Not Encountered	7.98	0.0	5-15	30.61
ETMW-3	36.89	Not Encountered	7.24	0.0	5-15	29.65
ETMW-7	37.84	Not Encountered	7.75	45	5-15	30.09
Protective Coatings, Inc., 1215 2nd Avenue North						
MW-4	36.63	Not Encountered	7.43	20	5-15	29.20
MW-5	37.07	Not Encountered	7.40	0.4	5-15	29.67

Footnote:

AMSL = Above mean sea level.

PID = Photoionization Detector.

LNAPL = Light Non-Aqueous Phase Liquid.

(1) = Background PID reading of 2.8 Response Units.