

REPORT
GROUND WATER MONITORING
QUARTERLY REPORT (4QTR06)
HALCO PROPERTIES, LLC
SEATTLE, WASHINGTON

December 27, 2006

5232 SHILSHOLE AVE NW, SEATTLE, WA

11/8/2011 *AM*

Prepared by:
Chadrick Morse
Morse Environmental, Inc.
2 Auburn Way North, Suite No. 208
Auburn, Washington 98002
Office: (253) 887-1550
Fax: (253) 887-1449
Email: chadmorse@morseenvironmental.com
Website: morseenvironmental.com

Table of Contents

1.0 INTRODUCTION	2
1.1 GENERAL	2
1.2 PREVIOUS STUDIES AND HISTORICAL INFORMATION	2
1.3 PURPOSE AND SCOPE	4
2.0 SITE DESCRIPTION	5
2.1 SURFACE CONDITIONS	5
3.0 FINDINGS	5
3.1 FIELD EXPLORATIONS	5
3.2 SUBSURFACE CONDITIONS.....	5
3.3 SUBSURFACE ENVIRONMENTAL CONDITIONS	5
4.0 CONCLUSIONS.....	6
5.0 LIMITATIONS.....	7
4.0 SIGNATURE OF ENVIRONMENTAL PROFESSIONAL.....	7

TABLES

Summary of Water Chemical Analytical Results
Petroleum Hydrocarbons

Table No.
1

FIGURES

Vicinity Map
Site Plan

Figure No.
1
2

REPORT
GROUND WATER MONITORING
QUARTERLY REPORT (4QTR06)
HALCO PROPERTIES, LLC
SEATTLE, WASHINGTON

1.0 INTRODUCTION

1.1 GENERAL

This report presents the results of our Forth Quarter (2006) Ground Water Monitoring of the property located at 5221 Ballard Avenue NW, Seattle, Washington. The subject site currently is owned by the HALCO PROPERTIES LLC. The property is currently operated by the Salmon Bay Sand & Gravel Company. The location of the subject site relative to surrounding physical features is shown in Figure 1. The general layout of the site is shown in Figure 2.

Our monitoring studies concentrated on ten (10) pre-existing ground water monitoring wells.

1.2 PREVIOUS STUDIES AND HISTORICAL INFORMATION

While Morse Environmental did not review the following reports (except for the Halco Properties 2 & 3 QTR 06 Quarterly Monitoring Report), the Washington State Department of Ecology has made their existence known:

Site Assessment C&C Paint Company Report, prepared for C&C Paint Company, prepared by Bison Environmental Northwest Inc., February 19, 1991

Ballard Avenue Landmark Letter, prepared for Mr. Robert Campbell - Cowen Campbell Paint Company, prepared by Ms. Susan Kanimatsu - Ballard Avenue Landmark District Board, April 17, 1991

Buried Tanks in Alley - Cracks in Ballard Hardware South Wall Letter, prepared for Mr. E Arthur Cowman - C&C Paints, prepared by Mr. Charles E. Kitchin - Pacific Testing Laboratories, April 19, 1991

Underground Storage Tank Closure in Place Site Assessment Report - Cowman-Campbell Paint Company, prepared for Cowman-Campbell Paint Company, prepared by Bison Environmental Northwest Inc., November 30, 1992

Groundwater Survey and Monitoring Well Installation - C&C Paint Company Property, prepared for Mr. Robert D. Allen - BettsPatterson & Mines - Attorneys At Law, prepared by Mr. Henry Perrin - Columbia Environmental Inc., December 11, 1995

Phase 2 Environmental Site Assessment - C&C Paint Company Property, prepared for Mr. Hal Cowman - CZS Enterprises mc, prepared by Mr. Henry Perrin - Columbia Environmental Inc., February 12, 1996

Cleanup Proposal - C&C Paint Company Property, prepared for Mr. Joseph Hickey - Department of Ecology, prepared by Mr. Ronald D. Allen - Betts, Patterson & Mines, PS., May 17, 1996

Quarterly Groundwater Monitoring Report - C&C Paint Company Property, prepared for Mr. Joseph Hickey - Department of Ecology, prepared by Mr. Ronald D. Allen - Betts, Patterson & Mines, PS, July 26, 1996

Quarterly Groundwater Monitoring Report - C&C Paint Company Property, prepared for Mr. Joseph Hickey - Department of Ecology, prepared by Mr. Ronald D. Allen - Betts, Patterson & Mines, PS, October 15, 1996

Quarterly Groundwater Monitoring Report - C&C Paint Company Property, prepared for Mr. Joseph Hickey - Department of Ecology, prepared by Mr. Ronald D. Allen - Betts, Patterson & Mines, PS, January 21, 1997

Quarterly Groundwater Monitoring Report - C&C Paint Company Property, prepared for Mr. Joseph Hickey - Department of Ecology, prepared by Mr. Ronald D. Allen - Betts, Patterson & Mines, PS, April 25, 1997

UST Closure In Place - Site Assessment Report - C&C Paints, prepared for Mr. Hal Cowman -C&C Paint Company, prepared by Mr. Michael Lam - Nowicki & Associates, February 10, 1998

October 2000 Annual Groundwater Monitoring - C&C Paints Site, prepared for Mr. Hal Cowman, prepared by Mr. Michael Lam - Nowicki & Associates, October 28, 2000

300-Gallon Diesel Heating Oil UST Closure Site Assessment Report - C&C Paint, prepared for Mr. Hal Cowman - C&C Paint Company, prepared by Mr. Michael Lam - Nowicki & Associates, November 28, 2000

September 2002 Annual Groundwater Monitoring - C&C Paints Site, prepared for Mr. Hal Cowman, prepared by Mr. Michael Lam - Nowicki & Associates, September 26, 2002

Ground Water Monitoring, Quarterly Report 2ndQTR06, Halco Properties, LLC, Seattle Washington, prepared by Mr. Chadrick Morse, Morse Environmental, Inc., June 28, 2006.

Ground Water Monitoring, Quarterly Report 3rdQTR06, Halco Properties, LLC, Seattle Washington, prepared by Mr. Chadrick Morse, Morse Environmental, Inc., August 31, 2006.

1.3 PURPOSE AND SCOPE

The purpose of our Ground Water Monitoring was to evaluate any residual petroleum soil contamination after the removal of an Underground Storage Tank (UST).

Our specific scope of services included the following:

1. Develop a site safety plan for use by Morse Environmental staff during field activities.
2. Identify measurement of ground water level.
3. Removed (purge) stagnant water within the monitoring well using a peristaltic pump.
4. Obtain well samples using existing bailers.
5. Monitoring of pH, temperature and specific conductance.
6. Obtain ten (10) Ground Water Samples for Laboratory Analysis using the HCID method to screen and the WTPH-Dx method to quantify.
7. Quarterly Report of Findings.

2.0 SITE DESCRIPTION

2.1 SURFACE CONDITIONS

The site is occupied by the Salmon Bay Sand & Gravel Company. The site is comprised of three parcels that encompass 0.51 acres; the approximate location of the on-site building is shown in Figure 2.

3.0 FINDINGS

3.1 FIELD EXPLORATIONS

Morse Environmental monitored nine (9) of the ten (10) wells present on the site. One monitoring well (MW-9) sustained no access due to immobile dumpster on top of the well.

3.2 SUBSURFACE CONDITIONS

3.2.1 Soil

No soil was considered in this evaluation.

3.2.2. Ground Water

Ground water sampling results appear in Table 1. These results show no presence of the diesel or oil range hydrocarbons in any of the monitoring wells. Hydrocarbons in the gas-solvent range were found in only one monitoring well (MW3).

The absence of petroleum in the ground water may be due to the wetter than normal conditions of the site in the 4 QTR 06.

3.3 SUBSURFACE ENVIRONMENTAL CONDITIONS

3.3.1 Field Screening Results

Field screening was performed on wells upon arrival. The field screen results are found in Table 1.

Field screening results indicated no probable presence of volatile petroleum in any of the samples.

3.3.2 Soil Chemical Analyses

No soil samples were taken or analyzed

3.3.3 Ground Water Chemical Analyses

NWTPH-HCID is a qualitative and semi-quantitative screen to determine the presence and type of petroleum products that may exist in water or soil. This method should be used if the type of petroleum contamination is unknown. It should be performed on contaminated soil or water that is representative of the contamination at the site. The results of this method will determine what fully quantitative method/methods, if any, are to be used in determining compliance with the matrix criteria. Should the value of the analysis for gasoline, diesel or heavy oils (or any other identified petroleum product) exceed the reporting limits, then the specific analytical method for that product must be employed.

NWTPH-D is the qualitative and quantitative method (extended) for non-volatile ("oil") petroleum products in soil and water. Petroleum products applicable for this include motor oils.

NWTPH-Dx is the qualitative and quantitative method (extended) for semi-volatile ("diesel") petroleum products in soil and water. Petroleum products applicable for this include jet fuels, kerosene, diesel oils, hydraulic fluids, mineral oils, lubricating oils and fuel oils.

NWTPH-Gas is the qualitative and quantitative method for volatile ("gas-solvent") petroleum products in soil and water. Petroleum products applicable for this include stoddard solvent, gasoline fractions.

4.0 CONCLUSIONS

Petroleum hydrocarbons were detected in one Monitoring Well (MW3).

The previous monitoring report (dated 8/31/06) showed petroleum hydrocarbons in Monitoring Wells MW2, MW3, MW4, MW5 in the oil range. Hydrocarbons in the gas-solvent range were found in two monitoring wells (MW1, MW4).


The servicing of the Monitoring Wells, combined with the new well caps appear to stopped the diesel/oil hydrocarbon surface infiltration of the wells.

5.0 LIMITATIONS

Morse Environmental has prepared this report in a professional manner, using the level of skill and care normally exercised for similar projects under similar conditions by reputable and competent environmental consultants currently practicing in the area, and in accordance with the directives provided by the facility management. Morse Environmental is not responsible for conditions or consequences arising from relevant facts that were not disclosed at the time of our visit. We also note that the facts and conditions referenced in this report may change over time, and that the conclusions set forth here are applicable to the facts and conditions at the time of this report. Conclusions were made within the operative constraints of the scope, budget and schedule for this project. We believe that the conditions stated here are factual, but no guarantee is made or implied.

4.0 Signature of Environmental Professional

MORSE ENVIRONMENTAL, INC.



Chadrick Morse
Principal Chemist

TABLE 1
SUMMARY OF GROUND WATER CHEMICAL ANALYTICAL RESULTS
PETROLEUM HYDROCARBONS
HALCO PROPERTIES LLC
Seattle, Washington

Sample Number	Depth to Water Table	Date Sampled	Sheen	Headspace Vapors (ppm)	pH	Conductivity	HCID ¹	Diesel-range Hydrocarbons (ug/L)
MW-1		12/15/06	NS	0	6.97		ND	ND
MW-2		12/15/06	NS	0	6.90		ND	ND
MW-3		12/15/06	NS	0	6.35		Gas-Solvent Range	650
MW-4		12/15/06	NS	0	6.90		ND	ND
MW-5		12/15/06	NS	0	6.85		ND	ND
MW-6		12/15/06	NS	0	6.90		ND	ND
MW-8		12/15/06	NS	0	7.00		ND	ND
MW-9							NT	NT
MW-10		12/15/06	NS	0	6.90		ND	ND
MTCA Method A Cleanup Levels								500 Diesel 1,000 Gas ³

Notes:


¹ Analyzed by Ecology Method Hydrocarbon Identification Presence Absence Testing for G: Gas, D: Diesel, O: Heavy Oil

² Analyzed by Ecology Method TPH-Dx for Diesel Range or TPH-Gas for Gas-Solvent Range.

Chemical analyses conducted by Spectra Labs, Tacoma, Washington. The laboratory report is presented in Appendix B.

SS = Slight Sheen, NS= No Sheen ND=Not Detected above 10mg/Kg for Diesel and 100 mg/Kg for Oil.

³ Gas-Solvent Range Limit When No Benzene in Water Sample is Detected.



Morse
Environmental, Inc.

VICINITY MAP

FIGURE 1

