


2 SECTION-STAIR FOOTING  
3/4" = 1'-0"



3 ENLARGED PLAN @ RAMP  
1/2" = 1'-0"



1 SITE PLAN SIGNAGE  
1/16" = 1'-0"

SITE SIGNAGE LEGEND

- 1 ADA PARKING SIGN (WASHINGTON ACCESSIBLE SIGN) - 12" WIDE x 18" HIGH, REFLECTIVE, HEAVY DUTY ALUMINUM, .63 MIL, WITH ROUNDED CORNERS, PRINTED WITH 3M INKS AND MATERIALS, ENGINEER GRADE MINIMUM. WALL MOUNTED. COLOR: GREEN ON WHITE BACKGROUND W/ BLUE ADA SYMBOL.
- 2 "VAN ACCESSIBLE" SIGN AT STALLS MARKED AS "VAN" ON THE SITE PLAN ONLY. LETTERS ARE 2" CLASS 'B' WIDTH TYPICAL. PAINT BLACK, 2COATS ENAMEL.
- 3 NO PARKING, DELIVERY AREA SIGN - 12" WIDE x 18" HIGH, REFLECTIVE, HEAVY DUTY ALUMINUM, .63 MIL, WITH ROUNDED CORNERS, PRINTED WITH 3M INKS AND MATERIALS, ENGINEER GRADE MINIMUM. WALL MOUNTED. COLOR: RED ON WHITE BACKGROUND.




- 4 RESERVED PARKING, ELECTRIC VEHICLES ONLY - 12" WIDE x 18" HIGH, REFLECTIVE, HEAVY DUTY ALUMINUM, .63 MIL, WITH ROUNDED CORNERS, PRINTED WITH 3M INKS AND MATERIALS, ENGINEER GRADE MINIMUM. WALL MOUNTED. COLOR: GREEN ON WHITE BACKGROUND.
- 5 RESERVED PARKING, RETAIL PARKING ONLY 12" WIDE x 18" HIGH, REFLECTIVE, HEAVY DUTY ALUMINUM, .63 MIL, WITH ROUNDED CORNERS, PRINTED WITH 3M INKS AND MATERIALS, ENGINEER GRADE MINIMUM. WALL MOUNTED. COLOR: GREEN ON WHITE BACKGROUND.



4 SECTION @ RAMP  
3/4" = 1'-0"



THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

SITE SIGNAGE


A1.02

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.







10 EXTERIOR WALL @ RAISED SIDEWALK  
 3/4" = 1'-0"




11 SITE PLANTERS  
 1/2" = 1'-0"




7 SITE PARKING MARKINGS1  
 1/2" = 1'-0"




9 SHORT TERM BIKE STORAGE ELEVATION  
 1/4" = 1'-0"




8 PLANTER SITE PLAN  
 1/4" = 1'-0"




5 SITE PLAN - SHORT TERM BIKE PARKING 3  
 1/4" = 1'-0"




6 SITE PLAN - SHORT TERM BIKE PARKING 2  
 1/4" = 1'-0"




4 SITE PLAN - SHORT TERM BIKE PARKING 1  
 1/4" = 1'-0"



3 WHEELSTOP  
 1 1/2" = 1'-0"



2 TRASH RECEPTACLE  
 1/2" = 1'-0"



1 SITE BENCH  
 1/2" = 1'-0"

EAST BAY LOT A  
 WESTMAN MIL  
 510 STATE AVE OLYMPIA, WA - 98501

Project No: 1514  
 BUILDING PERMIT SET  
 09/09/2019

- 1R REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**SITE FEATURES**

**A1.03**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 18 RESPONSE TO COMMENTS. 01-31-2019
- 28 RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

FLOOR PLAN -  
LEVEL 1

A2.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**2 FLOOR PLAN**  
3/32" = 1'-0"  
0 4 8 16 32

- GENERAL NOTES**
- SEE SHEET A2.10 TO A2.36 FOR ENLARGED FLOOR PLANS.
  - DIMENSIONS TO FACE OF STUD UNLESS NOTED OTHERWISE.
  - GENERAL CONTRACTOR AND SPRINKLER DESIGNER TO DETERMINE NEED FOR FIRE PUMP PRIOR TO START OF CONSTRUCTION.
  - SEE SHEETS A6.11 & A6.12 FOR AIR BARRIER CALL OUTS AND DETAILS.

- PLAN LEGENDS**
- SECTION MARKER, NUMBER BELOW INDICATES PAGE WHERE SECTION CAN BE FOUND, NUMBER ABOVE INDICATES THE SECTION LOCATION ON THE PAGE.
  - DETAIL MARKER, NUMBER BELOW INDICATES PAGE WHERE DETAIL CAN BE FOUND, NUMBER ABOVE INDICATES THE DETAIL LOCATION ON THE PAGE.
  - DOOR MARKER, LETTER INDICATES TYPE OF DOOR, SCHEDULE LOCATED ON PAGE A - 801
  - AMBASSADOR- SEMI-RECESSED FIRE EXTINGUISHER CABINET WITH 1-1/2" SQUARE TIME OR EQUAL. PROVIDE WITH 2A- 10BC EXTINGUISHER. EVERY 3,000 SQUARE FEET AS LOCATED IN PLANS. NOT TO EXCEED 75 FEET OF TRAVEL.

**FIRE PROTECTION REQUIREMENTS FOR STRUCTURAL BUILDING ELEMENTS**

REINFORCED CAST IN PLACE CONCRETE COLUMN: 1-1/2" MIN. COVERAGE TO STEEL REINFORCING.

POST TENSION SLAB: MIN. THICKNESS 4.6" REQUIRED. THICKNESS PROVIDED 11" & 13"  
COVERAGE MIN. FOR TENDONS  
RESTRAINED: 1"  
UNRESTRAINED: 2"  
NOTE: COVERAGE OVER NONPRESTRESSED REINFORCEMENT = 3/4" MIN.

CONCRETE WALLS: MIN THICKNESS 5.7" REQUIRED. THICKNESS PROVIDED 8"

PER IBC 721 TABLES 722.2.1.(1), 722.2.1.(2), 722.2.1.(3)









THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**1 FLOOR 2 - FLOOR PLAN**

3/32" = 1'-0"  
0' 4' 8' 16' 32'

**GENERAL NOTES**

1. AT WATER HEATERS PROVIDE MINIMUM CLEARANCE FROM COMBUSTIBLES PER MANUFACTURER RECOMMENDATIONS TYPICAL.

**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**FLOOR PLAN -  
LEVEL 2**

**A2.02**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1. REVISION 1. 01-31-2019
- 1R. RESPONSE TO COMMENTS. 01-31-2019
- 2R. RESPONSE TO COMMENTS. 03-20-2019
- 3. REVISION 3. 06-13-2019
- 4. REVISION 4. 07-08-2019
- 5. REVISION 5. 08-02-2019
- 6. REVISION 6. 09-03-2019

FLOOR PLAN -  
LEVEL 3

A2.03

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**GENERAL NOTES**  
1. AT WATER HEATERS PROVIDE MINIMUM CLEARANCE FROM COMBUSTIBLES PER MANUFACTURER RECOMMENDATIONS TYPICAL.







THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

FLOOR PLAN -  
LEVEL 4 - 5


A2.04

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



1 FLOOR 4 & 5- FLOOR PLAN

3/32" = 1'-0"



GENERAL NOTES

1. AT WATER HEATERS PROVIDE MINIMUM CLEARANCE FROM COMBUSTIBLES PER MANUFACTURER RECOMMENDATIONS TYPICAL.







**EAST BAY LOT A  
 WESTMAN MIL**  
 510 STATE AVE OLYMPIA, WA. 98501



Project No: 1514  
**BUILDING PERMIT SET**  
 09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**ROOF PLAN**

**A2.05**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**ROOF DRAINAGE CALCULATIONS**

PER 2012 IPC, TABLE 1106.2 AT AN INTENSITY LEVEL OF 3\"/>

ROOF AREA:	NORTH	SOUTH	EAST GUTTER	WEST GUTTER	PATIO	COMMON AREA
	6,599.68 S.F.	6,642.61 S.F.	907.80 S.F.	907.19 S.F.	1,276.32 S.F.	351.56 S.F.

TOTAL ROOF AREA = 15,077.28 SQ. FEET  
 TOTAL PATIO AND COMMON AREA = 1,627.88 SQ. FEET

DOWNSPOUTS PLACED TO SPLIT ROOF EQUALLY BETWEEN THE WEST AND THE EAST.  
 15,077.28 SQ. FEET / 2 = 7,538.64 SQ. FEET @ WEST, 7,538.64 SQ. FEET @ EAST

WEST ROOF PROVIDED WITH (1) 5\"/>


EAST ROOF PROVIDED WITH (1) 4\"/>

PATIO AND COMMON ROOF PROVIDED WITH (1) 3\"/>










THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

ENLARGED  
PLANS - FLOOR  
1B


A2.07

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





1 PARTIAL FLOOR 1 - ENLARGED B  
1/4" = 1'-0"





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



**1 PARTIAL FLOOR 1 - ENLARGED C**



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA - 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019


- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**ENLARGED  
PLANS - FLOOR  
1C**

**A2.08**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com

4295 REGISTERED ARCHITECT  
RONALD S. THOMAS  
STATE OF WASHINGTON

Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019



**2 EXTERIOR MASONRY WALL**  
3" = 1'-0"  
NOTE: SEE ADDITIONAL WALL ASSEMBLY DETAILS ON SHEET A6.01

**1 PARTIAL FLOOR 1 - ENLARGED D**  
1/4" = 1'-0"

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

ENLARGED  
PLANS - FLOOR  
1D

A2.09

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com

**GENERAL NOTES**

1. PROVIDE DRAFT STOPPING IN FLOORING PER IBC 718.3, TYPICAL ALL FLOORS.



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**ENLARGED  
PLANS - FLOOR  
2A**

**A2.10**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




**1 PARTIAL FLOOR 2 - ENLARGED A**







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: *Lee Spence*  
09/17/2019

EAST BAY LOT A  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501



Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ENLARGED PLANS - FLOOR 2B**

**A2.11**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**2 RAILING CONDITION @ MIDDLE OF PT SLAB**  
3" = 1'-0"



**1 PARTIAL FLOOR 2 - ENLARGED B**






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**1 PARTIAL FLOOR 2 - ENLARGED C**



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**ENLARGED  
PLANS - FLOOR  
2C**


**A2.12**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





**THOMAS**  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: *[Signature]*  
09/17/2019

**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


**ENLARGED PLANS - FLOOR 2D**

**A2.13**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**1 PARTIAL FLOOR 2 - ENLARGED D**







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com

4295 REGISTERED ARCHITECT  
RONALD S. THOMAS  
STATE OF WASHINGTON

Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

ENLARGED  
PLANS - FLOOR  
3A


A2.14

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.


1 PARTIAL FLOOR 3 - ENLARGED A







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


ENLARGED  
PLANS - FLOOR  
3B

A2.15

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



1 PARTIAL FLOOR 3 - ENLARGED B








THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


ENLARGED  
PLANS - FLOOR  
3C

A2.16

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




1 PARTIAL FLOOR 3 - ENLARGED C







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Reviewed for Code Compliance  
Construction Permitting Dept.  
*Neil Robert*  
Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: *Joe Spence*  
09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ENLARGED  
PLANS - FLOOR 4  
- 5A**


**A2.17**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.


**1 PARTIAL FLOOR 4 - 5 - ENLARGED A**







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ENLARGED  
PLANS - FLOOR 4  
- 5B**

**A2.18**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




**1 PARTIAL FLOOR 4 - 5 - ENLARGED B**







THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

ENLARGED  
PLANS - FLOOR 4  
- 5C


A2.19

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

1 PARTIAL FLOOR 4 - 5 - ENLARGED C








**1 FLOOR 1 - REFLECTED CEILING PLAN**

1/16" = 1'-0"



**2 LEVEL 2**

1/16" = 1'-0"

**GENERAL NOTES**

1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES.
2. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
3. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
4. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
5. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
6. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
7. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
8. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (11 LUX).
9. ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
10. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
11. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
12. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
13. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.


**PLAN LEGEND**

SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E-100

- PENDANT LIGHT FIXTURE
- RECESSED CAN LIGHT FIXTURE. PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
- SURFACE MOUNT LIGHT FIXTURE
- WALL SCONCE FIXTURE
- VANITY LIGHT FIXTURE, WALL MOUNTED
- EXIT LIGHTS
- LINEAR LED LIGHTING FIXTURE
- 1X4 LINEAR LED LIGHTING FIXTURE
- LINEAR LED, WITH EMERGENCY BATTERY PACK
- BATHROOM LIGHT/EXHAUST FAN
- KITCHEN EXHAUST FAN
- 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
- T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
- SUSPENDED CEILING SYSTEM.
- DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
- 120V SMOKE DETECTOR
- 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
- FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
- FAN COIL UNIT, SEE MECHANICAL DRAWINGS
- SUPPLY DIFFUSER
- RETURN DIFFUSER



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lymplia.com



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- REVISION 1. 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3. 06-13-2019
- REVISION 4. 07-08-2019
- REVISION 5. 08-02-2019
- REVISION 6. 09-03-2019

**KEY RCP - LEVEL 1-2**

**A2.20**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

KEY RCP - LEVEL  
3-5

A2.21

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.


PLAN LEGENDS

- SECTION MARKER, NUMBER BELOW INDICATES PAGE WHERE SECTION CAN BE FOUND, NUMBER ABOVE INDICATES THE SECTION LOCATION ON THE PAGE.
- DETAIL MARKER, NUMBER BELOW INDICATES PAGE WHERE DETAIL CAN BE FOUND, NUMBER ABOVE INDICATES THE DETAIL LOCATION ON THE PAGE.
- DOOR MARKER, LETTER INDICATES TYPE OF DOOR, SCHEDULE LOCATED ON PAGE A - 801
- AMBASSADOR- SEMI-RECESSED FIRE EXTINGUISHER CABINET WITH 1-1/2" SQUARE TIME OR EQUAL. PROVIDE WITH 2A-10BC EXTINGUISHER. EVERY 3,000 SQUARE FEET AS LOCATED IN PLANS, NOT TO EXCEED 75 FEET OF TRAVEL.


PLAN LEGEND

SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100

- PENDANT LIGHT FIXTURE
- RECESSED CAN LIGHT FIXTURE. PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
- SURFACE MOUNT LIGHT FIXTURE
- WALL SCONCE FIXTURE
- VANITY LIGHT FIXTURE, WALL MOUNTED
- EXIT LIGHTS
- LINEAR LED LIGHTING FIXTURE
- 1X4 LINEAR LED LIGHTING FIXTURE
- LINEAR LED, WITH EMERGENCY BATTERY PACK
- BATHROOM LIGHT/EXHAUST FAN
- KITCHEN EXHAUST FAN
- 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
- T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
- SUSPENDED CEILING SYSTEM.
- DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
- 120V SMOKE DETECTOR
- 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
- FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
- FAN COIL UNIT. SEE MECHANICAL DRAWINGS
- SUPPLY DIFFUSER
- RETURN DIFFUSER



1 FLOOR 3 - REFLECTED CEILING PLAN  
1/16" = 1'-0"




2 FLOOR 4 - 5 - REFLECTED CEILING PLAN  
1/16" = 1'-0"





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**TOWNZEN & ASSOCIATES  
PLAN APPROVAL**  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: *Lee Jensen*  
09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

ENLARGED RCP -  
FLOOR 1A

A2.22

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



UNIT 101  
4004 SF

ELECTRICAL  
SHAFT



EXHAUST HOOD  
SHAFT

EGRESS LIGHTING REVIEW UNDER  
THE SCOPE OF TENANT IMPROVEMENT  
PERMIT APPLICATIONS

WT9x27.5 TAPERED WIDEFLANGE  
INTERMEDIATE SUPPORT PER STRUCTURAL.  
SEE DETAIL 6/A6.06 FOR ADDITIONAL  
INFORMATION.

1 PARTIAL FLOOR 1 - ENLARGED RCP A

1/4" = 1'-0"




KEY PLAN





**T H O M A S**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | [tasolympia.com](http://tasolympia.com)



**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501



Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ENLARGED RCP - FLOOR 1B**

**A2.23**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**1 PARTIAL FLOOR 1 - ENLARGED RCP B**







**T H O M A S**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Reviewed for Code Compliance  
Construction Permitting Only  
*Rich Balders*  
**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: *Lee Spence*  
09/17/2019

**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019



**ENLARGED RCP - FLOOR 1C**

**A2.24**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**1 PARTIAL FLOOR 1 - ENLARGED RCP C**







**T H O M A S**  
 architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
 360.915.8775 | tasolympia.com



Reviewed for Code Compliance  
 Construction Permitting Only

*Rich Balders*

Olympia  
 Building Plans Examiner  
 Community Planning & Development Department  
 601 4th Ave East  
 Olympia, WA 98501  
 (360) 753-8248  
 rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
 PLAN APPROVAL

The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.

Approved as submitted: *Joe Spence*  
 09/17/2019


**EAST BAY LOT A**  
**WESTMAN MIL**  
 510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
**BUILDING PERMIT SET**  
 09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ENLARGED RCP - FLOOR 1D**

**A2.25**




All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tsoolympia.com



GENERAL NOTES

1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES.
2. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
3. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
4. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
5. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
6. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
7. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
8. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS.
9. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX).
10. ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
11. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
12. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
13. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
14. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.4.2

PLAN LEGEND

SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100

- ⊕ PENDANT LIGHT FIXTURE
- ⊙ RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
- SURFACE MOUNT LIGHT FIXTURE
- ⊙ WALL SCONCE FIXTURE
- ▬ VANITY LIGHT FIXTURE, WALL MOUNTED
- ⊕ EXIT LIGHTS
- ▬ LINEAR LED LIGHTING FIXTURE
- ▬ 1X4 LINEAR LED LIGHTING FIXTURE
- ▬ LINEAR LED, WITH EMERGENCY BATTERY PACK
- ⊕ BATHROOM LIGHT/EXHAUST FAN
- ⊕ KITCHEN EXHAUST FAN
- ⊕ 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
- ⊕ T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
- ⊕ SUSPENDED CEILING SYSTEM.
- ⊕ DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
- ⊕ 120V SMOKE DETECTOR
- ⊕ 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
- ⊕ FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
- ⊕ FAN COIL UNIT, SEE MECHANICAL DRAWINGS
- ⊕ SUPPLY DIFFUSER
- ⊕ RETURN DIFFUSER

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL

The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.

Approved as submitted: 09/17/2019

Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us


EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- 1. REVISION 1. 01-31-2019
- 1R. RESPONSE TO COMMENTS. 01-31-2019
- 2R. RESPONSE TO COMMENTS. 03-20-2019
- 3. REVISION 3. 06-13-2019
- 4. REVISION 4. 07-08-2019
- 5. REVISION 5. 08-02-2019
- 6. REVISION 6. 09-03-2019

ENLARGED RCP - FLOOR 2A


A2.26



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



1 PARTIAL FLOOR 2 - ENLARGED RCP A








THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | thosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- REVISION 1. 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3. 06-13-2019
- REVISION 4. 07-08-2019
- REVISION 5. 08-02-2019
- REVISION 6. 09-03-2019

ENLARGED RCP - FLOOR 2B

A2.27

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

GENERAL NOTES

- ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES.
- CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
- CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
- ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
- ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
- WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
- ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
- ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX).
- ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
- ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.



PLAN LEGEND

SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100

- PENDANT LIGHT FIXTURE
- RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
- SURFACE MOUNT LIGHT FIXTURE
- WALL SCONCE FIXTURE
- VANITY LIGHT FIXTURE, WALL MOUNTED
- EXIT LIGHTS
- LINEAR LED LIGHTING FIXTURE
- 1X4 LINEAR LED LIGHTING FIXTURE
- LINEAR LED, WITH EMERGENCY BATTERY PACK
- BATHROOM LIGHT/EXHAUST FAN
- KITCHEN EXHAUST FAN
- 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
- T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
- SUSPENDED CEILING SYSTEM.
- DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
- 120V SMOKE DETECTOR
- 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
- FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
- FAN COIL UNIT, SEE MECHANICAL DRAWINGS
- SUPPLY DIFFUSER
- RETURN DIFFUSER



1 PARTIAL FLOOR 2 - ENLARGED RCP B








THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



GENERAL NOTES

- 1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
2. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
3. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
4. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
5. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
6. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX). ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
7. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
8. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
9. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
10. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

PLAN LEGEND

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
PENDING LIGHT FIXTURE
RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
SURFACE MOUNT LIGHT FIXTURE
WALL SCONCE FIXTURE
VANITY LIGHT FIXTURE, WALL MOUNTED
EXIT LIGHTS
LINEAR LED LIGHTING FIXTURE
1X4 LINEAR LED LIGHTING FIXTURE
LINEAR LED, WITH EMERGENCY BATTERY PACK
BATHROOM LIGHT/EXHAUST FAN
KITCHEN EXHAUST FAN
5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
SUSPENDED CEILING SYSTEM.
DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
120V SMOKE DETECTOR
120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
FAN COIL UNIT, SEE MECHANICAL DRAWINGS
SUPPLY DIFFUSER
RETURN DIFFUSER



EAST BAY LOT A WESTMAN MILL 510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514 BUILDING PERMIT SET 09/09/2019

- REVISION 1, 01-31-2019
REVISION 2, 01-31-2019
REVISION 3, 06-13-2019
REVISION 4, 07-08-2019
REVISION 5, 08-02-2019
REVISION 6, 09-03-2019


ENLARGED RCP - FLOOR 2C

A2.28

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



1 PARTIAL FLOOR 2 - ENLARGED RCP C






**GENERAL NOTES**


- ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
- CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
- ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
- ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
- WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
- ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
- ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX).
- ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
- ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.4.2

**PLAN LEGEND**


- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- PENDANT LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED, PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - BATHROOM LIGHT/EXHAUST FAN
  - KITCHEN EXHAUST FAN
  - 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - SUSPENDED CEILING SYSTEM.
  - DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WAIT STOPPER #DT-300L)
  - 120V SMOKE DETECTOR
  - 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - SUPPLY DIFFUSER
  - RETURN DIFFUSER



**1 PARTIAL FLOOR 3 - ENLARGED RCP A**







**GENERAL NOTES**


1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES.
2. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
3. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
4. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
5. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
6. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
7. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
8. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS.
9. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (11 LUX).
10. ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
11. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
12. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
13. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
14. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

**PLAN LEGEND**

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- PENDING LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE. PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - ⊗ EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - ☐ BATHROOM LIGHT/EXHAUST FAN
  - ⊗ KITCHEN EXHAUST FAN
  - 1 HEIGHT 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - T&G HEIGHT 2 HEIGHT T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - SUSPENDED CEILING SYSTEM.
  - DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
  - 120V SMOKE DETECTOR
  - 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - ☐ FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - ☐ FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - ☐ SUPPLY DIFFUSER
  - ☐ RETURN DIFFUSER



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosoolympia.com




**EAST BAY LOT A  
WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**ENLARGED RCP - FLOOR 3B**

**A2.30**




All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

**1 PARTIAL FLOOR 3 - ENLARGED RCP B**







**GENERAL NOTES**


1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
2. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
3. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
4. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
5. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
6. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
7. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX).
8. ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
9. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
10. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
11. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
12. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

**PLAN LEGEND**

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- PENDING LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED, PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - BATHROOM LIGHT/EXHAUST FAN
  - KITCHEN EXHAUST FAN
  - 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - SUSPENDED CEILING SYSTEM.
  - DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
  - 120V SMOKE DETECTOR
  - 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - SUPPLY DIFFUSER
  - RETURN DIFFUSER



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lympia.com



**EAST BAY LOT A  
WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**ENLARGED RCP - FLOOR 3C**

**A2.31**



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

**1 PARTIAL FLOOR 3 - ENLARGED RCP C**








THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**GENERAL NOTES**

- ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
- CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
- ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
- ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
- WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
- ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
- ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX). ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
- FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
- ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

**PLAN LEGEND**

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- PENDANT LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - BATHROOM LIGHT/EXHAUST FAN
  - KITCHEN EXHAUST FAN
  - 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - SUSPENDED CEILING SYSTEM.
  - DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
  - 120V SMOKE DETECTOR
  - 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - SUPPLY DIFFUSER
  - RETURN DIFFUSER




EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- REVISION 1, 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3, 06-13-2019
- REVISION 4, 07-08-2019
- REVISION 5, 08-02-2019
- REVISION 6, 09-03-2019

ENLARGED RCP - FLOOR 4 - 5A


A2.32




All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**1 PARTIAL FLOOR 4 - 5 - ENLARGED RCP A**







**GENERAL NOTES**


1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
2. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
3. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
4. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
5. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
6. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
7. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX). ALL SMOKE ALARMS SHALL BE INTERCONNECTED. HARDWIRED W/ BATTERY BACKUP.
8. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED. HARDWIRED W/ BATTERY BACKUP.
9. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED. HARDWIRED W/ BATTERY BACKUP.
10. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
11. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

**PLAN LEGEND**

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- PENDANT LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE, PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - BATHROOM LIGHT/EXHAUST FAN
  - KITCHEN EXHAUST FAN
  - 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - SUSPENDED CEILING SYSTEM.
  - DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
  - 120V SMOKE DETECTOR
  - 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - SUPPLY DIFFUSER
  - RETURN DIFFUSER



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lympia.com



**EAST BAY LOT A  
WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501



Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- REVISION 1. 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3. 06-13-2019
- REVISION 4. 07-08-2019
- REVISION 5. 08-02-2019
- REVISION 6. 09-03-2019

**ENLARGED RCP - FLOOR 4 - 5B**


**A2.33**

**1 PARTIAL FLOOR 4 - 5 - ENLARGED RCP B**



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





**GENERAL NOTES**


1. ALL MECHANICAL AND ELECTRICAL WORK SHALL BE INSTALLED PER CURRENT CODE AND LOCAL JURISDICTION REQUIREMENTS. NO TRIM SHALL BE CUT TO ACCOMMODATE SWITCH PLATES.
2. CONTRACTOR SHALL PROVIDE SUBMITTAL CUT SHEETS TO ARCHITECT FOR REVIEW ON ALL LIGHTING PRODUCTS TO BE INSTALLED PRIOR TO ORDERING.
3. CONTRACTOR SHALL PROVIDE ALL BACKING AS REQUIRED FOR ALL FIXTURES.
4. ALL SURFACE MOUNT FIXTURES SHALL BE INSTALLED FLUSH TO FINISH SURFACE. CONTRACTOR TO COORDINATE JUNCTION BOX LOCATIONS PRIOR TO COVER.
5. ALL CEILING MOUNTED FIXTURES SHALL BE CENTERED IN SPACE UNLESS NOTED OTHERWISE (U.N.O.).
6. WALL MOUNTED LIGHT FIXTURES SHALL BE CENTERED ON WALL UNLESS NOTED OTHERWISE. SEE EXTERIOR AND INTERIOR ELEVATIONS FOR MOUNTING HEIGHTS.
7. ALL LIGHT FIXTURE GROUPS ABOVE SINKS SHALL BE CENTERED ON SINK.
8. ALL INTERIOR FIXTURES SHALL HAVE A MINIMUM OF 75% OF LIGHTING TO BE SUPPLIED WITH HIGH EFFICIENCY LAMPS. CONTRACTOR SHALL CONFIRM STAIRS HAVE AN ILLUMINATION LEVEL ON TREAD RUNS OF NOT LESS THAN 1 FOOT-CANDLE (1 LUX).
9. ALL SMOKE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
10. ALL CARBON MONOXIDE ALARMS SHALL BE INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
11. EXIT SIGNS SHALL BE INTERNALLY ILLUMINATED INTERCONNECTED, HARDWIRED W/ BATTERY BACKUP.
12. FIXTURE LOCATIONS ARE SHOWN FOR REFERENCE. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
13. ALL LIGHT FIXTURE PENETRATIONS THROUGH RATED HORIZONTAL ASSEMBLIES SHALL BE PROTECTED IN ACCORDANCE WITH IBC 714.42.

**PLAN LEGEND**

- SEE ELECTRICAL PLANS FOR ADDITIONAL INFORMATION AND FIXTURE SCHEDULES. LETTERS IN PARENTHESIS NEXT TO LIGHT FIXTURE SYMBOLS INDICATES FIXTURE TYPE AS LISTED IN THE LIGHT FIXTURE SCHEDULE ON SHEET E - 100
- ⊙ PENDANT LIGHT FIXTURE
  - RECESSED CAN LIGHT FIXTURE. PROVIDE WET LOCATION FIXTURE AS REQUIRED. PROVIDE WITH LED
  - SURFACE MOUNT LIGHT FIXTURE
  - ⊙ WALL SCONCE FIXTURE
  - VANITY LIGHT FIXTURE, WALL MOUNTED
  - ⊙ EXIT LIGHTS
  - LINEAR LED LIGHTING FIXTURE
  - 1X4 LINEAR LED LIGHTING FIXTURE
  - LINEAR LED, WITH EMERGENCY BATTERY PACK
  - ⊙ BATHROOM LIGHT/EXHAUST FAN
  - ⊙ KITCHEN EXHAUST FAN
  - 1 HEIGHT 5/8" TYPE "X" GYPSUM BOARD W/ LEVEL 4 FINISH
  - 2 HEIGHT T & G 1x6 TONGUE AND GROOVE WOOD SOFFIT
  - OS DUAL TECHNOLOGY AUTOMATIC OCCUPANCY SENSOR DEVICE WITH POWER PACK (WATT STOPPER #DT-300L)
  - S 120V SMOKE DETECTOR
  - SC 120V COMBINATION SMOKE/CARBON MONOXIDE DETECTOR WITH SOUNDER BASE
  - ⊙ FLOOD LIGHT, WITH EMERGENCY BATTERY PACK
  - ⊙ FAN COIL UNIT, SEE MECHANICAL DRAWINGS
  - ⊙ SUPPLY DIFFUSER
  - ⊙ RETURN DIFFUSER



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com




**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**ENLARGED RCP - FLOOR 4 - 5C**

**A2.34**



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

**1 PARTIAL FLOOR 4 - 5 - ENLARGED RCP C**







T H O M A S  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


ENLARGED  
PLANS-BATHROOMS

A2.35


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




5 ENLARGED BATHROOM PLAN TYPE A UNIT-309  
1/2" = 1'-0"




4 ENLARGED BATHROOM PLAN TYPE B UNIT-216  
1/2" = 1'-0"



3 ENLARGED BATHROOM PLAN TYPE B UNIT-416  
1/2" = 1'-0"



2 ENLARGED BATHROOM TYPE A UNIT-414/514  
1/2" = 1'-0"





1 ENLARGED BATHROOM PLAN TYPE A UNIT-217  
1/2" = 1'-0"







THOMAS architecture studios


525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



6 SOUTH ELEVATION  
3/32" = 1'-0"



1 WEST ELEVATION  
3/32" = 1'-0"



3 EXHAUST DISCHARGE LOCATION  
1/2" = 1'-0"

### ELEVATION KEY NOTES

- 1 BRICK FIELD - FOREST BLEND
- 2 BRICK SOLDIER - RAVEN
- 3 BRICK STILL - RAVEN
- 4 BRICK ACCENT BAND - RAVEN
- 5 WOOD RAINSCREEN - CEDAR
- 6 CEMENT PANEL W/ REGLET REVEAL - HARDI
- 7 METAL FLASHING - BLACK
- 8 STEEL CANOPY - BLACK, SEE DETAIL
- 9 WINDOWS - SEE SCHEDULE
- 10 STORE FRONT - SEE SCHEDULE
- 11 METAL RAILING - BLACK, SEE DETAIL
- 12 LIGHT FIXTURES - SEE ELECTRICAL SCHEDULE
- 13 BRICK RECESS - SEE DETAILS
- 14 METAL SUNSHADE - SEE DETAIL
- 15 PTHP GRILLE - ARCHITECTURE GRILL, SEE DETAIL
- 16 SOLID WASTE ENCLOSURE - SEE SHEET A1.01
- 17 HARDI INFILL PANEL
- 18 WOOD DOOR - SEE DOOR SCHEDULE
- 20 BREAK METAL INFILL PANEL
- 22 WOOD GRAIN DOOR AT STOREFRONT

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA - 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

### ELEVATIONS

# A3.01



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.







THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



2 NORTH ELEVATION-MAIN BLDG  
3/32" = 1'-0"



1 EAST ELEVATION  
3/32" = 1'-0"



### ELEVATION KEY NOTES

- 1 BRICK FIELD - FOREST BLEND
- 2 BRICK SOLDIER - RAVEN
- 3 BRICK STILL - RAVEN
- 4 BRICK ACCENT BAND - RAVEN
- 5 WOOD RAINSCREEN - CEDAR
- 6 CEMENT PANEL W/ REGLET REVEAL - HARDI
- 7 METAL FLASHING - BLACK
- 8 STEEL CANOPY - BLACK, SEE DETAIL
- 9 WINDOWS - SEE SCHEDULE
- 10 STORE FRONT - SEE SCHEDULE
- 11 METAL RAILING - BLACK, SEE DETAIL
- 12 LIGHT FIXTURES - SEE ELECTRICAL SCHEDULE
- 13 BRICK RECESS - SEE DETAILS
- 14 METAL SUNSHADE - SEE DETAIL
- 15 PTHP GRILLE - ARCHITECTURE GRILL, SEE DETAIL
- 16 SOLID WASTE ENCLOSURE - SEE SHEET A1.01
- 17 HARDI INFILL PANEL
- 18 WOOD DOOR - SEE DOOR SCHEDULE
- 20 BREAK METAL INFILL PANEL
- 22 WOOD GRAIN DOOR AT STOREFRONT

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA - 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

### ELEVATIONS

# A3.02


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | thosolympia.com




NOTE: ALIGN SIDING PANEL BREAKS WITH EDGE OF WINDOW, TYPICAL


1 SOUTH ELEVATION PANEL BREAKS  
3/32" = 1'-0"




5 REVEAL A (TYPICAL)  
1/8" = 1'-0"



6 Elevation 3 - a  
1/8" = 1'-0"



4 CEDAR SIDING PANEL BREAK  
3" = 1'-0"



3 HARDIEPANEL BREAK  
3" = 1'-0"



NOTE: ALIGN SIDING PANEL BREAKS WITH EDGE OF WINDOW, TYPICAL

2 WEST ELEVATION PANEL BREAKS  
3/32" = 1'-0"

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

ELEVATIONS

A3.03



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com




① NORTH ELEVATION-MAIN BLDG PANEL BREAKS  
3/32" = 1'-0"

NOTE: ALIGN SIDING PANEL BREAKS WITH EDGE OF WINDOW, TYPICAL



④ Elevation 2 - c  
1/8" = 1'-0"

③ Elevation 1 - c  
1/8" = 1'-0"



② EAST ELEVATION PANEL BREAK  
3/32" = 1'-0"

NOTE: ALIGN SIDING PANEL BREAKS WITH EDGE OF WINDOW, TYPICAL

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- ① REVISION 1, 01-31-2019
- ①R RESPONSE TO COMMENTS, 01-31-2019
- ②R RESPONSE TO COMMENTS, 03-20-2019
- ③ REVISION 3, 06-13-2019
- ④ REVISION 4, 07-08-2019
- ⑤ REVISION 5, 08-02-2019
- ⑥ REVISION 6, 09-03-2019

ELEVATION

A3.04


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


SECTIONS

A4.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



1 SECTION - WEST/EAST BUILDING KEY  
3/32" = 1'-0"



2 SECTION - WEST/EAST BUILDING KEY 1  
3/32" = 1'-0"





T H O M A S  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


SECTIONS

A4.02

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



4 SECTION - NORTH/SOUTH WALL A  
1/8" = 1'-0"



3 SECTION - NORTH/SOUTH WALL B  
1/8" = 1'-0"





T H O M A S  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


SECTIONS

A4.03

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



2 SECTION - NORTH/SOUTH WALL C  
1/8" = 1'-0"



1 SECTION - NORTH/SOUTH WALL D  
1/8" = 1'-0"





**THOMAS**  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com

4295 REGISTERED ARCHITECT  
RONALD S. THOMAS  
STATE OF WASHINGTON

Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not release the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501












Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1R REVISION 1. 01-31-2019
- 2R RESPONSE TO COMMENTS. 01-31-2019
- 3R RESPONSE TO COMMENTS. 03-20-2019
- 4 REVISION 3. 06-13-2019
- 5 REVISION 4. 07-08-2019
- 6 REVISION 5. 08-02-2019
- 7 REVISION 6. 09-03-2019

**SECTIONS - EAST STAIR**

**A4.04**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**8 STEEL TREAD/RISER**  
1 1/2" = 1'-0"

**4 EAST STAIR SECTION - C**  
1/4" = 1'-0"

**2 PLAN-EAST STAIR-FLOOR 1 TYP.**  
1/4" = 1'-0"

**3 PLAN-EAST STAIR-FLOOR 2-4 TYP.**  
1/4" = 1'-0"

**1 EAST STAIR SECTION**  
3/16" = 1'-0"

**5 EAST STAIR SECTION - B**  
1/4" = 1'-0"

**6 EAST STAIR SECTION - A**  
1/4" = 1'-0"

**9 BOTTOM OF STEEL LANDING**  
1 1/2" = 1'-0"

**10 TOP OF STEEL LANDING**  
1 1/2" = 1'-0"

**11 CONNECTION TO SLAB**  
1 1/2" = 1'-0"










THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501



Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS, 01-31-2019
- 2R RESPONSE TO COMMENTS, 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

**ELEVATOR SECTIONS**

**A4.06**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**2 SECTION - ELEVATOR @ NORTH ELEVATION**  
1/4" = 1'-0"

**1 SECTION - ELEVATOR @ EAST ELEVATION**  
1/4" = 1'-0"

**3 CEILING CHASE**  
1" = 1'-0"










THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- 1R REVISION 1. 01-31-2019
- 2R RESPONSE TO COMMENTS. 01-31-2019
- 3R RESPONSE TO COMMENTS. 03-20-2019
- 4 REVISION 3. 06-13-2019
- 5 REVISION 4. 07-08-2019
- 6 REVISION 5. 08-02-2019
- 7 REVISION 6. 09-03-2019

WALL SECTIONS

A5.02

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.

NOTE: LEVEL 3 AND LEVEL 4 ARE SIMILAR TO LEVEL 2.




3 SECTION I  
1/2" = 1'-0"

2 SECTION H  
1/2" = 1'-0"


1 SECTION G  
1/2" = 1'-0"

5 SECTION F  
1/2" = 1'-0"







**2 SECTION O**  
1/2" = 1'-0"



**4 SECTION L**  
1/2" = 1'-0"



**3 SECTION K**  
1/2" = 1'-0"



**1 SECTION J**  
1/2" = 1'-0"

NOTE: LEVEL 3 AND LEVEL 4 ARE SIMILAR TO LEVEL 2.



**THOMAS**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**WALL SECTIONS**

**A5.03**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

WALL SECTION


A5.04

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



NOTE: LEVEL 3 AND LEVEL 4 ARE SIMILAR TO LEVEL 2.




1 WALL SECTION E  
1/2" = 1'-0"





2 SECTION M  
1/2" = 1'-0"









**18 COLUMN WRAP (1 HR)**  
3" = 1'-0"




**17 ROOF CEILING ASSEMBLY**  
3" = 1'-0"




**16 FLOOR ASSEMBLY (1HR)**  
3" = 1'-0"




**15 INTERIOR STAIR WALL 2HR**  
3" = 1'-0"




**14 P.T. SLAB - INTERIOR (3 HOUR)**  
3" = 1'-0"




**13 DEMISING WALL 1HR**  
3" = 1'-0"




**12 INTERIOR 2X6 SHEAR WALL**  
3" = 1'-0"




**11 CORRIDOR WALL 2X6 1HR**  
3" = 1'-0"




**10 2X4 WALL 1 HR**  
3" = 1'-0"



**9 INTERIOR PARTITION-2HR**  
3" = 1'-0"




**10 2X4 WALL 1 HR**  
3" = 1'-0"




**11 CORRIDOR WALL 2X6 1HR**  
3" = 1'-0"




**6 EXTERIOR MASONRY WALL 1HR**  
3" = 1'-0"




**5 EXTERIOR MASONRY ON CONCRETE**  
3" = 1'-0"




**4 EXT. SIDING ON CONCRETE**  
3" = 1'-0"



**3 SHAFT WALL 2HR.**  
3" = 1'-0"




**2 EXT. CONCRETE WALL**  
3" = 1'-0"



**1 CONCRETE WALL**  
3" = 1'-0"



THOMAS architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tsoolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with applicable codes.  
Approved as submitted: 09/17/2019

**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1. REVISION 1. 01-31-2019
- 2. RESPONSE TO COMMENTS. 01-31-2019
- 3. RESPONSE TO COMMENTS. 03-20-2019
- 4. REVISION 3. 06-13-2019
- 5. REVISION 4. 07-08-2019
- 6. REVISION 5. 08-02-2019
- 7. REVISION 6. 09-03-2019

**ASSEMBLY DETAILS**

**A6.01**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1. REVISION 1. 01-31-2019
- 2. RESPONSE TO COMMENTS. 01-31-2019
- 3. RESPONSE TO COMMENTS. 03-20-2019
- 4. REVISION 3. 06-13-2019
- 5. REVISION 4. 07-08-2019
- 6. REVISION 5. 08-02-2019
- 7. REVISION 6. 09-03-2019


DOOR DETAILS

A6.02


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




3 DOOR OVERHEAD @ TRANSOM  
3" = 1'-0"




2 DOOR JAMB @ BRICK  
3" = 1'-0"




1 DOOR THRESHOLD @ SLAB  
3" = 1'-0"




7 DOOR HEAD/JAMB @ INT.  
3" = 1'-0"




6 THRESHOLD @ INTERIOR  
3" = 1'-0"




5 DOOR HEAD/JAMB @ UNIT  
3" = 1'-0"




4 THRESHOLD @ UNIT ENTRY  
3" = 1'-0"




13 DOOR HEAD @ STOREFRONT  
3" = 1'-0"




12 DOOR JAMB @ STOREFRONT  
3" = 1'-0"



11 THRESHOLD @ STOREFRONT  
3" = 1'-0"




15 DOOR THRESHOLD @ PATIO  
3" = 1'-0"



14 THRESHOLD FLASHING  
3" = 1'-0"


AR






**GENERAL NOTES:**


- SEE FORTIFIBER BUILDING SYSTEMS HIGH PERFORMANCE WINDOW FLASHING SYSTEM WITH ADDITION OF CORNER SHIELD AND SILL WRAP FOR MANUFACTURER'S SPECIFIC INSTRUCTIONS
- PREPARE ALL SURFACES AS RECOMMENDED BY WINDOW FLASHING MANUFACTURER.



**3 WINDOW HEAD**  
3" = 1'-0"




**2 WINDOW MULLION**  
3" = 1'-0"




**1 WINDOW SILL AT SIDING**  
3" = 1'-0"


**10 TYPICAL TRIM @ INTERIOR**  
1/2" = 1'-0"




**9 TYP. TRIM ELEVATION @ INT.**  
3/4" = 1'-0"




**7 WINDOW JAMB PLAN**  
3" = 1'-0"




**5 WINDOW JAMB @ BRICK**  
3" = 1'-0"




**8 TYP. WINDOW @ SIDING**  
3/4" = 1'-0"



**6 WINDOW SILL @ BRICK**  
3" = 1'-0"



**4 WINDOW HEAD @ BRICK**  
3" = 1'-0"



EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**WINDOW DETAILS**

**A6.03**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





T H O M A S  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**WINDOW STOREFRONT DETAILS**

**A6.04**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




**3 STOREFRONT HEAD @ BALCONY**  
3" = 1'-0"



**2 STOREFRONT JAMB**  
3" = 1'-0"




**4 STOREFRONT HEAD @ CONCRETE**  
3" = 1'-0"




**1 STOREFRONT SILL**  
3" = 1'-0"







**8 TYP. CONCRETE SLAB**  
3" = 1'-0"



**7 BASE OF WALL @ BRICK**  
3" = 1'-0"




**6 BASE OF WALL @ CONCRETE**  
3" = 1'-0"




**5 THROUGH WALL**  
3" = 1'-0"

**9 NOT USED**  
1 1/2" = 1'-0"




**4 PLAN DETAIL AT COLUMN**  
3" = 1'-0"




**3 ELEVATOR PIT**  
3" = 1'-0"

**2 NOT USED**  
1" = 1'-0"




**1 CONCRETE FOOTING**  
1 1/2" = 1'-0"







**10 SUNSHADE @ FIBER CEMENT SIDIN**  
1" = 1'-0"




**9 SUNSHADE @ WOOD SIDING**  
1" = 1'-0"




**8 SUNSHADE @ BRICK**  
1" = 1'-0"




**7 ROOF SCUTTLE**  
3" = 1'-0"




**6 CANOPY**  
1" = 1'-0"




**5 PIPE PENETRATION @ ROOF**  
3" = 1'-0"




**4 PARAPET @ BRICK**  
3" = 1'-0"



**3 INSULATION @ OVERHANG**  
1 1/2" = 1'-0"



**02 PARAPET @ SIDING**  
3" = 1'-0"



**1 PARAPET BASE OF WALL**  
3" = 1'-0"


1R	REVISION 1. 01-31-2019
1R	RESPONSE TO COMMENTS. 01-31-2019
2R	RESPONSE TO COMMENTS. 03-20-2019
3	REVISION 3. 06-13-2019
4	REVISION 4. 07-08-2019
5	REVISION 5. 08-02-2019
6	REVISION 6. 09-03-2019





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1R REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


BUILDING ENVELOPE

A6.07


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




4 KNIFE PLATE DETAIL PLAN  
3" = 1'-0"




3 MECHANICAL CURB  
3" = 1'-0"




2 RAILING @ CORNER CONDITION  
3" = 1'-0"




1 RAILING @ END  
3" = 1'-0"




7 OUTSIDE CORNER  
3" = 1'-0"




6 INSIDE CORNER @ BRICK  
3" = 1'-0"




5 INSIDE CORNER @ SIDING & BRICK  
3" = 1'-0"




10 BRICK LEDGER  
3" = 1'-0"




9 BRICK SIDING @ JOINT  
3" = 1'-0"




8 DECK EDGE GUARD RAIL DETAIL  
3" = 1'-0"



13 ROOF HATCH DETAIL  
1" = 1'-0"



12 STOREFRONT SILL ON SLAB  
3" = 1'-0"




11 BRICK @ TIE  
3" = 1'-0"





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


EXTERIOR  
BUILDING  
DETAILS

A6.08


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




9 INSIDE CORNER CONCRETE WALL BRICK TO WOOD  
3" = 1'-0"




8 INSIDE CORNER CONCRETE WALL  
3" = 1'-0"




7 CONCRETE @ RECESS  
1 1/2" = 1'-0"




6 GAURDRAIL @ OUTDOOR PATIO  
1 1/2" = 1'-0"




3 CONCRETE WALL @ BRICK & STOREFRONT JAMB  
1 1/2" = 1'-0"




5 CONCRETE WALL @ CANOPY  
1 1/2" = 1'-0"



4 CONCRETE WALL @ BRICK & STOREFRONT SILL  
1 1/2" = 1'-0"




1 CONCRETE @ WINDOW HEAD & BRICK  
1 1/2" = 1'-0"





2 CONCRETE THROUGH WALL  
1 1/2" = 1'-0"






**8 PTHP MECHANICAL UNIT**  
3" = 1'-0"




**7 EXHAUST VENTING**  
3" = 1'-0"


**6 EXTERIOR WALL WOOD SIDING**  
3" = 1'-0"




**5 EXTERIOR WALL PANEL SIDING**  
3" = 1'-0"




**3 BRICK ACCENT BAND**  
3" = 1'-0"



**2 ROUGH CONCRETE WALL**  
3" = 1'-0"



**1 OUTSIDE CORNER CONCRETE WALL BRICK TO BRICK**  
3" = 1'-0"



- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019

EXTERIOR WALL  
DETAILS


A6.09





**THOMAS**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



**EAST BAY LOT A  
WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


**AIR BARRIER**

**A6.11**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




**3 TYPICAL WINDOW MULLION @ CONCRETE**  
1 1/2" = 1'-0"




**6 WINDOW HEAD @ ROOF CONDITION**  
1 1/2" = 1'-0"




**2 CONNECTION @ ROOF AND FLOOR**  
1 1/2" = 1'-0"




**5 TYPICAL TROUGH WALL**  
1 1/2" = 1'-0"



**1 PARAPIT DETAIL @ 2ND FLOOR ROOF**  
1 1/2" = 1'-0"




**4 TYPICAL WINDOW MULLION @ WOOD**  
1 1/2" = 1'-0"




**8 TYPICAL EXTERIOR WALL SECTION**  
1/2" = 1'-0"

**7 TYPICAL EXTERIOR WALL SECTION @ 2ND FLOOR ROOF**  
1/2" = 1'-0"





**6 TYPICAL UNIT LAYOUT**  
3/16" = 1'-0"



**3 BUILDING SECTION**  
1/8" = 1'-0"



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Reviewed for Code Compliance  
Companion Permitting Only

*Mark Robert*

Olympia  
Building Plans Examiner  
Community Planning & Development Department  
601 4th Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**TOWNZEN & ASSOCIATES**  
PLAN APPROVAL

The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.

Approved as submitted: *Joe Spence*  
09/17/2019

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1, 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3, 06-13-2019
- 4 REVISION 4, 07-08-2019
- 5 REVISION 5, 08-02-2019
- 6 REVISION 6, 09-03-2019


**AIR BARRIER**

**A6.12**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




**7 UNIT DEMISING WALL TO CEILING/FLOOR**  
1 1/2" = 1'-0"




**5 DRYWALL PENETRATIONS, TYP.**  
1 1/2" = 1'-0"



**4 UNIT DEMISING WALL @ L2-L5 TYP.**  
1 1/2" = 1'-0"




**2 PENETRATION @ CLG, TYP.**  
1 1/2" = 1'-0"



**1 RECESSED FIXTURE @ CLG, TYP.**  
1 1/2" = 1'-0"

1. SEAL THE GWB AT THE WALL/ CEILING AND WALL FLOOR INTERSECTION AT THE EXTERIOR, CORRIDOR AND PARTY WALLS OF ALL DWELLING UNITS. SEE DETAILS 4.5, AND 7 ON SHEET A6.12 FOR TYPICAL DETAILS AND ACOUSTIC DETAILS
2. PROVIDE SEALANT AT ALL PLUMBING PIPE PENETRATIONS THROUGH THE GWB. SEE ACOUSTIC CAULKING REQUIREMENTS ON SHEET DETAILS 1.2, AND 5 IN SHEET A6.12. THIS INCLUDES BUT IS NOT LIMITED TO:
  - 2.1 THE WATER CLOSET SUPPLY LINE
  - 2.2 PLUMBING WASTE LINES
  - 2.3 SINK, LAV WASTE, AND SUPPLY LINES.
  - 2.4 SHOWER AND TUB DRAIN LINES
3. SEAL THE GWB AND WINDOW SILLS TO THE WINDOW FRAMES AT THE SILL, JAMBS, AND HEAD. SEE DETAILS ON SHEET A6.03 FOR TYPICAL CONDITIONS
4. PROVIDE A PUTTY PACK AT ALL OUTLETS AND SWITCHES AT THE UNIT PARTY WALLS WHEN THE DEVICES ARE LESS THAN 24" APART. SEE DETAIL 5 ON SHEET A6.12.
5. PROVIDE 20 MINUTE RATED SMOKE GASKETS AT THE UNIT ENTRY DOORS AT THE DOOR HEAD AND JAMBS. SEE DETAILS ON SHEET A6.02.
6. PROVIDE A THRESHOLD AND DOOR SWEEP AT THE UNIT ENTRY DOORS. SEE DETAILS ON SHEET A6.02.
7. SEAL THE GWB AT THE WALL/ CEILING INTERSECTION AT INTERIOR WALLS AT ALL DWELLING UNITS. SEE DETAILS ON SHEET >>>>
8. SEAL UNIT ELECTRICAL PANEL AND LOW VOLTAGE PANELS TO THE GWB.
9. SEAL ANY WIRING PENETRATIONS THAT DO NOT REQUIRE FIRE SEALING TREATMENT.
10. COMPLETED BUILDING TO BE TESTED PER WSEC C402.5.1.2.








THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



TOWNZEN & ASSOCIATES  
PLAN APPROVAL  
The plans submitted for review are approved in accordance with local state applicable standards. This approval does not relieve the applicant of the responsibility of compliance with the applicable codes.  
Approved as submitted: 09/17/2019

EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1. REVISION 1. 01-31-2019
- 2. RESPONSE TO COMMENTS. 01-31-2019
- 3. RESPONSE TO COMMENTS. 03-20-2019
- 4. REVISION 3. 06-13-2019
- 5. REVISION 4. 07-08-2019
- 6. REVISION 5. 08-02-2019
- 7. REVISION 6. 09-03-2019


### KITCHEN ELEVATIONS

# A7.01


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




14 KITCHEN ELEV. 4 - D  
SCALE: 1/2" = 1'-0"




13 KITCHEN ELEV. 4 - A  
SCALE: 1/2" = 1'-0"




12 KITCHEN ELEV. 4 - B  
SCALE: 1/2" = 1'-0"




11 UNIT 409 KITCHEN ELEV. 9-A  
SCALE: 1/2" = 1'-0"



10 UNIT 409 KITCHEN ELEV. 9-B  
SCALE: 1/2" = 1'-0"




9 UNIT 409 KITCHEN ELEV. 9-C  
SCALE: 1/2" = 1'-0"




8 UNIT 211 KITCHEN ELEV. 8-A  
SCALE: 1/2" = 1'-0"




7 UNIT 211 KITCHEN ELEV. 8-B  
SCALE: 1/2" = 1'-0"




6 UNIT 211 KITCHEN ELEV. 8-C  
SCALE: 1/2" = 1'-0"




5 UNIT 214 KITCHEN ELEV. 1 - B  
SCALE: 1/2" = 1'-0"




4 UNIT 214 KITCHEN ELEV. 1-A  
SCALE: 1/2" = 1'-0"



3 UNIT 213 KITCHEN ELEV. 3 - D (TYPICAL)  
SCALE: 1/2" = 1'-0"



2 UNIT 213 KITCHEN ELEV. 3 - A (TYPICAL)  
SCALE: 1/2" = 1'-0"



1 UNIT 213 KITCHEN ELEV. 3 - B (TYPICAL)  
SCALE: 1/2" = 1'-0"

#### KITCHEN ELEVATION GENERAL NOTES


1. ALL INTERIOR ELEVATIONS ARE TYPE B UNITS UNLESS NOTED OTHERWISE.
2. ALL TYPE A UNITS ARE TO COMPLY WITH SECTION 1003 OF THE ICC A117.1 2009.
3. ALL TYPE B UNITS ARE TO COMPLY WITH SECTION 1004 OF THE ICC A117.1 2009.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019


- REVISION 1. 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3. 06-13-2019
- REVISION 4. 07-08-2019
- REVISION 5. 08-02-2019
- REVISION 6. 09-03-2019

KITCHEN ELEVATIONS


A7.02

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.


**TYPE A ACCESSIBLE UNITS:**  
1003.9 OPERABLE PARTS.  
LIGHTING CONTROLS, ELECTRICAL PANELBOARD, ELECTRICAL SWITCHES AND RECEPTACLE OUTLETS, ENVIRONMENTAL CONTROLS, APPLIANCE CONTROLS, OPERATING HARDWARE FOR OPERABLE WINDOWS, PLUMBING FIXTURE CONTROLS, AND USER CONTROLS FOR SECURITY OR INTERCOM SYSTEMS SHALL COMPLY WITH SECTION 309.




13 TYPICAL TYPE A UNIT 217-A  
SCALE: 1/2" = 1'-0"




9 UNIT 216 KITCHEN ELEV. 2 - C  
SCALE: 1/2" = 1'-0"




10 UNIT 317 KITCHEN ELEV. 5-C  
SCALE: 1/2" = 1'-0"




11 UNIT 317 KITCHEN ELEV. 5-A  
SCALE: 1/2" = 1'-0"




12 UNIT 317 KITCHEN ELEV. 5-B  
SCALE: 1/2" = 1'-0"




14 TYPICAL TYPE A UNIT 217-B  
SCALE: 1/2" = 1'-0"




5 COMMUNAL KITCHEN ADA-B  
SCALE: 1/2" = 1'-0"




6 COMMUNAL KITCHEN ADA-C  
SCALE: 1/2" = 1'-0"




7 UNIT 216 KITCHEN ELEV. 2 - B  
SCALE: 1/2" = 1'-0"




8 UNIT 216 KITCHEN ELEV. 2 - A  
SCALE: 1/2" = 1'-0"




1 UNIT 206 KITCHEN ELEV. 10-C  
SCALE: 1/2" = 1'-0"



2 UNIT 206 KITCHEN ELEV. 10-B  
SCALE: 1/2" = 1'-0"



3 UNIT 206 KITCHEN ELEV. 10-A  
SCALE: 1/2" = 1'-0"




4 COMMUNAL KITCHEN ADA-A  
SCALE: 1/2" = 1'-0"

**KITCHEN ELEVATION GENERAL NOTES**  
1. ALL INTERIOR ELEVATIONS ARE TYPE B UNITS UNLESS NOTED OTHERWISE.  
2. ALL APPLIANCES IN COMMUNITY ROOM KITCHEN IS TO BE EQUIPPED WITH OPERABLE PARTS IN COMPLIANCE W/ A117.1 2009 804.5/ 309




**GENERAL NOTES**


- ALL INTERIOR ELEVATIONS ARE TYPE B UNITS UNLESS NOTED OTHERWISE.
- ALL TYPE A UNITS ARE TO COMPLY WITH SECTION 1003 OF THE ICC A117.1 2009.
- ALL TYPE B UNITS ARE TO COMPLY WITH SECTION 1004 OF THE ICC A117.1 2009.
- FLUSH CONTROL SHALL BE LOCATED ON THE OPEN SIDE OF THE WATER CLOSET PER A117.1-1003.11.2.4.6.
- ALL RESTROOMS IN THE TYPE 'B' UNITS SHALL COMPLY WITH OPTION A OR B PER A117.2009 1004.11.3.
- REMOVABLE BASE CABINETS IN TYPE 'A' UNITS UNDER SINK, TYPICAL COMPLY W/ A117.1 1003.11.2.2.




**11 TYPICAL TYPE A UNIT 217 4-B**  
SCALE: 1/2" = 1'-0"




**10 TYPICAL TYPE A UNIT 217 4-A**  
SCALE: 1/2" = 1'-0"




**9 UNIT 213 BATH TUB 1-D, (TYPICAL)**  
SCALE: 1/2" = 1'-0"




**8 COMMUNITY BATHROOM ELEV. A**  
SCALE: 1/2" = 1'-0"




**7 COMMUNITY BATHROOM ELEV. B**  
SCALE: 1/2" = 1'-0"




**6 UNIT 317 STANDING, ( RIGHT, TYP.)**  
SCALE: 1/2" = 1'-0"




**5 UNIT 201 STANDING, (LEFT, TYP.)**  
SCALE: 1/2" = 1'-0"




**4 UNIT 217 SMALL BATHROOM 5-D, (RIGHT, TYP.)**  
SCALE: 1/2" = 1'-0"




**3 UNIT 216 SMALL BATHROOM 3-F, (LEFT, TYP.)**  
SCALE: 1/2" = 1'-0"



**2 UNIT 211 STD. BATHROOM 1-E, (RIGHT, TYP.)**  
SCALE: 1/2" = 1'-0"



**1 UNIT 213 STD. BATHROOM 1-B, (LEFT, TYP.)**  
SCALE: 1/2" = 1'-0"




**12 TYPICAL TYPE A UNIT 217 4-C**  
SCALE: 1/2" = 1'-0"





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


LOBBY  
ELEVATIONS

A7.05


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




6 LOBBY PARCEL BOX  
1/4" = 1'-0"




5 LOBBY MAIL BOX  
1/4" = 1'-0"




2 LOBBY WEST  
1/4" = 1'-0"



4 LOBBY NORTH  
1/4" = 1'-0"



1 LOBBY EAST  
1/4" = 1'-0"




3 LOBBY SOUTH  
1/4" = 1'-0"





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA - 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019


CORRIDOR  
ELEVATION

A7.06


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




4 CORRIDOR ELEVATION- NORTH (TYPICAL 1)  
1/4" = 1'-0"



3 CORRIDOR ELEVATION- NORTH (TYPICAL 2)  
1/4" = 1'-0"



2 CORRIDOR ELEVATION - SOUTH (TYPICAL 1)  
1/4" = 1'-0"




1 CORRIDOR ELEVATION - SOUTH (TYPICAL 2)  
1/4" = 1'-0"







**T H O M A S**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



3


- WALL SCONCE  
KUZCO 606031 B2  
(TYPICAL)
- 3 UNIT NUMBER RAISED, BLACK
- 4 UNIT NUMBER BRAILLE




**5 UNIT SCONCE**  
SCALE: 1/2" = 1'-0"

**4 CORRIDOR ELEVATION- EAST**  
1/4" = 1'-0"

**3 CORRIDOR ELEVATION- WEST**  
1/4" = 1'-0"



**2 CORRIDOR ELEVATION- 2ND FLOOR NORTH Copy 1**  
1/4" = 1'-0"



**1 CORRIDOR ELEVATION- 2ND FLOOR NORTH**  
1/4" = 1'-0"

**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019

- 1 REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- 3 REVISION 3. 06-13-2019
- 4 REVISION 4. 07-08-2019
- 5 REVISION 5. 08-02-2019
- 6 REVISION 6. 09-03-2019

**CORRIDOR ELEVATION**

**A7.07**



All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.






**T H O M A S**  
architecture studios


525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com




**6 ELEVATOR LOBBY 3-WEST (TYPICAL)**  
SCALE: 1/4" = 1'-0"




**5 ELEVATOR LOBBY 3 - EAST (TYPICAL)**  
SCALE: 1/4" = 1'-0"




**3 ELEVATOR LOBBY - SECOND FLOOR WEST**  
SCALE: 1/4" = 1'-0"



**4 ELEVATOR LOBBY - SECOND FLOOR EAST**  
SCALE: 1/4" = 1'-0"



**2 ELEVATOR LOBBY - FIRST FLOOR WEST**  
SCALE: 1/4" = 1'-0"



**1 ELEVATOR LOBBY - FIRST FLOOR EAST**  
SCALE: 1/4" = 1'-0"

**EAST BAY LOT A**  
**WESTMAN MIL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**BUILDING PERMIT SET**  
09/09/2019




- △ REVISION 1. 01-31-2019
- 1R RESPONSE TO COMMENTS. 01-31-2019
- 2R RESPONSE TO COMMENTS. 03-20-2019
- △ 3 REVISION 3. 06-13-2019
- △ 4 REVISION 4. 07-08-2019
- △ 5 REVISION 5. 08-02-2019
- △ 6 REVISION 6. 09-03-2019

**ELEVATOR LOBBY**


**A7.08**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





### 3 TYPICAL WINDOW GROUPS



### 2 WINDOW TYPES (ALT.)



### DOOR SCHEDULE

TYPE	HEIGHT	WIDTH	CONSTRUCTION TYPE	FINISH	FIRE RATING	HARDWARE	TYPE COMMENTS
A	7'-0"	3'-0"	WOOD	PAINT	20 MIN.		UNIT ENTRY DOOR
A2	7'-0"	3'-0"					UNIT BATHROOM
B	7'-0"	2'-10"	WOOD				UNIT BEDROOM
C	7'-0"	2'-10"	WOOD	PAINT		3.5	UNIT CLOSET
D	7'-0"	2'-10"	WOOD	PAINT		3.5	UNIT CLOSET
D1	7'-0"	2'-0"	WOOD				UNIT CLOSET
D2	7'-0"	2'-6"	WOOD	PAINT		3.5	UNIT CLOSET
E	7'-0"	5'-0"	WOOD	PAINT		4	UNIT CLOSET
E1	7'-0"	6'-0"	WOOD	PAINT		4	UNIT CLOSET
F1	7'-0"	5'-0"					UNIT LAUNDRY
G1	7'-0"	2'-0"	WOOD	PAINT	90 MIN.	3.5,7,10	MISC.
H	7'-0"	3'-0"	METAL	PAINT		5.6,11,13	BIKE STORAGE
H1	7'-0"	3'-0"	METAL	PAINT	90 MIN.	5.6,11,13	STAIR EXTERIOR
J	7'-0"		WOOD	CLEAR SEALER		5(PAIR),6,7,11,14,15	MAIN ENTRY
J1	7'-0"		WOOD				RETAIL ENTRY
J2	7'-9 1/2"	5'-9 3/16"	ALUMINUM	DARK BRONZE		3.5 (PAIR),6,10,11	COMMON SPACE
K	7'-0"	3'-0"	WOOD		90 MIN.		STAIR INTERIOR
N	7'-9 1/2"	2'-11 3/4"	FIBERGLASS	DARK BRONZE		3.5,6,10,11	UNIT W/ PATIO
S	7'-0"	3'-0"	FIBERGLASS	DARK BRONZE	60 MIN.	2.5,7,9,10,11	
T	7'-0"	3'-0"				3	
Z	7'-0"	6'-0"				5.6,11,13	COMMUNAL ROOM

### GENERAL NOTES:


- WINDOWS SHALL HAVE A MINIMUM U-VALUE = 0.30 OR BETTER & A SHGC = 0.40 OR BETTER.
- ALL WINDOWS TO RECEIVE GYPSUM WALL BOARD WRAP @ HEAD AND JAMBS, PAINT GRADE WOOD AT SILL & APRON.
- BASIS OF DESIGN: VINYL WINDOWS SHALL BE MILGARD VINYL, OR APPROVED EQUAL. COLOR: DARK BRONZE EXTERIOR, WHITE INTERIOR.
- ALL PRODUCTS SHALL BE LABELED W/ RATED U-FACTOR, SHGC, VT, & LEAKAGE RATING.
- EMERGENCY ESCAPE SHALL BE OPERATIONAL FROM INSIDE THE ROOM WITHOUT USE OF TOOLS. PER IBC 1030.4. AND OPERATIONAL PARTS SHALL BE OPERABLE W/ ONE HAND & SHALL NOT REQUIRE TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST TO ACTIVATE. OPERABLE FORCE SHALL BE 5 POUNDS MAX.
- ALL OPERABLE WINDOWS ABOVE THE FIRST FLOOR WITH A SILL HEIGHT LESS THAN 36" ABOVE THE FINISHED FLOOR SHALL BE EQUIPPED WITH A FACTORY INSTALLED FALL PREVENTION DEVICE PER ASTM F 2090
- ALL WIDOWS TO HAVE TRICKLE VENTS 15" TO 48" AFF. PROVIDE 12 SQUARE INCHES PER UNIT. SEE MECHANICAL FOR WHOLE HOUSE VENTILATION METHODS.

### HARDWARE TYPES - DESIGN BASIS


TYPE	NAME	NOTE
1	ENTRY	KEYED LEVERSET
2	PRIVACY	PRIVACY LEVERSET
3	PASSAGE	PASSAGE LEVERSET
4	BI-PASS	FINGER PULL
5	HINGES	OIL RUBBED BRONZE FINISH
6	CLOSER	PROVIDE SELF CLOSING HINGES OR CLOSER PER IBC 716.5.9
7	DEAD BOLT	OIL RUBBED BRONZE FINISH
8	PANIC BAR	VON DUPRIN 987.5, OIL RUBBED BRONZE FINISH
9	DOOR BUMPER	WALL MOUNTED DOOR BUMPER
10	SMOKE/WEATHER SEAL	BLACK
11	THRESHOLD	BLACK
12	DOOR VIEWER MOUNT	50" ABOVE FINISH FLOOR
13	KEYPAD	COMBO LOCK, OIL RUBBED BRONZE FINISH
14	FLUSH BOLT	RECESSED FLUSH BOLT
15	DOOR STOP	FOLD DOWN DOOR STOP

### NOTES:


- DOOR BASIS OF DESIGN:  
EXTERIOR ENTRY: SIMPSON DOOR COMPANY, EXTERIOR FRENCH AND SASH DOOR WIDE SILE W/ 3/4" GLASS IN DOOR, OR APPROVED EQUAL. "SHALL HAVE A MINIMUM U-VALUE = 0.6 OR BETTER & SHGC = 0.40 OR BETTER"  
INTERIOR DOORS: 2-PANEL DOORS SHALL BE MASONITE, HERITAGE SERIES, LOGAN, SOLID CORE DOOR, SMOOTH FINISH. PAINT PER FINISH SCHEDULE, OR APPROVED EQUAL.
- PROVIDE STEEL FLUSH PANEL DOORS AT EXTERIOR UTILITY SPACES.
- MAXIMUM AIR INFILTRATION RATE TO COMPLY WITH TABLE C402.4.3 OF THE WAC 51-11C-40243. MAXIMUM RATE:  
3.a. SWINGING DOORS TO HAVE 0.2 CFM/SF, 0.30 CFM PER SQ FT IS ALLOWED WHEN TESTED IN ACCORDANCE, PER WAC 51-11C-40243.
- ALL EXTERIOR DOORS SHALL BE AAMA PERFORMANCE RATED DOOR TO MEET MINIMUM THERMAL PERFORMANCE CRITERIA AND AIR LEAKAGE PER THE ENERGY CODE, WITH A WATER PENETRATION RESISTANCE RATING.
- HANDLES, PULLS, LATCHES, LOCKS, AND OTHER OPERATING DEVICES ON ACCESSIBLE DOORS SHALL HAVE A SHAPE THAT IS EASY TO GRASP WITH ONE HAND AND DOES NOT REQUIRE TIGHT GRASPING, TIGHT PINCHING, OR TWISTING OF THE WRIST TO OPERATE.
- ALL DOORS W/GLAZING SHALL BE SAFETY GLAZING PER IBC 2406.



### 1 DOOR TYPES



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- REVISION 1, 01-31-2019
- RESPONSE TO COMMENTS. 01-31-2019
- RESPONSE TO COMMENTS. 03-20-2019
- REVISION 3, 06-13-2019
- REVISION 4, 07-08-2019
- REVISION 5, 08-02-2019
- REVISION 6, 09-03-2019

### DOOR SCHEDULE

# A8.01


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
WESTMAN MIL  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
BUILDING PERMIT SET  
09/09/2019

- △ REVISION 1. 01-31-2019
- △ RESPONSE TO COMMENTS. 01-31-2019
- △ RESPONSE TO COMMENTS. 03-20-2019
- △ REVISION 3. 06-13-2019
- △ REVISION 4. 07-08-2019
- △ REVISION 5. 08-02-2019
- △ REVISION 6. 09-03-2019


STOREFRONT  
SCHEDULE

A8.02


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.




13 STOREFRONT JAMB @ TRANSOM  
3" = 1'-0"




9 STOREFRONT J1 & J2  
1/4" = 1'-0"




10 STOREFRONT K  
1/4" = 1'-0"




11 STOREFRONT L  
1/4" = 1'-0"




12 STOREFRONT M1 & M2  
1/4" = 1'-0"



15 STOREFRONT P @ LOBBY WEST  
1/4" = 1'-0"




14 STOREFRONT - SECOND FLOOR BALCONY  
1/4" = 1'-0"




5 STOREFRONT E  
1/4" = 1'-0"


NOTE: STOREFRONT WINDOWS SHALL HAVE A MINIMUM U-VALUE = 0.38 OR BETTER & SHGC = 0.40 OR BETTER




6 STOREFRONT F1 & F2  
1/4" = 1'-0"




7 STOREFRONT G  
1/4" = 1'-0"




8 STOREFRONT H  
1/4" = 1'-0"




1 STOREFRONT A  
1/4" = 1'-0"



2 STOREFRONT B  
1/4" = 1'-0"



3 STOREFRONT C  
1/4" = 1'-0"



4 STOREFRONT D1 & D2  
1/4" = 1'-0"



## BASIS OF DESIGN: WESTMAN MILL

### SITE FINISHES

- PATIOS AND WALKWAYS
- CONCRETE W/ BROOM FINISH (UNO)
- BOARDWALK: STAMPED CONCRETE; SLIP RESISTENT

### EXTERIOR BUILDING FINISHES

- ROOFING
- TPO ROOF MEMBRANE

### SIDING

- FIBER CEMENT SIDING: JAMES HARDI; 5/16" HARDIPANEL VERTICAL SIDING, SMOOTH; PRIME AND PAINT W/ SHERWIN WILLIAMS; COLOR TBD
- FIBER CEMENT SIDING REVEAL: FRY REGLET REVEAL - DRM-50-50- PAINT TO MATCH FCP SIDING
- BRICK: MUTUAL MATERIALS - FACING BRICK - FROST BLEND, EBONY, RAVEN

### TRIM

- WINDOW TRIM: CEDAR (FLASH AS REQ'D); PRIME AND PAINT W/ SHERWIN WILLIAMS "BEST BRONZE" SW 6160

TOP CASING: 5/4" X 6"

SIDE CASING: 1" X 4"

STOOL: 2x SHAPED TO DRAIN AND DRIP

APRON: NONE

- EAVES FASCIA (BEHIND GUTTERS): PRIME AND PAINT TO MATCH WINDOW TRIM AT 2X8 RAFTERS 5/4" X 6" CEDAR
- AT 2X10 RAFTERS 5/4" X 8" CEDAR
- GABLE FASCIA: PRIME AND PAINT TO MATCH WINDOW TRIM AT 2X10 RAFTERS; 1X3 CEDAR RAKE ON 5/4" X 10 CEDAR FASCIA
- AT 2X8 RAFTERS; 1X3 CEDAR RAKE ON 5/4" X 8 CEDAR FASCIA

### WINDOWS

- VINYL WINDOWS: PLY-GEM 600 SERIES, DARK BRONZE
- AT MAIN ENTRY: ALUMINIUM STOREFRONT WINDOWS AND DOORS; 1" LOW-E INSULATED GLAZING IN THERMALLY BROKEN STOREFRONT SYSTEM, ANODIZED "BRONZE" FACTORY FINISH

### SHEET METAL

- PARAPET CAP, GUTTERS, DOWNSPOUTS, AND SCUPPER/OVERFLOW; FF TO MATCH METAL ROOFING

### EXTERIOR GUARD

- POST: 1/2" X 3" STEEL POST; CUSTOM SHAPE (WELD TO 5" X 7" X 1/2" CONNECTION PLATE); FINISH PER STRUCTURAL METAL
- 1/2" SQUARE VERTICAL STEEL PICKETS AT 4" OC
- TOP RAIL CAP: 2X8 CEDAR; SLOPE TO DRAIN BACK TO BALCONY; STAIN AND SEAL

### EXTERIOR HAND RAIL

- HAND RAIL: GALVANIZED METAL 1 1/4" I.D. PIPE; PRIME AND PAINT TO MATCH METAL ROOFING

### PATIOS

- CONCRETE WITH BROOM FINISH

### INTERIOR FINISHES

#### CEILING:

- GWB: LIGHT ORANGE PEEL TEXTURE; PAINT WITH SHERWIN WILLIAMS, COLOR TBD, EGGSHELL SHEEN (UNO); VERIFY ALL PAINTS WITH TEST SAMPLE BEFORE FINAL PAINTING; COORDINATE W/ OWNER AND DESIGN PROFESSIONAL
- AT KITCHEN: CEILING TO HAVE SMOOTH SURFACE AND EPOXY PAINT FINISH; "WHITE" (TYP.)
- SEE GENERAL ROOM SCHEDULE FINISH NOTES FOR ADDITIONAL INFORMATION.
- ACCOUSTICAL TILE: LOBBY CEILING, GAME ROOM CEILING, LOUNGE CEILING; ARMSTRONG SURFACE APPLIED: DUNE - SECOND LOOK

#### WALLS:

- GWB WALLS: LIGHT ORANGE PEEL TEXTURE; PAINT WITH SHERWIN WILLIAMS, COLOR TBD, EGGSHELL SHEEN (UNO); VERIFY ALL PAINTS WITH TEST SAMPLE BEFORE FINAL PAINTING; COORDINATE W/ OWNER AND DESIGN PROFESSIONAL
- UP TO 3 ACCENT PAINT COLORS
- WOOD ACCENT WALLS IN LOBBY: 1x6 CEDAR PLANKS (1/4" GAP) WITH ON 5/8" FURRING STRIPS PAINTED BLACK. 2 SCREW FASTENERS PER END OF PLAN
- ELEVATOR LOBBY FLOORS 2-5: VINYL WALL ART FULL HEIGHT

#### WALL BASE:

- AT CARPETED AREAS: 4" RUBBER BASE: JOHNSONITE CONTOURED WALL BASE;
- AT VINYL FLOORING: 4" PAINT GRADE WOOD TRIM. PAINT: SHERWIN WILLIAMS; COLOR TBD

#### DOORS AND HARDWARE:

- AT RATED METAL FRAMES: TIMLEY (OR EQUAL) PRIMED AND PAINTED WITH SHERWIN WILLIAMS ENAMEL.
- SOLID CORE WOOD LEAF: SIMPSON; FLUSH PANEL (STRAIGHT GRAIN FIR) WITH CLEAR STAIN FINISH; OR EQUAL
- HOLLOW METAL LEAF: PRIMED AND PAINTED WITH SHERWIN WILLIAMS ENAMEL
- METAL FRAMES: TIMLEY (OR EQUAL) PRIMED AND PAINTED WITH SHERWIN WILLIAMS ENAMEL.
- HARDWARE: ALL SIDE HINGE SWING DOORS TO HAVE 1 1/2 PAIR OF HINGES, STOP, SILENCER, AND LATCH SET WITH LEVER DOOR HANDLE; "ATHENS" OR "SPARTA" LEVER DESIGN (OR EQUAL); 626 "OIL RUBBED BRONZE" FINISH
- DESIGNATED MAIN ENTRY DOORS SHALL BE PROVIDED W/ KAWNEER STANDARD ARCHITECTS CLASSICS HARDWARE (OR EQUAL) W/ EXTERIOR MOUNTED 1" ROUND 9" OFFSET PULL (CO-9/CO-12); INTERIOR MOUNTED PANIC HARDWARE; OIL RUBBED BRONZE FINISH



### ELECTRICAL TRIM

- WHITE

### FLOORING:

- AT CORRIDORS: CARPET TILE; MOHAWK, PT359 AUDACIOUS TILE; 999 LEATHER JACKET
- AT LOUNGE: CARPET TILE: MOHAWK, EB104-7879 BASALT WATERVILLE
- AT UNITS & GAME ROOM: VINYL PLANK: KARNDEAN K-TRADE SERIES, COLOR TBD.
- AT ALL RESTROOMS: 12X24 TILE: UNITED TILE – CROSSVILLE- GOTHAM-AV324 MAINLINE.
- 4" TILE BASE TO MATCH 4"x24" SINGLE BULLNOSE
- AT LOBBY: STAINED CONCRETE
- STAIRWAYS: CARPET TILE OR SHEET CARPET

### FLOOR TRANSITIONS:

- TYPICALLY USE SCHLUTER SYSTEMS EDGING (OR EQUAL) AT FLOOR MATERIAL TRANSITIONS, STAINLESS STEEL, OR DARK ANNOXIDIZED ALUMINUM

### TRIM:

- AT COMMON AREAS: 4" RUBBER BASE, JOHNSONITE MANDALAY
- AT ADMINISTRATIVE, STAFF, UTILITY AREAS: STANDARD 4" RUBBER BASE – COLORS, TBD
- WINDOWS: GWB WRAP WITH 1/4" WOOD SILL (ROUNDED NOSE) AND 3/4" APRON TRIM; CLEAR FACTORY FINISH

### WINDOW BLINDS:

- ROLLER SHADES : LEVOLOR - BLACK-OUT – COLOR: WHITE

### CASEWORK:

- ARISTOKRAFT, BRELLIN. COLOR TBD
- PULLS: STANDARD WIRE PULLS (96MM CENTER TO CENTER) WITH "OIL RUBBED BRONZE" FINISH (UNO)
- HARDWARE: EUROPEAN HINGES, SOFT-CLOSE WITH "OIL RUBBED BRONZE" FINISH; (UNO)

### COUNTERTOP EDGE AND BACKSPLASH:

- AT UNITS: CORIAN: QUARTZ
- AT COMMON AREAS: QUARTZ

### TOILET ROOM FIXTURES

- TOILET TISSUE DISPENSER: CHROME FINISH
- PAPER TOWEL DISPENSER: BRUSHED STAINLESS STEEL FINISH
- GRAB BARS: BRUSHED STAINLESS STEEL FINISH


### ELEVATOR

- DUAL, SIDE BY SIDE
- MANUFACTURE: SCHINDLER ELEVATOR CORPORATION
- TYPE: 330A HOLELESS HYDRAULIC
- SPEED: FPM UP 125
- CAPACITY: 4500 LBS
- DOOR TYPE: 4'-0" WIDE SIDE OPENING
- CAB DIMENSIONS (CLEAR INSIDE) 7'-9.5" X 5'-8"
- ADA COMPLIANT PER IBC, 3002.4, 1009.2.1, 1009.4, 1009.8



**THOMAS**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA 98501

Project No: 1514

**BUILDING PERMIT SET**

09/09/2019

- 1. REVISION 1. 01-31-2019
- 1R. RESPONSE TO COMMENTS. 01-31-2019
- 2R. RESPONSE TO COMMENTS. 03-20-2019
- 3. REVISION 3. 06-13-2019
- 4. REVISION 4. 07-08-2019
- 5. REVISION 5. 08-02-2019
- 6. REVISION 6. 09-03-2019

## BASIS OF DESIGN

# A8.03

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2019 by Thomas Architecture Studio. All rights reserved.



**GENERAL NOTES**

THESE GENERAL NOTES ARE TO BE USED AS A SUPPLEMENT TO THE SPECIFICATIONS. ANY DISCREPANCIES FOUND AMONG THE DRAWINGS, THE SPECIFICATIONS, THESE GENERAL NOTES AND THE SITE CONDITIONS SHALL BE REPORTED TO THE ARCHITECT, WHO SHALL CORRECT SUCH DISCREPANCY IN WRITING. ANY WORK DONE BY THE GENERAL CONTRACTOR AFTER DISCOVERY OF SUCH DISCREPANCY SHALL BE DONE AT THE GENERAL CONTRACTOR'S RISK. THE GENERAL CONTRACTOR SHALL VERIFY AND COORDINATE DIMENSIONS AMONG ALL DRAWINGS PRIOR TO PROCEEDING WITH ANY WORK OR FABRICATION. THE STRUCTURE HAS BEEN DESIGNED TO RESIST CODE SPECIFIED VERTICAL AND LATERAL FORCES AFTER THE CONSTRUCTION OF ALL STRUCTURAL ELEMENTS HAS BEEN COMPLETED. STABILITY OF THE STRUCTURE PRIOR TO COMPLETION IS THE SOLE RESPONSIBILITY OF THE GENERAL CONTRACTOR. THIS RESPONSIBILITY INCLUDES BUT IS NOT LIMITED TO JOB SITE SAFETY, ERECTION MEANS, METHODS, AND SEQUENCES; TEMPORARY SHORING, FORMWORK, BRACING; USE OF EQUIPMENT AND CONSTRUCTION PROCEDURES. PROVIDE ADEQUATE RESISTANCE TO LOADS ON THE STRUCTURES DURING CONSTRUCTION PER SEI/ASCE STANDARD NO. 37-14 "DESIGN LOADS ON STRUCTURES DURING CONSTRUCTION."

CONSTRUCTION OBSERVATION BY THE STRUCTURAL ENGINEER IS FOR GENERAL CONFORMANCE WITH DESIGN ASPECTS ONLY AND IS NOT INTENDED IN ANY WAY TO REVIEW THE CONTRACTOR'S CONSTRUCTION PROCEDURES.

**STANDARDS**

ALL METHODS, MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE 2015 INTERNATIONAL BUILDING CODE (IBC) AS AMENDED AND ADOPTED BY THE LOCAL BUILDING OFFICIAL OR APPLICABLE JURISDICTION.

**CONTRACT DRAWINGS / DIMENSIONS**

ARCHITECTURAL DRAWINGS ARE THE PRIME CONTRACT DRAWINGS. CONSULTANT DRAWINGS BY OTHER DISCIPLINES ARE SUPPLEMENTARY TO ARCHITECTURAL DRAWINGS. REPORT DIMENSIONAL OMISSIONS OR DISCREPANCIES BETWEEN ARCHITECTURAL DRAWINGS AND STRUCTURAL, MECHANICAL, ELECTRICAL OR CIVIL DRAWINGS TO ARCHITECT PRIOR TO PROCEEDING WITH WORK.

STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH ARCHITECTURAL DRAWINGS. PRIMARY STRUCTURAL ELEMENTS ARE DIMENSIONED ON STRUCTURAL PLANS AND DETAILS AND OVERALL LAYOUT OF STRUCTURAL PORTION OF WORK. SOME SECONDARY ELEMENTS ARE NOT DIMENSIONED SUCH AS, WALL CONFIGURATIONS, INCLUDING EXACT DOOR AND WINDOW LOCATIONS, ALCOVES, SLAB SLOPES AND DEPRESSIONS, CURBS, ETC. VERTICAL DIMENSIONAL CONTROL IS DEFINED BY ARCHITECTURAL WALL SECTIONS AND BUILDING SECTIONS. STRUCTURAL DETAILS SHOW DIMENSIONAL RELATIONSHIPS TO CONTROL DIMENSIONS DEFINED BY ARCHITECTURAL DRAWINGS. DETAILING AND SHOP DRAWING PRODUCTION FOR STRUCTURAL ELEMENTS WILL REQUIRE DIMENSIONAL INFORMATION CONTAINED IN BOTH ARCHITECTURAL AND STRUCTURAL DRAWINGS.

**DESIGN CRITERIA**

**VERTICAL LOADS**

AREA	DESIGN DEAD LOAD	LIVE LOAD (2)	CONCENTRATED LOADS
ROOF	20 PSF	30 PSF (1)	300#
RESIDENTIAL	35 PSF	40 PSF	
STAIRS	20 PSF	100 PSF	300#

- (1) LIVE LOADS EXCEPT SNOW LOADS ARE REDUCED PER IBC SECTION 1607.10.
- (2) LIVE LOAD REDUCTION NOT PERMITTED EXCEPT AS NOTED IN IBC SECTION 1607.10.

**SNOW:** (MINIMUM ROOF SNOW LOAD = 25 PSF + 5 PSF RAIN ON SNOW)

**LATERAL FORCES**

LATERAL FORCES ARE TRANSMITTED BY DIAPHRAGM ACTION OF ROOF AND FLOORS TO SHEAR WALLS. LOADS ARE THEN TRANSFERRED TO FOUNDATION BY SHEAR WALL ACTION WHERE ULTIMATE DISPLACEMENT IS RESISTED BY PASSIVE PRESSURE OF EARTH IN CONJUNCTION WITH STEEL PILES. OVERTURNING IS RESISTED BY DEAD LOAD OF THE STRUCTURE IN ADDITION TO STRUCTURAL PILES.

**WIND:**

THE BUILDING MEETS THE CRITERIA TO USE THE "METHOD 2 - SIMPLIFIED ENVELOPE PROCEDURE" PER ASCE 7-10.

- EXPOSURE CATEGORY = C
- BASIC WIND SPEED, (3 SEC. GUST),  $V_{ult} = 110$  MPH
- RISK CATEGORY PER TABLE 1.5-1 = II
- TOPOGRAPHIC FACTOR  $K_{zt} = 1.0$
- INTERNAL PRESSURE COEFFICIENT (ENCLOSED) = ± 0.18
- COMPONENTS AND CLADDING LOADS, SEE THE FOLLOWING TABLES:

ROOF SURFACES 1						
EFFECTIVE WIND AREA	POSITIVE PRESSURES (PSF)			NEGATIVE PRESSURES (PSF)		
	ZONE 2					
	1	2	3	1	2	3
10 SF	16.0	16.0	16.0	-35.3	-59.1	-89.1
20 SF	16.0	16.0	16.0	-34.3	-52.8	-43.7
50 SF	16.0	16.0	16.0	-33.2	-44.6	-53.6
100 SF	16.0	16.0	16.0	-32.2	-38.2	-38.2

WALL SURFACES AND ROOF OVERHANGS 1						
EFFECTIVE WIND AREA	POSITIVE PRESSURE (PSF)	NEGATIVE PRESSURE (PSF)		ROOF OVERHANGS (PSF)		
	ZONE 2					
	4	5	4	5	2	3
10 SF	35.3	35.3	-38.2	-47.1	-50.9	-83.6
20 SF	33.7	33.7	-36.6	-44.1	-49.9	-65.6
50 SF	31.6	31.6	-34.5	-39.9	-48.8	-47.0
100 SF	30.0	30.0	-33.0	-36.6	-47.8	-24.0
500 SF	26.2	26.2	-29.3	-29.3	-47.8	-24.0

- 1. VALUES SHOWN IN TABLE ARE GROSS ULTIMATE WIND PRESSURES.
- 2. ZONES ARE AS DEFINED BY FIGURE 30.5-1 IN ASCE 7-10.

**SEISMIC:** (ASCE 7-10)  $V = C_s W$

WHERE  $C_s = \frac{S_{DS}}{\left(\frac{R}{I_e}\right)}$ ; WITH

$C_s$  MINIMUM =  $0.044 S_{DS} I_e \geq$   
OR  
 $C_s$  MINIMUM =  $\frac{0.5 S_1}{R}$  FOR  $S_1 > 0.6g$

$C_s$  MAXIMUM =  $\frac{S_{D1}}{\left(\frac{R}{I_e}\right)}$  FOR  $T \leq$   
OR

$C_s$  MAXIMUM =  $\frac{S_{D1} T_L}{T^2 \left(\frac{R}{I_e}\right)}$  FOR  $T > T_L$

SEISMIC IMPORTANCE FACTOR,  $I_e = 1.0$   
RISK CATEGORY OF BUILDING PER TABLE 1.5-1 = II  
SPECTRAL RESPONSE ACCELERATIONS  $S_D = 1.33$  &  $S_1 = 0.55$   
SITE CLASS PER TABLE 20.3-1 = E  
DESIGN SPECTRAL RESPONSE ACCELERATIONS  $S_{D1} = 0.80$  &  $S_{D2} = 0.87$   
SEISMIC DESIGN CATEGORY = D  
 $W$  = EFFECTIVE SEISMIC WEIGHT OF WOOD FRAMING = 3,091 K  
TOTAL SEISMIC WEIGHT OF CENTRAL BUILDING = 6,065 K  
ANALYSIS PROCEDURE USED = EQUIVALENT LATERAL FORCE PROCEDURE  
RESPONSE MODIFICATION FACTOR PER TABLE 12.2-1,  $R$  FOR WOOD FRAMING = 6.5, FOR SPECIALLY REINFORCED CONCRETE SHEAR WALLS = 5  
 $C_s$  FOR WOOD FRAMING = 0.123, SPECIALLY REINFORCED CONCRETE SHEAR WALLS = 0.160  
DESIGN BASE SHEAR  $V$  FOR WOOD FRAMING = 381 K  
TOTAL BASE SHEAR  $V$  FOR CENTRAL BUILDING = 975 K

PIPES, DUCTS AND MECHANICAL EQUIPMENT SUPPORTED OR BRACED FROM STRUCTURE. CONFORM TO SHEET METAL AND AIR CONDITIONING CONTRACTORS' NATIONAL ASSOCIATION, INC. PUBLICATION "SEISMIC RESTRAINT MANUAL: GUIDELINES FOR MECHANICAL SYSTEMS". SPRINKLER LINE ATTACHMENTS SHALL CONFORM TO NFPA PAMPHLET 13.

**FOUNDATION DESIGN CRITERIA** (REFER TO GEOTECHNICAL REPORT BY LANDAU ASSOCIATES.)

16"Ø STEEL OPEN ENDED PILE CAPACITY: 380 KIPS ALLOWABLE STATIC BEARING CAPACITY PER GEOTECHNICAL REPORT, PILE DRIVEN 95-115FT BGS TYPICAL UNLESS NOTED OTHERWISE ON PLAN

PASSIVE RESISTANCE: 200 PCF STATIC (INCLUDES F.O.S. ≥ 1.5)  
390 PCF SEISMIC (INCLUDES F.O.S. ≥ 1.1)

IN THE CASE THAT THE ALLOWABLE BEARING CAPACITY IS ACHIEVED PRIOR TO REACHING THE MINIMUM STATED BGS DEPTH, THE CONTRACTOR SHALL CONTACT THE GEOTECHNICAL ENGINEER FOR FURTHER INSTRUCTION OR APPROVAL.

ALL FOOTINGS SHALL BEAR ON FIRM, UNDISTURBED EARTH OR "STRUCTURAL BACKFILL". NATIVE EARTH BEARING SHALL BE SURFACE COMPACTED. AREAS OVER-EXCAVATED SHALL BE BACKFILLED WITH LEAN CONCRETE (F<sub>c</sub> = 2000 PSI) OR "STRUCTURAL BACKFILL". AREAS DESIGNATED "STRUCTURAL BACKFILL" SHALL BE FILLED WITH APPROVED WELL-GRADED BANKRUN MATERIAL. MAXIMUM SIZE OF ROCK 4". FROZEN SOIL, ORGANIC MATERIAL AND DELETERIOUS MATTER NOT ALLOWED. COMPACT TO AT LEAST 95% OF ITS MAXIMUM DENSITY AS DETERMINED BY ASTM D1557. CONTRACTOR SHALL EXERCISE EXTREME CARE DURING EXCAVATION TO AVOID DAMAGE TO BURIED LINES, TANKS, AND OTHER CONCEALED ITEMS. UPON DISCOVERY, DO NOT PROCEED WITH WORK UNTIL RECEIVING WRITTEN INSTRUCTIONS FROM ARCHITECT. A COMPETENT REPRESENTATIVE OF THE OWNER SHALL INSPECT ALL FOOTING EXCAVATIONS FOR SUITABILITY OF BEARING SURFACES PRIOR TO PLACEMENT OF REINFORCING STEEL. PROVIDE DRAINAGE AND DEWATERING AROUND ALL WORK TO AVOID WATER-SOFTENED FOOTINGS.

**FREE DRAINING BACKFILL MATERIAL**

A CLEAN, FREE DRAINING, WELL GRADED GRANULAR MATERIAL CONFORMING TO ASTM D2487 GW OR SW WHOSE MAXIMUM PARTICLE SIZE DOES NOT EXCEED 3/4" AND WHOSE FINES CONTENT (MATERIAL PASSING THE NO. 200 SIEVE) DOES NOT EXCEED 5%,

WITH A MAXIMUM DUST RATIO  $\frac{\% \text{ PASSING U.S. NO. 200 SIEVE}}{\% \text{ PASSING U.S. NO. 40 SIEVE}} = 2/3 \text{ MAX.}$

**STEEL PILES**

PDA TESTING IS AT THE CONTRACTOR'S OPTION. THIS TESTING METHOD IS RECOMMENDED AS IT MAY JUSTIFY SHALLOWER PILE EMBEDMENT DEPTHS WHICH WOULD RESULT IN A MORE COST EFFECTIVE DEEP FOUNDATION.

AT A MINIMUM A WAVE EQUATION ANALYSIS PROGRAM (WEAP) SHALL BE PERFORMED PER THE WSDOT STANDARD SPECIFICATION SECTION 6-05.

**MATERIAL:** PIPE PILES - ASTM A252 GR3 (F<sub>y</sub> = 45 KSI)

**TIP DESIGN:** TIP DESIGN SHALL BE PER CONTRACTOR AND TAKE INTO CONSIDERATION INSTALLATION REQUIREMENTS.

**INSTALLATION:** INSTALL IN A TRUE VERTICAL POSITION. REFER TO THE GEOTECHNICAL REPORT TO DETERMINE THE GENERALIZED SUBSURFACE PROFILES, DRIVEABILITY, SOIL PROPERTIES, CONSTITUENTS, EXISTING SITE FEATURES AND CONDITIONS, AND LOAD TESTING PROTOCOLS.

**INDICATOR PILES:** THE LENGTH OF THE PILE REQUIRED AND THE PILE INSTALLATION SHALL BE VERIFIED IN THE FIELD BY A QUALIFIED INSPECTOR WHO WILL EVALUATE THE CONTRACTOR'S OPERATION AND COLLECT, INTERPRET AND RECORD DATA. A MINIMUM OF TWO INDICATOR PILES SHALL BE DRIVEN BEFORE ORDERING PRODUCTION PILES TO ESTIMATE THE TRUE PILE LENGTHS AND DETERMINE DRIVING CHARACTERISTICS AND PROBLEMS. A QUALIFIED INSPECTOR SHALL EVALUATE INSTALLATION OF INDICATOR PILES.

**CONCRETE**

**CAST-IN-PLACE CONCRETE**

CODES, SPECIFICATIONS, AND STANDARDS. CONCRETE WORK SHALL CONFORM TO THE FOLLOWING CODES, SPECIFICATIONS, AND STANDARDS, AND THE STANDARDS AND SPECIFICATIONS THEY REFERENCE. THE CONTRACTOR SHALL OBTAIN AND HAVE READILY AVAILABLE ON SITE THE LATEST VERSION OF THE "ACI MANUAL OF CONCRETE PRACTICE":

ACI:

1. ACI-117 'SPECIFICATIONS FOR TOLERANCES FOR CONCRETE CONSTRUCTION, MATERIALS AND COMMENTARY'.
2. ACI-301 'STANDARD SPECIFICATIONS FOR STRUCTURAL CONCRETE'.
3. ACI-302.1 'GUIDE TO CONCRETE FLOOR AND SLAB CONSTRUCTION'.
4. ACI-304 'GUIDE FOR MEASURING, MIXING, TRANSPORTING, AND PLACING CONCRETE'.
5. ACI-305.1 'SPECIFICATIONS FOR HOT WEATHER CONCRETING'.
6. ACI-306.1 'STANDARD SPECIFICATION FOR COLD WEATHER CONCRETING'.
7. ACI-308.1 'STANDARD SPECIFICATION FOR CURING CONCRETE'.
8. ACI-309 'GUIDE FOR CONSOLIDATION OF CONCRETE'.
9. ACI-311.4 'GUIDE FOR CONCRETE INSPECTION'.
10. ACI-315 'DETAILS AND DETAILING OF CONCRETE REINFORCEMENT'.
11. ACI-318 'BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE'.
12. ACI 347 'GUIDE TO FORMWORK FOR CONCRETE'.
13. ACI 303.1 'STANDARD SPECIFICATION FOR CAST-IN PLACE/ARCHITECTURAL CONCRETE'.

ASTM:

1. ASTM C33 'STANDARD SPECIFICATION FOR CONCRETE AGGREGATES'.
2. ASTM C94 'STANDARD SPECIFICATION FOR READY-MIX CONCRETE'.
3. ASTM C150 'STANDARD SPECIFICATION FOR PORTLAND CEMENT'.
4. ASTM C260 'STANDARD SPECIFICATION FOR AIR-ENTRAINED ADMIXTURES FOR CONCRETE'.
5. ASTM C309 'STANDARD SPECIFICATION FOR LIQUID MEMBRANE-FORMING COMPOUNDS FOR CURING CONCRETE'.
6. ASTM C494 'STANDARD SPECIFICATION FOR CHEMICAL ADMIXTURES FOR CONCRETE'.
7. ASTM C595 'STANDARD SPECIFICATION FOR BLENDED HYDRAULIC CEMENTS'.
8. ASTM C618 'STANDARD SPECIFICATION FOR ... FLY-ASH...'
9. ASTM C989 'STANDARD SPECIFICATION FOR SLAG...'
10. ASTM C1017 'STANDARD SPECIFICATION FOR CHEMICAL ADMIXTURES FOR USE IN PRODUCING FLOWING CONCRETE'.
11. ASTM C-1116 'STANDARD SPECIFICATION FOR FIBER-REINFORCED CONCRETE'.
12. ASTM C-1218 'STANDARD TEST METHOD FOR WATER-SOLUBLE CHLORIDE IN MORTAR AND CONCRETE'.
13. ASTM C-1315 'STANDARD SPECIFICATION FOR LIQUID MEMBRANE-FORMING COMPOUNDS HAVING SPECIAL PROPERTIES FOR CURING AND SEALING'


**MIX DESIGNS:** THE CONTRACTOR SHALL DESIGN CONCRETE MIXES THAT MEET OR EXCEED THE REQUIREMENTS OF THE CONCRETE MIX TABLE. THE MIX DESIGNS SHALL FACILITATE ANTICIPATED PLACEMENT METHODS, WEATHER, REBAR CONGESTION, ARCHITECTURAL FINISHES, CONSTRUCTION SEQUENCING, STRUCTURAL DETAILS, AND ALL OTHER FACTORS REQUIRED TO PROVIDE A STRUCTURALLY SOUND, AESTHETICALLY ACCEPTABLE FINISHED PRODUCT. WATER REDUCING ADMIXTURES WILL LIKELY BE REQUIRED TO MEET THESE REQUIREMENTS. CONCRETE MIX DESIGNS SHALL CLEARLY INDICATE THE TARGET SLUMP. SLUMP TOLERANCE SHALL BE ± 1-1/2 INCHES.

STRUCTURAL DRAWING INDEX	
SHEET NUMBER	SHEET DESCRIPTION
S1.00	GENERAL NOTES
S1.01	GENERAL NOTES
S1.02	GENERAL NOTES
S1.03	GENERAL NOTES
S1.04	GENERAL NOTES
S2.00	MAIN BUILDING PILE PLAN
S2.01	MAIN BUILDING FOUNDATION PLAN
S2.02A	MAIN BUILDING SECOND FLOOR SLAB REINFORCEMENT PLAN
S2.02B	MAIN BUILDING SECOND FLOOR SLAB P.T. PLAN
S2.02C	MAIN BUILDING SECOND FLOOR FRAMING PLAN
S2.03	MAIN BUILDING THIRD FLOOR FRAMING PLAN
S2.04	MAIN BUILDING FOURTH FLOOR FRAMING PLAN
S2.05	MAIN BUILDING FIFTH FLOOR FRAMING PLAN
S2.06	MAIN BUILDING ROOF FRAMING PLAN
S3.00	GRADE BEAM DETAILS
S3.01	CONCRETE SLAB ON GRADE DETAILS
S3.02	TWO WAY PT DETAILS
S3.03	TWO WAY PT DETAILS
S3.04	CONCRETE COLUMN SCHEDULE
S3.05	CONCRETE WALL ELEVATIONS AND DETAILS
S4.00	WALL FRAMING DETAILS
S4.01	WALL FRAMING DETAILS
S4.02	HOLDDOWN DETAILS
S4.03	WALL ON SLAB FRAMING DETAILS
S4.04	WALL FRAMING DETAILS
S4.05	MASONRY VENEER DETAILS
S5.00	COLUMN AND GLULAM BEAM DETAILS
S6.00	FLOOR FRAMING DETAILS
S6.01	FLOOR FRAMING DETAILS
S6.02	FLOOR FRAMING DETAILS
S7.00	ROOF FRAMING DETAILS
S7.01	ROOF FRAMING DETAILS
Grand total:	32



**THOMAS**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**GENERAL NOTES**

**\$1.00**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.



**AGGREGATE:** COARSE AND FINE AGGREGATE SHALL CONFORM TO ASTM C33

**CEMENT:** CEMENT SHALL CONFORM TO ASTM C150, TYPE II PORTLAND CEMENT, UNLESS NOTED OTHERWISE.

**FLYASH:** SHALL CONFORM TO ASTM C618 CLASS C OR F, MAXIMUM LOSS OF IGNITION SHALL BE 1.0%.

**SLAG:** GROUND GRANULATED BLAST-FURNACE (GGBF) SLAG SHALL CONFORM TO ASTM C989 GRADE 100 OR 120.

**ALTERNATE MIX DESIGNS:** VARIATIONS TO THE MIX DESIGN PROPORTIONS MAY BE ACCEPTED IF SUBSTANTIATED IN ACCORDANCE WITH ACI 318, CHAPTER 19. PROVIDE SUBMITTALS A MINIMUM OF TWO WEEKS PRIOR TO BID FOR DETERMINATION OF ACCEPTABILITY.

**ADMIXTURES:** ADMIXTURES SHALL BE BY MASTER BUILDERS, W.R. GRACE, OR PRE-APPROVED EQUAL. ALL MANUFACTURER'S RECOMMENDATIONS SHALL BE FOLLOWED.

**WATER:** SHALL BE CLEAN AND POTABLE.

**MAXIMUM CHLORIDE CONTENT:** THE MAXIMUM WATER SOLUBLE CHLORIDE CONTENT SHALL NOT EXCEED 0.15% BY WEIGHT OF CEMENTITIOUS MATERIAL UNLESS NOTED OTHERWISE.

**CONCRETE EXPOSED TO WEATHER:** PROVIDE 5.0% TOTAL AIR CONTENT FOR ALL CONCRETE EXPOSED TO WEATHER. TOTAL AIR CONTENT IS THE SUM OF ENTRAINED AIR PROVIDED BY ADMIXTURES AND NATURALLY OCCURRING ENTRAPPED AIR. AIR CONTENT SHALL BE TESTED PRIOR TO BEING PLACED IN THE PUMP HOPPER OR BUCKET; IT IS NOT REQUIRED TO BE TESTED AT THE DISCHARGE END OF THE PUMP HOSE. THE TOLERANCE ON ENTRAPPED AIR SHALL BE +2.0% AND -1.5% WITH THE AVERAGE OF ALL TESTS NOT LESS THAN THE SPECIFIED AMOUNT.

**TOTAL CEMENTITIOUS MATERIAL:** THE SUM OF ALL CEMENT PLUS FLYASH AND SLAG. AT THE CONTRACTORS OPTION FLYASH OR SLAG MAY BE SUBSTITUTED FOR CEMENT BUT SHALL NOT EXCEED 25% BY WEIGHT OF TOTAL CEMENTITIOUS MATERIAL. IN NO CASE SHALL THE AMOUNT OF FLYASH OR SLAG BE LESS THAN REQUIRED BY THE CONCRETE MIX DESIGN TABLE. FOOTING MIXES SHALL CONTAIN NOT LESS THAN **5 SACKS** OF CEMENTITIOUS MATERIAL PER CUBIC YARD, ALL OTHER MIXES SHALL CONTAIN NOT LESS THAN **5-1/2 SACKS** OF CEMENTITIOUS MATERIAL PER CUBIC YARD, UNLESS NOTED OTHERWISE.

ITEM	DESIGN f <sub>c</sub> (PSI) (AT 28 DAYS U.N.O.)	MAX. W/C RATIO	MIN. FLYASH OR SLAG (PCY)	AGGREGATE GRADING ASTM AASHTO	NOTES
SLAB ON GRADE - EXPOSED TO WEATHER	5000	0.40	100	57 OR 67	1
SLABS ON GRADE - UNO	4000	0.45	100	57 OR 67	1
ARCHITECTURALLY EXPOSED SLABS ON GRADE	4000	0.45	100	57 OR 67	1, 2, 4
FOUNDATIONS - UNO	3000	0.50	--	57 OR 67	
STEM WALLS AND OTHER WALLS EXPOSED TO EARTH OR WEATHER	4500	0.45	100	57 OR 67	
STEM WALLS AND OTHER WALLS - UNO	4000	0.50	100	57 OR 67	
ELEVATED PT BEAMS AND SLABS	3000 AT 3 DAYS 5000 AT 56 DAYS	0.40	100	57 OR 67	2,3
CLOSURE STRIPS	5000 @ 56 DAYS	0.40	100	57 OR 67	2,3,4
COLUMNS AND SHEAR WALLS	4000	0.50	--	7 OR 8	
TOPPING SLAB OVER I-JOISTS	3000	0.50	--	7 OR 8	
ALL OTHER CONCRETE	4000	0.50	--	57 OR 67	

**CONCRETE MIX NOTES:**

- FIBROUS CONCRETE REINFORCEMENT SHALL BE "FIBERMESH" MANUFACTURED BY PROPEX CONCRETE SYSTEMS OR PRE-APPROVED EQUAL AND SHALL CONFORM TO ASTM C1116 TYPE III 4.1.3, PERFORMANCE LEVEL 1, AND SHALL BE 100 PERCENT VIRGIN POLYPROPYLENE, FIBRILLATED FIBERS CONTAINING NO REPROCESSED OLEFIN MATERIALS AND SPECIFICALLY MANUFACTURED FOR USE AS CONCRETE SECONDARY REINFORCEMENT. DOSAGE SHALL FOLLOW MANUFACTURER'S RECOMMENDATION BUT NOT LESS THAN 1.5 LB/CU. YD.
- MAXIMUM WATER CONTENT 240 PCY.
- MAXIMUM WATER SOLUBLE CHLORIDE ION CONCENTRATION 0.06 PERCENT BY WEIGHT OF CEMENTITIOUS MATERIAL.
- THIS MIX SHALL CONTAIN 1 GALLON PER CY OF 'ECLIPSE' SHRINKAGE REDUCING ADD MIXTURE BY W.R. GRACE OR APPROVED ALTERNATE. FOR CONCRETE REQUIRING AN AIR ENTRAINMENT ADMIXTURE, 'ECLIPSE PLUS' SHALL BE USED.

**CONCRETE PLACEMENT**

PLACE CONCRETE FOLLOWING ALL APPLICABLE ACI RECOMMENDATIONS. CONCRETE SHALL BE PROPERLY CONSOLIDATED PER ACI 309 USING INTERIOR MECHANICAL VIBRATORS, DO NOT OVER-VIBRATE. CONCRETE SHALL BE POURED MONOLITHICALLY BETWEEN CONSTRUCTION OR EXPANSION JOINTS. IF CONCRETE IS PLACED BY THE PUMP METHOD, HORSES SHALL BE PROVIDED TO SUPPORT THE HOSE, THE HOSE SHALL NOT BE ALLOWED TO RIDE ON THE REINFORCING. WEATHER FORECASTS SHALL BE MONITORED AND ACI RECOMMENDATIONS FOR HOT AND COLD WEATHER CONCRETING SHALL BE FOLLOWED AS REQUIRED. CONCRETE SHALL NOT FREE FALL MORE THAN 5 FEET DURING PLACEMENT WITHOUT WRITTEN APPROVAL OF STRUCTURAL ENGINEER.

**FLOATING & FINISHING OPERATIONS**

WATER SHALL NOT BE ADDED TO THE CONCRETE SURFACE DURING FLOATING & FINISHING OPERATIONS. PRE-APPROVED EVAPORATION RETARDER SPECIFICALLY DESIGNED FOR FLOATING & FINISHING OPERATIONS ARE ACCEPTABLE.

**FORMED SURFACES:**

FORMWORK CLASS OF SURFACE PER ACI 347 TABLE 3.1	
ITEM	CLASS OF FINISH
ALL SURFACES EXPOSED TO PUBLIC VIEW, U.N.O.	A
ALL SURFACES RECEIVING A COURSE TEXTURED COATING SUCH AS PLASTER OR STUCCO, UNLESS NOTED OTHERWISE	B
ALL OTHER SURFACES, UNLESS NOTED OTHERWISE	C

**FORMWORK STRIPPING:**

**COLUMNS & WALLS:** COLUMNS AND WALLS NOT SUPPORTING FRAMING WEIGHT MAY BE STRIPPED AS SOON AS FORMS CAN BE REMOVED WITHOUT DAMAGING THE CONCRETE AND THE CONCRETE HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 500 PSI.

**BEAMS & SLABS:** BEAMS AND SLABS MAY BE STRIPPED AND BECOME SELF SUPPORTING AS SOON AS THEIR COMPRESSIVE STRENGTH REACHES 75% OF THE SPECIFIED DESIGN STRENGTH. RESHORING SHALL BE PROVIDED FOR ALL CONSTRUCTION LOADS THEREAFTER PER THE GENERAL CONTRACTOR.

**COLD WEATHER PLACEMENT:**

- COLD WEATHER IS DEFINED BY ACI 306 AS "A PERIOD WHEN FOR MORE THAN 3 SUCCESSIVE DAYS THE MEAN DAILY TEMPERATURE DROPS BELOW 40° F."
- NO CONCRETE SHALL BE PLACED ON FROZEN OR PARTIALLY FROZEN GROUND. THAWING THE GROUND WITH HEATERS IS PERMISSIBLE.
- CONCRETE MIX TEMPERATURES SHALL BE AS SHOWN BELOW. HEATING OF WATER AND/OR AGGREGATES MAY BE REQUIRED TO ATTAIN THESE TEMPERATURES.
- THE CONCRETE MAY REQUIRE PROTECTION FOR 4-7 DAYS AFTER POURING. IF TEMPERATURES REMAIN BELOW FREEZING, INSULATING BLANKET COVERAGE IS REQUIRED. IF TEMPERATURES ARE SLIGHTLY BELOW FREEZING (30° F MIN.) AT NIGHT AND ABOVE FREEZING DURING THE DAY, KRAFT PAPER WITH COMPLETE COVERAGE MAY BE USED IN LIEU OF INSULATED BLANKETS.
- NO ADDITIVES CONTAINING CHLORIDES SHALL BE USED. USE "POZZUTEC 20+" BY MASTER BUILDERS OR "POLARSET" BY W.R. GRACE OR PRE-APPROVED EQUAL.

CONDITION OF PLACEMENT AND CURING		WALLS & SLABS	FOOTINGS
MIN. TEMP. FRESH CONCRETE AS MIXED FOR WEATHER INDICATED, DEGREES F.	ABOVE 30° F. 0° TO 30° F. BELOW 0° F.	60° 65° 70°	55° 60° 65°
MIN. TEMP. FRESH CONCRETE AS PLACED AND MAINTAINED, DEGREES F.		55°	50°
MAX. ALLOWABLE GRADUAL DROP IN TEMP. THROUGHOUT FIRST 24 HOURS AFTER END OF PROTECTION, DEGREES F.		50°	40°

**HOT OR WINDY WEATHER PLACEMENT**

HOT WEATHER IS DEFINED BY ACI 305 AS "ANY COMBINATION OF HIGH AIR TEMPERATURE, LOW RELATIVE HUMIDITY, AND WIND VELOCITY, TENDING TO IMPAIR THE QUALITY OF FRESH HARDENED CONCRETE. ACI 305 FIGURE 2.1.5 SHALL BE USED BY THE CONTRACTOR TO ESTIMATE THE RATE OF EVAPORATION. WHEN THE ESTIMATED RATE OF EVAPORATION IS GREATER THAN 0.2 PSF/HOUR THE PLACEMENT SHALL BE CONSIDERED A HOT WEATHER PLACEMENT. PRECAUTIONS AGAINST PLASTIC SHRINKAGE CRACKING ARE NECESSARY. PRECAUTIONS TAKEN BY THE CONTRACTOR VARY DEPENDING UPON THE FACTORS ASSOCIATED WITH WATER EVAPORATION AND INCLUDE BUT ARE NOT LIMITED TO:

- LIMITING CONCRETE TEMPERATURE TO 100°F AT TIME OF PLACEMENT.
- APPLICATION OF AN EVAPORATION RETARDER.
- USE OF FOG SPRAY.
- REDUCTION OF POUR SIZE.
- PLACING CONCRETE AT NIGHT.

**CONTROL AND CONSTRUCTION JOINTS**

CONSTRUCTION JOINTS SHALL MEET THE REQUIREMENTS OF ACI 301 SECTIONS 2.2.2.5 AND 5.3.2.6. SPECIAL BONDING METHODS PER SECTION 5.3.2.6 SHALL BE SATISFIED BY ITEM 6 BELOW UNLESS OTHERWISE DETAILED ON THE STRUCTURAL DRAWINGS. WHERE CONSTRUCTION JOINTS ARE NOT SHOWN ON PLAN OR ADDITIONAL CONSTRUCTION JOINTS ARE REQUIRED SUBMIT PROPOSED JOINTING FOR STRUCTURAL ENGINEERS APPROVAL. PROVIDE CONSTRUCTION JOINTS AS INDICATED BELOW UNLESS NOTED OTHERWISE ON THE PLANS:

- SLABS ON GRADE: PROVIDE CONSTRUCTION AND/OR CONTROL JOINTS AT 16 FEET O.C. MAXIMUM FOR UNEXPOSED SLABS ON GRADE AND 12 FEET O.C. FOR EXPOSED SLABS ON GRADE. COORDINATE JOINTS WITH ARCHITECTURAL DRAWINGS.
- WALLS AND COLUMNS: COORDINATE CONSTRUCTION JOINTS WITH ARCHITECTURAL REVEALS.
- TOPPING OVER WOOD FRAMING: PROVIDE JOINTS AT 12' O.C. MAXIMUM.

**EMBEDDED ITEMS**

- NO ALUMINUM ITEMS SHALL BE EMBEDDED IN ANY CONCRETE.
- ALL EMBED PLATES SHALL BE SECURELY FASTENED IN PLACE.
- ALL EMBEDDED STEEL ITEMS EXPOSED TO EARTH SHALL BE GALVANIZED.
- ALL EMBEDDED STEEL ITEMS EXPOSED TO WEATHER SHALL BE PAINTED UNLESS NOTED AS GALVANIZED. SEE DRAWINGS AND SPECIFICATIONS FOR PAINT, PRIMER, AND GALVANIZING REQUIREMENTS.
- EMBEDDED CONDUIT IS NOT PERMITTED IN CONCRETE SLABS ON METAL DECK UNLESS SPECIFICALLY NOTED ON THE STRUCTURAL DRAWINGS.

- EMBEDDED FLEXIBLE CONDUIT IS PERMITTED IN OTHER CAST IN PLACE CONCRETE SLABS WITH A THICKNESS GREATER OR EQUAL TO 5-1/2 INCHES. WHERE PERMITTED IT MAY BE PLACED ON TOP OF THE BOTTOM MAT OF REINFORCING. THE OUTSIDE DIAMETER OF THE CONDUIT SHALL NOT BE GREATER THAN 1-INCH. A MINIMUM OF 2-INCHES CLEAR SHALL BE PROVIDED BETWEEN CONDUIT AND PARALLEL REINFORCING. SPACE CONDUITS A MINIMUM OF 12-INCHES APART, WHERE THIS IS NOT POSSIBLE NOTIFY ENGINEER FOR ADDITIONAL REINFORCING REQUIREMENTS.

**CONCRETE CURING AND SEALING**

CURING PROCEDURES SHALL COMMENCE IMMEDIATELY AFTER FINISHING CONCRETE TO MAINTAIN CONCRETE IN A MOIST CONDITION. VERIFY CURING AND/OR SEALING PRODUCTS ARE COMPATIBLE WITH FLOOR COVERINGS SHOWN ON THE ARCHITECTURAL DRAWINGS. FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS. SLABS ARE DEFINED AS SLABS ON GRADE, CONCRETE ON METAL DECK, ELEVATED POST-TENSIONED OR MILD REINFORCED DECKS, AND TOPPING SLABS.

ITEM	CONCRETE CURING NOTES
SLABS EXPOSED TO EARTH OR WEATHER OR VEHICLE OR FORKLIFT TRAFFIC INCLUDING LOADING DOCKS	1, (3 OR 4 OR 5), 6
ALL OTHER SLABS	1, (3 OR 4 OR 5)
FORMED SURFACES EXCLUDING FOUNDATIONS	2
ALL OTHER CONCRETE	NONE

**CONCRETE CURING NOTES:**

- WHEN THE ESTIMATED EVAPORATION RATE IS GREATER THAN 0.2 PSF/HOUR PROVIDE A SPRAY APPLIED EVAPORATION RETARDER IMMEDIATELY AFTER CONCRETE PLACEMENT. THE EVAPORATION RATE MAY BE CALCULATED PER ACI 305 FIGURE 2.1.5.
- APPLY A LIQUID MEMBRANE FORMING CURING COMPOUND, CONFORMING TO ASTM C309 TYPE 1 CLASS B SPECIFICATIONS, PER MANUFACTURER'S RECOMMENDATIONS TO ALL FORMED SURFACES IMMEDIATELY AFTER FINAL FORM REMOVAL. NOT REQUIRED IF FORMWORK REMAINS IN PLACE FOR MORE THAN 7 DAYS.
- PROVIDE PRE-APPROVED CONTINUOUS WET CURE METHOD FOR A MINIMUM OF 14 DAYS.
- APPLY A LIQUID MEMBRANE FORMING CURING COMPOUND, CONFORMING TO ASTM C309 TYPE 1 CLASS B SPECIFICATIONS OR ASTM C1315 TYPE 1 CLASS A SPECIFICATIONS, PER MANUFACTURER'S RECOMMENDATIONS IMMEDIATELY AFTER FINAL FINISHING. CURING COMPOUND SHALL BE COMPATIBLE WITH ARCHITECTURAL FLOOR COVERINGS AND SEALERS.
- PROVIDE 'ULTRACURE MAX' MOISTURE RETAINING COVER BY MCTECH GROUP, OR APPROVED EQUAL, FOR A MINIMUM OF 14 DAYS.
- APPLY A SILANE SEALER WITH MINIMUM SOLIDS CONTENT OF 40% PER MANUFACTURER'S RECOMMENDATIONS.

**GROUT**

**NON-SHRINK GROUT:** MASTER BUILDERS "MASTERFLOW 928" OR PRE-APPROVED EQUAL. GROUT SHALL CONFORM TO CRD-C621 AND ASTM C1107 WHEN TESTED AT A FLUID CONSISTENCY PER CRD-C611-85 FOR 30 MINUTES. GROUT MAY BE PLACED FROM A 25 SECOND FLOW TO A STIFF PACKING CONSISTENCY. FILL OR PACK ENTIRE SPACE UNDER PLATES OR SHAPES. FOLLOW MANUFACTURER'S RECOMMENDATIONS FOR PREPARATION, INSTALLATION, AND CURING.

**REINFORCING STEEL**

REINFORCING STEEL SHALL CONFORM TO:

ASTM A615, GRADE 60 TYPICAL

ASTM A706 GRADE 60 FOR ALL MOMENT FRAME HORIZONTAL BEAM BARS, MOMENT FRAME VERTICAL COLUMN BARS, VERTICAL SHEAR WALL BARS AND ALL COUPLING BEAM BARS (EXCEPT TIES). PER ACI 318, ASTM A615 GRADE 60 MAY BE SUBSTITUTED FOR THESE MEMBERS IF THE ACTUAL YIELD STRENGTH BASED ON MILL TESTS DOES NOT EXCEED THE SPECIFIED YIELD STRENGTH BY MORE THAN 18 KSI, THE RATIO OF ACTUAL ULTIMATE TENSILE STRENGTH TO ACTUAL YIELD STRENGTH IS NOT LESS THAN 1.25, AND IF THE ELONGATION OVER AN 8" GAGE LENGTH MEETS THE FOLLOWING:

BAR SIZE	MINIMUM ELONGATION
#3 - #6	≥ 14%
#7 - #11	≥ 12%

ASTM A706 GRADE 60 FOR ALL WELDED BARS.

DETAIL FABRICATE AND PLACE PER ACI 315 AND ACI 318.

WELDED WIRE REINFORCEMENT SHALL CONFORM TO ASTM A185. LAP ONE FULL MESH ON SIDES AND ENDS BUT NOT LESS THAN 8 INCHES. WELDED WIRE REINFORCING SHALL BE SUPPORTED TO WITHSTAND CONCRETE PLACEMENT. PULLING OF MESH INTO PLACE AFTER PLACEMENT IS NOT ALLOWED.

EPOXY COATED BARS SHALL CONFORM TO ASTM A775. BARS SHOULD BE HANDLED CAREFULLY, AVOIDING DAMAGE TO THE COATING. IN THE EVENT THAT THE COATING INCURS MINOR CHIPS OR CRACKS, FIELD REPAIRS MAY BE DONE WITH A TWO PART EPOXY.

GALVANIZED BARS SHALL CONFORM TO ASTM A767. BARS SHOULD BE HANDLED CAREFULLY, AVOIDING DAMAGE TO THE COATING. IN THE EVENT THAT THE COATING INCURS MINOR DAMAGE, FIELD REPAIRS MAY BE DONE WITH A COLD APPLIED ZINC GALVANIZING PAINT HAVING A MINIMUM OF 65% ZINC DUST IN THE DRY FILM.



THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514

PERMIT SET

5/11/18

REVISION 9

07/17/19

**GENERAL NOTES**

S1.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.







EPOXY GROUTED ANCHORS: ASTM F1554, GRADE 36 UNLESS NOTED OTHERWISE.

HEADED STUDS: SHALL BE "H4L HEADED CONCRETE ANCHORS" FOR STUDS 5/8" DIAMETER AND SMALLER AND "S3L SHEAR CONNECTORS" FOR STUDS 3/4" DIAMETER AND LARGER AS MANUFACTURED BY NELSON STUD WELDING, INC. OR PRE-APPROVED EQUAL AND SHALL CONFORM TO AWS D1.1. ALL HEADED STUDS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS USING A NELSON WELD GUN, UNLESS NOTED OTHERWISE ON DETAILS. ALL WELDS SHALL BE MADE AND INSPECTED IN ACCORDANCE WITH AWS D1.1.

DEFORMED BAR ANCHORS: SHALL BE "D2L DEFORMED BAR ANCHORS" AS MANUFACTURED BY NELSON STUD WELDING, INC. OR PRE-APPROVED EQUAL AND SHALL CONFORM TO AWS D1.1. ALL DEFORMED BAR ANCHORS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS USING A NELSON WELD GUN, UNLESS NOTED OTHERWISE ON DETAILS. ALL WELDS SHALL BE MADE AND INSPECTED IN ACCORDANCE WITH AWS D1.1.

FINISH: STRUCTURAL STEEL SHALL BE UNPAINTED, UNLESS NOTED OTHERWISE, AND SHALL BE CLEAN OF LOOSE RUST, LOOSE MILL SCALE, OIL, GREASE AND OTHER FOREIGN SUBSTANCES AND SHALL MEET THE REQUIREMENTS OF SSPC-SP1. WHERE STRUCTURAL STEEL IS NOTED TO BE PAINTED, ALL AREAS COMPRISING THE FAYING SURFACES OF BOLTED CONNECTIONS MADE WITH SLIP-CRITICAL TYPE BOLTS (A325SC OR A490SC) SHALL COMPLY WITH THE REQUIREMENTS OF THE RCSC SPECIFICATION. WHERE STRUCTURAL STEEL IS NOTED TO BE GALVANIZED, IT SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH ASTM A123, A384, AND A385. ALL SURFACES WITHIN TWO INCHES OF ANY FIELD WELD LOCATION SHALL BE FREE OF MATERIALS THAT WOULD PREVENT PROPER WELDING OR PRODUCE OBJECTIONABLE FUMES. FIELD TOUCH-UP OF PRIMED, PAINTED, AND GALVANIZED SURFACES SHALL BE PERFORMED TO REPAIR COATING ABRASIONS, AS WELL AS TO PROTECT ALL AREAS AT CONNECTIONS.

ARCHITECTURALLY EXPOSED STRUCTURAL STEEL (AESS): ALL MEMBERS DESIGNATED AS AESS SHALL CONFORM TO SECTION 10, ARCHITECTURALLY EXPOSED STRUCTURAL STEEL, OF THE AISC CODE OF STANDARD PRACTICE.

CARPENTRY:

NAILS: CONNECTION DESIGNS ARE BASED ON "COMMON WIRE" NAILS WITH THE FOLLOWING PROPERTIES:

Table with 4 columns: PENNYWEIGHT, DIAMETER (INCHES), LENGTH (INCHES), TRACKER\*\* EMBOSSED HEAD / COLOR. Rows include 8d, 10d, 16d, 20d and 8d, 10d, 14 GA, 15 GA.

FOR DIAPHRAGM OR SHEAR WALL NAILING THE FOLLOWING FASTENER TYPES MAY BE USED AT EQUIVALENT SPACING TO THAT SPECIFIED ON PLANS

Table with 6 columns: FASTENER TYPE, DIAMETER (INCHES), LENGTH (INCHES), EQUIVALENT SPACING (INCHES), TRACKER\*\* EMBOSSED HEAD / COLOR. Rows include 8d COMMON WIRE, 8d 'DIPPED GALV. BOX', 8d 'SHINY BOX', 12 GA STAPLES, 14 GA STAPLES, 15 GA STAPLES, 10d COMMON WIRE, 10d 'HOT DIPPED GALV. BOX', 10d 'SHINY BOX'.

\*BASED ON 15/32" PLYWOOD OR OSB.
\*\*REFERENCE TO EMBOSSED HEAD / COLOR CODED NAILS PER TRACKERS SYSTEM.

WOOD SHEATHING (STRUCTURAL): SHEATHING ON ROOF SURFACES SHALL BE PLYWOOD ONLY. SHEATHING ON FLOOR AND WALLS SHALL BE PLYWOOD OR ORIENTED STRAND BOARD (OSB). PLYWOOD SHEATHING SHALL BE 5-PLY MINIMUM WHERE INDICATED AS PERFORMANCE CATEGORY 3/4" OR THICKER. WOOD SHEATHING SHALL BE "STRUCTURAL I" CONFORMING TO PS1-09 AND/OR PS2-10. ALL PANELS SHALL BEAR THE STAMP OF AN APPROVED GRADING AGENCY. SPAN RATING SHALL BE PROVIDED AS FOLLOWS: ROOF FRAMING AT 32"O.C. (48/24); ROOF FRAMING AT 24"O.C. (32/16); WALLS (32/16); FLOORS (48/24) ALL WOOD SHEATHED WALLS SHALL BE BLOCKED AT ALL PANEL EDGES UNLESS NOTED OTHERWISE.

GLUE-LAMINATED MEMBERS: CONFORM TO ANSI/AITC A190.1. MEMBERS SHALL BE COMBINATION 24F-V4 DOUGLAS FIR (DF) FOR SIMPLE SPANS AND 24F-V8 DF FOR CANTILEVERED SPANS (Fb=2400 PSI, Fv=265 PSI, E=1.8X10^6 PSI) AND DF COMBINATION 2 FOR COLUMNS.

TRUSSES SHALL HAVE A BALANCED LAY-UP FOR CHORDS AND COMBINATION 2 FOR WEBS.

MEMBERS INDICATED IN STRUCTURAL DRAWINGS AS "POC" SHALL BE PORT ORFORD CEDAR COMBINATION 22F-VIPOC1 (Fb=2200 PSI, Fv=265 PSI, E=1.8X10^6 PSI) AND POC COMBINATION 2 FOR COLUMNS.

MEMBERS INDICATED IN STRUCTURAL DRAWINGS AS "AYC" SHALL BE ALASKAN YELLOW CEDAR COMBINATION 20F-V13 (Fb=2000 PSI, Fv=265 PSI, E=1.5X10^6 PSI) AND AYC COMBINATION 2 FOR COLUMNS.

MEMBERS INDICATED IN STRUCTURAL DRAWINGS AS "PPT" SHALL BE PRESERVATIVE PRESSURE TREATED COMBINATION 24F-V5 SOUTHERN PINE (SP) (Fb=2400 PSI, Fv=300 PSI, E=1.7X10^6 PSI) AND SP COMBINATION 2 FOR COLUMNS.

ARCHITECTURAL APPEARANCE GRADE WHERE EXPOSED TO VIEW; INDUSTRIAL APPEARANCE WHERE NOT EXPOSED TO VIEW. ALL MEMBERS TO HAVE EXTERIOR GLUE AND HAVE AN APPROVED GRADE STAMP. CAMBER AS SHOWN ON STRUCTURAL DRAWINGS.

FRAMING LUMBER: STANDARDS. EACH PIECE SHALL BEAR THE GRADE TRADEMARK OF THE WEST COAST LUMBER INSPECTION BUREAU (WCLIB), WESTERN WOOD PRODUCTS ASSOCIATION (WWPA), OR OTHER AGENCY ACCREDITED BY THE AMERICAN LUMBER STANDARD COMMITTEE (ALSC) TO GRADE UNDER ALSC CERTIFIED GRADING RULES.

SPECIES AND GRADE (BASE DESIGN VALUE)

- 1. 6x BEAMS AND HEADERS. "DOUG FIR-LARCH" NO. 1 (Fb=1350 PSI, Fv=170 PSI)
2. 2x TO 4x JOISTS, PURLINS AND HEADERS. "DOUG FIR-LARCH" NO. 2 (Fb=900 PSI, Fv=180 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fv=150 PSI)
3. 6x POSTS AND COLUMNS. "DOUG FIR-LARCH" NO. 1 (Fc=1000 PSI)
4. EXTERIOR STUDS, INTERIOR BEARING WALLS AND 4x COLUMNS. "DOUG FIR-LARCH" NO. 2 (Fb= 900 PSI, Fc=1350 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fc=1350 PSI).
5. INTERIOR NON-BEARING STUD WALLS. "DOUG FIR-LARCH" NO. 2 (Fb=900 PSI, Fc=1350 PSI) OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fc=1350 PSI)
6. THE MINIMUM GRADE OF ALL OTHER STRUCTURAL FRAMING. "DOUG FIR-LARCH" NO. 2 (Fb= 900 PSI, Fc=1350 PSI), OR "HEM-FIR" NO. 1 (Fb=975 PSI, Fc=1350 PSI).
7. UTILITY & STANDARD GRADES NOT PERMITTED.

STRUCTURAL COMPOSITE LUMBER (SCL): SHALL BE MANUFACTURED BY REDBUILT LLC., OR PRE-APPROVED EQUAL IN ACCORDANCE WITH APPROVED SHOP AND INSTALLATION DRAWINGS CONFORMING TO A CURRENT EVALUATION REPORT.

MINIMUM DESIGN VALUES:

- 1. 2x SCL: Fb = 1700 PSI, Fv = 285 PSI, E = 1300 KSI
2. 1-3/4" SCL: Fb = 2600 PSI, Fv = 285 PSI, E = 1800 KSI
3. 3-1/2" SCL: Fb = 2900 PSI, Fv = 285 PSI, E = 2000 KSI
4. 5-1/4" SCL: Fb = 2900 PSI, Fv = 285 PSI, E = 2000 KSI
5. RIMBOARD: APA/EWS PERFORMANCE RATED RIM (PRR-401) 1-1/4" MINIMUM THICKNESS

MEMBERS HAVE BEEN DESIGNED TO SERVICEABILITY AND OTHER PERFORMANCE BASED REQUIREMENTS, WHICH MAY EXCEED MINIMUM DESIGN LOADS AND CODE REQUIREMENTS. SUBSTITUTIONS MUST MEET OR EXCEED MOMENT, SHEAR, AND STIFFNESS OF THOSE MEMBERS SPECIFIED AT THE SAME DEPTH AND SPACING.

PRESERVATIVE TREATED WOOD REQUIREMENTS:

TREATMENTS OTHER THAN THOSE LISTED BELOW ARE NOT PERMITTED.

Table with 5 columns: APPLICATION, SPECIFIED MATERIAL, PRESERVATIVE TREATMENT (1), CONNECTORS & FASTENERS (2)(3). Rows include FOUNDATION SILL PLATES, FRAMING, DECKING, POSTS & LEDGERS, BEAMS & COLUMNS.

- 1. CCA: CHROMATED COPPER ARSENATE NOT PERMITTED FIR: DOUG-FIR OR HEM-FIR
SBX: DOT SODIUM BORATE SP: SOUTHERN PINE
ACQ: ALKALINE COPPER QUAT
CBA & CA: COPPER AZOLE
2. CONNECTORS: JOIST HANGERS, STRAPS, FRAMING CONNECTORS, COLUMN CAPS AND BASES, ETC. FASTENERS: MACHINE BOLTS, ANCHOR BOLTS AND LAG SCREWS WITH ASSOCIATED PLATE WASHERS AND NUTS. NAILS, SPIKES, WOOD SCREWS, ETC.
3. G60, G90 & G185 PER ASTM A653 FOR COLD-FORMED STEEL CONNECTORS. BATCH/POST HOT-DIP GALVANIZED PER ASTM A123 FOR CONNECTORS AND ASTM A153 STRUCTURAL STEEL CONNECTORS. HOT-DIP GALVANIZED PER ASTM A153 FOR FASTENERS OR MECHANICALLY GALVANIZED FASTENERS PER ASTM B695, CLASS 55 OR GREATER.
4. AT CONTRACTORS OPTION, LEDGERS AND TOP PLATES A MINIMUM OF 8 FEET ABOVE GRADE ON CONCRETE OR MASONRY WALLS MAY BE UN-TREATED IF COMPLETELY SEPARATED FROM THE WALL BY A SELF ADHERING ICE & WATER SHIELD BARRIER (40 MIL MINIMUM).

GENERAL REQUIREMENTS: PROVIDE MINIMUM NAILING PER IBC TABLE 2304.10.1 OR MORE, AS OTHERWISE SHOWN. STAGGER ALL NAILING TO PREVENT SPLITTING OF WOOD MEMBERS. ALL WOOD IN CONTACT WITH CONCRETE OR MASONRY SHALL BE PRESERVATIVE TREATED WITH THE EXCEPTION OF INTERIOR CONCRETE TOPPING ON WOOD FLOOR SYSTEMS. HOLES AND CUTS IN 3x OR 4x PLATES SHOULD BE TREATED WITH A 9% SOLUTION OF COPPER NAPHTHENATE. BOLT HOLES IN WOOD MEMBERS SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN THE BOLT DIAMETER. PROVIDE CUT WASHERS WHERE BOLT HEADS, NUTS AND LAG SCREW HEADS BEAR ON WOOD. PROVIDE A MINIMUM 3"x3"x0.229" PLATE WASHER ON ALL ANCHOR BOLTS WHICH CONNECT MUD SILLS TO FOUNDATION. DO NOT NOTCH OR DRILL STRUCTURAL MEMBERS, EXCEPT AS ALLOWED BY IBC SECTIONS 2308.4.2.4, 2308.5.9, 2308.5.10 AND 2308.7.4 OR AS RESTRICTED BY PLANS OR DETAILS, OR AS APPROVED PRIOR TO INSTALLATION. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

WOOD SHRINKAGE AND CONSOLIDATION: SHRINKAGE OF WOOD MEMBERS AND CONSOLIDATION OF BEARING WALLS IS EXPECTED FROM TIME OF FRAMING UNTIL AFTER BUILDING IS PUT IN SERVICE. MECHANICAL, ELECTRICAL, AND PLUMBING SYSTEMS SHALL BE CONSTRUCTED TO ACCOMODATE 1/4" OF TOTAL SETTLEMENT PER STORY.

FRAMING CONNECTORS: SHALL CONFORM TO CURRENT EVALUATION REPORT AND BE MANUFACTURED BY SIMPSON STRONG-TIE COMPANY, SAN LEANDRO, CA., OR PRE-APPROVED EQUAL. PROVIDE MAXIMUM SIZE AND QUANTITY OF NAILS OR BOLTS PER MANUFACTURER, EXCEPT AS NOTED OTHERWISE. PROVIDE LEAD HOLES AS REQUIRED TO PREVENT SPLITTING OF WOOD MEMBERS. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

LAG SCREWS: SHALL CONFORM TO ANSI/ASME STANDARD B18.2.1. LAG SCREWS SHALL BE OF A DIAMETER INDICATED ON DRAWINGS WITH A MINIMUM OF 8x DIA. EMBEDMENT IN SUPPORTING MEMBER UNLESS NOTED OTHERWISE. CLEARANCE HOLE FOR THE SHANK SHALL BE THE SAME DIAMETER AS THE SHANK AND THE SAME DEPTH OF PENETRATION AS THE UNTHREADED PORTION OF THE SHANK. THE LEAD HOLE FOR THE THREADED PORTION SHALL HAVE A DIAMETER EQUAL TO 60 TO 75 PERCENT OF THE SHANK DIAMETER AND A LENGTH EQUAL TO AT LEAST THE LENGTH OF THE THREADED PORTION. THE THREADED PORTION OF THE SCREW SHALL BE INSERTED IN ITS LEAD HOLE BY TURNING WITH A WRENCH. SOAP OR OTHER LUBRICANT SHALL BE USED ON THE SCREWS OR IN THE LEAD HOLE TO FACILITATE INSERTION AND PREVENT DAMAGE TO THE SCREW. LAG SCREWS SHALL NOT BE DRIVEN WITH A HAMMER. REFER TO PRESERVATIVE TREATED WOOD REQUIREMENTS IN THESE GENERAL NOTES FOR GALVANIZING REQUIREMENTS FOR CONNECTORS AND FASTENERS.

METAL-PLATE-CONNECTED WOOD TRUSSES: SHALL BE MANUFACTURED BY AN APPROVED TRUSS MANUFACTURER IN ACCORDANCE WITH APPROVED SHOP AND INSTALLATION DRAWINGS. TRUSS CALCULATION PACKAGE SHALL BE DESIGNED UNDER THE DIRECT SUPERVISION OF A <STRUCTURAL/PROFESSIONAL> ENGINEER LICENSED IN THE STATE OF PROJECT PER IBC SECTION 2303.4 TO CARRY THE LOADS LISTED IN THE DESIGN CRITERION AND ANY ADDITIONAL LOADS INDICATED ON THE FRAMING PLANS AND DETAILS. THE TRUSS ENGINEER SHALL ASSUME ALL RESPONSIBILITY FOR THE WORK OF ALL SUBORDINATES INVOLVED IN THE PREPARATION OF THE TRUSS PLACEMENT PLANS AND TRUSS DESIGN DRAWINGS. ALL ROOF TRUSSES ARE TO BE PRE-ENGINEERED. ROOF TRUSSES SHALL BE PROVIDED TO COMPLETE THE ROOF FRAMING FROM THE ROOF SHEATHING TO THE SUPPORTING MEMBERS BELOW. TRUSSES DESIGNATED ON PLANS ARE FOR TYPICAL UNIFORMLY LOADED CONDITIONS. TRUSS ENGINEER SHALL PROVIDE ADDITIONAL TRUSSES AS REQUIRED TO SUPPORT SPECIAL LOADING CONDITIONS INDICATED ON DRAWINGS. PROVIDE SHOP AND INSTALLATION DRAWINGS AND CALCULATIONS PRODUCED UNDER THE SUPERVISION OF AND BEARING THE STAMP OF A <STRUCTURAL/PROFESSIONAL> ENGINEER REGISTERED IN THE STATE OF PROJECT. DETAIL DRAWINGS TO INDICATE ALL INFORMATION AS REQUIRED IN IBC SECTION 2303.4.1. ALONG WITH THE FOLLOWING:


- \*KEY PLAN SHOWING EACH TRUSS
\*INDIVIDUAL TRUSS DESIGNS
\*PERMANENT BRACING REQUIREMENTS INCLUDING PLACEMENT AND CONNECTIONS DETAILS
\*TRUSS DRAWINGS SHALL SPECIFY ALL TRUSS CONNECTIONS/HARDWARE TO MEET THE REQUIREMENTS OF THE PLAN.

TRUSS DESIGN CALCULATIONS SHALL BE PROVIDED FOR STANDARD LOADING ALONG WITH DESIGN CHECKS FOR SPECIAL LOADING CONDITIONS WHICH INCLUDE FREE BODY DIAGRAMS, LOADING BREAK DOWN, DESCRIPTION OF LOADS (I.E. MECH UNIT, SUSPENDED WALL, ETC.) AND THE RATIONALE FOR LOADING DISTRIBUTION ON MULTIPLE MEMBERS. SUBMITTAL SHALL ALSO PROVIDE ANY DOCUMENTATION NECESSARY TO INTERPRET DATA INDICATED ON CALCULATIONS.

REFER TO THE FRAMING CONNECTORS SECTION OF THESE GENERAL NOTES FOR REQUIREMENTS PLACED UPON CONNECTOR HARDWARE SPECIFIED BY TRUSS ENGINEER AND/OR PROVIDED BY TRUSS MANUFACTURER.

PROVIDE CERTIFICATE OF CONFORMANCE FROM AN INDEPENDENT TESTING LABORATORY OR A LICENSED PROFESSIONAL ENGINEER CERTIFYING THAT THEY HAVE INSPECTED THE FINISHED TRUSSES AND THAT ALL TRUSSES ARE CONSTRUCTED IN CONFORMANCE WITH THE TRUSS DESIGN DRAWINGS.

I-JOISTS: SHALL BE MANUFACTURED BY REDBUILT LLC, OR PRE-APPROVED EQUAL IN ACCORDANCE WITH APPROVED SHOP AND INSTALLATION DRAWINGS. MEMBERS SHALL BE DESIGNED UNDER THE DIRECT SUPERVISION OF A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF PROJECT. THE ENTIRE OPEN-WEB TRUSS/I-JOIST ASSEMBLY SHALL BE AS APPROVED BY CURRENT EVALUATION REPORT. MEMBERS SHALL BE DESIGNED TO CARRY THE LOADS LISTED IN THE DESIGN CRITERION AND ANY ADDITIONAL LOADS INDICATED ON THE FRAMING PLANS AND DETAILS. THE TRUSS ENGINEER SHALL ASSUME ALL RESPONSIBILITY FOR THE WORK OF ALL SUBORDINATES INVOLVED IN THE PREPARATION OF THE TRUSS PLACEMENT PLANS AND TRUSS DESIGN DRAWINGS. TRUSSES/I-JOISTS SHALL BE PROVIDED TO COMPLETE THE ROOF AND/OR FLOOR FRAMING FROM THE SHEATHING TO THE SUPPORTING MEMBERS BELOW. MEMBER DESIGNATIONS ON PLANS ARE FOR TYPICAL UNIFORMLY LOADED CONDITIONS. MANUFACTURER SHALL PROVIDE ADDITIONAL MEMBERS AS REQUIRED TO SUPPORT SPECIAL LOADING CONDITIONS INDICATED ON DRAWINGS. TOP CHORD AT STRAP CONNECTIONS TO CONCRETE OR MASONRY WALLS SHALL BE COMPOSED OF A STRUCTURAL COMPOSITE LUMBER MEMBER APPROVED BY A CURRENT EVALUATION REPORT FOR SUCH A USE OR AT CONTRACTORS OPTION, STRAP NAIL HOLES SHALL BE PRE-DRILLED IN CHORD. PROVIDE SHOP AND INSTALLATION DRAWINGS AND CALCULATIONS PRODUCED UNDER THE SUPERVISION OF AND BEARING THE STAMP OF A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF PROJECT. DETAIL DRAWINGS TO INDICATE MEMBER TYPES, SIZE, SPACING, BRIDGING, BLOCKING, CONNECTIONS, ANCHORING, BEARING PLATE AND OTHER PERTINENT DETAILS. PROVIDE 1 1/2" DIA. OPEN KNOCKOUTS AT 12" O.C. ON ALL ROOF I-JOISTS.



MEMBER DESIGN CALCULATIONS SHALL BE PROVIDED FOR STANDARD LOADING ALONG WITH DESIGN CHECKS FOR SPECIAL LOADING CONDITIONS WHICH INCLUDE FREE BODY DIAGRAMS, LOADING BREAK DOWN, DESCRIPTION OF LOADS (I.E. MECH UNIT, SUSPENDED WALL, ETC.) AND THE RATIONALE FOR LOADING DISTRIBUTION ON MULTIPLE MEMBERS. SUBMITTAL SHALL ALSO PROVIDE ANY DOCUMENTATION NECESSARY TO INTERPRET DATA INDICATED ON CALCULATIONS.


MEMBERS HAVE BEEN DESIGNED TO MEET SERVICEABILITY AND OTHER PERFORMANCE BASED REQUIREMENTS, WHICH MAY EXCEED MINIMUM DESIGN LOADS AND CODE REQUIREMENTS. SUBSTITUTIONS MUST MEET OR EXCEED MOMENT, SHEAR, AND STIFFNESS OF THOSE MEMBERS SPECIFIED AT THE SAME DEPTH AND SPACING.

REFER TO THE FRAMING CONNECTORS SECTION OF THESE GENERAL NOTES FOR REQUIREMENTS PLACED UPON CONNECTOR HARDWARE SPECIFIED BY TRUSS ENGINEER AND/OR PROVIDED BY TRUSS MANUFACTURER.

SPRINKLER LINE ATTACHMENTS SHALL CONFORM TO NFPA 13 AND COMMERCIAL PUBLICATION "SPRINKLER SYSTEM INSTALLATION WITH GUIDELINES FOR REDBUILT OPEN-WEB TRUSSES AND I-JOISTS". LOADS HUNG FROM JOIST NOT SPECIFICALLY IDENTIFIED ON STRUCTURAL DRAWINGS SHALL NOT EXCEED 30 POUNDS AT ANY ONE POINT, NOR SHALL TOTAL LOADS IN POUNDS ON ANY ONE JOIST EXCEED 8 TIMES THE JOIST SPAN IN FEET, UNLESS DETAILED OTHERWISE ON THE DRAWINGS. ATTACHMENT OF LOADS EXCEEDING 90 POUNDS SHALL BE APPROVED PRIOR TO INSTALLATION. DO NOT NOTCH OR DRILL THRU TRUSS MEMBERS.



525 COLUMBIA ST. | OLYMPIA, WA 98501
360.915.8775 | taso@olympia.com



EAST BAY LOT A
WESTMAN MILL
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514

PERMIT SET
5/11/18

REVISION 9

07/17/19

GENERAL NOTES

\$1.03

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.



**MISCELLANEOUS:**

PRE-APPROVED SUBSTITUTIONS: SUBSTITUTIONS MAY BE ALLOWED ONLY IF THEY MEET THE REQUIREMENTS OF THESE GENERAL NOTES AND THE SPECIFICATIONS, AND IF COMPLETE WRITTEN ENGINEERING DATA FOR EACH CONDITION REQUIRED FOR THIS PROJECT IS PROVIDED TO THE STRUCTURAL ENGINEER TWO WEEKS PRIOR TO BID DATE AND APPROVED IN WRITTEN ADDENDA BY THE ARCHITECT. DATA IS TO INDICATE CODE BASIS BY YEAR, AUTHORITY FOR STRESSES AND STRESS INCREASES, IF ANY, AND AMOUNT OF EXPECTED DEFLECTION FOR FLEXURAL MEMBERS UNDER (1) TOTAL LOAD AND (2) LIVE LOAD ONLY. ALL INCREASED COSTS IN MECHANICAL, SPRINKLER, ELECTRICAL OR GENERAL INSTALLATION AND ANY ARCHITECTURAL OR STRUCTURAL REDESIGN RESULTING FROM SUBSTITUTION SHALL BE BORNE BY THE GENERAL CONTRACTOR.

**SHOP DRAWINGS/SUBMITTALS**

	STRUCTURAL ENGR.	BLDG. DEPT.
1. CONCRETE MIX DESIGNS	X	X
2. REINFORCING STEEL SHOP DRAWINGS	X	
3. VENEER ANCHORAGE SYSTEMS	X	X
4. STRUCTURAL STEEL	X	X
5. MISCELLANEOUS STEEL	X	X
6. GLU-LAMINATED MEMBERS	X	X
7. STRUCTURAL COMPOSITE LUMBER	X	X
8. METAL-PLATE-CONNECTED WOOD TRUSSES	X	X
9. CONTRACTOR'S STATEMENT OF RESPONSIBILITY	X	X

**DEFERRED SUBMITTALS**

THE FOLLOWING ARE NOT INCLUDED WITH THE BUILDING PERMIT DRAWINGS AND SHALL BE SUBMITTED TO THE BUILDING DEPARTMENT AND THE STRUCTURAL ENGINEER FOR REVIEW AND APPROVAL AS A DEFERRED SUBMITTAL. SUBMITTALS SHALL BEAR THE SEAL OF AN ENGINEER LICENSED IN THE STATE OF THE PROJECT AS NOTED.

	ENGINEER STAMP REQUIRED
1. I-JOISTS	PE
2. METAL-PLATE-CONNECTED WOOD TRUSSES	PE
3. POST TENSIONING SYSTEM	PE
4. CONTINUOUS HOLD-DOWN SYSTEMS	PE

**SPECIAL INSPECTION:** SPECIAL INSPECTION SHALL BE PROVIDED BY AN INDEPENDENT TESTING LABORATORY PER THE REQUIREMENTS OF IBC CHAPTER 17 AND THE LOCAL BUILDING OFFICIAL OR APPLICABLE JURISDICTION AND THE CONTRACT DOCUMENTS. THE SPECIAL INSPECTOR SHALL SUBMIT INSPECTION REPORTS AND A FINAL SIGNED REPORT TO THE BUILDING OFFICIAL FOR THE ITEMS LISTED IN THE QUALITY ASSURANCE/SPECIAL INSPECTION SECTION:

**STATEMENT OF SPECIAL INSPECTIONS:**

**SPECIAL INSPECTION:** SPECIAL INSPECTION SHALL BE PROVIDED PER THE REQUIREMENTS OF IBC SECTION 1704 AND 1705 AND AS NOTED HEREIN.

STRUCTURAL SYSTEM	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	COMMENTS	REFERENCES	
DRIVEN-PILE FOUNDATIONS	VERIFY PILE MATERIALS, SIZES AND LENGTHS COMPLY WITH THE REQUIREMENTS	X			IBC 1705.7	
	DETERMINE CAPACITIES OF TEST PILES AND CONDUCT ADDITIONAL LOAD TESTS AS REQUIRED	X				
	INSPECT DRIVING OPERATIONS AND MAINTAIN COMPLETE AND ACCURATE RECORDS FOR EACH PILE	X				
	VERIFY PLACEMENT LOCATIONS AND PLUMBNESS, CONFIRM TYPE AND SIZE OF HAMMER, RECORD NUMBER OF BLOWS PER FOOT OF PENETRATION, DETERMINE REQUIRED PENETRATIONS TO ACHIEVE DESIGN CAPACITY, RECORD TIP AND BUTT ELEVATIONS AND DOCUMENT ANY DAMAGE TO FOUNDATION ELEMENT	X				
	STEEL PILE INSPECTION			SEE STEEL CONSTRUCTION SPECIAL INSPECTION REQUIREMENTS	IBC 1705.2	
STEEL CONSTRUCTION	MATERIAL VERIFICATION OF STRUCTURAL STEEL A. FOR STRUCTURAL STEEL, IDENTIFICATION MARKINGS TO CONFORM TO AISC 360 B. MANUFACTURER'S CERTIFIED MILL TEST REPORTS		X	MANUFACTURER TO PROVIDE CERTIFIED MILL TEST REPORTS	AISC 360 CHAPTER N5 AISC 341 CHAPTER J6	
	MATERIAL VERIFICATION OF WELD FILLER MATERIALS A. IDENTIFICATION MARKINGS TO CONFORM TO AWS SPECIFICATIONS LISTED IN GENERAL NOTES B. MANUFACTURER'S CERTIFICATE OF COMPLIANCE		X	MANUFACTURER TO PROVIDE CERTIFICATE OF COMPLIANCE	AISC 360 CHAPTER N5	
	INSPECTION OF WELDING A. COMPLETE AND PARTIAL JOINT PENETRATION GROOVE WELDS B. PLUG AND SLOT WELDS C. SINGLE-PASS FILLET WELDS ≤ 5/16"	X		X	SPECIAL INSPECTIONS IN THIS SECTION ARE WAIVED WHERE FABRICATION IS PERFORMED ON THE PREMISES OF A FABRICATOR REGISTERED AND APPROVED IN ACCORDANCE WITH IBC SECTION 1704.2.5	AISC 360 CHAPTER N5 AISC 341 CHAPTER J6 AWS D1.1
	INSPECTION OF STEEL FRAME JOINT DETAILS FOR COMPLIANCE WITH APPROVED CONSTRUCTION DOCUMENTS			X		
STEEL CONSTRUCTION OTHER THAN STRUCTURAL STEEL	INSPECTION OF WELDING REINFORCING STEEL: 1. VERIFICATION OF WELDABILITY OF REINFORCING STEEL OTHER THAN ASTM A 706 2. REINFORCING STEEL IN MOMENT FRAMES AND BOUNDARY ELEMENTS 3. SHEAR REINFORCEMENT 4. OTHER REINFORCING STEEL	X		X	AWS D1.3 AWS D1.4 ACI 318 SECTION 26.6.4	

STRUCTURAL SYSTEM	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	COMMENTS		
CONCRETE	ANCHORS CAST IN CONCRETE-PRIOR TO AND DURING PLACEMENT OF CONCRETE		X	SPECIAL INSPECTIONS NOT REQUIRED FOR THE FOLLOWING CONDITIONS: NON-STRUCTURAL SLAB ON GRADE	ACI 318: 17.8.2 AISC 360 SECTION N7	
	VERIFY USE OF REQUIRED DESIGN MIX		X	CONCRETE FOUNDATION WALLS WITH F'c ≤ 2500 PSI	ACI 318, CH 19	
	PRIOR TO CONCRETE PLACEMENT, FABRICATE SPECIMENS FOR STRENGTH TESTS, PERFORM SLUMP AND AIR CONTENT TESTS, AND DETERMINE THE TEMPERATURE OF THE CONCRETE	X		ISOLATED SPREAD FOOTINGS FOR BUILDINGS THREE-STORIES AND LESS ABOVE GRADE PLANE	ASTM C172, C31 ACI 318: 26.4, 26.12 IBC 1908.10	
	MAINTENANCE OF SPECIFIED CURING TEMPERATURE AND TECHNIQUES		X	CONTINUOUS FOOTINGS SUPPORTING WALLS OF THREE-STORIES AND LESS ABOVE GRADE PLANE WHERE WALLS ARE LIGHT-FRAME CONSTRUCTION AND STRUCTURAL DESIGN IS BASED ON F'c ≤ 2500 PSI	ACI 318: 26.5.3 TO 26.5.5 IBC 1908.9	
	ANCHORS POST-INSTALLED IN HARDENED CONCRETE (MECHANICAL ANCHORS AND ADHESIVE ANCHORS INSTALLED DOWNWARD)			X	PERIODIC INSPECTION TO INCLUDE A QUANTITY OF 10% WITH A MINIMUM OF (5) ANCHORS INSPECTED PER INSTALLER ON A DAILY BASIS.	ACI 318: 17.8.2 MFR EVAL REPORT MFR PUBLISHED INSTALLATION INSTRUCTIONS
	MATERIAL VERIFICATION OF REINFORCEMENT STEEL FOR ASTM A615 REINFORCING			X	MANUFACTURER SHALL PROVIDE MILL TEST REPORTS. CONTINUOUS INSPECTION FOR ALL WELDS GREATER THAN 5/16" FILLET. PERIODIC INSPECTION FOR FILLET WELD 5/16" AND SMALLER	ACI 318: 26.6.4 AWS D1.4 IBC 1705.3.1
	TESTING OF MATERIALS			X		IBC 1705.3.2
WOOD FRAMING	SHEAR WALL NAILING		X	SPECIAL INSPECTION NOT REQUIRED FOR FASTENER SPACING > 4" O.C.	IBC 1705.11.1, 1705.12.2, 1705.5	
	DIAPHRAGM NAILING		X	SPECIAL INSPECTION NOT REQUIRED FOR FASTENER SPACING > 4" O.C.	IBC 1705.11.1, 1705.12.2, 1705.5	
	NAILING, BOLTING, AND ANCHORAGE OF COMPONENTS THAT ARE PART OF DRAG STRUTS, BRACES AND HOLD-DOWNS THAT ARE PART OF THE SEISMIC RESISTING SYSTEM		X		IBC 1705.11.1, 1705.12.2	
ANCHORED VENEER	INSPECTION PROGRAM SHALL VERIFY: 1. SIZE, TYPE OF VENEER ANCHORS 2. SIZE, GRADE OF JOINT REINF. 3. PROPORTIONS OF MORTAR 4. CONSTRUCTION OF MORTAR JOINTS 5. INSTALLATION OF TIES		X X X X X	VERIFICATION AT BEGINNING OF CONSTRUCTION	IBC 1705.12.5, 1705.4 TMS 402 / ACI 530 / ASCE 5	

TESTING AND SPECIAL INSPECTION REPORTS SHALL BE PREPARED FOR EACH INSPECTION ITEM ON A DAILY BASIS WHENEVER WORK IS PERFORMED ON THAT ITEM. REPORTS SHALL BE DISTRIBUTED TO OWNER, CONTRACTOR, BUILDING OFFICIAL, ARCHITECT AND STRUCTURAL ENGINEER OF RECORD.


STRUCTURAL OBSERVATIONS SHALL BE PERFORMED BY THE STRUCTURAL ENGINEER OF RECORD OR DESIGNATED REPRESENTATIVE IN ACCORDANCE WITH IBC 1704.6. STRUCTURAL OBSERVATION SHALL BE PERFORMED AS FOLLOWS:

- » PERIODIC VISUAL OBSERVATION OF STRUCTURAL SYSTEMS FOR GENERAL CONFORMANCE TO CONSTRUCTION DOCUMENTS AT SIGNIFICANT CONSTRUCTION STAGES.
- » REVIEW OF TESTING AND INSPECTION REPORTS.
- » REPORTS SHALL BE PREPARED FOR EACH SITE VISIT AND SHALL BE DISTRIBUTED TO ARCHITECT.

GENERAL CONTRACTOR SHALL SUBMIT A WRITTEN CONTRACTOR'S STATEMENT OF RESPONSIBILITY TO THE BUILDING OFFICIAL AND OWNER PRIOR TO COMMENCEMENT OF WORK. THE CONTRACTOR'S STATEMENT OF RESPONSIBILITY SHALL INCLUDE ACKNOWLEDGMENT OF AWARENESS OF THE SPECIAL INSPECTION REQUIREMENTS CONTAINED IN THE STATEMENT OF SPECIAL INSPECTION.



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tasolympia.com



C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_sontilla.rvt

8/6/2019 2:10:30 PM

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19


**GENERAL NOTES**

**S1.04**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.



8/6/2019 2:10:33 PM C:\Revit Models\16574 Westman Mill v2017 (Central)\_samfilla.rvt



1 PILE PLAN - EAST  
52.00 1/8" = 1'-0"



2 PILE PLAN - WEST  
52.00 1/8" = 1'-0"

PILE PLAN NOTES

- INDICATES 16" DIAMETER x 0.375" OPEN-ENDED STEEL PILES DRIVEN APPROXIMATELY 95-115 FEET DEEP UNLESS NOTED OTHERWISE ON PLAN. SEE GENERAL NOTES AND GEOTECHNICAL REPORT FOR ADDITIONAL INFORMATION.
- FOR SITE PLAN & PILE LOCATIONS & DIMENSIONS SEE A0.10.

PILE SCHEDULE<sup>6</sup>

PILE ID	MAX. ASD LOAD <sup>2</sup>	MINIMUM PROOF RESISTANCE <sup>3</sup>					REQ'D PILE WALL THICKNESS <sup>4</sup>	MIN. TIP DEPTH	ESTIMATED TIP DEPTH
		WEAP		PDA		WSDOT DRIVING FORMULA			
		EOD	BOR	EOD	BOR				
A	350	440	637	415	534	700	0.375	95	>115
B	290	406	528	344	447	500	0.375	95	95-115
C	200	280	364	237	308	400	0.375	95	95-115
D	100	140	182	118	154	200	0.375	95	95-115

- NOTES:
- ALL LOADS IN KIPS, DEPTHS IN FEET, PILE WALL THICKNESS IN INCHES.
  - DL+LL ASSUMED TO BE CONTROLLING LOAD COMBINATIONS.
  - ASSUMES A SETUP FACTOR OF 1.3 FOR EOD PROOF RESISTANCE.
  - TO LIMIT DRIVING STRESSES TO 90% OF YIELD STRESS (MIN.  $f_y = 52$  KSI) DURING EOD. ASSUMES WEAP AND NO PDA AND NO DELMAG D30 HAMMER OR EQUIVALENT.
  - ALL PILES ARE D UNLESS NOTED OTHERWISE.
  - SCHEDULE AND DRIVING CRITERIA PER LANDAU ASSOCIATE'S RESPONSE LETTER DATED MAY 22, 2018.

ASD = ALLOWABLE STRESS DESIGN      PDA = PILE DRIVING ANALYSIS  
 BOR = BEGINNING OF RESTRIKE      WEAP = WAVE EQUATION ANALYSIS OF PILES  
 EOD = END OF DRIVING



525 COLUMBIA ST. | OLYMPIA, WA 98501  
 360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
 Community Planning & Development Department  
 602 4<sup>th</sup> Ave East  
 Olympia, WA 98501  
 (360) 753-8248  
 rkaider@olympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
 510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
 5/11/18

4 REVISION 9  
 07/17/19

**MAIN BUILDING  
 PILE PLAN**

**\$2.00**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com




FOUNDATION PLAN NOTES

- INDICATES 8" THICK CONCRETE WALL WITH #5 AT 12" ON CENTER EACH WAY UNLESS NOTED OTHERWISE ON PLANS.
- INDICATES 24"x24" CONCRETE GRADE BEAM. SEE S3.00 FOR DETAILS
- (#) INDICATES THE NUMBER OF VERTICAL REINFORCING BARS AT THE END OF A CONCRETE SHEAR WALL. PROVIDE (2) AT 3" ON CENTER TYPICAL AND PROVIDE ADDITIONAL PER PLAN. BARS TO BE SAME SIZE AS TYPICAL WALL REINFORCING.
- PROVIDE 180° HORIZONTAL SEISMIC HOOKS AROUND CONCRETE SHEAR WALL END REINFORCEMENT DESCRIBED IN NOTE #3. MATCH TYPICAL WALL REINFORCING AND PROVIDE  $\lambda_d$  PER THE GENERAL NOTES.
- INDICATES 16" DIAMETER STEEL PILE PER PILE PLAN S2.00.
- INDICATES CONCRETE COLUMN. FOR REINFORCING SEE 1/S3.04.
- FOR SLAB ON GRADE DETAILS SEE S3.01.
- PROVIDE #5  $\lambda_d$  CORNER BARS AT 12" ON CENTER AT ALL CONCRETE WALL INTERSECTIONS. AT "T" INTERSECTIONS ALTERNATE CORNER BAR DIRECTION INTO ADJACENT WALL.
- FOR TYPICAL OPENING IN CONCRETE WALL GREATER THAN 1'-0" IN EITHER DIRECTION SEE 7/S3.05.
- FOR TYPICAL OPENING IN CONCRETE WALL INCLUDING DOORWAYS SEE 8/S3.05.
- SEE ARCHITECTURAL DRAWING FOR VAPOR BARRIER INFORMATION.



1 FOUNDATION PLAN - EAST  
1/8" = 1'-0"



2 FOUNDATION PLAN - WEST  
1/8" = 1'-0"

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

MAIN BUILDING  
FOUNDATION  
PLAN


S2.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.










- POST TENSIONING NOTES**
- COORDINATE ALL DIMENSIONS WITH ARCHITECTURAL DRAWINGS.
  - INDICATES C.G.S. OF POST TENSIONING TENDONS AT CONTROL POINT MEASURED FROM SLAB SOFFIT TYPICAL. SEE DETAIL 1/S3.02 FOR TYPICAL LAYOUT OF CONTROL POINTS.
  - "C-\_" TYPICAL SLAB POST-TENSIONING PROFILES.  
 13' P.T. SLAB = 2.00" AT SLAB MID-SPAN U.N.O. = 8.75" CENTERED OVER SUPPORTS U.N.O. = 6.50" AT ANCHOR U.N.O.  
 11' P.T. SLAB = 2.00" AT SLAB MID-SPAN U.N.O. = 5.50" AT ANCHOR U.N.O.
  - INDICATES POUR STRIP. CAST NO EARLIER THAN 56 DAYS AFTER FINAL DECK ASSOCIATED WITH FLAT DECK.



525 COLUMBIA ST. | OLYMPIA, WA 98501  
 360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
 Community Planning & Development Department  
 602 4<sup>th</sup> Ave East  
 Olympia, WA 98501  
 (360) 753-8248  
 rkaider@cityofolympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
 510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
 5/11/18

**REVISION 9**  
 07/17/19

**MAIN BUILDING  
 SECOND FLOOR  
 SLAB P.T. PLAN**

**S2.02B**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

8/6/2019 2:10:43 PM C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lympia.com




FRAMING NOTES

- COORDINATE ALL DIMENSIONS WITH ARCHITECTURAL DRAWINGS. FINISH FLOOR = 0'-0" A.F.F. UNLESS NOTED OTHERWISE.
- INDICATES WOOD STUD WALL. WOOD STUDS SHOULD ALIGN WITH TRUSS LAYOUT AND BE SPACED @ 16" O.C. MAXIMUM UNLESS NOTED OTHERWISE. PROVIDE 1/2" WOOD SHEATHING AT ALL EXTERIOR WALLS NAILED WITH 10d @ 6" O.C. AT ALL PANEL EDGES (PROVIDE 2x BLOCKING AT UNSUPPORTED PANEL EDGES) AND 10d @ 12" O.C. AT INTERMEDIATE FRAMING TYPICAL UNLESS NOTED OTHERWISE. SEE NOTE 9 FOR ADDITIONAL SHEAR WALL NAILING.
- INDICATES MASONRY VENEER. FOR ATTACHMENT OF VENEER TO BACKING SEE GENERAL NOTES. FOR VENEER LINTEL ANGLES AT OPENINGS SEE 1/S4.05. FOR CONTROL JOINT SEE 2/S4.05.
- INDICATES WALL EXTENDING TO FLOOR STRUCTURE.
- INDICATES TYPICAL HEADER IN WALL BELOW. SEE 1/S4.00.
- INDICATES HOLLOW STRUCTURAL SECTION COLUMNS ORIGINATING AT FLOOR LEVEL.
- INDICATES WOOD STUD BUILT-UP COLUMN. SEE 2/S4.00 FOR TYPICAL DETAIL.
- INDICATES SPECIAL BUILT-UP WOOD STUD COLUMN REQUIREMENTS UNDER HEADER. FOR TYPICAL FRAMING REQUIREMENTS AT OPENING IN STRUCTURAL WALLS SEE 1/S4.00 FOR TYPICAL DETAIL.
- INDICATES SPECIAL WOOD STUD WALL TYPE. SEE 4/S4.00 FOR SCHEDULE.
- INDICATES CONTINUOUS ROD HOLDDOWN. SEE S4.02 FOR SCHEDULES.
- INDICATES DEPRESSED OR SLOPED SLABS. FOR SLOPE AND EXACT LOCATION SEE ARCHITECTURAL DRAWINGS.
- INDICATES PENETRATION IN FLOOR STRUCTURE.
- NON-STRUCTURAL STUD WALLS ARE NOT SHOWN OR SHOWN SCREENED. FOR LOCATION SEE ARCHITECTURAL DRAWINGS. FOR BRACING AT TOPS OF WALLS SEE S4.04.



1 SECOND FLOOR FRAMING PLAN - EAST  
S2.02C 1/8" = 1'-0"



2 SECOND FLOOR FRAMING PLAN - WEST  
S2.02C 1/8" = 1'-0"

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

MAIN BUILDING  
SECOND FLOOR  
FRAMING PLAN

S2.02C

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.










THOMAS architecture studios


525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
360.753.8248  
matters@olympia.wa.us



1 **FOURTH FLOOR FRAMING PLAN - EAST** FOR FLOOR FRAMING NOTES SEE SHEET S2.03



2 **FOURTH FLOOR FRAMING PLAN - WEST** FOR FLOOR FRAMING NOTES SEE SHEET S2.03

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**MAIN BUILDING  
FOURTH FLOOR  
FRAMING PLAN**

**S2.04**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.





THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19


**MAIN BUILDING  
FIFTH FLOOR  
FRAMING PLAN**

**S2.05**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.



**1 FIFTH FLOOR FRAMING PLAN - EAST** FOR FLOOR FRAMING NOTES SEE SHEET S2.03



**2 FIFTH FLOOR FRAMING PLAN - WEST** FOR FLOOR FRAMING NOTES SEE SHEET S2.03


8/6/2019 2:11:12 PM C:\Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt





THOMAS  
architecture studios


525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | thosolympia.com



ROOF FRAMING NOTES

- COORDINATE ALL DIMENSIONS WITH ARCHITECTURAL DRAWINGS. FINISH FLOOR = 0'-0" A.F.F. UNLESS NOTED OTHERWISE.
- INDICATES WOOD STUD WALL EXTENDING ABOVE ROOF TO FORM PARAPET.
- INDICATES WALL EXTENDING TO ROOF STRUCTURE.
- INDICATES TYPICAL HEADER IN WALL BELOW. SEE 1/S4.00.
- INDICATES PENETRATION IN ROOF STRUCTURE.
- PROVIDE 23/32" T&G WOOD SHEATHING OVER ENTIRE ROOF STRUCTURE. NAIL WOOD FLOOR SHEATHING WITH 10d @ 6" O.C. AT ALL SUPPORTED PANEL EDGES AND 10d @ 10" O.C. AT INTERMEDIATE FRAMING. TYPICAL UNLESS NOTED OTHERWISE. SEE 3/S4.00 FOR ADDITIONAL INFORMATION.
- INDICATES OVER-LAY FRAMING. SEE 3/S7.01 & 4/S7.01.
- FOR SUPPORT OF MISCELLANEOUS MECHANICAL EQUIPMENT AND PIPES FROM ROOF STRUCTURE, SEE 5/S7.01.
- BETWEEN GRID LINES 1-2, 4-7, & 9-10 PROVIDE BLOCKED DIAPHRAGM. PROVIDE 2x FLAT BLOCKING AT ALL PANEL EDGES. NAIL WITH 10d @ 4" O.C. AT SUPPORT EDGES & BOUNDARIES AND 10d @ 6" O.C. AT INTERMEDIATE SUPPORTS AT ALL LEVELS.
- FOR TYPICAL MECHANICAL UNIT ATTACHMENT TO ROOF TRUSSES SEE 6/S7.01.

1 ROOF FRAMING PLAN - EAST  
52.06 1/8" = 1'-0"



2 ROOF FRAMING PLAN - WEST  
52.06 1/8" = 1'-0"

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

MAIN BUILDING  
ROOF FRAMING  
PLAN

S2.06

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

8/6/2019 2:11:16 PM C:\Revit Models\16574 Westman Mill v2017 (Central)\_samfilia.rvt







**T H O M A S**  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com




**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
rklaides@olympia.wa.us




**1 ELEVATION**  
53.00 NO SCALE




**2 SECTION**  
53.00 NO SCALE




**3 SECTION**  
53.00 NO SCALE




**4 SECTION**  
53.00 NO SCALE




**5 SECTION**  
53.00 NO SCALE




**6 SECTION**  
53.00 NO SCALE



**9 PLAN DETAIL**  
53.00 1/2" = 1'-0"



**7 SECTION**  
53.00 NO SCALE



**8 SECTION**  
53.00 NO SCALE

**EAST BAY LOT A  
WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**GRADE BEAM  
DETAILS**

**S3.00**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

8/6/2019 2:11:20 PM C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt





THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18



**REVISION 9**  
07/17/19

**CONCRETE SLAB ON GRADE DETAILS**



**S3.01**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

NOTE:  
LOCATE JOINTS AT NON-BEARING WALLS WHERE POSSIBLE - SUBMIT PATTERN TO ARCHITECT FOR APPROVAL.




**1 SECTION**  
53.01 NO SCALE




**2 PLAN DETAILS**  
53.01 NO SCALE


NOTES:  
1. AROUND OPENINGS 6" Ø OR LESS, NO ADD'L REINF. REQ'D  
2. REINF. SHOWN IS #4 @ SLAB MID-DEPTH HOOK BARS THAT CANNOT BE EXTENDED




**3 DETAIL**  
53.01 NO SCALE




**TYPICAL 8" OR LESS SLAB STEPS OR DEPRESSIONS**




**4 SECTION**  
53.01 NO SCALE




**5 SECTION**  
53.01 NO SCALE




**6 SECTION**  
53.01 NO SCALE




**7 SECTION**  
53.01 NO SCALE



**8 SECTION**  
53.01 NO SCALE



**9 SECTION**  
53.01 NO SCALE




**10 SECTION**  
53.01 NO SCALE

C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt  
8/6/2019 2:11:23 PM











STRESSING END ANCHOR AT BANDED TENDONS

**1 SECTION**  
53.03 NO SCALE




DEAD END AT BANDED TENDONS

**2 SECTION**  
53.03 NO SCALE




STRESSING END ANCHOR AT DISTRIBUTED TENDONS

**3 SECTION**  
53.03 NO SCALE




TYPICAL REINFORCEMENT OF TENDON BAND AT SLAB EDGES

**4 SECTION**  
53.03 NO SCALE



TYPICAL PLACEMENT OF ADDED TENDON


**5 DETAIL**  
53.03 NO SCALE



- NOTES:
- SEE PLAN DETAIL FOR COLUMN REINFORCEMENT DETAILS
  - AT EXTERIOR AND CORNER COLUMNS PROVIDE 90° STD HOOK WHERE BARS CANNOT BE EXTENDED THROUGH COLUMN


TYPICAL COLUMN - SLAB SECTION

**6 SECTION**  
53.03 NO SCALE



BANDED TENDONS AT MID-SPAN

**7 SECTION**  
53.03 NO SCALE




NOTE:  
VERTICAL SLEEVES WHICH ARE EQUAL TO OR LESS THAN 16" O.C. ARE CONSIDERED TO FORM A COMBINED OPENING.

- PROVIDE (1) #5 TOP AND BOTTOM WITH 1'-6" EMBEDMENT PAST THE OPENING.
- IF EFFECTIVE LENGTH OF COMBINED OPENING IS LARGER THAN 24" PROVIDE TRIM REINFORCEMENT
- NO DIAGONAL BARS ARE REQUIRED AT ROUND VERTICAL SLEEVES.
- MULTIPLE VERTICAL SLEEVES ARE NOT TO BE LOCATED AT BANDED TENDON LOCATIONS.

TRIM BARS FOR MULTIPLE VERTICAL SLEEVED CONDUIT PENETRATIONS

**8 DETAIL**  
53.03 NO SCALE



TYPICAL TOP-OF-WALL CONN. TO CONG. SLAB

**9 SECTION**  
53.03 NO SCALE



25 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
603 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
tklein@cityofolympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**TWO WAY PT DETAILS**

**S3.03**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.






**T H O M A S**  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com




**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
mklein@ci.olympia.wa.us




**NOTES:**  
1. ALL CONCRETE COLUMNS STOP AT PODIUM LEVEL.  
2. FOR SHEAR STUD REINFORCING AT TOP OF COLUMN TO SLAB, SEE 2/53.04.

GRAVITY COLUMN REINFORCING SCHEDULE								
MARK LEVEL	C1		C2		C3		C4	
	VERTS	HORIZ.	VERTS	HORIZ.	VERTS	HORIZ.	VERTS	HORIZ.
SECOND FLR.	16x16		12x20		8x28		8x24	
FND	(b) #8	#5 @ 6" O.C.	(b) #8	#5 @ 5" O.C.	(b) #8	#5 @ 5" O.C.	(b) #8	#5 @ 5" O.C.




**1**  
53.04  
**DETAIL**  
NO SCALE

SHEAR STUD REINFORCING SCHEDULE							
COLUMN TYPE PER COL SCHEDULE	CONFIGURATION	QTY. OF RAILS LONG/SHORT SIDES	OVERALL SHEAR STUD LENGTH	END SPACING/ TYP. SPACING	# OF STUDS PER STUD RAIL	STUD RAIL DIAMETER	STUD RAIL HEIGHT
C1	1	2 / 2	41"	4" / 3"	14	1/2"φ	10"
C2	1 OR 2 PER PLAN	3 / 2	32"	4" / 3"	9	1/2"φ	10"
C3	2	3 / 2	32"	4" / 3"	9	1/2"φ	10"
C4	1 OR 2 PER PLAN	3 / 2	26"	4" / 3"	7	1/2"φ	10"



**NOTES:** 1) PROVIDE 2" CLEAR SPACING MINIMUM FROM SLAB EDGES.  
2) PROVIDE 3/4" CLEAR TOP AND BOTTOM.



**2**  
53.04  
**DETAIL**  
NO SCALE

TYPICAL STUD RAIL LAYOUT AT SECOND FLOOR

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**CONCRETE COLUMN SCHEDULE**

**S3.04**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.








- FOR MULTI-SPAN OPENINGS SEE 3



TYPICAL STUD WALL CONSTRUCTION AT HEADER

1 SECTION  
54.00 NO SCALE



TYPICAL BUILT-UP COLUMN AT BEAM PERPENDICULAR TO WALL

2 DETAIL  
54.00 NO SCALE

DIAPHRAGM NAILING SCHEDULE			
DIAPHRAGM TYPE	LOCATION	NAILS	SPACING
FLOOR DIAPHRAGM 23/32" T&G SHEATHING UNBLOCKED UNLESS NOTED ON PLAN	DIAPHRAGM BOUNDARY	10d	6" O.C.
	FIELD NAILS	10d	12" O.C.
	SUPPORTED PANEL EDGES	10d	6" O.C.
ROOF DIAPHRAGM 23/32" T&G SHEATHING UNBLOCKED UNLESS NOTED ON PLAN	DIAPHRAGM BOUNDARY	10d	6" O.C.
	FIELD NAILS	10d	10" O.C.
	SUPPORTED PANEL EDGES	10d	6" O.C.

NOTES:

- PROVIDE (2) ROWS OF SPECIFIED DIAPHRAGM BOUNDARY NAILING OVER INTERIOR SHEAR WALLS AND THE FULL LENGTH OF "COLLECTORS" WHERE INDICATED ON PLAN.
- WHERE BLOCKED DIAPHRAGM INDICATED ON PLAN PROVIDE 2x4 FLATWISE BLOCKING WITH "Z2" CLIPS AT EACH END AT ALL UNSUPPORTED PANEL EDGES. USE 2x4 SCL FLATWISE BLOCKING IN LIEU OF SOLID SAWN WHERE NAILING SIZE OR SPACING EXCEEDS 10d AT 4" ON CENTER.

TYPICAL DIAPHRAGM NAILING

3 SCHEDULE  
54.00 NO SCALE

ALL FASTNERS SHALL BE DRIVEN FLUSH W/ SURFACE OF STRUCT. PANEL

DIAPHRAGM BOUNDARY STRUCT. PANEL TYP.

SUPPORTED PANEL EDGES FIELD NAILS

WALL OR HDR BELOW UNSUPPORTED PANEL EDGE

"COLLECTOR OR SHEAR WALL WHERE INDICATED ON PLAN

SUPPORTED PANEL EDGES

BM OR WALL BELOW

ROOF EAVE OR CANTILEVERED EDGE

DIAPHRAGM BOUNDARY

FASCIA

FIELD NAILS

ALIGN STRUCT. PANEL W/ FIRST MEMBER AT OVERHANG

FRMG CLIP OR H6R - SEE APPLICABLE DETAILS

OUTRIGGERS

CONT. PANEL EDGES HDR

OPN'G PER PLAN

ORIENT LONG EDGE PANEL PERP. TO FRMG MEMBERS U.N.O.

ROOF RAFTERS OR FLR JSTS - TYP.

STUD WALL CONSTRUCTION SCHEDULE									
TABLE 1 - SHEAR WALL REQUIREMENTS									
MARK	WALL SHT'G	SIDES W/ SHT'G	SHT'G NAILS note 2	EDGE NAILING O.C.	EDGE FRAMING note 5	FIELD NAILING O.C.	SOLE NAILING	5/8" ANCHOR BOLT SPACING (EMBED 1" MIN.)	RIM/BLOCKING CONNECTOR TO TOP PLATE BELOW
A	15/32"	(1)	10d	6"	2x	12"	16d @ 6" O.C.	48"	A35 @ 16" O.C.
B	15/32"	(1)	10d	4"	3x	12"	16d @ 6" O.C.	32"	A35 @ 8" O.C.
C	15/32"	(1)	10d	3"	3x	12"	16d @ 6" O.C.	16"	A35 @ 8" O.C.
D	15/32"	(1)	10d	2"	3x	12"	1/4"φ x 3" SD5 SCREW @ 6" O.C.	16"	A35 @ 8" O.C.
E	15/32"	(2)	10d	4"	3x	12"	1/4"φ x 3" SD5 SCREW @ 3" O.C.	16"	A35 @ 8" O.C.

TABLE 2 - STUD REQUIREMENTS		
MARK	STUD SIZE & SPACING	# STUDS REQ'D AT MEMBER BRG
1	2x6 @ 16" O.C.	(1)
2	2x6 @ 16" O.C.	(2)
3	2x4 @ 16" O.C.	(1)
4	2x4 @ 16" O.C.	(2)
5	2x4 @ 16" O.C.	(3)
6	2x4 @ 16" O.C.	(4)


- NOTES:
- xx INDICATES SPECIAL STRUCTURAL WALL TYPE. ALL WALLS SHOWN ON STRUCTURAL DRAWINGS ARE 2x6 AT 16" ON CENTER UNLESS DESIGNATED SPECIAL. STUD LAYOUT SHALL MATCH FRAMING MEMBER LAYOUT ABOVE WHERE APPLICABLE. ALL EXTERIOR WALLS SHALL HAVE 15/32" WOOD SHEATHING AND BE NAILED WITH 10d AT 6" ON CENTER AT EDGES AND 12" ON CENTER IN FIELD UNLESS DESIGNATED SPECIAL.

FIRST CHARACTER INDICATES SPECIAL SHEAR WALL REQUIREMENTS PER TABLE 1

SECOND CHARACTER INDICATES SPECIAL STUD SPACING PER TABLE 2

- ALL EXTERIOR WALLS AND ALL DESIGNATED SHEAR WALLS SHALL BE BLOCKED AT ALL SHEATHING EDGES. EDGE NAILING APPLIES TO ALL TOP AND BOTTOM PLATES, VERTICAL JOINTS, HORIZONTAL BLOCKED JOINTS, WALL CORNERS, AND HOLDDOWN ANCHORED STUDS.
- WHERE BEAMS OR HEADERS FRAME INTO WALLS AND A COLUMN IS NOT CALLED OUT, PROVIDE BUILT-UP COLUMN PER 2/54.00 FOR BEAM PERPENDICULAR TO WALL.
- [X/X] INDICATES BUILT-UP STUD COLUMNS AT HEADERS IN WALLS - SEE 1/54.00 FOR BEAM PARALLEL TO WALL.
- PROVIDE 3x OR DOUBLE 2x MEMBERS FACE NAILED PER 5/54.00 ARE REQUIRED AT ALL ABUTTING PANEL EDGES WHERE INDICATED.
- WHERE SOLID SAWN STUD LENGTH CANNOT BE OBTAINED, SCL STUDS MAY BE SUBSTITUTED. SOLID SAWN FRAMING MAY NOT BE SUBSTITUTED FOR SPECIFIED SCL FRAMING.

4 SCHEDULE  
54.00 NO SCALE



TYPICAL SHEARWALL NAILING

EDGE NAILING DETAIL

NOTES:


- PANEL EDGE NAILING AND PLATE NAILING SHALL BE STAGGERED IN ALL CASES.
- SHEATHING JOINT SHALL OCCUR AT COMMON MEMBER UNLESS IT OCCURS AT A SPECIFIED DOUBLE MEMBER.
- EDGE NAILING AS CALLED FOR ON PLANS AND DETAILS APPLIES TO AREAS INDICATED AND AT HOLDDOWN ANCHORED STUDS

5 SCHEDULE  
54.00 NO SCALE



THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
rklein@ci.olympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

WALL FRAMING  
DETAILS

\$4.00


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.






THOMAS architecture studios


525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso.lympia.com




1 DETAIL NO SCALE




2 DETAIL NO SCALE




3 SECTION NO SCALE



4 DETAIL NO SCALE



5 PLAN DETAIL NO SCALE



6 SECTION NO SCALE

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

WALL FRAMING  
DETAILS

S4.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

C:\Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt

8/6/2019 2:11:44 PM





**THOMAS**  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
rkla@cityofolympia.com

**EAST BAY LOT A  
WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**HOLDDOWN  
DETAILS**

**S4.02**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

CONTINUOUS HOLDDOWN SCHEDULE			
HOLDOWN	FLOOR	DIAMETER	GRADE
CRH-1	5	1/2"	F1554 GR 55
	4	1/2"	
	3	5/8"	
	2	1"	
CRH-2	5	1/2"	F1554 GR 55
	4	5/8"	
	3	1"	
	2	1 1/4"	


CRH-1				CRH-2			
LEVEL	LOAD	STRETCH	POST ON EA. SIDE	LEVEL	LOAD	STRETCH	POST ON EA. SIDE
5	620#	.071"	(2) STUDS PER PLAN	5	1,040#	.119"	(2) STUDS PER PLAN
4	1,500#	.069"	(2) STUDS PER PLAN	4	7,620#	.117"	6x MEMBER PER PLAN
3	6,800#	.104"	6x MEMBER PER PLAN	3	21,260#	.122"	10x MEMBER PER PLAN
2	17,470#	.101"	10x MEMBER PER PLAN	2	45,790#	.115"	12x MEMBER PER PLAN

- CONTINUOUS ROD HOLDDOWN SCHEDULE**
- NOTES:**
- LOAD: THE DESIGN CUMULATIVE TENSION LOAD IN POUNDS AT SERVICE LEVEL.  
STRETCH: SYSTEM ELONGATION IN INCHES AT LISTED LOAD.  
POSTS: PROVIDE SIZE & QUANTITY SHOWN EACH SIDE OF ROD HOLDDOWN MINIMUM.
  - FOR TYPICAL ELEVATION SEE 2/54.02.
  - FOR TYPICAL ANCHORAGE TO PODIUM SLAB DETAIL SEE 3/54.02.
  - FOR TYPICAL ROD TERMINATION DETAIL SEE 4/54.02.
  - A SHRINKAGE COMPENSATING TAKE UP DEVICE SHALL BE PROVIDED AT EACH FLOOR CAPABLE OF ACCOMODATING 3/8" OF SHRINKAGE/CONSOLIDATION.

**1 SCHEDULE**  
54.02 NO SCALE




**2 TYPICAL CONTINUOUS ROD HOLDDOWN ELEVATION**  
54.02 NO SCALE




**3 DETAIL**  
54.02 NO SCALE

NOTE: REINF. & P.T. TENDON'S NOT SHOWN FOR CLARITY




**4 TYPICAL ROD TERMINATION DETAIL**  
54.02 NO SCALE




**5 SECTION**  
54.02 NO SCALE







1 SECTION  
S4.03 NO SCALE




2 SECTION  
S4.03 NO SCALE



3 DETAIL  
S4.03 NO SCALE



4 SECTION  
S4.03 NO SCALE



5 SECTION  
S4.03 1" = 1'-0"



THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



Olympia  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
mklein@ci.olympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**WALL ON SLAB  
FRAMING  
DETAILS**

**S4.03**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.






THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com




**Jeffrey S. Klein**  
Professional Engineer  
Olympia  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
jklein@ci.olympia.wa.us




TYPICAL CONNECTION AT TOP OF NON-BEARING WALL  
EXTENDING TO ROOF STRUCTURE PARALLEL TO JOIST

1 SECTION  
5/4.04 NO SCALE



TYPICAL CONNECTION AT TOP OF NON-BEARING WALL  
EXTENDING TO ROOF STRUCTURE PERPENDICULAR TO JOISTS

2 SECTION  
5/4.04 NO SCALE



TYPICAL STUD WALL CONSTRUCTION AT HEADER WITH  
INTERMEDIATE MULLION

3 SECTION  
5/4.04 3/4" = 1'-0"

C:\\_Revit Models\6574 Westman Mill v2017 (Central)\_sanfilia.rvt 8/6/2019 2:11:54 PM

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19


**WALL FRAMING  
DETAILS**

**S4.04**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.




LINTEL ANGLE SCHEDULE		
MAX. WIDTH OF OPENING	ANGLE SIZE	MIN. BEARING REQ'D AT END OF ANGLE
5'-0"	L3½x3½x1/4	4"
8'-0"	L6x3½x5/16	4"
10'-0"	L7x4x3/8	8"
14'-0"	L7x4x1/2	12"



NOTES:  
ALL LINTEL ANGLES SHALL BE GALVANIZED.

1  
S4.05  
DETAIL  
NO SCALE

NOTE:  
SEE ARCH. FOR LOCATION OF  
VENEER CONTROL JOINTS



TYPICAL VENEER CONTROL JOINT

2  
S4.05  
DETAIL  
NO SCALE



THOMAS  
architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com



Olympia  
Building Plans Examiner  
Community Planning & Development Department  
603 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
mklein@ci.olympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18



**REVISION 9**  
07/17/19

**MASONRY  
VENEER DETAILS**


**S4.05**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.






SECTION 1  
 55.00 NO SCALE



SECTION 2  
 55.00 NO SCALE




SECTION 3  
 55.00 NO SCALE

**NOTE:**


- AT TOP OF COLUMN - PROVIDE 3/8" END W/ PERIMETER WELD - UNLESS OTHERWISE NOTED.
- RECESS BOLT HEADS & NUTS AS REQUIRED FOR FINISHES. DAP GLULAM FOR FLUSH BEARING W/ AT EXPOSED CONDITION.

GL. BM WIDTH	BRG W	KERF W	WELD	MIN. BOLT SIZE
5 1/2"	5/8"	3/8"	3/16"	3/4"




GL. BM WIDTH	BRG W	SIDE W	WELD	MIN. BOLT SIZE
5 1/2"	5/8"	3/16"	3/16"	3/4"


DETAIL 4  
 55.00 NO SCALE




SECTION 5  
 55.00 NO SCALE




DETAIL 6  
 55.00 NO SCALE




SECTION 7  
 55.00 NO SCALE




SECTION 8  
 55.00 NO SCALE




SECTION 9  
 55.00 NO SCALE




SECTION 10  
 55.00 NO SCALE



SECTION 11  
 55.00 NO SCALE



DETAIL 12  
 55.00 NO SCALE



SECTION 13  
 55.00 NO SCALE



525 COLUMBIA ST. | OLYMPIA, WA 98501  
 360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
 Community Planning & Development Department  
 602 4<sup>th</sup> Ave East  
 Olympia, WA 98501  
 (360) 753-8248  
 rklein@cityofolympia.wa.us

**EAST BAY LOT A  
 WESTMAN MILL**  
 510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
 5/11/18

**REVISION 9**  
 07/17/19

**COLUMN AND  
 GLULAM BEAM  
 DETAILS**

**\$5.00**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt

8/6/2019 2:12:03 PM







**T H O M A S**  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | tosolympia.com




Olympia Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
mailto:plans@ci.olympia.wa.us




**1 SECTION**  
56.00 NO SCALE  
TYPICAL I-JOIST BEARING AT EXTERIOR WALL




**2 SECTION**  
56.00 NO SCALE  
TYPICAL I-JOIST BLOCKING PARALLEL TO EXTERIOR WALL




**3 SECTION**  
56.00 NO SCALE  
TYPICAL I-JOIST AT BEARING STUD WALL




**4 SECTION**  
56.00 NO SCALE  
NOTE: SIM. WHERE WALL ABOVE IS NON-STRUCTURAL




**5 SECTION**  
56.00 NO SCALE  
TYPICAL I-JOIST BEARING AT BEAM (ONE SIDE)




**6 SECTION**  
56.00 NO SCALE  
TYPICAL I-JOIST BEARING AT BEAM (EACH SIDE)




**7 SECTION**  
56.00 NO SCALE




**8 SECTION**  
56.00 NO SCALE




**9 DETAIL**  
56.00 NO SCALE  
FOR DETAILS & CALLOUTS IN COMMON SEE 2




**10 SECTION**  
56.00 NO SCALE



**11 SECTION**  
56.00 NO SCALE



**12 SECTION**  
56.00 1" = 1'-0"



**13 SECTION**  
56.00 1" = 1'-0"

**EAST BAY LOT A**  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19

**FLOOR FRAMING**  
**DETAILS**

**S6.00**

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.

C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_smtflla.rvt  
8/6/2019 2:12:07 PM





THOMAS architecture studios

525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | fosolympia.com



Olympia Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
mklein@ci.olympia.wa.us

EAST BAY LOT A  
**WESTMAN MILL**  
510 STATE AVE OLYMPIA, WA. 98501


Project No: 1514  
**PERMIT SET**  
5/11/18

**REVISION 9**  
07/17/19


**FLOOR FRAMING DETAILS**

**S6.01**


All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.




**1 SECTION**  
S6.01 NO SCALE  
TYPICAL STAIR STRINGER




**2 SECTION**  
S6.01 NO SCALE  
TYPICAL STRINGER CONNECTION TO FLOOR/LANDING




**3 SECTION**  
S6.01 NO SCALE




**4 SECTION**  
S6.01 NO SCALE




**5 SECTION**  
S6.01 NO SCALE  
TYPICAL SPRINKLER LINE ATTACHMENT FOR LINES 3/8" OR SMALLER




**6 SECTION**  
S6.01 NO SCALE  
TYPICAL DETAIL FOR HANGING LOADS FROM I-JOIST (ALL HEAT PUMPS, R FANS OR E FANS OVER 90#)




**7 SECTION**  
S6.01 1" = 1'-0"




**8 SECTION**  
S6.01 NO SCALE



**9 SECTION**  
S6.01 NO SCALE



**10 SECTION**  
S6.01 NO SCALE




**11 SECTION**  
S6.01 NO SCALE

C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt 8/6/2019 2:12:10 PM












1 SECTION  
57.00 NO SCALE




2 SECTION  
57.00 NO SCALE




3 SECTION  
57.00 NO SCALE




4 SECTION  
57.00 NO SCALE




5 SECTION  
57.00 NO SCALE



6 SECTION  
57.00 NO SCALE



7 SECTION  
57.00 NO SCALE



8 SECTION  
57.00 NO SCALE

C:\\_Revit Models\16574 Westman Mill v2017 (Central)\_santilla.rvt 8/6/2019 2:12:17 PM



525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18


REVISION 9  
07/17/19

ROOF FRAMING  
DETAILS


S7.00

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.







1 SECTION  
S7.01 NO SCALE




2 SECTION  
S7.01 NO SCALE




3 SECTION  
S7.01 NO SCALE



4 SECTION  
S7.01 NO SCALE



5 SECTION  
S7.01 NO SCALE



6 SECTION  
S7.01 NO SCALE



THOMAS  
architecture studios  
525 COLUMBIA ST. | OLYMPIA, WA 98501  
360.915.8775 | taso@olympia.com



Olympia  
Building Plans Examiner  
Community Planning & Development Department  
602 4<sup>th</sup> Ave East  
Olympia, WA 98501  
360.753.8248  
mklein@ci.olympia.wa.us

EAST BAY LOT A  
WESTMAN MILL  
510 STATE AVE OLYMPIA, WA. 98501

Project No: 1514  
PERMIT SET  
5/11/18

REVISION 9  
07/17/19

ROOF FRAMING  
DETAILS

S7.01

All material herein constitutes the original and unpublished work of the architect and may not be used, duplicated, or disclosed without the written consent of the architect. Copyright © 2018 by Thomas Architecture Studio. All rights reserved.





**Westman Mill**

Project #110805 Olympia, WA

**Reference Documents:**

**5/24/2019**

<i>Drawing Section</i>	<i>By</i>	<i>Date</i>	<i>Revision</i>	<i>Type</i>	<i>Sheets</i>
Architectural	Thomas Architecture Studio, Inc.	6/7/2018		Bid	Full set
Structural	PCS Structural	6/7/2018		Bid	Full set
Mechanical					

**IF YOU HAVE QUESTIONS...**

**Your primary contact is your Project Manager:**

Tim Kolb  
(208) 395-2454  
tkolb@redbuilt.com

**Your secondary contact is your Technical Representative:**

Nolan Franks  
(253) 857-7600  
nfranks@redbuilt.com



Reviewed for Code Compliance  
Construction Permitting Only

**Olympia**  
Building Plans Examiner  
Community Planning & Development Department  
601 4<sup>th</sup> Ave East  
Olympia, WA 98501  
(360) 753-8248  
rbalders@ci.olympia.wa.us

**CM 7/30/19- EOR stamped calculations located on Page #15 of submittal package**

**CM 7/30/19- Submittal has been updated to include the beam deletions that occurred along the Level 2 lounge.**

Material List & Calculations pp. 1-25, Drawings pp. 1-8

Our responsibility is limited to the design of RedBuilt products in accordance with the above referenced documents based on design loads specified by the engineer of record.

**IMPORTANT (Please Read)**

- Installation of the materials is the sole responsibility of the installer.
- Refer to Installation Information sheets for more detailed instruction.
- All materials shall be furnished by others unless included on the material list provided herein.

**APPROVED FOR PRODUCTION**





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D1: 3rd Fl 1-7  
 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products			Joists												
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.	Footage	Notes			
30	A1	Red-I45	11.88	15'-6.00"	None					No	465.0				
17	A10	Red-I45	11.88	8'-0.00"	None					No	136.0				
6	A11	Red-I45	11.88	4'-6.00"	None					No	27.0				
164	A2	Red-I45	11.88	12'-6.00"	None					No	2050.0				
36	A3	Red-I45	11.88	11'-6.00"	None					No	414.0				
13	A4	Red-I45	11.88	9'-0.00"	None					No	117.0				
21	A5	Red-I45	11.88	17'-6.00"	None					No	367.5				
126	A6	Red-I45	11.88	15'-0.00"	None					No	1890.0				
21	A7	Red-I45	11.88	14'-0.00"	None					No	294.0				
19	A8	Red-I45	11.88	12'-0.00"	None					No	228.0				
33	A9	Red-I45	11.88	5'-0.00"	None					No	165.0				
24	B1	Red-I45	9.5	4'-6.00"	None					No	108.0	1			
27	C1	Red-I65	11.88	18'-0.00"	None					No	486.0				
14	C2	Red-I65	11.88	10'-0.00"	None					No	140.0				
24	***	Red-I45	9.5										Total	108.0	
41	***	Red-I65	11.88										Total	626.0	
486	***	Red-I45	11.88										Total	6153.5	
Note 1	Use 18 for stair landings below 3rd floor.														

Red-I™ Products			Blocking Panels									
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts				Notes	
215		Red-I45	11.875	14.188	1 Attached							
30		Red-I65	11.875	13.438	1 Attached							
160		Red-I45	11.875	14.188	None							
10		Red-I65	11.875	13.438	None							

Red-I™ Products			Connectors										
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Fig. Slope	Fig. Angle	Fig. Offset	NetH	Finish	Notes
98	1	ITS1.81/11.88	4-N10	2-N10									
48	2	ITS1.81/9.5	4-N10	2-N10									2
148	3	IUS1.81/11.88		10-10d									
27	4	IUS2.56/11.88		10-10d									
Note 2	Use 36 for stair landings below 3rd floor.												



RedLam™ LVL Products					LVL Beams				
Quantity	Type	Size	Length	Grade	P.E.T.		Footage	Notes	
2	RA1	5.25x11.88	9'-6.00"	2.0E			19.0		
1	RA2	5.25x11.88	12'-0.00"	2.0E			12.0		
1	RA3	5.25x11.88	14'-0.00"	2.0E			14.0		
2	RA4	5.25x11.88	8'-0.00"	2.0E			16.0		
4	RA5	5.25x11.88	4'-0.00"	2.0E			16.0		
1	RA6	5.25x11.88	10'-0.00"	2.0E			10.0		
6	RB1	5.25x11.88	16'-0.00"	2.0E			96.0	3	
6	RB2	5.25x11.88	18'-0.00"	2.0E			108.0	3	
12	RC1	3.5x11.88	12'-0.00"	2.0E			144.0	3	
4	RC2	3.5x11.88	14'-0.00"	2.0E			56.0	3	
2	RC3	3.5x11.88	18'-0.00"	2.0E			36.0	3	
18	***	3.5x11.88	.....				Total	236.0	
23	***	5.25x11.88	.....				Total	291.0	
Note 3		WF Beam fillers							

RedLam™ LVL Products					LVL Rim Board			
Lineal Ft	Type	Size	Grade	LSL Substitution		Footage	Notes	
784		1.75x11.88		N/A		784.0		

RedBuilt™ Products					LSL Rim Board			
Lineal Ft	Type	Size	Grade	LVL Substitution		Footage	Notes	
144		1.5x9.5	1.3E	Allowed		144.0		
672		1.5x11.88	1.3E	Allowed		672.0		
144.0	***	1.5x9.5	.....			Total	144.0	
672.0	***	1.5x11.88	.....			Total	672.0	

Third-Party (Sourced by RedBuilt™)					Glulam Beams				
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.	Footage	Notes
5	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial		50.0	
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial		8.0	
3	GB3	5.125x12	15'-0.00"	24F-V4	5000'	Industrial		45.0	
1	GB4	5.125x12	13'-0.00"	24F-V4	5000'	Industrial		13.0	
5	***	5.125x9 V4	.....				Total	50.0	
6	***	5.125x12 V4	.....				Total	66.0	

					Hardware			
Quantity	Type	Description					Notes	
8.0 lb		10dx1.5" Nails						
25.0 lb		10dx3" Nails						





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D2: 3rd Fl 7-10 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products				Joists										
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.		Footage	Notes	
26	A1	Red-I45	11.88	15'-6.00"	None					No		403.0		
6	A11	Red-I45	11.88	4'-6.00"	None					No		27.0		
107	A2	Red-I45	11.88	12'-6.00"	None					No		1337.5		
36	A3	Red-I45	11.88	11'-6.00"	None					No		414.0		
13	A4	Red-I45	11.88	9'-0.00"	None					No		117.0		
21	A5	Red-I45	11.88	17'-6.00"	None					No		367.5		
67	A6	Red-I45	11.88	15'-0.00"	None					No		1005.0		
24	B1	Red-I45	9.5	4'-6.00"	None					No		108.0	1	
24	•••	Red-I45	9.5	•••••	•••••	•••••	•••••	•••••	•••••	•••••	•••••	Total	108.0	
276	•••	Red-I45	11.88	•••••	•••••	•••••	•••••	•••••	•••••	•••••	•••••	Total	3671.0	
Note 1		Use 18 for stair landings below 3rd floor.												

Red-I™ Products				Blocking Panels								
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts				Notes	
130		Red-I45	11.875	14.188	1 Attached							
96		Red-I45	11.875	14.188	None							

Connectors													
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Fig. Slope	Fig. Angle	Fig. Offset	NetH	Finish	Notes
102	1	ITS1.81/11.88	4-N10	2-N10									
50	2	ITS1.81/9.5	4-N10	2-N10									2
Note 2		Use 36 for stair landings below 3rd floor.											

RedLam™ LVL Products				LVL Beams									
Quantity	Type	Size	Length	Grade	P.E.T.							Footage	Notes
2	RA1	5.25x11.88	9'-6.00"	2.0E								19.0	
1	RA2	5.25x11.88	12'-0.00"	2.0E								12.0	
1	RA3	5.25x11.88	14'-0.00"	2.0E								14.0	
2	RA4	5.25x11.88	8'-0.00"	2.0E								16.0	
4	RA5	5.25x11.88	4'-0.00"	2.0E								16.0	
1	RA6	5.25x11.88	10'-0.00"	2.0E								10.0	
11	•••	5.25x11.88	•••••	•••••	•••••	•••••	•••••	•••••	•••••	•••••	•••••	Total	87.0



RedLam™ LVL Products					LVL Rim Board				
Lineal Ft	Type	Size	Grade	LSL Substitution				Footage	Notes
448		1.75x11.88		N/A				448.0	

RedBuilt™ Products					LSL Rim Board					
Lineal Ft	Type	Size	Grade	LVL Substitution				Footage	Notes	
416		1.5x11.88	1.3E	Allowed				416.0		
144		1.5x9.5	1.3E	Allowed				144.0		
144.0	***	1.5x9.5	..... Total						144.0	
416.0	***	1.5x11.88	..... Total						416.0	

Third-Party (Sourced by RedBuilt™)					Glulam Beams					
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.	Footage	Notes	
5	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial		50.0		
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial		8.0		
5	***	5.125x9 V4	..... Total						50.0	
2	***	5.125x12 V4	..... Total						8.0	

					Hardware			
Quantity	Type	Description						Notes
8.5 lb		10dx1.5" Nails						





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D3: 4th Fl 1-7 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products				Joists								
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.	Footage	Notes
30	A1	Red-I45	11.88	15'-6.00"	None					No	465.0	
6	A11	Red-I45	11.88	4'-6.00"	None					No	27.0	
183	A2	Red-I45	11.88	12'-6.00"	None					No	2287.5	
36	A3	Red-I45	11.88	11'-6.00"	None					No	414.0	
13	A4	Red-I45	11.88	9'-0.00"	None					No	117.0	
21	A5	Red-I45	11.88	17'-6.00"	None					No	367.5	
147	A6	Red-I45	11.88	15'-0.00"	None					No	2205.0	
6	B1	Red-I45	9.5	4'-6.00"	None					No	27.0	
27	C1	Red-I65	11.88	18'-0.00"	None					No	486.0	
14	C2	Red-I65	11.88	10'-0.00"	None					No	140.0	
6	•••	Red-I45	9.5	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	Total	27.0
41	•••	Red-I65	11.88	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	Total	626.0
436	•••	Red-I45	11.88	•••••	••••••~•••••	••••~•••••	•••••	•••••	•••••	•••••	Total	5883.0

Red-I™ Products				Blocking Panels							
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts				Notes
200		Red-I45	11.875	14.188	1 Attached						
194		Red-I45	11.875	14.188	None						
30		Red-I65	11.875	13.438	1 Attached						
28		Red-I65	11.875	13.438	None						



				<b>Connectors</b>									
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Flg. Slope	Flg. Angle	Flg. Offset	NetH	Finish	Notes
98	1	ITS1.81/11.88	4-N10	2-N10									
12	2	ITS1.81/9.5	4-N10	2-N10									

<b>RedLam™ LVL Products</b>				<b>LVL Beams</b>									
Quantity	Type	Size	Length	Grade	P.E.T.							Footage	Notes
2	RA1	5.25x11.88	9'-6.00"	2.0E								19.0	
1	RA2	5.25x11.88	12'-0.00"	2.0E								12.0	
1	RA3	5.25x11.88	14'-0.00"	2.0E								14.0	
2	RA4	5.25x11.88	8'-0.00"	2.0E								16.0	
4	RA5	5.25x11.88	4'-0.00"	2.0E								16.0	
1	RA6	5.25x11.88	10'-0.00"	2.0E								10.0	
11	***	5.25x11.88	.....	.....	.....							Total	87.0

<b>RedLam™ LVL Products</b>				<b>LVL Rim Board</b>									
Lineal Ft	Type	Size	Grade	LSL Substitution							Footage	Notes	
832		1.75x11.88		N/A							832.0		

<b>RedBuilt™ Products</b>				<b>LSL Rim Board</b>									
Lineal Ft	Type	Size	Grade	LVL Substitution							Footage	Notes	
928		1.5x11.88	1.3E	Allowed							928.0		
32		1.5x9.5	1.3E	Allowed							32.0		
32.0	***	1.5x9.5	.....	.....							Total	32.0	
928.0	***	1.5x11.88	.....	.....							Total	928.0	

<b>Third-Party (Sourced by RedBuilt™)</b>				<b>Glulam Beams</b>									
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.				Footage	Notes	
2	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial					20.0		
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial					8.0		
1	GB3	5.125x12	15'-0.00"	24F-V4	5000'	Industrial					15.0		
2	***	5.125x9 V4	.....	.....	.....	.....	.....				Total	20.0	
3	***	5.125x12 V4	.....	.....	.....	.....	.....				Total	23.0	

				<b>Hardware</b>									
Quantity	Type	Description										Notes	
6.0 lb		10dx1.5" Nails											





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D4: 4th Fl 7-10 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products				Joists								
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.	Footage	Notes
26	A1	Red-I45	11.88	15'-6.00"	None					No	403.0	
6	A11	Red-I45	11.88	4'-6.00"	None					No	27.0	
107	A2	Red-I45	11.88	12'-6.00"	None					No	1337.5	
36	A3	Red-I45	11.88	11'-6.00"	None					No	414.0	
13	A4	Red-I45	11.88	9'-0.00"	None					No	117.0	
21	A5	Red-I45	11.88	17'-6.00"	None					No	367.5	
67	A6	Red-I45	11.88	15'-0.00"	None					No	1005.0	
6	B1	Red-I45	9.5	4'-6.00"	None					No	27.0	
6	•••	Red-I45	9.5	•••••	••••••••••	•••••	•••••	•••••	•••••	•••••	Total	27.0
276	•••	Red-I45	11.88	•••••	••••••••••	•••••	•••••	•••••	•••••	•••••	Total	3671.0

Red-I™ Products				Blocking Panels							
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts	Notes			
128		Red-I45	11.875	14.188	1 Attached						
96		Red-I45	11.875	14.188	None						

				Connectors										
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Fig. Slope	Fig. Angle	Fig. Offset	NetH	Finish	Notes	
102	1	ITS1.81/11.88	4-N10	2-N10										
12	2	ITS1.81/9.5	4-N10	2-N10										



RedLam™ LVL Products				LVL Beams					
Quantity	Type	Size	Length	Grade	P.E.T.			Footage	Notes
2	RA1	5.25x11.88	9'-6.00"	2.0E				19.0	
1	RA2	5.25x11.88	12'-0.00"	2.0E				12.0	
1	RA3	5.25x11.88	14'-0.00"	2.0E				14.0	
2	RA4	5.25x11.88	8'-0.00"	2.0E				16.0	
4	RA5	5.25x11.88	4'-0.00"	2.0E				16.0	
1	RA6	5.25x11.88	10'-0.00"	2.0E				10.0	
11	***	5.25x11.88	.....	.....	.....	.....	.....	Total	87.0

RedLam™ LVL Products				LVL Rim Board					
Lineal Ft	Type	Size	Grade	LSL Substitution			Footage	Notes	
448		1.75x11.88		N/A			448.0		

RedBuilt™ Products				LSL Rim Board					
Lineal Ft	Type	Size	Grade	LVL Substitution			Footage	Notes	
1024		1.5x11.88	1.3E	Allowed			1024.0		
32		1.5x9.5	1.3E	Allowed			32.0		
32.0	***	1.5x9.5	.....	.....	.....	.....	Total	32.0	
1024.0	***	1.5x11.88	.....	.....	.....	.....	Total	1024.0	

Third-Party (Sourced by RedBuilt™)				Glulam Beams					
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.	Footage	Notes
2	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial		20.0	
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial		8.0	
2	***	5.125x9 V4	.....	.....	.....	.....	.....	Total	20.0
2	***	5.125x12 V4	.....	.....	.....	.....	.....	Total	8.0

				Hardware					
Quantity	Type	Description					Notes		
6.5 lb		10dx1.5" Nails							





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D5: 5th Fl 1-7 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products				Joists								
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.	Footage	Notes
30	A1	Red-I45	11.88	15'-6.00"	None					No	465.0	
6	A11	Red-I45	11.88	4'-6.00"	None					No	27.0	
183	A2	Red-I45	11.88	12'-6.00"	None					No	2287.5	
36	A3	Red-I45	11.88	11'-6.00"	None					No	414.0	
13	A4	Red-I45	11.88	9'-0.00"	None					No	117.0	
21	A5	Red-I45	11.88	17'-6.00"	None					No	367.5	
147	A6	Red-I45	11.88	15'-0.00"	None					No	2205.0	
6	B1	Red-I45	9.5	4'-6.00"	None					No	27.0	
27	C1	Red-I65	11.88	18'-0.00"	None					No	486.0	
14	C2	Red-I65	11.88	10'-0.00"	None					No	140.0	
6	•••	Red-I45	9.5	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	Total	27.0
41	•••	Red-I65	11.88	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	Total	626.0
436	•••	Red-I45	11.88	•••••	••••••~•••••	••••~•••••	•••••	•••••	•••••	•••••	Total	5883.0

Red-I™ Products				Blocking Panels							
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts				Notes
200		Red-I45	11.875	14.188	1 Attached						
200		Red-I45	11.875	14.188	None						
30		Red-I65	11.875	13.438	1 Attached						
30		Red-I65	11.875	13.438	None						



				<b>Connectors</b>									
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Flg. Slope	Flg. Angle	Flg. Offset	NetH	Finish	Notes
96	1	ITS1.81/11.88	4-N10	2-N10									
12	2	ITS1.81/9.5	4-N10	2-N10									

<b>RedLam™ LVL Products</b>				<b>LVL Beams</b>									
Quantity	Type	Size	Length	Grade	P.E.T.							Footage	Notes
2	RA1	5.25x11.88	9'-6.00"	2.0E								19.0	
1	RA2	5.25x11.88	12'-0.00"	2.0E								12.0	
1	RA3	5.25x11.88	14'-0.00"	2.0E								14.0	
2	RA4	5.25x11.88	8'-0.00"	2.0E								16.0	
4	RA5	5.25x11.88	4'-0.00"	2.0E								16.0	
1	RA6	5.25x11.88	10'-0.00"	2.0E								10.0	
11	***	5.25x11.88	.....	.....	.....							<i>Total</i>	87.0

<b>RedLam™ LVL Products</b>				<b>LVL Rim Board</b>									
Lineal Ft	Type	Size	Grade	LSL Substitution							Footage	Notes	
816		1.75x11.88		N/A							816.0		

<b>RedBuilt™ Products</b>				<b>LSL Rim Board</b>									
Lineal Ft	Type	Size	Grade	LVL Substitution							Footage	Notes	
624		1.5x11.88	1.3E	Allowed							624.0		
32		1.5x9.5	1.3E	Allowed							32.0		
32.0	***	1.5x9.5	.....	.....							<i>Total</i>	32.0	
624.0	***	1.5x11.88	.....	.....							<i>Total</i>	624.0	

<b>Third-Party (Sourced by RedBuilt™)</b>				<b>Glulam Beams</b>									
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.				Footage	Notes	
2	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial					20.0		
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial					8.0		
1	GB3	5.125x12	15'-0.00"	24F-V4	5000'	Industrial					15.0		
1	GC1	5.125x16.5	16'-0.00"	24F-V4	5000'	Industrial					16.0	1	
1	GC2	5.125x16.5	19'-0.00"	24F-V4	5000'	Industrial					19.0	1	
2	***	5.125x9 V4	.....	.....							<i>Total</i>	20.0	
3	***	5.125x12 V4	.....	.....							<i>Total</i>	23.0	
2	***	5.125x16.5 V4	.....	.....							<i>Total</i>	35.0	
Note 1		Roof beams from S2.06											

				<b>Hardware</b>									
Quantity	Type	Description											Notes
6.0 lb		10dx1.5" Nails											





# Material List

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D6: 5th Fl 7-10 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

AFP

Red-I™ Products				Joists										
Quantity	Type	Series	Depth	Length	Profile	Bevel Cut	WS Att.	Knockouts	Camber	P.E.T.		Footage	Notes	
26	A1	Red-I45	11.88	15'-6.00"	None					No		403.0		
6	A11	Red-I45	11.88	4'-6.00"	None					No		27.0		
107	A2	Red-I45	11.88	12'-6.00"	None					No		1337.5		
36	A3	Red-I45	11.88	11'-6.00"	None					No		414.0		
13	A4	Red-I45	11.88	9'-0.00"	None					No		117.0		
21	A5	Red-I45	11.88	17'-6.00"	None					No		367.5		
67	A6	Red-I45	11.88	15'-0.00"	None					No		1005.0		
6	B1	Red-I45	9.5	4'-6.00"	None					No		27.0		
6	•••	Red-I45	9.5	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	•••••	Total	27.0	
276	•••	Red-I45	11.88	•••••	••••••••••	••••••••••	•••••	•••••	•••••	•••••	•••••	Total	3671.0	

Red-I™ Products				Blocking Panels								
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts				Notes	
125		Red-I45	11.875	14.188	1 Attached							
96		Red-I45	11.875	14.188	None							

				Connectors										
Quantity	Type	Model	Top	Face	Member	Slope	Skew	Fig. Slope	Fig. Angle	Fig. Offset	NetH	Finish	Notes	
100	1	ITS1.81/11.88	4-N10	2-N10										
12	2	ITS1.81/9.5	4-N10	2-N10										



RedLam™ LVL Products				LVL Beams					
Quantity	Type	Size	Length	Grade	P.E.T.		Footage	Notes	
2	RA1	5.25x11.88	9'-6.00"	2.0E			19.0		
1	RA2	5.25x11.88	12'-0.00"	2.0E			12.0		
1	RA3	5.25x11.88	14'-0.00"	2.0E			14.0		
2	RA4	5.25x11.88	8'-0.00"	2.0E			16.0		
4	RA5	5.25x11.88	4'-0.00"	2.0E			16.0		
1	RA6	5.25x11.88	10'-0.00"	2.0E			10.0		
11	***	5.25x11.88	.....	.....	.....	.....	Total	87.0	

RedLam™ LVL Products				LVL Rim Board					
Lineal Ft	Type	Size	Grade	LSL Substitution		Footage	Notes		
448		1.75x11.88		N/A		448.0			

RedBuilt™ Products				LSL Rim Board					
Lineal Ft	Type	Size	Grade	LVL Substitution		Footage	Notes		
416		1.5x11.88	1.3E	Allowed		416.0			
16		1.5x9.5	1.3E	Allowed		16.0			
16.0	***	1.5x9.5	.....	.....	.....	Total	16.0		
416.0	***	1.5x11.88	.....	.....	.....	Total	416.0		

Third-Party (Sourced by RedBuilt™)				Glulam Beams					
Quantity	Type	Size	Length	Layup	Camber	Appearance	P.E.T.	Footage	Notes
2	GA1	5.125x9	10'-0.00"	24F-V4	5000'	Industrial		20.0	
2	GB1	5.125x12	4'-0.00"	24F-V4	5000'	Industrial		8.0	
2	***	5.125x9 V4	.....	.....	.....	.....	.....	Total	20.0
2	***	5.125x12 V4	.....	.....	.....	.....	.....	Total	8.0

				Hardware					
Quantity	Type	Description						Notes	
6.5 lb		10dx1.5" Nails							





# Material List

AFP

**RB Number** | 110805  
**Project Name** | Westman Mill  
**Location** | Olympia, WA

**Operator** | Joe Legerski  
**Office** | Boise

**Delivery Plant** | D7: 3rd Fl Grid 6  
 Stayton

**Comment** |  
**Status** | Approved For Production  
**Report Type** | Customer

Red-I™ Products				Blocking Panels							
Quantity	Type	Series	Depth	Length	End Blocks	Custom Depth	Knockouts			Notes	
20		Red-I45	11.875	14.188	None						
20		Red-I65	11.875	13.438	None						

RedLam™ LVL Products				LVL Rim Board						
Lineal Ft	Type	Size	Grade	LSL Substitution					Footage	Notes
32		1.75x11.88		N/A					32.0	

CM 7/30/19- See Rev. 03 provided on page #28 which includes beam revisions per RFI 008





RedBuilt™, LLC  
200 E Mallard Drive; Boise, Idaho 83706 • Mail: PO Box 60; Boise, Idaho 83707  
Ph: (208) 395-2400 • Fx: (208) 395-2443

## RedBuilt Calculations

Date: 5/24/2019  
Project: Westman Mill  
Location: Olympia, WA  
Job No.: 110805

The professional engineer's seal on this letter is to confirm the RedBuilt products identified on the attached calculation(s) are designed to support the loads shown for the span(s) and spacing(s) indicated. The attached calculation(s) assumes that adequate detailing has been performed by others in accordance with RedBuilt recommendations.

I have only reviewed the RedBuilt calculation(s). I have not reviewed the project construction documents or any other project information. The design loads, span(s) and spacing(s) were provided by others. If this information is incorrect or incomplete, notify your RedBuilt Project Manager, Tim Kolb at 208-395-2454, immediately. The suitability and application of the identified RedBuilt products for this project are the responsibility of the *Design Professional of Record*.

### Calculation(s) included:

- Type(s): A1, A1-overspace, A5, A5-overspace, B1, A11, A7, A7-overspace, C2, C1 & A10



05/24/2019

### RedBuilt™ Product Approvals:

RedLam™ ESR 2993, Red-I™ Joists: ESR 2994, Open-web trusses (Red-L™, Red-W™, Red-S™, Red-M™, Red-H™): ESR 1774





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/21/19 9:01 AM  
**Designer:** Joe Legerski  
**Comment:** @ flush beam

**Type: A1**

## 11.875" Red-I45™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	42%	750	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	60%	2812	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	52%	0.195	0.375	L / 925	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	49%	0.365	0.750	L / 493	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 5.4**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	400 (100)	400 (100)
<b>Dead Reaction (lb)</b>	350	350
<b>Total Reaction (lb) (DOL%)</b>	750 (100)	750 (100)
<b>Bearing Support</b>	Flush Beam	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

HANGERS	Model	Top	Face	Member	Header	Size
<b>Left</b>	ITS1.81/11.88	4-10dx1.5"	2-10dx1.5"	2-Strong-Grip	LVL DF/SP	5.25x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/25/19 10:59 AM  
**Designer:** Joe Legerski  
**Comment:** 2" overspace


**Type:** A1-overspace

## 11.875" Red-I45™ @ 18" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	47%	844	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	68%	3164	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	58%	0.217	0.375	L / 829	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	54%	0.407	0.750	L / 442	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 4.6**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	450 (100)	450 (100)
<b>Dead Reaction (lb)</b>	394	394
<b>Total Reaction (lb) (DOL%)</b>	844 (100)	844 (100)
<b>Bearing Support</b>	Flush Beam	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

HANGERS	Model	Top	Face	Member	Header	Size
<b>Left</b>	ITS1.81/11.88	4-10dx1.5"	2-10dx1.5"	2-Strong-Grip	LVL DF/SP	5.25x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	18"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/20/19 3:55 PM  
**Designer:** Joe Legerski  
**Comment:** longest I45

**Type: A5**

## 11.875" Red-I45™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	47%	838	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	75%	3507	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	70%	0.294	0.419	L / 683	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	66%	0.552	0.838	L / 364	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 2.7**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, rigid supports. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	447 (100)	447 (100)
<b>Dead Reaction (lb)</b>	391	391
<b>Total Reaction (lb) (DOL%)</b>	838 (100)	838 (100)
<b>Bearing Support</b>	Bottom Wall	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/25/19 11:00 AM  
**Designer:** Joe Legerski  
**Comment:** 2" overspace

**Type:** A5-overspace

## 11.875" Red-I45™ @ 18" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	53%	942	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	84%	3945	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	78%	0.328	0.419	L / 612	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	73%	0.615	0.838	L / 327	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 2.1**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, rigid supports. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	502 (100)	502 (100)
<b>Dead Reaction (lb)</b>	440	440
<b>Total Reaction (lb) (DOL%)</b>	942 (100)	942 (100)
<b>Bearing Support</b>	Bottom Wall	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	18"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

2/25/2019 11:00:52 AM

Westman Mill : Floors : A5-overspace

Page 1 of 1

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.

RedBuilt™, RedSpec™, Red-I™, Red-I45™, Red-I45L™, Red-I58™, Red-I65™, Red-I65T™, Red-I90™, Red-I90H™, Red-I90HS™, Red-L™, Red-LT™, Red-W™, Red-S™, Red-M™, Red-H™, RedLam™, FloorChoice™ are trademarks of RedBuilt LLC, Boise ID, USA. Copyright © 2010-2018 RedBuilt LLC. All rights reserved.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/20/19 3:58 PM  
**Designer:** Joe Legerski  
**Comment:** stair landing

**Type: B1**

## 9.5" Red-I45™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
Shear (lb)	21%	340	1590	Floor(100%)	1.0D+1.0L	All Spans	PASS	
Positive Moment (ft-lb)	10%	361	3620	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
Span Live	11%	0.011	0.106	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
Span Total	6%	0.014	0.213	L / 999+	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 9.9**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, rigid supports. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
Live Reaction, Critical (lb) (DOL%)	283 (100)	283 (100)
Dead Reaction (lb)	57	57
Total Reaction (lb) (DOL%)	340 (100)	340 (100)
Bearing Support	Flush Ledger	Flush Ledger
Req'd Bearing, No Stiffeners (in)	1.75	1.75
Req'd Bearing, Stiffeners (in)	-	-

HANGERS	Model	Top	Face	Member	Header	Size
Left	ITS1.81/9.5	4-10dx1.5"	2-10dx1.5"	2-Strong-Grip	LSL	1.5x9.5
Right	ITS1.81/9.5	4-10dx1.5"	2-10dx1.5"	2-Strong-Grip	LSL	1.5x9.5

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	100	20	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/25/19 2:58 PM  
**Designer:** Joe Legerski  
**Comment:** stair landing

**Type: A11**

## 11.875" Red-I45™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
Shear (lb)	20%	360	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
Positive Moment (ft-lb)	9%	405	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
Span Live	8%	0.009	0.113	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
Span Total	5%	0.011	0.225	L / 999+	L / 240	1.0D+1.0L	All Spans	PASS

FloorChoice™ Rating: 9.9




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, rigid supports. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
Live Reaction, Critical (lb) (DOL%)	300 (100)	300 (100)
Dead Reaction (lb)	60	60
Total Reaction (lb) (DOL%)	360 (100)	360 (100)
Bearing Support	Bottom Wall	Flush Ledger
Req'd Bearing, No Stiffeners (in)	1.75	1.75
Req'd Bearing, Stiffeners (in)	-	-

HANGERS	Model	Top	Face	Member	Header	Size
Right	ITS1.81/11.88	4-10dx1.5"	2-10dx1.5"	2-Strong-Grip	LSL	1.5x9.5

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	100	20	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/21/19 7:24 AM  
**Designer:** Joe Legerski  
**Comment:** @ WF beam

**Type: A7**

## 11.875" Red-I45™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	39%	688	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	50%	2363	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	41%	0.141	0.344	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	38%	0.265	0.688	L / 624	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 7.4**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	367 (100)	367 (100)
<b>Dead Reaction (lb)</b>	321	321
<b>Total Reaction (lb) (DOL%)</b>	688 (100)	688 (100)
<b>Bearing Support</b>	Flush Beam	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

HANGERS	Model	Top	Face	Member	Header	Size
<b>Left</b>	IUS1.81/11.88		10-10d	2-Strong-Grip	LVL DF/SP	5.25x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.



RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/25/19 11:02 AM  
**Designer:** Joe Legerski  
**Comment:** 2" overspace

**Type:** A7-overspace

## 11.875" Red-I45™ @ 18" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	43%	773	1785	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	57%	2659	4685	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	46%	0.157	0.344	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	43%	0.295	0.688	L / 559	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 6.8**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	412 (100)	412 (100)
<b>Dead Reaction (lb)</b>	361	361
<b>Total Reaction (lb) (DOL%)</b>	773 (100)	773 (100)
<b>Bearing Support</b>	Flush Beam	Bottom Wall
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

HANGERS	Model	Top	Face	Member	Header	Size
<b>Left</b>	IUS1.81/11.88		10-10d	2-Strong-Grip	LVL DF/SP	5.25x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	18"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 5/24/19 8:41 AM  
**Designer:** Joe Legerski  
**Comment:** Elevator lobby

**Type: C2**

## 11.875" Red-I65™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
Shear (lb)	21%	475	2255	Floor(100%)	1.0D+1.0L	All Spans	PASS	
Positive Moment (ft-lb)	17%	1128	6750	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
Span Live	12%	0.029	0.238	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
Span Total	11%	0.054	0.475	L / 999+	L / 240	1.0D+1.0L	All Spans	PASS

FloorChoice™ Rating: **9.8**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
Live Reaction, Critical (lb) (DOL%)	253 (100)	253 (100)
Dead Reaction (lb)	222	222
Total Reaction (lb) (DOL%)	475 (100)	475 (100)
Bearing Support	Bottom Wall	Flush Beam
Req'd Bearing, No Stiffeners (in)	1.75	1.75
Req'd Bearing, Stiffeners (in)	-	-

HANGERS	Model	Top	Face	Member	Header	Size
Right	IUS2.56/11.88		10-10d	2-Strong-Grip	LVL DF/SP	3.5x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.



RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 5/24/19 8:43 AM  
**Designer:** Joe Legerski  
**Comment:** Elevator lobby

**Type: C1**

## 11.875" Red-I65™ @ 16" o.c.

This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
<b>Shear (lb)</b>	32%	712	2255	Floor(100%)	1.0D+1.0L	All Spans	PASS	
<b>Positive Moment (ft-lb)</b>	38%	2538	6750	Floor(100%)	1.0D+1.0L	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
<b>Span Live</b>	34%	0.121	0.356	L / 999+	L / 480	1.0D+1.0L	All Spans	PASS
<b>Span Total</b>	32%	0.226	0.713	L / 756	L / 240	1.0D+1.0L	All Spans	PASS

**FloorChoice™ Rating: 8.0**




Performance rating is based on: 24 oc (23/32", 3/4") sheathing, nailed only, 1 1/2" Lightweight Concrete topping, 1/2" Gypsum ceiling, simple span, flexible support. RedSpec has not performed a structural analysis of the sheathing.

SUPPORTS	Support 1	Support 2
<b>Live Reaction, Critical (lb) (DOL%)</b>	380 (100)	380 (100)
<b>Dead Reaction (lb)</b>	333	333
<b>Total Reaction (lb) (DOL%)</b>	713 (100)	713 (100)
<b>Bearing Support</b>	Bottom Wall	Flush Beam
<b>Req'd Bearing, No Stiffeners (in)</b>	1.75	1.75
<b>Req'd Bearing, Stiffeners (in)</b>	-	-

HANGERS	Model	Top	Face	Member	Header	Size
<b>Right</b>	IUS2.56/11.88		10-10d	2-Strong-Grip	LVL DF/SP	3.5x11.875

### SPANS AND LOADS

Dimensions represent horizontal design spans.



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Floor(100%)	40	35	0	16"	Floor Joist

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Deflection analysis is based on composite action with 24 oc (23/32", 3/4") sheathing, nailed only.
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red

The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.





RedSpec™ by RedBuilt™  
v7.1.9

**Project:** Westman Mill  
**Location:** Olympia, WA  
**Folder:** Floors  
**Date:** 2/26/19 7:21 AM  
**Designer:** Joe Legerski  
**Comment:** Low roof - longest

**Type: A10**

## 11.875" Red-I45™ @ 16" o.c.


This product meets or exceeds the set design controls for the application and loads listed

DESIGN CONTROLS	%	Design	Allow.	DOL	Combination	Pattern	Pass/Fail	
Shear (lb)	12%	253	2053	Snow(115%)	1.0D+1.0S	All Spans	PASS	
Positive Moment (ft-lb)	9%	479	5388	Snow(115%)	1.0D+1.0S	All Spans	PASS	
Negative Moment (ft-lb)	1%	-105	7496	Wind(160%)	0.6D+0.6W	All Spans	PASS	
DEFLECTIONS (in)	%	Design	Allow.	Design	Allow.	Combination	Pattern	Pass/Fail
Span Live	4%	0.014	0.379	L / 999+	L / 240	1.0D+1.0S	All Spans	PASS
Span Total	5%	0.024	0.506	L / 999+	L / 180	1.0D+1.0S	All Spans	PASS
SUPPORTS		Support 1	Support 2					
Live Reaction, Critical (lb) (DOL%)		152 (115)	152 (115)					
Dead Reaction (lb)		101	101					
Total Reaction (lb) (DOL%)		253 (115)	253 (115)					
Net Uplift Reaction (lb) (DOL%)		-55 (160)	-55 (160)					
Bearing Support		Flush Beam	Bottom Wall					
Req'd Bearing, No Stiffeners (in)		1.75	1.75					
Req'd Bearing, Stiffeners (in)		-	-					
HANGERS	Model	Top	Face	Member	Header	Size		
Left	IUS1.81/11.88		10-10d	2-Strong-Grip	LVL DF/SP	5.25x11.875		

### SPANS AND LOADS

Dimensions represent horizontal design spans.

Member Slope: 0/12



### APPLICATION LOADS

Type	Units	DOL	Live	Dead	Partition	Tributary	Member Type
Uniform	psf	Snow(115%)	30	20	0	16"	Snow Roof Joist

### ADDITIONAL LOADS

Type	Units	DOL	Live	Dead	Location from left	Application	Comment
Uniform	psf	Wind(160%)	-38.2	0	0'-0.0" to 7'-7.0"	Adds To	Gross ULT

### NOTES

- Building code and design methodology: 2015 IBC ASD (US).
- Continuous lateral support required at top edge. Lateral support at bottom edge shall be per RedBuilt recommendations.

\\redb-file400v\Secure\\_Sold Projects\11xxxx\1108xx\110805 Westman Mill\Design\110805 We.red


The products noted are intended for interior, untreated, non-corrosive applications with normal temperatures and dry conditions of use, and must be installed in accordance with local building code requirements and RedBuilt™ recommendations. The loads, spans, and spacing have been provided by others and must be approved for the specific application by the design professional for the project. Unless otherwise noted, this output has not been reviewed by a RedBuilt™ associate. PRODUCT SUBSTITUTION VOIDS THIS ANALYSIS.

# I-JOIST INSTALLATION INFORMATION


**ATTENTION BUILDER**  
Enclosed is **IMPORTANT** information on how to safely and properly install RedBuilt™ Joists. Personal injury or death may result from failure to read and follow this information.



## 1 PRODUCT HANDLING



## 2 PRODUCT STORAGE



**WARNING**  
Workers should stay clear when cutting the banding to avoid possible injury from flying banding or toppling joists.

## 3 GENERAL INFORMATION


- All nails specified in framing package to be "common" nails unless noted otherwise.
- All joists not marked "Precision End Trim" (PET) on the material list may be sent up to 2'-0" longer than the length indicated on the material list.
- Do not scale drawings: written dimensions take precedence.
- Manufacturer's responsibility is only for the design of the RedBuilt™ products and not for any supporting structure or loads other than indicated herein. All materials shall be supplied by others, unless specifically noted as "by RB" or "by RedBuilt™" herein.

Abbreviation	Term
AFP	Approved for Production
AOR	Architect of Record
CI	Centerline
DBL	Double
DL	Dead Load
EOR	Engineer of Record
FBO	Framing by Others
FOC	Face of Concrete
FOS	Face of Stud
GC	General Contractor
LL	Live Load
LSL	Laminated Strand Lumber
LVL	Laminated Veneer Lumber
OFA	Out for Approval
OW	Open-Web Trusses by RedBuilt™
PLT	Plate
PSL	Parallel Stranded Lumber
RB	RedBuilt™

## 4 WEB STIFFENER REQUIREMENTS

### Web Stiffener Size and Material


Flange Width	Web Stiffener Size	Web Stiffener Material
1 3/4"	5/8" x 2 5/16"	Sheathing (with face grain vertical) that meets the requirements of PS1 or PS2
2.3", 2 1/2"	7/8" x 2 5/16"	
3 1/2"	2x4	Construction grade or better Red-190HS™ Joists require LVL/LSL



- Web stiffener requirements vary based on joist series and depth; they are always required at bearing on joists 20" in depth or greater.
- See plan/details for requirements specific to the joists being used on this project.
- If web stiffeners are required at hanger locations, they must be attached before placing joist in hanger.


### Nailing Quantities for Web Stiffener Attachment

I-Joist Depth	Red-145L™ & Red-145™ Joists	Red-158™ & Red-165™ Joists	Red-190™ & Red-190HS™ Joists	Red-190HS™ Joists
	End or Intermediate	End or Intermediate	End or Intermediate	End or Intermediate
9 1/2"	3	N/A	N/A	N/A
11 7/8"	3	3	3	4
14"	3	5	3	6
16"	3	6	4	6
18"	3	7	4	8
20"	3	8	5	10
22"	N/A	9	6	11
24"	N/A	10	6	13
26"	N/A	11	7	14
28"	N/A	12	8	15
30"	N/A	13	8	17
32"	N/A	N/A	9	18



## 5 FLANGE AND BEAM NAILING

Nailing pattern to be per contract drawings and specifications. In addition, nail spacing shall comply with the criteria listed.




**Joist attachment:** For 1 1/2" thick flanges, attach with a minimum of one 8dx2 1/2" box nail, each side of Red-I™ joist at bearing. Use 10dx3" box nails with 1 1/2" thick flanges, 12dx3 3/4" box nails with 1 3/4" thick flanges and 16dx3 3/4" box nails with 2 1/2" thick flanges. Maintain 1 1/2" minimum end distance to minimize splitting.

**IMPORTANT**  
Nailing closer than specified may cause the flange to split.

Nail Type	Nail Size	Closest On-Center Spacing Per Row <sup>(1)</sup>		
		1 1/2" Thick I-Joist Flange <sup>(2)</sup>	1 3/4" Thick I-Joist Flange <sup>(3)(4)</sup>	RedLam™ LVL Narrow Face
8dx2 1/2"	.113" x 2 1/2"	2"	4"	3"
10d	.131" x 2 1/2"	2"	4"	3"
	.128" x 3"	2"	4"	3"
	.148" x 3"	3"	4"	4" <sup>(5)</sup>
12d	.128" x 3 3/4"	2"	4"	3"
	.148" x 3 3/4"	3"	4"	4" <sup>(5)</sup>
	.135" x 3 3/2"	3"	4"	4"
16d	.148" x 3 3/4"	3"	4"	4" <sup>(5)</sup>
	.162" x 3 3/2"	4"	6"	8" <sup>(5)</sup>

(1) If more than one row of nails is used, offset rows at least 1/2" and stagger. Maintain 3/8" minimum edge distance.  
(2) Sheathing must be nailed to the full length of the top (or compression) flange on the I-joist with the maximum nail spacing as follows:  
• 18" OC for I-joists with flange widths less than 2".  
• 24" OC for I-joists with flange widths greater than 2".  
(3) 14-gauge staples may be a direct substitute for 8dx2 1/2" nails if a minimum penetration of 1" into the flange is maintained.  
(4) Minimum spacing must be 5" for 4 rows of nails.  
(5) Spacing may be reduced to 5" where nail penetration does not exceed 1 1/8".  
(6) For diaphragm nailing criteria see section 4.2.7 AWC SDPWS-2008.  
Maximum diaphragm nail penetration for Red-145L™ and Red-158™ joists is 1 3/8".

## 6 INSTALLATION BRACING



**WARNING**  
Without correctly installed bracing, joists can buckle sideways or roll over, causing death, serious personal injury, or property damage.

**NOTICE**  
Installation bracing and procedures, as well as the safety of workers, are the responsibility of the installer. The installer should make sure that this installation information is understood by all persons involved in the joist installation.


**IMPORTANT**  
Strut lines must extend to braced end wall, beam or sheathing.

- 6' on-center for joists with 1 3/4" wide flanges
- 8' on-center for joists with 2.3" & 2 1/2" wide flanges
- 10' on-center for joists with 3 1/2" wide flanges

Strut lines are required at all bearing locations where joists are not otherwise braced.


Ends of cantilevers must be laterally stabilized with blocking, bracing or rim joist

I-joist blocking panel (or equal) required at each side of I-joist for lateral stability and to transfer wall load above (as occurs) to bearing wall below. See plan/details for specific applications.  
Blocking attachment: Minimum 10dx3" nails at 12" OC each side of I-joist blocking panel. When used for shear transfer, nail to bearing plate with connections equivalent to sheathing nail schedule.






- WARNING**
- All blocking, hangers, rim boards, and rim joists at the end supports of the I-joists must be completely installed and properly nailed.
  - I-joist flanges must remain straight within 1/2" from true alignment.
  - Sheathing must be completely attached to each I-joist before additional loads can be placed on the system.
  - Without bracing, buckling sideways or rollover is highly probable under light construction loads like a worker or stacked sheathing.

## 7 STANDARD INSTALLATION DETAILS



Distance "X"	
Under Roof	Under Floor
Span "x"	Span "x"
0'-20"	1 1/4"
20'-40"	2 1/2"
40'-60"	4"
60'-80"	5"
80'-100"	6"
100'-120"	7"
120'-140"	8"
140'-160"	9"
160'-180"	10"
180'-200"	11"
200'-220"	12"
220'-240"	13"
240'-260"	14"
260'-280"	15"
280'-300"	16"
300'-320"	17"
320'-340"	18"

**Recommended Attachment for Non-load Bearing Partitions**




**Filler Nailing Chart**

Specified Framing Nails	Req'd Filler Nails <sup>(1)</sup> (each side)
2-10d (3")	2
4-10d (3")	3
6-10d (3")	5
2-16d (3 1/2")	2
4-16d (3 1/2")	3
6-16d (3 1/2")	5

<sup>(1)</sup> Filler nails shall be 16d sinker or 12d common (0.148" x 3 1/2" long)

## 8 ALLOWABLE HOLES



**Table A - End Support**  
Minimum distance from edge of hole to inside face of nearest end support

Joist Depth	Joist Series	Round Hole Size															
		Square or Rectangular Hole Size															
		2"	4"	6"	8"	10"	12"	14"	16"	18"	20"						
9 1/2"	145L / 145	1.25"	2.5"	4"	5"	6"	7"	8.5"	9.5"	10.5"	13"	-	-	-	-	-	-
	158 / 165	1'-6"	3'-0"	5'-0"	-	-	-	-	-	-	-	-	-	-	-	-	-
	190	2'-0"	3'-6"	5'-6"	-	-	-	-	-	-	-	-	-	-	-	-	-
11 7/8"	145L / 145	1'-0"	2'-0"	3'-6"	5'-0"	-	-	-	-	-	-	-	-	-	-	-	-
	158 / 165	1'-6"	3'-0"	4'-6"	6'-6"	-	-	-	-	-	-	-	-	-	-	-	-
	190 / 190H	1'-6"	3'-6"	5'-6"	7'-0"	-	-	-	-	-	-	-	-	-	-	-	-
14"	145L / 145	1'-0"	2'-0"	3'-0"	4'-0"	6'-0"	-	-	-	-	-	-	-	-	-	-	-
	158 / 165	1'-0"	2'-6"	4'-0"	5'-6"	8'-0"	-	-	-	-	-	-	-	-	-	-	-
	190 / 190H	1'-0"	3'-0"	5'-0"	6'-6"	9'-0"	-	-	-	-	-	-	-	-	-	-	-
16"	145 / 165	1'-0"	1'-6"	3'-0"	4'-0"	5'-0"	8'-0"	-	-	-	-	-	-	-	-	-	-
	158	1'-0"	1'-6"	3'-0"	4'-6"	6'-6"	9'-6"	-	-	-	-	-	-	-	-	-	-
	190 / 190H	1'-0"	2'-0"	4'-0"	6'-0"	8'-6"	10'-6"	-	-	-	-	-	-	-	-	-	-
18"	145 / 165	1'-0"	1'-6"	3'-0"	4'-0"	5'-0"	8'-0"	-	-	-	-	-	-	-	-	-	-
	158	1'-0"	1'-6"	3'-0"	4'-6"	6'-6"	9'-6"	-	-	-	-	-	-	-	-	-	-
	190 / 190H	1'-0"	1'-0"	2'-6"	5'-0"	7'-0"	9'-6"	12'-6"	-	-	-	-	-	-	-	-	-
20"	145 / 165	1'-0"	1'-0"	2'-0"	3'-0"	4'-0"	5'-0"	7'-0"	7'-0"	10'-6"	-	-	-	-	-	-	-
	158	1'-0"	1'-0"	2'-0"	4'-0"	6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	-	-	-	-	-	-	-
	190 / 190H	1'-0"	1'-0"	2'-0"	4'-0"	6'-0"	8'-0"	10'-0"	11'-0"	14'-0"	-	-	-	-	-	-	-
22"	145 / 165	1'-0"	1'-0"	1'-6"	2'-6"	3'-6"	4'-6"	5'-6"	7'-6"	7'-6"	11'-6"	-	-	-	-	-	-
	158	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	-	-	-	-	-	-	-
	190 / 190H	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	-	-	-	-	-	-	-
24" to 26"	145 / 165	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	-	-	-	-	-	-	-
	158	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	-	-	-	-	-	-	-
	190 / 190H	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	-	-	-	-	-	-	-
28" to 32"	145 / 165	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	18'-0"	-	-	-	-	-	-
	158	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	18'-0"	-	-	-	-	-	-
	190 / 190H	1'-0"	1'-0"	1'-0"	3'-0"	5'-0"	7'-0"	9'-0"	12'-6"	16'-0"	18'-0"	-	-	-	-	-	-

**Table B - Intermediate or Cantilever Support**  
Minimum distance from edge of hole to inside face of nearest intermediate or cantilever support

Joist Depth	Joist Series	Round Hole Size															
		Square or Rectangular Hole Size															
		2"	4"	6"	8"	10"	12"	14"	16"	18"	20"						
9 1/2"	145L / 145	1'-0"	2'-6"	5'-0"	-	-	-	-	-	-	-	-	-	-	-	-	-
	158 / 165	1'-6"	4'-0"	6'-6"	-	-	-	-	-	-	-	-	-	-	-	-	-
	190	3'-0"	5'-6"	8'-0"	-	-	-	-	-	-	-	-	-	-	-	-	-
11 7/8"	145L / 145	1'-0"	2'-0"	4'-0"	6'-6"	-	-	-	-	-	-	-	-	-	-	-	-
	158 / 165	1'-0"	3'-0"	5'-6"	8'-6"	-	-	-	-	-	-	-	-	-	-	-	-
	190 / 190H	2'-0"	4'-6"	7'-6"	10'-0"	-	-	-									



GENERAL NOTES & LEGEND

DESIGN CONSIDERATIONS

BUILDING CODE:	2015 IBC
FLOOR DESIGN	
RESIDENTIAL LIVE LOAD:	40 PSF
RESIDENTIAL DEAD LOAD:	35 PSF
STAIRS LIVE LOAD:	100 PSF
STAIRS DEAD LOAD:	20 PSF
ROOF DESIGN	
-TYPE A9 & A10 JOISTS-	
SNOW LOAD (@ 115%):	30 PSF
(INCLUDES 5 PSF RAIN ON SNOW)	
DEAD LOAD:	20 PSF
GROSS WIND PRESSURE (ULT @ 160%):	-38.2 PSF

DRAWING NOTES & LEGEND

- FOR TYPICAL NOTES, STANDARD DETAILS, AND ABBREVIATIONS, SEE INSTALLATION COVERSHEET(S).
- ALL DIMENSIONS ARE FROM FACE-OF-STUD, FACE-OF-CONCRETE OR CENTER-OF COLUMN/BEAM UNLESS OTHERWISE NOTED
- XX(##) - PRODUCT CALLOUT AND QUANTITY ON PLAN.  
"XX" - STRUCTURAL MEMBER TYPE CALLOUT  
"##" - QUANTITY OF STRUCTURAL MEMBERS IN BAY
- RIM BOARD/FASCIA MATERIAL WILL BE SUPPLIED @ "STANDARD" 16'-0" LENGTHS AND AS EITHER LSL OR LVL

I-JOIST NOTES & LEGEND

- ALL I-JOISTS WILL BE SENT LONG TO BE FIELD TRIMMED
- (X) - CONTINUOUS HANGER TYPE. SEE HANGER INFO.

THIRD PARTY PRODUCTS SOURCED BY REDBUILT

REDBUILT WILL PROVIDE GLULAM BEAMS WITH A 5000' RADIUS CAMBER. V8 BEAMS WILL NOT BE CAMBERED.

- G? - LOCATION OF GLULAM BEAM. SEE MATERIAL LIST FOR MORE INFORMATION.
- ALL GLULAM BEAMS ARE SUPPLIED BASED ON THE SPECIFICATION SHOWN IN THE CONTRACT DOCUMENTS. REDBUILT SERVICES FOR THESE ITEMS ARE LIMITED TO PLACEMENT DRAWINGS ONLY. APPLICATION AND ADEQUACY REVIEW OF GLULAM BEAMS ARE THE SOLE RESPONSIBILITY OF THE DESIGN PROFESSIONAL OF RECORD AND ARE NOT PROVIDED BY REDBUILT.

RECTANGULAR SECTIONS


- R? - LOCATION OF BEAM OR COLUMN BY RB. SEE MATERIAL LIST FOR MORE INFORMATION.
- ALL REDLAM LVL MATERIAL AND ASSOCIATED HARDWARE PROVIDED BY REDBUILT IS AS SPECIFIED ON THE CONTRACT DRAWINGS. SPECIFICATIONS AND SIZE HAVE NOT BEEN VERIFIED BY REDBUILT ENGINEERING UNLESS OTHERWISE NOTED.

PRODUCT TYPE CHART

SEE MATERIAL LIST FOR MORE INFORMATION	
CALLOUT	MEMBER
A	11 7/8" RED-145 JOIST
B	9 1/2" RED-145 JOIST
C	11 7/8" RED-165 JOIST
GA	5 1/2"x9" GLULAM BEAM (THIRD PARTY)
GB	5 1/2"x12" GLULAM BEAM (THIRD PARTY)
RA	5 1/2"x11 7/8" REDLAM BEAM

PROJECT ASSUMPTIONS

- ALL MISCELLANEOUS ITEMS (SPRINKLER LINES, SOFFITS, DUCTWORK, ELECTRICAL CONDUITS, ETC.) ARE ASSUMED TO BE INCLUDED IN THE UNIFORM DESIGN DEAD LOAD SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.
- ALL OPENINGS (HATCHES, DUCTWORK, SKYLIGHTS, ETC.) ARE ASSUMED TO FIT BETWEEN REGULAR ON-CENTER SPACING AS SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.



3RD FLOOR - GRIDS 1 TO 7  
FRAMING LOCATION PLAN  
SCALE 1/8"=1'-0"

KEY NOTES

1. JOIST LAYOUT SHOWN DOES NOT ACCOUNT FOR CLEARANCE TO ANY FLOOR DRAINS. THE CONTRACTOR IS RESPONSIBLE FOR DRAIN LAYOUT. (NOTE: LIVING UNIT FLOOR JOISTS MAY BE OVERSPACED UP TO 2" FOR DRAIN CLEARANCE, THIS ALLOWS MOVING ANY ONE JOIST 4" MAX)
2. STAIR LANDING FRAMING BELOW THE 3RD FLOOR LEVEL WILL BE SHIPPED WITH THE 3RD FLOOR PRODUCT (SEE MATERIAL LIST). NOTE: LVL MATERIAL CAN NOT BE LOCATED DIRECTLY IN CONTACT WITH CONCRETE, USE MOISTURE BARRIER, BY OTHERS.
3. STAIR STRINGERS (AND ANY HARDWARE) ARE BY OTHERS
4. WIDE FLANGE BEAM FILLERS SHOWN IN DETAILS 11/56.00 & 12/56.00 ARE PROVIDED BY RB, SEE THE MATERIAL LIST.

Hangers



Quantity	Type	Model	Nailing			Web Stiffeners Required
			Top	Face	Member	
96	1	1T51.81/11.88	4-N10	2-N10		
12	2	1T51.81/9.5	4-N10	2-N10		
146	3	1U51.81/11.88		10-10d		
27	4	1U52.56/11.88		10-10d		

- REFER TO CURRENT SIMPSON STRONG TIE® LITERATURE FOR HANGER SPECIFIC INSTALLATION INSTRUCTIONS.
- WEB STIFFENERS IF REQUIRED MUST BE ATTACHED BEFORE PLACING JOIST IN HANGER.



IN ACCORDANCE WITH IBC SECTION 1603.1, THE PRODUCTS IN THIS PACKAGE HAVE BEEN DESIGNED FOR ONLY THOSE LOADS SPECIFICALLY SHOWN ON THE CONSTRUCTION DOCUMENTS. THE CONSTRUCTION DOCUMENTS AND PLACEMENT DIAGRAMS HAVE NOT BEEN REVIEWED BY A REDBUILT ENGINEER. IF OTHER LOADS (WIND UPLIFT, SNOW DRIFT, BRACE LOADS, ETC.) ARE TO BE APPLIED, PLEASE PROVIDE THE MAGNITUDE AND LOCATION.

APPROVED FOR PRODUCTION

RedBUILT Engineered Wood Products					
Westman Mill Olympia, WA	3rd Floor - Grids 1 to 7				
DRAWN	DATE	CHECKED	DATE	ORDER #	SHEET
JL	5/24/19	OFA	Comments	110805	2 of 8
BY	DATE	REMARKS			



CM 7/30/19- Rev. 03  
 indicating revisions  
 per RFI 008 to  
 include deletion of  
 the lounge beams





GENERAL NOTES & LEGEND

DESIGN CONSIDERATIONS

BUILDING CODE:	2015 IBC
FLOOR DESIGN	
RESIDENTIAL LIVE LOAD:	40 PSF
RESIDENTIAL DEAD LOAD:	35 PSF
STAIRS LIVE LOAD:	100 PSF
STAIRS DEAD LOAD:	20 PSF

DRAWING NOTES & LEGEND

- FOR TYPICAL NOTES, STANDARD DETAILS, AND ABBREVIATIONS, SEE INSTALLATION COVERSHEET(S).
- ALL DIMENSIONS ARE FROM FACE-OF-STUD, FACE-OF-CONCRETE OR CENTER-OF COLUMN/BEAM UNLESS OTHERWISE NOTED

XX(##) - PRODUCT CALLOUT AND QUANTITY ON PLAN.  
 "XX" - STRUCTURAL MEMBER TYPE CALLOUT  
 "##" - QUANTITY OF STRUCTURAL MEMBERS IN BAY

RIM BOARD/FASCIA MATERIAL WILL BE SUPPLIED @ "STANDARD" 16'-0" LENGTHS AND AS EITHER LSL OR LVL

I-JOIST NOTES & LEGEND

- ALL I-JOISTS WILL BE SENT LONG TO BE FIELD TRIMMED
- (X) - CONTINUOUS HANGER TYPE. SEE HANGER INFO.

THIRD PARTY PRODUCTS SOURCED BY REDBUILT

REDBUILT WILL PROVIDE GLULAM BEAMS WITH A 5000' RADIUS CAMBER. V8 BEAMS WILL NOT BE CAMBERED.


G? - LOCATION OF GLULAM BEAM. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL GLULAM BEAMS ARE SUPPLIED BASED ON THE SPECIFICATION SHOWN IN THE CONTRACT DOCUMENTS. REDBUILT SERVICES FOR THESE ITEMS ARE LIMITED TO PLACEMENT DRAWINGS ONLY. APPLICATION AND ADEQUACY REVIEW OF GLULAM BEAMS ARE THE SOLE RESPONSIBILITY OF THE DESIGN PROFESSIONAL OF RECORD AND ARE NOT PROVIDED BY REDBUILT.

RECTANGULAR SECTIONS

R? - LOCATION OF BEAM OR COLUMN BY RB. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL REDLAM LVL MATERIAL AND ASSOCIATED HARDWARE PROVIDED BY REDBUILT IS AS SPECIFIED ON THE CONTRACT DRAWINGS. SPECIFICATIONS AND SIZE HAVE NOT BEEN VERIFIED BY REDBUILT ENGINEERING UNLESS OTHERWISE NOTED.



**3RD FLOOR - GRIDS 7 TO 10  
FRAMING LOCATION PLAN**  
 SCALE 1/8"=1'-0"

KEY NOTES

1. JOIST LAYOUT SHOWN DOES NOT ACCOUNT FOR CLEARANCE TO ANY FLOOR DRAINS. THE CONTRACTOR IS RESPONSIBLE FOR DRAIN LAYOUT. (NOTE: LIVING UNIT FLOOR JOISTS MAY BE OVERSPACED UP TO 2" FOR DRAIN CLEARANCE, THIS ALLOWS MOVING ANY ONE JOIST 4" MAX)
2. STAIR LANDING FRAMING BELOW THE 3RD FLOOR LEVEL WILL BE SHIPPED WITH THE 3RD FLOOR PRODUCT (SEE MATERIAL LIST). NOTE: LVL MATERIAL CAN NOT BE LOCATED DIRECTLY IN CONTACT WITH CONCRETE, USE MOISTURE BARRIER, BY OTHERS.
3. STAIR STRINGERS (AND ANY HARDWARE) ARE BY OTHERS

Hangers						
Quantity	Type	Model	Nailing			Web Stiffeners Required
			Top	Face	Member	
100	1	ITS1.81/11.88	4-NIO	2-NIO		
12	2	ITS1.81/9.5	4-NIO	2-NIO		

- REFER TO CURRENT SIMPSON STRONG TIE® LITERATURE FOR HANGER SPECIFIC INSTALLATION INSTRUCTIONS.
- WEB STIFFENERS IF REQUIRED MUST BE ATTACHED BEFORE PLACING JOIST IN HANGER.

IN ACCORDANCE WITH IBC SECTION 1603.1, THE PRODUCTS IN THIS PACKAGE HAVE BEEN DESIGNED FOR ONLY THOSE LOADS SPECIFICALLY SHOWN ON THE CONSTRUCTION DOCUMENTS. THE CONSTRUCTION DOCUMENTS AND PLACEMENT DIAGRAMS HAVE NOT BEEN REVIEWED BY A REDBUILT ENGINEER. IF OTHER LOADS (WIND UPLIFT, SNOW DRIFT, BRACE LOADS, ETC.) ARE TO BE APPLIED, PLEASE PROVIDE THE MAGNITUDE AND LOCATION.

PRODUCT TYPE CHART	
SEE MATERIAL LIST FOR MORE INFORMATION	
CALLOUT	MEMBER
A	11 7/8" RED-145 JOIST
B	9 1/2" RED-145 JOIST
GA	5 1/8"x9" GLULAM BEAM (THIRD PARTY)
GB	5 1/8"x12" GLULAM BEAM (THIRD PARTY)
RA	5 1/4"x11 1/8" REDLAM BEAM

PROJECT ASSUMPTIONS  
 - ALL MISCELLANEOUS ITEMS (SPRINKLER LINES, SOFFITS, DUCTWORK, ELECTRICAL CONDUITS, ETC.) ARE ASSUMED TO BE INCLUDED IN THE UNIFORM DESIGN DEAD LOAD SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.  
 - ALL OPENINGS (HATCHES, DUCTWORK, SKYLIGHTS, ETC.) ARE ASSUMED TO FIT BETWEEN REGULAR ON-CENTER SPACING AS SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.

**APPROVED FOR PRODUCTION**

△						
△	JL	5/24/19	OFA Comments			
△	BY	DATE	REMARKS			
Westman Mill Olympia, WA						
DRAWN		DATE	CHECKED	DATE	ORDER #	SHEET
JL		2/26/19	-	-	110805	3 of 8

GENERAL NOTES & LEGEND

DESIGN CONSIDERATIONS

BUILDING CODE:	2015 IBC
FLOOR DESIGN	
RESIDENTIAL LIVE LOAD:	40 PSF
RESIDENTIAL DEAD LOAD:	35 PSF
STAIRS LIVE LOAD:	100 PSF
STAIRS DEAD LOAD:	20 PSF

DRAWING NOTES & LEGEND

- FOR TYPICAL NOTES, STANDARD DETAILS, AND ABBREVIATIONS, SEE INSTALLATION COVERSHEET(S).
- ALL DIMENSIONS ARE FROM FACE-OF-STUD, FACE-OF-CONCRETE OR CENTER-OF COLUMN/BEAM UNLESS OTHERWISE NOTED

XX(##) - PRODUCT CALLOUT AND QUANTITY ON PLAN.  
 "XX" - STRUCTURAL MEMBER TYPE CALLOUT  
 "##" - QUANTITY OF STRUCTURAL MEMBERS IN BAY

- RIM BOARD/FASCIA MATERIAL WILL BE SUPPLIED @ "STANDARD" 16'-0" LENGTHS AND AS EITHER LSL OR LVL

I-JOIST NOTES & LEGEND

- ALL I-JOISTS WILL BE SENT LONG TO BE FIELD TRIMMED
- (X) - CONTINUOUS HANGER TYPE. SEE HANGER INFO.

THIRD PARTY PRODUCTS SOURCED BY REDBUILT

REDBUILT WILL PROVIDE GLULAM BEAMS WITH A 5000' RADIUS CAMBER. V8 BEAMS WILL NOT BE CAMBERED.

G? - LOCATION OF GLULAM BEAM. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL GLULAM BEAMS ARE SUPPLIED BASED ON THE SPECIFICATION SHOWN IN THE CONTRACT DOCUMENTS. REDBUILT SERVICES FOR THESE ITEMS ARE LIMITED TO PLACEMENT DRAWINGS ONLY. APPLICATION AND ADEQUACY REVIEW OF GLULAM BEAMS ARE THE SOLE RESPONSIBILITY OF THE DESIGN PROFESSIONAL OF RECORD AND ARE NOT PROVIDED BY REDBUILT.

RECTANGULAR SECTIONS

R? - LOCATION OF BEAM OR COLUMN BY RB. SEE MATERIAL LIST FOR MORE INFORMATION.


- ALL REDLAM LVL MATERIAL AND ASSOCIATED HARDWARE PROVIDED BY REDBUILT IS AS SPECIFIED ON THE CONTRACT DRAWINGS. SPECIFICATIONS AND SIZE HAVE NOT BEEN VERIFIED BY REDBUILT ENGINEERING UNLESS OTHERWISE NOTED.

PRODUCT TYPE CHART

SEE MATERIAL LIST FOR MORE INFORMATION	
CALLOUT	MEMBER
A	11 7/8" RED-145 JOIST
B	9 1/2" RED-145 JOIST
C	11 7/8" RED-165 JOIST
GA	5 1/2"x9" GLULAM BEAM (THIRD PARTY)
GB	5 1/2"x12" GLULAM BEAM (THIRD PARTY)
RA	5 1/2"x11 7/8" REDLAM BEAM

PROJECT ASSUMPTIONS

- ALL MISCELLANEOUS ITEMS (SPRINKLER LINES, SOFFITS, DUCTWORK, ELECTRICAL CONDUITS, ETC.) ARE ASSUMED TO BE INCLUDED IN THE UNIFORM DESIGN DEAD LOAD SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.
- ALL OPENINGS (HATCHES, DUCTWORK, SKYLIGHTS, ETC.) ARE ASSUMED TO FIT BETWEEN REGULAR ON-CENTER SPACING AS SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.



4TH FLOOR - GRIDS 1 TO 7  
FRAMING LOCATION PLAN

SCALE 1/8" = 1'-0"

KEY NOTES

1. JOIST LAYOUT SHOWN DOES NOT ACCOUNT FOR CLEARANCE TO ANY FLOOR DRAINS. THE CONTRACTOR IS RESPONSIBLE FOR DRAIN LAYOUT. (NOTE: LIVING UNIT FLOOR JOISTS MAY BE OVERSPACED UP TO 2" FOR DRAIN CLEARANCE, THIS ALLOWS MOVING ANY ONE JOIST 4" MAX.)

Hangers

Quantity	Type	Model	Nailing			Web Stiffeners Required
			Top	Face	Member	
96	1	ITS1.81/11.88	4-N10	2-N10		
12	2	ITS1.81/9.5	4-N10	2-N10		

- REFER TO CURRENT SIMPSON STRONG TIE® LITERATURE FOR HANGER SPECIFIC INSTALLATION INSTRUCTIONS.

- WEB STIFFENERS IF REQUIRED MUST BE ATTACHED BEFORE PLACING JOIST IN HANGER.

IN ACCORDANCE WITH IBC SECTION 1603.1, THE PRODUCTS IN THIS PACKAGE HAVE BEEN DESIGNED FOR ONLY THOSE LOADS SPECIFICALLY SHOWN ON THE CONSTRUCTION DOCUMENTS. THE CONSTRUCTION DOCUMENTS AND PLACEMENT DIAGRAMS HAVE NOT BEEN REVIEWED BY A REDBUILT ENGINEER. IF OTHER LOADS (WIND UPLIFT, SNOW DRIFT, BRACE LOADS, ETC.) ARE TO BE APPLIED, PLEASE PROVIDE THE MAGNITUDE AND LOCATION.

APPROVED FOR PRODUCTION

△				 Engineered Wood Products	
△	JL	5/24/19	OFA Comments		
△	BY	DATE	REMARKS		
Westman Mill Olympia, WA					
DRAWN	DATE	CHECKED	DATE	ORDER #	SHEET
JL	2/26/19	-	-	110805	4 of 8



GENERAL NOTES & LEGEND

DESIGN CONSIDERATIONS

BUILDING CODE:	2015 IBC
FLOOR DESIGN	
RESIDENTIAL LIVE LOAD:	40 PSF
RESIDENTIAL DEAD LOAD:	35 PSF
STAIRS LIVE LOAD:	100 PSF
STAIRS DEAD LOAD:	20 PSF

DRAWING NOTES & LEGEND

- FOR TYPICAL NOTES, STANDARD DETAILS, AND ABBREVIATIONS, SEE INSTALLATION COVERSHEET(S).
- ALL DIMENSIONS ARE FROM FACE-OF-STUD, FACE-OF-CONCRETE OR CENTER-OF COLUMN/BEAM UNLESS OTHERWISE NOTED

XX(##) - PRODUCT CALLOUT AND QUANTITY ON PLAN.  
 "XX" - STRUCTURAL MEMBER TYPE CALLOUT  
 "##" - QUANTITY OF STRUCTURAL MEMBERS IN BAY

RIM BOARD/FASCIA MATERIAL WILL BE SUPPLIED @ "STANDARD" 16'-0" LENGTHS AND AS EITHER L5L OR LVL

I-JOIST NOTES & LEGEND

- ALL I-JOISTS WILL BE SENT LONG TO BE FIELD TRIMMED

(X) - CONTINUOUS HANGER TYPE. SEE HANGER INFO.

THIRD PARTY PRODUCTS SOURCED BY REDBUILT

REDBUILT WILL PROVIDE GLULAM BEAMS WITH A 5000' RADIUS CAMBER. V8 BEAMS WILL NOT BE CAMBERED.


G? - LOCATION OF GLULAM BEAM. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL GLULAM BEAMS ARE SUPPLIED BASED ON THE SPECIFICATION SHOWN IN THE CONTRACT DOCUMENTS. REDBUILT SERVICES FOR THESE ITEMS ARE LIMITED TO PLACEMENT DRAWINGS ONLY. APPLICATION AND ADEQUACY REVIEW OF GLULAM BEAMS ARE THE SOLE RESPONSIBILITY OF THE DESIGN PROFESSIONAL OF RECORD AND ARE NOT PROVIDED BY REDBUILT.

RECTANGULAR SECTIONS

R? - LOCATION OF BEAM OR COLUMN BY RB. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL REDLAM LVL MATERIAL AND ASSOCIATED HARDWARE PROVIDED BY REDBUILT IS AS SPECIFIED ON THE CONTRACT DRAWINGS. SPECIFICATIONS AND SIZE HAVE NOT BEEN VERIFIED BY REDBUILT ENGINEERING UNLESS OTHERWISE NOTED.



4TH FLOOR - GRIDS 7 TO 10  
 FRAMING LOCATION PLAN  
 SCALE 1/8" = 1'-0"

KEY NOTES

1. JOIST LAYOUT SHOWN DOES NOT ACCOUNT FOR CLEARANCE TO ANY FLOOR DRAINS. THE CONTRACTOR IS RESPONSIBLE FOR DRAIN LAYOUT. (NOTE: LIVING UNIT FLOOR JOISTS MAY BE OVERSPACED UP TO 2" FOR DRAIN CLEARANCE, THIS ALLOWS MOVING ANY ONE JOIST 4" MAX)

Hangers						
Quantity	Type	Model	Nailing			Web Stiffeners Required
			Top	Face	Member	
100	1	ITS1.81/11.88	4-N10	2-N10		
12	2	ITS1.81/9.5	4-N10	2-N10		

- REFER TO CURRENT SIMPSON STRONG TIE® LITERATURE FOR HANGER SPECIFIC INSTALLATION INSTRUCTIONS.
- WEB STIFFENERS IF REQUIRED MUST BE ATTACHED BEFORE PLACING JOIST IN HANGER.

IN ACCORDANCE WITH IBC SECTION 1603.1, THE PRODUCTS IN THIS PACKAGE HAVE BEEN DESIGNED FOR ONLY THOSE LOADS SPECIFICALLY SHOWN ON THE CONSTRUCTION DOCUMENTS. THE CONSTRUCTION DOCUMENTS AND PLACEMENT DIAGRAMS HAVE NOT BEEN REVIEWED BY A REDBUILT ENGINEER. IF OTHER LOADS (WIND UPLIFT, SNOW DRIFT, BRACE LOADS, ETC.) ARE TO BE APPLIED, PLEASE PROVIDE THE MAGNITUDE AND LOCATION.

PRODUCT TYPE CHART	
SEE MATERIAL LIST FOR MORE INFORMATION	
CALLOUT	MEMBER
A	11 7/8" RED-145 JOIST
B	9 1/2" RED-145 JOIST
GA	5 1/8"x9" GLULAM BEAM (THIRD PARTY)
GB	5 1/8"x12" GLULAM BEAM (THIRD PARTY)
RA	5 1/2"x11 7/8" REDLAM BEAM

- PROJECT ASSUMPTIONS
- ALL MISCELLANEOUS ITEMS (SPRINKLER LINES, SOFFITS, DUCTWORK, ELECTRICAL CONDUITS, ETC.) ARE ASSUMED TO BE INCLUDED IN THE UNIFORM DESIGN DEAD LOAD SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.
  - ALL OPENINGS (HATCHES, DUCTWORK, SKYLIGHTS, ETC.) ARE ASSUMED TO FIT BETWEEN REGULAR ON-CENTER SPACING AS SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.

APPROVED FOR PRODUCTION

Westman Mill Olympia, WA		
4th Floor - Grids 7 to 10		
DRAWN JL	DATE 5/24/19	CHECKED -
BY JL	DATE 2/26/19	REMARKS OFA Comments
ORDER # 110805	SHEET 5 of 8	

GENERAL NOTES & LEGEND

DESIGN CONSIDERATIONS

BUILDING CODE:	2015 IBC
FLOOR DESIGN	
RESIDENTIAL LIVE LOAD:	40 PSF
RESIDENTIAL DEAD LOAD:	35 PSF
STAIRS LIVE LOAD:	100 PSF
STAIRS DEAD LOAD:	20 PSF

DRAWING NOTES & LEGEND

- FOR TYPICAL NOTES, STANDARD DETAILS, AND ABBREVIATIONS, SEE INSTALLATION COVERSHEET(S).
- ALL DIMENSIONS ARE FROM FACE-OF-STUD, FACE-OF-CONCRETE OR CENTER-OF COLUMN/BEAM UNLESS OTHERWISE NOTED

XX(##) - PRODUCT CALLOUT AND QUANTITY ON PLAN.  
 "XX" - STRUCTURAL MEMBER TYPE CALLOUT  
 "##" - QUANTITY OF STRUCTURAL MEMBERS IN BAY

RIM BOARD/FASCIA MATERIAL WILL BE SUPPLIED @ "STANDARD" 16'-0" LENGTHS AND AS EITHER L5L OR LVL

I-JOIST NOTES & LEGEND

- ALL I-JOISTS WILL BE SENT LONG TO BE FIELD TRIMMED
- (X) - CONTINUOUS HANGER TYPE. SEE HANGER INFO.

THIRD PARTY PRODUCTS SOURCED BY REDBUILT

REDBUILT WILL PROVIDE GLULAM BEAMS WITH A 5000' RADIUS CAMBER. V8 BEAMS WILL NOT BE CAMBERED.


G? - LOCATION OF GLULAM BEAM. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL GLULAM BEAMS ARE SUPPLIED BASED ON THE SPECIFICATION SHOWN IN THE CONTRACT DOCUMENTS. REDBUILT SERVICES FOR THESE ITEMS ARE LIMITED TO PLACEMENT DRAWINGS ONLY. APPLICATION AND ADEQUACY REVIEW OF GLULAM BEAMS ARE THE SOLE RESPONSIBILITY OF THE DESIGN PROFESSIONAL OF RECORD AND ARE NOT PROVIDED BY REDBUILT.

RECTANGULAR SECTIONS

R? - LOCATION OF BEAM OR COLUMN BY RB. SEE MATERIAL LIST FOR MORE INFORMATION.

- ALL REDLAM LVL MATERIAL AND ASSOCIATED HARDWARE PROVIDED BY REDBUILT IS AS SPECIFIED ON THE CONTRACT DRAWINGS. SPECIFICATIONS AND SIZE HAVE NOT BEEN VERIFIED BY REDBUILT ENGINEERING UNLESS OTHERWISE NOTED.



5TH FLOOR - GRIDS 1 TO 7  
 FRAMING LOCATION PLAN  
 SCALE 1/8"=1'-0"

KEY NOTES

- JOIST LAYOUT SHOWN DOES NOT ACCOUNT FOR CLEARANCE TO ANY FLOOR DRAINS. THE CONTRACTOR IS RESPONSIBLE FOR DRAIN LAYOUT. (NOTE: LIVING UNIT FLOOR JOISTS MAY BE OVERSPACED UP TO 2" FOR DRAIN CLEARANCE, THIS ALLOWS MOVING ANY ONE JOIST 4" MAX)
- ROOF BEAMS (2 GLULAMS SHOWN ON SHEET S2.06) WILL BE SHIPPED WITH THE 5TH FLOOR (SEE MATERIAL LIST).

Hangers						
Quantity	Type	Model	Nailing			Web Stiffeners Required
			Top	Face	Member	
96	1	ITS1.81/11.88	4-N10	2-N10		
12	2	ITS1.81/9.5	4-N10	2-N10		

- REFER TO CURRENT SIMPSON STRONG TIE® LITERATURE FOR HANGER SPECIFIC INSTALLATION INSTRUCTIONS.
- WEB STIFFENERS IF REQUIRED MUST BE ATTACHED BEFORE PLACING JOIST IN HANGER.

IN ACCORDANCE WITH IBC SECTION 1603.1, THE PRODUCTS IN THIS PACKAGE HAVE BEEN DESIGNED FOR ONLY THOSE LOADS SPECIFICALLY SHOWN ON THE CONSTRUCTION DOCUMENTS. THE CONSTRUCTION DOCUMENTS AND PLACEMENT DIAGRAMS HAVE NOT BEEN REVIEWED BY A REDBUILT ENGINEER. IF OTHER LOADS (WIND UPLIFT, SNOW DRIFT, BRACE LOADS, ETC.) ARE TO BE APPLIED, PLEASE PROVIDE THE MAGNITUDE AND LOCATION.

APPROVED FOR PRODUCTION

PRODUCT TYPE CHART	
SEE MATERIAL LIST FOR MORE INFORMATION	
CALLOUT	MEMBER
A	11 7/8" RED-145 JOIST
B	9 1/2" RED-145 JOIST
C	11 7/8" RED-165 JOIST
GA	5 1/2"x9" GLULAM BEAM (THIRD PARTY)
GB	5 1/2"x12" GLULAM BEAM (THIRD PARTY)
RA	5 1/2"x11 7/8" REDLAM BEAM

PROJECT ASSUMPTIONS

- ALL MISCELLANEOUS ITEMS (SPRINKLER LINES, SOFFITS, DUCTWORK, ELECTRICAL CONDUITS, ETC.) ARE ASSUMED TO BE INCLUDED IN THE UNIFORM DESIGN DEAD LOAD SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.
- ALL OPENINGS (HATCHES, DUCTWORK, SKYLIGHTS, ETC.) ARE ASSUMED TO FIT BETWEEN REGULAR ON-CENTER SPACING AS SHOWN, UNLESS SPECIFICALLY SHOWN OTHERWISE ON THESE SHOP DRAWINGS.

△					
△	JL	5/24/19	OFA Comments		
△	BY	DATE	REMARKS		
Westman Mill			5th Floor - Grids 1 to 7		
Olympia, WA					
DRAWN	DATE	CHECKED	DATE	ORDER #	SHEET
JL	2/26/19	-	-	110805	6 OF 8

