



**REPORT**

# DECEMBER 2022 GROUNDWATER MONITORING PASCO BULK FUEL TERMINALS SITE

Submitted to:

**Pasco Bulk Fuel Terminals Site Coordinating Group**

Submitted by:


**WSP USA Inc.**

18300 NE Union Hill Road, Suite 200, Redmond, Washington, USA 98052

+1 425 883-0777

GL003-1025-21.200

March 3, 2023



## Distribution List

Sandra Treccani, Washington State Department of Ecology

Pasco Bulk Fuel Terminals Site Coordinating Group

# Table of Contents

<b>1.0 INTRODUCTION .....</b>	<b>1</b>
1.1 Field Work .....	1
1.2 Field Equipment .....	2
1.3 Micropurging.....	2
1.4 Purge Water .....	3
<b>2.0 ATA SUMMARY.....</b>	<b>3</b>
2.1 Water Level Data .....	3
2.2 Analytical Results.....	3
2.3 Monitored Natural Attenuation Performance Assessment and Cleanup Determination.....	3
2.3.1 MNA Performance Assessment.....	3
2.3.2 Cleanup Determination .....	5
<b>3.0 REFERENCES .....</b>	<b>6</b>

## TABLES

Table 1: Monitoring Well Completion Data

Table 2: Groundwater Sampling Field Parameters

Table 3: Water Levels

Table 4: Geochemical Evaluation of Natural Attenuation Parameters

Table 5: Concentrations of Compounds Detected During the Last Four Sampling Events – Monitoring Wells Sorted by Area

## FIGURES

Figure 1: Site Map

Figure 2: Groundwater Elevations – December 2022

## APPENDICES

### APPENDIX A

Complete Tabulated Results for Groundwater Samples – December 2022

### APPENDIX B

Trend Graphs

## ACRONYMS AND ABBREVIATIONS

As	Arsenic
CMP	Compliance Monitoring Plan
COE	United States Army Corps of Engineers
Ecology	Washington State Department of Ecology
EPA	United States Environmental Protection Agency
Golder	Golder Associates USA Inc.
HDPE	High-density polyethylene
IAS	In-situ air sparging
MCL	Maximum Contaminant Limit
MDL	Method detection limit
ml/min	Milliliters per minute
MNA	Monitored Natural Attenuation
PCE	Perchloroethylene (tetrachloroethene)
PQL	Practical quantitation limit
SAP	Sampling and Analysis Plan
SEP-OUT	Sample identification for the COE oil-water separator outlet
Site	Pasco Bulk Fuel Terminals Site
SVE	Soil vapor extraction
TCE	Trichloroethene (trichloroethylene)
TPH	Total petroleum hydrocarbons
µg/L	micrograms per liter

## 1.0 INTRODUCTION

This report presents the results of the December 2022 groundwater monitoring fieldwork conducted by WSP USA Inc. (WSP; formerly Golder Associates USA Inc. [Golder]) at the Pasco Bulk Fuel Terminals Site (the Site) in Pasco, Washington. A site map is presented in Figure 1. This work was conducted in accordance with the Monitored Natural Attenuation (MNA) Performance Monitoring Plan (Golder 2019) in conjunction with the Sampling and Analysis Plan (SAP) contained within the Compliance Monitoring Plan (CMP) for the Site dated December 20, 2000 (Golder 2000).

Remedial actions conducted at the Site from 1999 through 2014 consisted primarily of in-situ air sparging (IAS) in combination with soil vapor extraction (SVE). Groundwater extraction and treatment (“pump-and-treat”) was also used in some areas. During active remediation, major progress was made towards achieving cleanup across the Site. Based on SVE off-gas monitoring data, approximately 58,000 pounds of total petroleum hydrocarbons (TPH) were removed by IAS-SVE. The total TPH removal was greater because this estimate does not account for removal that occurred by pump-and-treat nor for in-situ biodegradation. TPH mass removal rates using IAS-SVE reached asymptotic levels; thus, IAS-SVE was no longer effective.

Under MNA, the group evaluated the Site risk and various alternatives to achieve Site closure (Golder 2013). The results of the evaluation indicated that MNA and institutional controls (institutional controls as described in the CAP [Ecology 1999]) were protective of human health and the environment and were the preferred alternative for achieving groundwater cleanup levels throughout the Site. Ecology issued a decision letter dated September 19, 2018 (Ecology 2018) that indicated MNA as a remedial action was covered under the existing Consent Decree for the Site, such that MNA can be implemented at the Site without modifying the Consent Decree.

The MNA Performance Monitoring Plan (Golder 2019) was prepared to work in conjunction with the SAP and QAPP contained within the CMP (Golder 2000) to provide the scope, methods, and procedures that will occur to ensure natural attenuation is occurring, is effective and protective of human health and the environment and demonstrates compliance with Site cleanup standards. Groundwater monitoring conducted under the MNA Performance Monitoring Plan was started in June 2019.

### 1.1 Field Work

The December 2022 groundwater monitoring was performed on December 5 and 6, 2022 and included the following activities:

- Groundwater monitoring was conducted on 18 groundwater-monitoring wells (MW-06, MW-08, MW-10A, MW-11A, MW-12, MW-13, MW-17, MW-18, MW-19, MW-20, MW-33, MW-34, MW-47, MW-48, MW-49, MW-62R, MW-63, and MW-66).
- Water level measurements were made on these wells, except for MW-48 and MW-49. These wells contain roots within them that obstruct a water level tape.
- Surface water sampling of the discharge from the oil-water separator (SEP-OUT) on the United States Army Corps of Engineers’ (COE) drain. In accordance with the CMP (Golder 2000), the COE drain is only sampled when there has been no measurable rain during the four days prior to sample collection. This ensures that the sample collected is predominately associated with groundwater from the COE drain.

In accordance with the MNA Performance Monitoring Plan (Golder 2019), each well was analyzed for those indicator substances that remain above cleanup levels in that well. In addition, select monitoring wells were also

analyzed for geochemical parameters - dissolved oxygen, nitrate, manganese, iron, sulfate, methane, redox potential (Eh), and alkalinity. Changes in these geochemical parameters can indicate that biodegradation is occurring. These changes can be evaluated over time within a well, or by comparing levels of these parameters in wells that are still impacted with indicator substances to wells that are located upgradient or in clean areas of the Site.

Positive evidence of biodegradation includes:

- Depressed oxygen, nitrate, or sulfate levels in source area wells as compared to background wells
- Low Oxidation-Reduction Potential (i.e., reducing conditions) in source area wells as compared to background wells
- Higher iron (Fe<sup>2+</sup>), manganese (Mn<sup>2+</sup>), and methane in source area wells as compared to background wells

During performance monitoring, natural attenuation parameters are measured in two wells (MW-18 and MW-62R) that have been below cleanup levels for more than five years, and in a selection of wells that have relatively higher petroleum hydrocarbon concentrations (MW-08, MW-11A, MW-12, MW-33, MW-34, and MW-63). The testing of these wells allows for comparison of geochemical parameters in areas where contaminants are being biodegraded compared to clean areas of the Site.

## 1.2 Field Equipment

Wells were sampled using peristaltic pumps with dedicated high-density polyethylene (HDPE) and silicone tubing. During previous sampling events, HDPE tubing was placed in each well at a depth approximately halfway between the bottom of the well screen and the water level in the well. A summary of monitoring well completion data, including tubing depths for each well, is presented in Table 1.

The HDPE tubing was inserted into a short (< 0.5 foot) length of silicone tubing that was inserted into the peristaltic pump. An extra length of HDPE tubing was used to connect the silicon tubing to a flow-through cell. Each length of silicon tubing and HDPE sample tubing were used only once to avoid cross-contamination between wells, except for well-specific dedicated tubing. The flow-through cell consisted of a 2-inch-diameter acrylic cylinder with a capped bottom that was attached to a 5-gallon bucket. The flow-through cell had an inlet port near the bottom and another outlet port near the top. The sample tubing was connected to the bottom port, so the cell filled from the bottom and flowed out the top port into a purge water container. A multimeter (pH, temperature, specific conductance, dissolved oxygen, and Eh) was inserted into the flow cell from the top and was monitored every 3-5 minutes to determine when field parameters had stabilized in the purge water.

Once the well was purged and field parameters had stabilized, the tubing was disconnected from the flow cell and the groundwater samples were collected directly from the sample tubing. The flow cells were rinsed with deionized water between wells. The HDPE tubing dedicated to each well was capped and left hanging in the well by attaching it to the well cap using line. The thermos-type well caps were used to secure the well after sampling. Well monument covers were securely bolted.

## 1.3 Micropurging

Well purging was conducted following the “micropurging” procedure accepted by EPA and described in Groundwater Sampling Procedure Low Stress Purging and Sampling (EPA 1997). This procedure recommends an initial purging rate of 200 to 500 milliliters per minute (ml/min) and a sampling rate of 100 to 250 ml/min, while

ensuring water level drawdown does not exceed 0.3 feet. This low-flow method minimizes well disturbances and therefore reduces turbidity, minimizes aeration of the groundwater during sample collection, and reduces the volume of purge water generated. In some cases, the well yield was insufficient to maintain a drawdown of less than 0.3 feet while continuously pumping at the minimal purge rate. Wells were considered sufficiently purged when field parameters remained stable for three consecutive measurements taken approximately 3 to 5 minutes apart. The field parameters were considered stable based on the following criteria:

- +/- 0.1 for pH
- +/- 3% for specific conductance
- +/- 10% for dissolved oxygen

The stabilized field measurements for pH, temperature, specific conductance, dissolved oxygen, and Eh for each well at the time sampling was initiated are presented in Table 2.

## **1.4 Purge Water**

Purge water was collected in 5-gallon containers at each sampling location. The purge water was then transferred into the 55-gallon drums for subsequent treatment and disposal.

## **2.0 ATA SUMMARY**

### **2.1 Water Level Data**

Water level data collected during December 2022 are presented in Figure 2 and Table 3.

### **2.2 Analytical Results**

Groundwater samples were stored in coolers with ice until delivered to Eurofins, an Ecology-certified laboratory located in Tacoma, Washington. Chain-of-custody procedures were followed. A complete tabulation of analytical results is provided in Appendix A.

All analytical data were subject to a data validation review. Data validation was conducted in accordance with the EPA Contract Laboratory Program, National Functional Guidelines for Organic and Inorganic Data Review (EPA 2017a, b). Data reporting qualifiers are included with the analytical results in Appendix A.

### **2.3 Monitored Natural Attenuation Performance Assessment and Cleanup Determination**

#### **2.3.1 MNA Performance Assessment**

Table 4 provides a summary of the geochemical analytical results obtained from the two background wells and from the six higher concentration wells or “impacted wells”. Evaluation of the results confirms that biodegradation is occurring in the remaining higher concentration areas. Evidence of biodegradation includes the following:

- Alkalinity is generally higher in the impacted wells, which is caused as carbon dioxide and is produced during biodegradation.
- Oxygen, nitrate, and sulfate concentrations are lower in the impacted wells as these electron acceptors are used up in the biodegradation process.

- Reduced forms of iron and manganese concentrations are higher in the impacted wells, due to the reduction of forms Fe<sup>3+</sup> and Mn<sup>4+</sup>.
- Methane concentrations are significantly higher in the impacted wells as methane is produced during biodegradation under anaerobic conditions. Methane was not detected above the reporting limit in the clean wells.

The above noted geochemical markers of biodegradation were more pronounced in some of the higher concentration wells, but all the impacted wells tested for geochemical parameters had indications that contaminant biodegradation is occurring in those wells.

Trend graphs of the analytical results since the start of monitored natural attenuation in 2014 are presented in Appendix B. Evaluation of trend graphs indicate the following:

- Area 2 – Arsenic is above cleanup levels in MW-06, MW-12, MW-13, and MW-63, with a long-term stable to slightly decreasing trend. Benzene is above cleanup level in MW-12 and MW-63, with a slight long-term decreasing trend. TPH is above cleanup level in MW-12 with a slight long-term decreasing trend since 2014. TPH and has been below the cleanup level in MW-63 in three out of the last four sampling rounds.
- Area 3 – Arsenic concentrations detected in MW-10A have been below the cleanup level during the last four sampling rounds. Arsenic is slightly above the cleanup level in MW-17.
- Area 4 – Arsenic and TPH are above the cleanup level in MW-11A, with no apparent recent trend. Trichloroethene (TCE) in MW-47 has been below the cleanup level for the last four consecutive sampling rounds.
- Area 6 – TPH is above the cleanup level in MW-08 and MW-19. Arsenic is above the cleanup level in MW-19. Concentrations of arsenic and TPH are steady to slightly decreasing in MW-19, and TPH concentrations are slightly decreasing in MW-08.
- Area 7 – Tetrachlorethene (PCE) is above the cleanup level in MW-20 and MW-49. TCE has been below the cleanup level for the last four sampling rounds in MW-20, and TCE is slightly below the cleanup level in MW-49. TPH is above the cleanup level in MW-33 and MW-34 and has a slight decreasing trend. Arsenic is above the cleanup level in MW-34 and has a slightly decreasing long-term trend.
- Area 8 – Arsenic concentrations have been decreasing in MW-48 in the long-term and have been fluctuating around the cleanup level since 2018. Arsenic concentrations in MW-48 were below the cleanup level during the last two sampling rounds.
- COE Drain Oil-Water Separator - Starting with the October 2019 sampling round, the COE Drain sample is collected from the oil-water separator discharge pipe. During previous rounds, samples were collected from inside of the concrete vault of the oil-water separator. Samples collected directly from the end of the discharge pipe of the oil-water separator are safer for sampling personnel and is more representative of the actual concentration contained in the water discharged from the COE Drain oil-water separator. PCE has historically been detected slightly above the 1.75 micrograms per liter (µg/L) cleanup level, however, PCE has been below the drinking water Maximum Contaminant Limit (MCL) of 5 µg/L since October 2008. PCE concentrations have been decreasing since 2015. The concentration of PCE detected during three of the last four sampling rounds was below the cleanup level.



### 2.3.2 Cleanup Determination

Under the MNA Performance Monitoring Plan, groundwater cleanup for each Remediation Area will be determined as follows:

- a) Within a Remediation Area, if any single well has not exceeded cleanup levels for a particular indicator substance for two consecutive annual monitoring events, then the performance monitoring for that contaminant in that well can be suspended.
- b) A well that has met Condition "a" can move into confirmational monitoring. Once in confirmational monitoring, if the indicator substance remains below its cleanup level for two consecutive confirmational sampling rounds, then that well will be considered clean for that substance. Monitoring events will occur not more frequently than semi-annually.

When all wells within a Remediation Area have met Condition "b" for all indicator substances, then the Remediation Area will have met groundwater cleanup levels.

To assist in evaluating compliance with the above criteria, Table 5 presents the analytical results for each indicator substance detected during the last four sampling events. Table 5 is sorted by cleanup area, and results presented in the table indicate the following criteria have been achieved:

- Area 2: MW-13 TPH concentrations have been below cleanup level for four consecutive rounds. TPH analysis is no longer required for MW-13.
- Area 3: MW-10A Arsenic concentrations have been below cleanup level for four consecutive rounds and the well is now considered to meet cleanup criteria. Sampling of MW-10A is no longer required.
- Area 4: MW-47 TCE concentrations have been below cleanup level for four consecutive rounds and the well is now considered to meet cleanup criteria. Sampling of MW-47 is no longer required.
- Area 7 MW-20 – TCE concentrations have been below cleanup level for four consecutive rounds. TCE analysis is no longer required for MW-20.

No other changes to the Performance Monitoring Plan are indicated. Annual sampling will continue in accordance with the Performance Monitoring Plan (Golder 2019).

#### WSP USA Inc.



Autumn Pearson  
*Assistant Consultant, Env. Scientist*



Gary L. Zimmerman  
*Vice President*

AP/GLZ/tp

v:\projects\2000 projects\003-1025 pasco\_holder\deliverables and tech work\reports\_gw\2022-12-gw-report\final\gl003102521-r-rev0-pasco groundwater-030323.docx

### 3.0 REFERENCES

- Golder Associates Inc. (Golder). 2013. Proposed Revised Cleanup Approach at the Pasco Bulk Fuel Terminals Site. Golder Associates Inc. May 8.
- Golder. 2019. Monitored Natural Attenuation Performance Monitoring Plan for Pasco Bulk Fuel Terminals Site. Golder Associates Inc. Redmond, Washington. June 12.
- Golder. 2000. Compliance Monitoring Plan for Pasco Bulk Fuel Terminals Site. Golder Associates Inc. Redmond, Washington. December 20.
- United States Environmental Protection Agency (EPA). 1997. Groundwater Sampling Procedures Low Stress Purging and Sampling, U.S. Environmental Protection Agency Memorandum, Region II. October 1.
- EPA. 2017a. National Functional Guidelines for Superfund Organic Methods Data Review. January.
- EPA. 2017b. National Functional Guidelines for Superfund Inorganic Methods Data Review. January.
- Washington State Department of Ecology (Ecology). 1999. Final Cleanup Action Plan, Port of Pasco Site.
- Ecology. 2018. Decision on Future Remedial Activities at the Pasco Bulk Fuels Terminal Site. Letter from Sandra Treccani (Ecology) to Daniel Smith (Crowley Maritime Corporation). September 19.

## Tables

**Table 1: Monitoring Well Completion Data**

Well	Installation Date	Coordinates		Ground Elevation (ft)	Top of Casing (ft elevation)	Stick-up (ft-bgs)	Total Boring Depth (ft-bgs)	Total Well Depth (ft-bgs)	Tubing Depth (ft-bgs)	Screened Interval			
		Northing	Eastings							(ft-bgs)		(ft elevation)	
		(ft)	(ft)							from	to	from	to
MW-06	11/22/86	326,727	2,354,911	342.31	342.10	-0.21	14.5	13	10	3.0	13.0	339.3	329.3
MW-08	11/22/86	327,200	2,354,238	339.86	339.67	-0.19	10	10	7	2.0	10.0	337.9	329.9
MW-10A	10/20/87	327,147	2,354,587	342.70	342.35	-0.35	13	12.5	10	2.5	12.5	340.2	330.2
MW-11A	10/20/87	327,031	2,354,586	342.36	342.04	-0.32	15	14.9	11	5.0	14.9	337.4	327.5
MW-12	03/03/87	327,036	2,354,771	343.07	342.74	-0.33	13	13	10	3.5	13.0	339.6	330.1
MW-13	03/03/87	326,833	2,354,689	342.31	342.15	-0.16	13.6	13.6	10	4.0	13.6	338.3	328.7
MW-17	03/03/87	327,230	2,354,567	343.68	343.32	-0.36	12.9	12.9	10	3.3	12.9	340.4	330.8
MW-18	03/04/87	327,235	2,354,422	340.98	340.68	-0.30	9.3	9.3	7	2.0	9.3	339.0	331.7
MW-19	03/04/87	327,069	2,354,360	340.58	340.17	-0.41	10.3	10.3	8	2.8	10.3	337.8	330.3
MW-20	03/04/87	326,907	2,354,277	340.23	339.93	-0.30	10.4	10.4	7	3.0	10.4	337.2	329.8
MW-21R	02/02/99	327,230	2,354,735	343.42	343.10	-0.32	14.5	14	10	3.4	13.4	340.0	330.0
MW-31	05/09/93	326,849	2,353,859	339.81	339.40	-0.41	9	8.5	7	3.0	8.0	336.8	331.8
MW-33	05/07/93	326,955	2,354,035	340.64	340.12	-0.52	10	9	7	3.5	8.5	337.1	332.1
MW-34	05/07/93	326,815	2,354,243	341.29	340.90	-0.39	9	8.75	8	3.3	8.3	338.0	333.0
MW-47	08/16/94	326,943	2,354,388	341.0	340.24	-0.76	9	8.5	6	3.5	8.5	337.5	332.5
MW-48	08/16/94	327,277	2,353,896	342.0	341.79	-0.21	13	11	9	6.0	11.0	336.0	331.0
MW-49	08/16/94	326,998	2,353,747	343.0	343.65	0.65	14	14	12	7.5	14.0	335.5	329.0
MW-62R	02/25/10	--	--	343.24	343.04	-0.2	16	15	10	5.0	15.0	338.2	328.2
MW-63	03/29/01	326,885	2,354,856	343.11	342.81	-0.30	16	15.5	11	5.5	15.5	337.6	327.6
MW-66	06/08/06	326,651	2,354,825	342.87	342.23	-0.64	26.5	24	21	4.0	24.0	338.9	318.9

Notes:

Survey data not obtained for replacement well MW-62R; elevation data relative to MW-63

ft-bgs = feet below ground surface

**Table 2: Groundwater Sampling Field Parameters**

Well	Date Sampled	Time Sampled	pH	Conductivity (uS/cm)	Temp. (°C)	Dissolved Oxygen (mg/L)	Eh (rel mV)
MW-06	12/5/2022	14:15	6.91	813	16.4	0.56	-19
MW-08	12/6/2022	9:05	6.91	734	14.9	3.71	-90
MW-10A	12/6/2022	8:22	6.96	712	17.5	0.25	151
MW-11A	12/5/2022	15:34	6.75	864	17.2	0.13	-60
MW-12	12/5/2022	9:12	6.97	733	17.2	2.40	-62
MW-13	12/5/2022	14:55	6.86	700	16.4	0.19	-10
MW-17	12/6/2022	8:59	6.96	1,005	17.6	0.21	-20
MW-18	12/5/2022	11:40	7.15	1711*	16.2	3.79	215
MW-19	12/5/2022	12:41	6.96	1475*	16.8	2.84	-123
MW-20	12/5/2022	13:51	7.31	1366*	13.3	3.77	-112
MW-33	12/5/2022	16:14	6.97	1616*	13.7	3.32	-130
MW-34	12/5/2022	15:01	7.22	1584*	13.3	3.36	-110
MW-47	12/5/2022	16:37	7.33	678	15.1	1.40	-22
MW-48	12/6/2022	9:58	7.01	816	16.4	0.15	-17
MW-49	12/6/2022	10:04	6.94	748	15.6	3.55	90
MW-62R	12/5/2022	13:36	6.99	710	16.4	1.28	13
MW-63	12/5/2022	13:40	7.06	1,618	16.1	1.60	-21
MW-66	12/6/2022	10:32	6.99	624	16.5	0.20	-67

## Notes:

NS = not sampled

nm = not measured; meter was not working properly

The field parameters on this sheet were recorded after values stabilized, just prior to sample collection

uS/cm = microsiemens per centimeter

mg/L = milligrams per liter

rel mV = relative millivolts

\* = the conductivity probe on one of the multimeters would not calibrating properly 12/5/2022, measurements are likely high

**Table 3: Water Levels**

Well	Date	Time	Water Level (ft-bgs)	Water Level (ft elevation)	Comments
MW-06	12/5/2022	13:55	5.60	336.71	
MW-08	12/6/2022	8:17	4.67	335.19	
MW-10A	12/6/2022	8:06	6.84	335.86	
MW-11A	12/5/2022	15:13	6.43	335.93	
MW-12	12/5/2022	8:42	6.73	336.34	
MW-13	12/5/2022	14:30	5.91	336.40	
MW-17	12/6/2022	8:37	7.88	335.80	
MW-18	12/5/2022	10:55	5.49	335.49	
MW-19	12/5/2022	12:08	5.30	335.28	
MW-20	12/5/2022	13:20	5.00	335.23	
MW-33	12/5/2022	15:40	5.86	334.78	
MW-34	12/5/2022	14:25	6.25	335.04	
MW-47	12/5/2022	16:19	5.62	335.38	
MW-48	12/6/2022				Roots obstruct well
MW-49	12/6/2022				Roots obstruct well
MW-62R	12/5/2022	13:15	6.42	336.82	
MW-63	12/5/2022	12:10	6.69	336.42	
MW-66	12/6/2022	10:12	6.58	336.29	

Notes:

Survey data is estimated for replacement wells MW-46R and MW-62R

ft-bgs = feet below ground surface

**Table 4: Geochemical Evaluation of Natural Attenuation Parameters**

Well	Sample Date	Total Organics (µg/L)	Alkalinity, Total as CaCO <sub>3</sub> (mg/L)	Sulfate (mg/L)	Nitrogen, Nitrate (mg/L)	Iron (mg/L)	Man-ganese (mg/L)	Methane (µg/L)	Field DO (mg/L)	Field Redox
<b>Background Wells (1)</b>										
MW-18	12/5/2022	ND	250	52	9.4	0.2	0.27	1	3.79	215
MW-62R	12/5/2022	ND	170	45	13	0.1	0.005	< 5	1.28	13
<b>Higher Concentration Wells (2)</b>										
MW-08	12/6/2022	3300	300	< 1.5	0.04	2.9	3.1	1600	3.71	-90
MW-11A	12/5/2022	2360	350	2.2	0.04	5.3	2.9	6900	0.13	-60
MW-12	12/5/2022	3331	300	1.2	< 0.1	4.5	1.6	2300	2.40	-62
MW-33	12/5/2022	4500	290	2	0.16	5.0	3.8	7700	3.32	-130
MW-34	12/5/2022	1660	340	4.0	0.25	1.3	1.10	2700	3.36	-110
MW-63	12/5/2022	975	670	7	0.42	1.5	0.24	1500	1.60	-21

Notes: No organic compounds were detected in the "background" wells (ND).

(1) - Background wells are wells that have been clean for at least 10 years

(2) - Higher Concentration Wells are located either within or immediately downgradient of historical source areas.

Indications of biodegradation:

Reduced levels of sulfate and nitrate in the source area wells

Increased iron and manganese in the source area wells

Production of methane in the source area wells

Lower dissolved oxygen (DO) and lower Redox values in source area wells

**Table 5: Concentrations of Compounds Detected During the Last Four Sampling Event Monitoring Wells Sorted by Area**

**AREA 2 WELLS**

Parameter	Units	Cleanup Level	MW-06	MW-06	MW-06	MW-06
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	92	84	81	87
Parameter	Units	Cleanup Level	MW-12	MW-12	MW-12	MW-12
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	43	34	40	43
Benzene	µg/L	5	18	16	12	11
TPH-Total	µg/L	1000	2290	2020	2660	3320
Parameter	Units	Cleanup Level	MW-13	MW-13	MW-13	MW-13
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	63	48	44	49
TPH-Total	µg/L	1000	600	750	830	780
Parameter	Units	Cleanup Level	MW-63	MW-63	MW-63	MW-63
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	85	89	84	59
Benzene	µg/L	5	59	86	99	45
TPH-Total	µg/L	1000	760	770	1030	930

Notes:

"<" - indicates compound was not detected; followed by the reporting limit

µg/L = micrograms per liter

\*Highlighted concentration is above the cleanup level.

Four rounds below cleanup level



**Table 5: Concentrations of Compounds Detected During the Last Four Sampling Event Monitoring Wells Sorted by Area****AREA 3 WELLS**

Parameter	Units	Cleanup Level	MW-10A	MW-10A	MW-10A	MW-10A
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	9.8	9.3	6.1	5.2
Parameter	Units	Cleanup Level	MW-17	MW-17	MW-17	MW-17
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	23	11	13	11

**AREA 4 WELLS**

Parameter	Units	Cleanup Level	MW-11A	MW-11A	MW-11A	MW-11A
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	100	110	92	94
TPH-Total	µg/L	1000	2410	2630	2670	2360
Parameter	Units	Cleanup Level	MW-47	MW-47	MW-47	MW-47
			Oct-19	Oct-20	Nov-21	Dec-23
Trichloroethene (TCE)	µg/L	2	1.8	< 0.2	1.1	1.1

**AREA 6 WELLS**

Parameter	Units	Cleanup Level	MW-08	MW-08	MW-08	MW-08
			Oct-19	Oct-20	Nov-21	Dec-23
TPH-Total	µg/L	1000	2220	2430	3600	3300
Parameter	Units	Cleanup Level	MW-19	MW-19	MW-19	MW-19
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	94	94	78	74
TPH-Total	µg/L	1000	1850	1520	1790	1240

Notes:

"&lt;" - indicates compound was not detected; followed by the reporting limit

µg/L = micrograms per liter

\*Highlighted concentration is above the cleanup level.

Four rounds below cleanup level

**Table 5: Concentrations of Compounds Detected During the Last Four Sampling Event Monitoring Wells Sorted by Area**

### AREA 7 WELLS

Parameter	Units	Cleanup Level	MW-20	MW-20	MW-20	MW-20
			Oct-19	Oct-20	Nov-21	Dec-23
Tetrachloroethene (PCE)	µg/L	1.75	3.2	2.3	1.1	2.1
Trichloroethene (TCE)	µg/L	2	2.0	0.89	0.82	1.0
Parameter	Units	Cleanup Level	MW-33	MW-33	MW-33	MW-33
			Oct-19	Oct-20	Nov-21	Dec-23
TPH-Total	µg/L	1000	5620	4700	4200	4500
Parameter	Units	Cleanup Level	MW-34	MW-34	MW-34	MW-34
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	19	25	20	16
TPH-Total	µg/L	1000	1790	1460	1860	1660
Parameter	Units	Cleanup Level	MW-49	MW-49	MW-49	MW-49
			Oct-19	Oct-20	Nov-21	Dec-23
Tetrachloroethene (PCE)	µg/L	1.75	17	19	18	16
Trichloroethene (TCE)	µg/L	2	3.0	2.1	1.8	2.0

Notes:

"<" - indicates compound was not detected; followed by the reporting limit

µg/L = micrograms per liter

\*Highlighted concentration is above the cleanup level.

Four rounds below cleanup level

**Table 5: Concentrations of Compounds Detected During the Last Four Sampling Event  
Monitoring Wells Sorted by Area****AREA 8 WELL**

Parameter	Units	Cleanup Level	MW-48	MW-48	MW-48	MW-48
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	12	17	6.5	9.5

**AREA 9 WELL**

Parameter	Units	Cleanup Level	MW-66	MW-66	MW-66	MW-66
			Oct-19	Oct-20	Nov-21	Dec-23
Arsenic	µg/L	10	27	17	na	15
TPH-Total	µg/L	1000	540	790	1020	970

**COE Drain Oil Water Separator**

Parameter	Units	Cleanup Level	SEP-OUT	SEP-OUT	SEP-OUT	SEP-OUT
			Oct-19	Oct-20	Nov-21	Dec-23
Tetrachloroethene (PCE)	µg/L	1.75	0.33	0.33	2.2	0.36 J

## Notes:

"<" - indicates compound was not detected; followed by the reporting limit


µg/L = micrograms per liter

\*Highlighted concentration is above the cleanup level.

na - 11/21 arsenic analysis in MW-66 was inadvertently omitted from the requested analyses

## Figures

Path: \\golder-gis.com\pdx\data\official\Remediation\gis\mxd\PROJECTS\003102521\_SiteCleanup\200\_Monitoring02\_PROD\TWO\DWG | File Name: 003102521\_200\_008.dwg | Last Edited By: traylor Date: 2023-02-07 Time: 12:22:24 PM | Printed By: Traylor Date: 2023-02-07 Time: 12:25:56 PM



- LEGEND**
- MW-48 MONITORING WELL LOCATION
  - REMEDIATION AREA BOUNDARY

**NOTE(S)**

1. BASE MAP MODIFIED FROM UNDATED USCOE DRAWING FILES TITLED "93-S1.DWG" AND "93-S2.DWG", AND ON DRAWING TITLED "PROPOSED TRENCH RECOVERY SYSTEM", BY ASSOCIATED EARTH SCIENCES, INC., UNDATED, AND ON DRAWING BY HDR ENGINEERS, FILE NAME "WASHST.DWG", DATED 1/22/99.

CLIENT  
PASCO BULK FUEL TERMINALS SITE COORDINATING GROUP

CONSULTANT	YYYY-MM-DD	2023-02-07
	DESIGNED	GZ
	PREPARED	REDMOND
	REVIEWED	GZ
	APPROVED	GZ



PROJECT  
SITE CLEANUP  
PASCO BULK FUEL TERMINALS SITE

TITLE  
**SITE MAP**

PROJECT NO. 003102521	PHASE 200	REV. A	FIGURE 1
--------------------------	--------------	-----------	-------------

1 in IF THIS MEASUREMENT DOES NOT MATCH WHAT IS SHOWN, THE SHEET SIZE HAS BEEN MODIFIED FROM ANSI B



**APPENDIX A**

**Complete Tabulated Results for  
Groundwater Samples – December  
2022**



## Appendix A: Complete Tabulated Results for Groundwater Samples - December 2022

Sample Location	Date Sampled	Parameter	Result	Qualifier	PQL	MDL	Units
FBMW-12	05-Dec-22	Arsenic	0.005	U	0.005	0.001	mg/L
FBMW-12	05-Dec-22	Benzene	0.81		0.4	0.093	ug/L
FBMW-12	05-Dec-22	Tetrachloroethene (PCE)	1	U	1	0.22	ug/L
FBMW-12	05-Dec-22	TPH-Diesel	0.11	U	0.11	0.066	mg/L
FBMW-12	05-Dec-22	TPH-gas	0.044	J	0.15	0.031	mg/L
FBMW-12	05-Dec-22	TPH-oil	0.35	U	0.35	0.097	mg/L
FBMW-12	05-Dec-22	Trichloroethene (TCE)	1	U	1	0.2	ug/L
FBMW-20	05-Dec-22	Tetrachloroethene (PCE)	1	U	1	0.22	ug/L
FBMW-20	05-Dec-22	Trichloroethene (TCE)	1	U	1	0.2	ug/L
MW-06	05-Dec-22	Arsenic	0.087		0.005	0.001	mg/L
MW-08	06-Dec-22	Alkalinity	300		7	7	mg/L
MW-08	06-Dec-22	Iron	2.9		0.5	0.067	mg/L
MW-08	06-Dec-22	Manganese	3.1		0.01	0.0023	mg/L
MW-08	06-Dec-22	Methane	1600		5	0.63	ug/L
MW-08	06-Dec-22	Nitrate + Nitrite (as N)	0.041	J	0.1	0.036	mg/L
MW-08	06-Dec-22	Sulfate	1.5	U	1.5	0.8	mg/L
MW-08	06-Dec-22	TPH-Diesel	1		0.12	0.073	mg/L
MW-08	06-Dec-22	TPH-gas	2.3		0.15	0.031	mg/L
MW-08	06-Dec-22	TPH-oil	0.39	U	0.39	0.11	mg/L
MW-10A	06-Dec-22	Arsenic	0.0052		0.005	0.001	mg/L
MW-11A	05-Dec-22	Alkalinity	350		7	7	mg/L
MW-11A	05-Dec-22	Arsenic	0.094		0.005	0.001	mg/L
MW-11A	05-Dec-22	Iron	5.3		0.5	0.067	mg/L
MW-11A	05-Dec-22	Manganese	2.9		0.01	0.0023	mg/L
MW-11A	05-Dec-22	Methane	6900		5	0.63	ug/L
MW-11A	05-Dec-22	Nitrate + Nitrite (as N)	0.038	J	0.1	0.036	mg/L
MW-11A	05-Dec-22	Sulfate	2.2		1.5	0.8	mg/L
MW-11A	05-Dec-22	TPH-Diesel	0.56		0.11	0.066	mg/L
MW-11A	05-Dec-22	TPH-gas	1.8		0.15	0.031	mg/L
MW-11A	05-Dec-22	TPH-oil	0.35	U	0.35	0.097	mg/L
MW-11A dup-75A	05-Dec-22	Alkalinity	380		7	7	mg/L
MW-11A dup-75A	05-Dec-22	Arsenic	0.093		0.005	0.001	mg/L
MW-11A dup-75A	05-Dec-22	Iron	5.1		0.5	0.067	mg/L
MW-11A dup-75A	05-Dec-22	Manganese	2.9		0.01	0.0023	mg/L
MW-11A dup-75A	05-Dec-22	Methane	6400		5	0.63	ug/L
MW-11A dup-75A	05-Dec-22	Nitrate + Nitrite (as N)	0.036	J	0.1	0.036	mg/L
MW-11A dup-75A	05-Dec-22	Sulfate	2.3		1.5	0.8	mg/L
MW-11A dup-75A	05-Dec-22	TPH-Diesel	0.61		0.11	0.066	mg/L
MW-11A dup-75A	05-Dec-22	TPH-gas	1.9		0.15	0.031	mg/L
MW-11A dup-75A	05-Dec-22	TPH-oil	0.36	U	0.36	0.098	mg/L
MW-12	05-Dec-22	Alkalinity	300		7	7	mg/L
MW-12	05-Dec-22	Arsenic	0.043		0.005	0.001	mg/L
MW-12	05-Dec-22	Benzene	11		0.4	0.093	ug/L
MW-12	05-Dec-22	Iron	4.5		0.5	0.067	mg/L
MW-12	05-Dec-22	Manganese	1.6		0.01	0.0023	mg/L
MW-12	05-Dec-22	Methane	2300		5	0.63	ug/L
MW-12	05-Dec-22	Nitrate + Nitrite (as N)	0.1	U	0.1	0.036	mg/L
MW-12	05-Dec-22	Sulfate	1.2	J	1.5	0.8	mg/L
MW-12	05-Dec-22	Tetrachloroethene (PCE)	1	U	1	0.22	ug/L
MW-12	05-Dec-22	TPH-Diesel	0.82		0.11	0.066	mg/L
MW-12	05-Dec-22	TPH-gas	2.5		0.15	0.031	mg/L
MW-12	05-Dec-22	TPH-oil	0.36	U	0.36	0.098	mg/L
MW-12	05-Dec-22	Trichloroethene (TCE)	1	U	1	0.2	ug/L
MW-13	05-Dec-22	Arsenic	0.049		0.005	0.001	mg/L
MW-13	05-Dec-22	TPH-Diesel	0.18		0.11	0.065	mg/L
MW-13	05-Dec-22	TPH-gas	0.6		0.15	0.031	mg/L
MW-13	05-Dec-22	TPH-oil	0.35	U	0.35	0.096	mg/L
MW-17	06-Dec-22	Arsenic	0.011		0.005	0.001	mg/L



## Appendix A: Complete Tabulated Results for Groundwater Samples - December 2022

Sample Location	Date Sampled	Parameter	Result	Qualifier	PQL	MDL	Units
MW-18	05-Dec-22	Alkalinity	250		7	7	mg/L
MW-18	05-Dec-22	Iron	0.15	J	0.5	0.067	mg/L
MW-18	05-Dec-22	Manganese	0.27		0.01	0.0023	mg/L
MW-18	05-Dec-22	Methane	0.77	J	5	0.63	ug/L
MW-18	05-Dec-22	Nitrate + Nitrite (as N)	9.4		1	0.36	mg/L
MW-18	05-Dec-22	Sulfate	52		1.5	0.8	mg/L
MW-19	05-Dec-22	Arsenic	0.074		0.005	0.001	mg/L
MW-19	05-Dec-22	TPH-Diesel	0.46		0.12	0.068	mg/L
MW-19	05-Dec-22	TPH-gas	0.78		0.15	0.031	mg/L
MW-19	05-Dec-22	TPH-oil	0.37	U	0.37	0.1	mg/L
MW-20	05-Dec-22	Tetrachloroethene (PCE)	2.1		1	0.22	ug/L
MW-20	05-Dec-22	Trichloroethene (TCE)	1		1	0.2	ug/L
MW-33	05-Dec-22	Alkalinity	290		7	7	mg/L
MW-33	05-Dec-22	Iron	5		0.5	0.067	mg/L
MW-33	05-Dec-22	Manganese	3.8		0.01	0.0023	mg/L
MW-33	05-Dec-22	Methane	7700		5	0.63	ug/L
MW-33	05-Dec-22	Nitrate + Nitrite (as N)	0.16		0.1	0.036	mg/L
MW-33	05-Dec-22	Sulfate	1.9		1.5	0.8	mg/L
MW-33	05-Dec-22	TPH-Diesel	1.5		0.12	0.07	mg/L
MW-33	05-Dec-22	TPH-gas	3		0.15	0.031	mg/L
MW-33	05-Dec-22	TPH-oil	0.38	U	0.38	0.1	mg/L
MW-34	05-Dec-22	Alkalinity	340		7	7	mg/L
MW-34	05-Dec-22	Arsenic	0.016		0.005	0.001	mg/L
MW-34	05-Dec-22	Iron	1.3		0.5	0.067	mg/L
MW-34	05-Dec-22	Manganese	1.1		0.01	0.0023	mg/L
MW-34	05-Dec-22	Methane	2700		5	0.63	ug/L
MW-34	05-Dec-22	Nitrate + Nitrite (as N)	0.25		0.1	0.036	mg/L
MW-34	05-Dec-22	Sulfate	4		1.5	0.8	mg/L
MW-34	05-Dec-22	TPH-Diesel	0.56		0.12	0.072	mg/L
MW-34	05-Dec-22	TPH-gas	1.1		0.15	0.031	mg/L
MW-34	05-Dec-22	TPH-oil	0.39	U	0.39	0.11	mg/L
MW-47	05-Dec-22	Trichloroethene (TCE)	1.1		1	0.2	ug/L
MW-48	06-Dec-22	Arsenic	0.0095		0.005	0.001	mg/L
MW-49	06-Dec-22	Tetrachloroethene (PCE)	16		1	0.22	ug/L
MW-49	06-Dec-22	Trichloroethene (TCE)	2		1	0.2	ug/L
MW-49 dup-79	06-Dec-22	Tetrachloroethene (PCE)	15		1	0.22	ug/L
MW-49 dup-79	06-Dec-22	Trichloroethene (TCE)	1.9		1	0.2	ug/L
MW-62R	05-Dec-22	Alkalinity	170		7	7	mg/L
MW-62R	05-Dec-22	Iron	0.14	J	0.5	0.067	mg/L
MW-62R	05-Dec-22	Manganese	0.0047	J	0.01	0.0023	mg/L
MW-62R	05-Dec-22	Methane	5	U	5	0.63	ug/L
MW-62R	05-Dec-22	Nitrate + Nitrite (as N)	13		2	0.72	mg/L
MW-62R	05-Dec-22	Sulfate	45		1.5	0.8	mg/L
MW-63	05-Dec-22	Alkalinity	670		7	7	mg/L
MW-63	05-Dec-22	Arsenic	0.059		0.005	0.001	mg/L
MW-63	05-Dec-22	Benzene	45		0.4	0.093	ug/L
MW-63	05-Dec-22	Iron	1.5		0.5	0.067	mg/L
MW-63	05-Dec-22	Manganese	0.24		0.01	0.0023	mg/L
MW-63	05-Dec-22	Methane	1500		5	0.63	ug/L
MW-63	05-Dec-22	Nitrate + Nitrite (as N)	0.42		0.1	0.036	mg/L
MW-63	05-Dec-22	Sulfate	7		1.5	0.8	mg/L
MW-63	05-Dec-22	Tetrachloroethene (PCE)	1	U	1	0.22	ug/L
MW-63	05-Dec-22	TPH-Diesel	0.31		0.11	0.066	mg/L
MW-63	05-Dec-22	TPH-gas	0.62		0.15	0.031	mg/L
MW-63	05-Dec-22	TPH-oil	0.35	U	0.35	0.097	mg/L
MW-63	05-Dec-22	Trichloroethene (TCE)	1	U	1	0.2	ug/L
MW-66	06-Dec-22	Arsenic	0.015		0.005	0.001	mg/L
MW-66	06-Dec-22	TPH-Diesel	0.2		0.11	0.066	mg/L

**Appendix A: Complete Tabulated Results for Groundwater Samples - December 2022**

Sample Location	Date Sampled	Parameter	Result	Qualifier	PQL	MDL	Units
MW-66	06-Dec-22	TPH-gas	0.77		0.15	0.031	mg/L
MW-66	06-Dec-22	TPH-oil	0.35	U	0.35	0.097	mg/L
SEP-OUT	06-Dec-22	Tetrachloroethene (PCE)	0.36	J	1	0.22	ug/L

**Notes:**

dupl = duplicate, PQL = practical quantitation limit, MDL = method detection limit, TPH = total petroleum hydrocarbons

FB = Field Blank, mg/L = milligrams per liter, ug/L = micrograms per liter TB = Trip Blanks

SEP-OUT is the outlet of the COE drain oil-water separator

U qualifier: Compound was not detected

UJ qualifier: Compound was not detected, the reporting limit is approximate due to minor data validation issue

J+ qualifier: The result is an estimated quantity; the result may be biased high


J qualifier: The result is an estimated quantity

J- qualifier: The result is an estimated quantity; the result may be biased low


## APPENDIX B

# Trend Graphs


## Area 2 MW-06




## Area 2 MW-12




## Area 2 MW-13



## Area 2 MW-63




Area 3 MW-10A







### Area 3 MW-17




Area 4 MW-11A




# Area 4 MW-47




# Area 6 MW-08




## Area 6 MW-19




## Area 7 MW-20



## Area 7 MW-33




# Area 7 MW-34






## Area 7 MW-49



## Area 8 MW-48



COE Separator Out (1)  
OWS — Separator Out

