Prepared for:

White Birch Group LLC 2116 Taylor Way Tacoma, WA 98401

and

The Chemours Company
Corporate Remediation Group
1007 Market Street, Room 13116A
Wilmington, Delaware 19899

March 28, 2023

Nathan Starr, L.G., Senior Hydrogeologist

Mark Som





Pacific Environmental and Redevelopment Corporation

424 East Meadow Lake Drive Snohomish, Washington 98290

and

PIONEER Technologies Corporation

5205 Corporate Center Ct. SE, Suite A Olympia, Washington 98503-5901

Table of Contents

1.	Intro	oduction	. 1		
	1.1	Overview	. 1		
	1.2	Property Location and Description	. 1		
	1.3	Report Organization	. 1		
2.	Sum	mary of Groundwater Monitoring	. 2		
	2.1	Monitoring Well Locations and Installation Chronology	. 2		
	2.2	Sampling Methods and Procedures	. 2		
	2.3	QA/QC Methods	. 2		
	2.4	Constituent Analyses	. 3		
3.	undwater Monitoring Results	. 4			
	3.1	Arsenic	. 4		
	3.2	Lead	. 5		
4.	Con	clusions	.6		
5	S. References				

Figures

Figure 1: Superlon Property Location

Figure 2: Property Features

Figure 3: Monitoring Well Locations

Figure 4: Dissolved Arsenic in the Shallow Aquifer

Figure 5: Dissolved Arsenic in the Intermediate Aquifer

Figure 6: Dissolved Lead in the Shallow Aquifer

Figure 7: Dissolved Lead in the Intermediate Aquifer

Figure 8: Dissolved Arsenic Trend in the Shallow Aquifer

Figure 9: Dissolved Arsenic Trend in the Intermediate Aquifer

Figure 10: Dissolved Lead Trend in the Shallow Aquifer

Figure 11: Dissolved Lead Trend in the Intermediate Aquifer

Tables

Table 1: Dissolved Arsenic Concentrations by Well and Groundwater Monitoring Event

Table 2: Dissolved Lead Concentrations by Well and Groundwater Monitoring Event

Table 3: pH by Well and Groundwater Monitoring Event

Table 4: Eh by Well and Groundwater Monitoring Event

Appendices

Appendix A: 2022 Groundwater Sampling Field Notes

Appendix B: 2022 Laboratory Reports and QA/QC Data Validation Reports

Appendix C: Dissolved Arsenic and Lead Trend Graphs including Decommissioned Wells

Acronyms and Abbreviations

Acronym/Abbreviation	Description		
Chemours	The Chemours Company FC, LLC		
COPC	Constituent of Potential Concern		
Ecology	Washington State Department of Ecology		
Eh	Activity of Electrons		
GWM	Groundwater Monitoring		
mg/L	Milligrams per liter		
MW	Groundwater Monitoring Well		
MTCA	Model Toxics Control Act		
PERC	Pacific Environmental and Redevelopment Corporation		
PIONEER	PIONEER Technologies Corporation		
Property	Superlon Plastics Property		
QA/QC	Quality Assurance / Quality Control		
RI	Remedial Investigation		
SAP/QAPP	Sampling and Analytical Plan / Quality Assurance Project Plan		
USEPA	United States Environmental Protection Agency		
White Birch	White Birch Group LLC		

1. Introduction

1.1 Overview

On behalf of The Chemours Company FC, LLC (Chemours), Pacific Environmental and Redevelopment Corporation (PERC) and PIONEER Technologies Corporation (PIONEER) have prepared this 2022 Annual Groundwater Monitoring (GWM) Report for the Superlon Plastics Site (Site). The purpose of this report is to document the GWM activities, results, and evaluations associated with Site groundwater samples collected on August 30, 2022 during the 2022 annual GWM sampling event. GWM is conducted at the Site as part of the remedial investigation (RI) for the Site. The RI is a requirement of the Washington State Department of Ecology (Ecology)-approved Agree Order (No. DE 5940) between White Birch Group LLC (White Birch) and the Chemours Company FC, LLC (Chemours). All RI-associated activities are being conducted in accordance with Washington State Model Toxics Control Act (MTCA), Chapter 173-340 of the Washington Administrative Code.

GWM has been conducted at the site since 2011. Initially, GWM was conducted quarterly from the third quarter of 2011 until the fourth quarter of 2015, when the sampling frequency was reduced to one event per year (Ecology 2015). The results of the 2015-2021 GWM events were documented in the 2015, 2016, 2017, 2018, 2019, 2020 and 2021 GWM Reports (Pacific Environmental and Redevelopment Corporation [PERC] and PIONEER Technologies Corporation [PIONEER] 2015, 2016, 2017, 2018, 2019, 2021a and 2021b).

1.2 Site Location and Description

The Site is located at 2116 Taylor Way, Tacoma, Washington in a highly industrial area of the Tacoma Tidal Flats between the Blair and Hylebos Waterways (see Figure 1). The parcel of land located at 2116 Taylor Way is referred to as the Property. Definition of the Site boundaries (per MTCA) and an evaluation of data from other off Property media will be presented in a future RI/Feasibility Study (FS) and Cleanup Action Plan (CAP) for the Site. This approach, which has been approved by Ecology, was adopted in order to continue progress toward a final remedy for on-Property media, while continuing to investigate off-Property issues and to define the Site boundary (Ecology 2013).

The Property is bordered to the northeast by Taylor Way, to the north by a curved rail road right-of-way owned by the City of Tacoma Public Works, to the northwest by Lincoln Avenue and a warehouse operation, and to the southeast by property leased and operated by Gardner-Fields Products, a roofing and waterproofing products manufacturing business (see Figure 2). To the southwest of the Property is a ditch located on the northeast side of a paved trucking yard owned by the Port of Tacoma (see Figure 2).

1.3 Report Organization

The remainder of this report is organized as follows:

- Section 2: Summary of Groundwater Monitoring
- Section 3: Groundwater Monitoring Results
- Section 4: Conclusions
- Section 5: References

2. Summary of Groundwater Monitoring

2.1 Monitoring Well Locations and Installation Chronology

Historically, a total of 26 Shallow and Intermediate Aquifer co-located MWs have been installed at 13 locations on and off of the Property. As of 2022, 10 MWs remain in place, while the other 16 have been decommissioned (see Figure 3). A brief history of MW locations is presented below:

- Seven Shallow Aquifer MWs (MW-1S MW-7S) were installed during Phase I RI activities in 2011, in accordance with the Phase I RI Work Plan (PERC 2010).
- One Shallow Aquifer MW (MW-8S) and eight Intermediate Aquifer MWs (MW-1I MW-8I) were installed during Phase III RI activities in 2012, in accordance with the Phase III RI Work Plan (PERC 2012).
- Four Shallow Aquifer MWs (MW-9S MW-12S) and four Intermediate Aquifer MWs (MW9I MW12I) were installed during Phase IV RI activities in 2014, in accordance with the Phase IV RI Work Plan (PERC 2014).
- Sixteen MWs were decommissioned in 2017 (MW-1I, MW-1S, MW-3I, MW-3S, MW-5I, MW-5S, MW-6I, MW-6S, MW-7I, MW-7S, MW-8I, MW-8S, MW-11I, MW-11S, MW-12I, and MW-12S; see Figure 3).
- One Shallow Aquifer MW (MW-13S) and one Intermediate Aquifer MW (MW-13I) were installed in November 2019.¹

2.2 Sampling Methods and Procedures

Groundwater sampling methodology and field quality controls were performed in accordance with the Project Sampling and Analytical Plan (SAP) & Quality Assurance Project Plan (QAPP) for the Superlon Plastics Property (PERC 2022). All samples were sent to a Washington State-certified laboratory in accordance with the SAP/QAPP (PERC 2022). Groundwater sampling field notes are presented in Appendix A.

2.3 QA/QC Methods

Laboratory results were verified for usability by performing Quality Assurance/Quality Control (QA/QC) data validation. QA/QC data validation generally followed the applicable guidance and requirements specified in the following:

- Guidance on Environmental Data Verification and Data Validation (United State Environmental Protection Agency [USEPA] 2002);
- USEPA Contract Laboratory Program, National Functional Guidelines for Superfund Organic Methods Data Review. Final. OSWER 9240.1-45. USEPA/540/R-08/01 (USEPA 2016a);
- USEPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Superfund Data Review. Final. OSWER 8240.1-51. EPA 540-R-10-011 (USEPA 2016b); and
- Method-specific and laboratory-established QA requirements, as applicable.

¹ MW-13S and MW-13I were installed in the proximate location of MW-3S and MW-3I which were abandoned in 2017 to allow for soil remediation.

QA/QC data validation procedures were performed in accordance with the SAP/QAPP (PERC 2022). The data validation reports are presented with laboratory reports in Appendix B. Overall the data is acceptable for use without qualification.

2.4 Constituent Analyses

The 2022 groundwater samples were analyzed for dissolved arsenic and dissolved lead only, with Ecology approval (Ecology 2015).² The list of constituents evaluated during the monitoring events has been reduced since sampling was initiated in 2011 as other constituents were consistently not detected or were below screening levels (PERC 2015; PERC and PIONEER 2013, 2015).³

2.5 2022 GWM Deviations

The following deviations were noted for 2021 GWM activities:

- Malfunction of the multimeter probe prevented the measuring of oxidation reduction potential during the sampling of MW-9I and MW-10I.
- Malfunction of the multimeter probe reported high turbidity values during sampling of MW-4I when the water was visually clear.

The deviations did not compromise the investigation objectives or the use of the data obtained during the investigation.

² Dissolved arsenic and lead refer to groundwater samples that have been filtered through a 0.45-micron filter (PERC 2022). All arsenic and lead groundwater samples collected in 2022 were filtered in the field during collection of the samples; prior to 2022 the samples were filtered at the laboratory.

³ The constituent list was reduced to focus the monitoring on constituents of potential concern (COPCs) and eliminate the analyses of constituents not detected or infrequently detected during consecutive sampling events.

3. Groundwater Monitoring Results

Shallow and Intermediate Aquifer groundwater samples were collected from ten MWs and analyzed for dissolved arsenic and lead. The laboratory reports and associated QA/QC data validation reports for the 2022 GWM event are presented in Appendix B.

Constituent concentrations are presented by MW and GWM event for arsenic and lead in Tables 1 and 2, respectively. Groundwater pH and Eh⁴ field measurements are presented by MW and GWM event in Tables 3 and 4, respectively. Arsenic and lead concentrations in the Shallow and Intermediate Aquifers are presented on Figures 4 through 7. Concentration trends for arsenic and lead in active MWs are presented on Figures 8 through 11.⁵

3.1 Arsenic

Arsenic concentration trends in the Shallow Aquifer are as follows (see Table 1 and Figure 8):

- Arsenic concentrations in MW-2S and MW-4S have slowly increased since the MWs were installed in 2011 going from detections in the hundredths and thousandths of mg/L to detections in the tenths of mg/L.
- Arsenic concentrations in MW-9S increased from 5.8 mg/L in 2014 to a maximum concentration in 2017 of 88 mg/L, followed by a decrease to 0.54 mg/L in 2022.
- Arsenic concentrations in MW-10S slowly increased from 0.42 mg/L in 2014 (when the MW was installed) to 3.3 mg/L in 2020 followed by decreases in 2021 (2.3 mg/L) and 2022 (1.7 mg/L).
- Arsenic concentrations in MW-13S have remained stable since it was installed in 2020 ranging from 9.1 to 22 mg/L.⁶ This is similar to the arsenic concentrations measured in MW-3S⁷ between 2012 and 2017 (4.9 to 20 mg/L).

Arsenic concentration trends in the Intermediate Aquifer are as follows (see Table 1 and Figure 9):

- Arsenic concentrations in MW-2I have remained stable and in the range of thousandths to tenths of mg/L since the MW was installed in 2011.
- Arsenic concentrations in MW-4I have remained stable since the MW was installed in 2011 with the highest detection being 0.055 mg/L in 2020, followed by a <0.005 mg/L in 2021 and 0.0068 mg/L in 2022.
- Arsenic concentrations in MW-9I have remained stable and in the range of <0.005 to 0.019 mg/L since the MW was installed in 2014, with the exception of a detection at 0.18 mg/L in 2016.
- Arsenic concentrations in MW-10I have remained < 0.005 mg/L since the MW was installed in 2014⁸, with the exception of a detection at 0.0078 mg/L in 2022.
- Arsenic concentrations in MW-13I have remained stable and in the low tenths of mg/L, which are similar to the concentrations detected in MW-3I⁵ between 2013 and 2017.

⁴ Eh is referred to as "Activity of Electrons" and is calculated from oxidation reduction potential.

⁵ Dissolved arsenic and lead trend graphs including decommissioned wells are located in Appendix C.

⁶ The 2021 Annual Groundwater Monitoring Report indicated that the 3Q 2021 event arsenic concentration in MW-13S was 220 mg/L. This was reported incorrectly. The 3Q 2021 event arsenic concentration in MW-13S was 22 mg/L as indicated in the laboratory report (see Appendix B of the 2021 Annual Groundwater Monitoring Report dated November 30, 2021).

⁷ MW-13S replaced MW-3S and MW-13I replaced MW-3I.

⁸ In 2017 the laboratory diluted the groundwater sample resulting in an elevated reporting limit of 0.10 mg/L (PERC and PIONEER 2017).

Arsenic concentrations in the Shallow Aquifer appear to be responding to the ongoing on-Property soil and perched groundwater interim action removal action with the most significant trend being a three-order of magnitude decrease in MW-9S and the beginning of a decreasing trend in MW-10S. The small increasing trends in MW-2S and MW-4S have maximum concentrations three-orders of magnitude less than the maximum concentration observed in MW-9S indicating that the increase in dissolved arsenic mass observed in MW-2S and MW-4S is much less than the decrease in dissolved mass observed in MW-9S. Arsenic concentrations in source area MW MW-13S remain stable. Arsenic concentrations in the Intermediate Aquifer are generally stable and are less than the Puget Sound groundwater arsenic background threshold value of 0.008 mg/L (Ecology 2022) with the exception of source area MW MW-13I.

3.2 Lead

Lead concentration trends in the Shallow Aquifer are as follows (see Table 2 and Figure 10):

- Lead concentrations in MW-2S have not been detected above the laboratory reporting limits since the MW was installed in 2011.
- Lead concentrations in MW-4S between 2011 and 2021 varied between 0.00015 and 0.0044 mg/L with laboratory reporting limits prior to 2019 being as high as 0.010 mg/L when lead was not detected above the laboratory reporting limit. The lead result was 0.019 mg/L in 2022, which is an order of magnitude higher than the previous maximum concentration.
- Lead concentrations in MW-9S have not been detected above the laboratory reporting limits since the MW was installed in 2014.
- Lead concentrations in MW-10S have slowly increased since the MW was installed in 2014, to a maximum concentration in 2020 of 0.25 mg/L, followed by a decrease to 0.0078 mg/L in 2022.
- Lead concentrations in MW-13S have remained stable and in the hundredths to tenths of mg/L, which are similar to the concentrations detected in MW-3S between 2013 and 2017.

Lead concentration trends in the Intermediate Aquifer are as follows (see Table 2 and Figure 11):

- Lead concentrations in MW-2I, MW-4I, MW-9I, and MW-10I have remained below the laboratory reporting limits in the ten thousandths to thousandths of mg/L since 2015.
- Lead concentrations in MW-13I have remained stable in the range of less than the laboratory reporting limit in the thousandths of mg/L to detections in the thousandths of mg/L, which are similar to the concentrations detected in MW-3I between 2013 and 2017 (with the exception of a detection in 2013 of 0.014 mg/L).

Lead concentrations are generally one to three-orders of magnitude less than arsenic concentrations with lead only being detected in three shallow MWs (MW-4S, MW-10S and MW-13S) and in one intermediate MW (MW-13I) in 2022. Lead concentrations in the Shallow Aquifer are similar to the arsenic trends with the most significant lead trend being a two-order of magnitude decrease in MW-10S. The increasing trend in MW-4S has a maximum concentration one-order of magnitude less than the maximum concentration observed in MW-10S indicating that the increase in dissolved lead mass observed in MW-4S is much less than the decrease in dissolved mass observed in MW-10S. Lead concentrations in the Intermediate Aquifer are stable.

4. Conclusions

Overall, arsenic and lead concentrations in the Shallow Aquifer appear to be responding to the ongoing on-Property soil and perched groundwater interim action removal action with significant decreases of arsenic and lead in MW-9S and MW-10S, respectively. While other MWs have small increasing trends of arsenic and lead the maximum concentrations detected in these MWs is orders of magnitude less than the maximum concentrations observed in the MWs with decreasing trends indicating that the increase in dissolved mass observed in the increasing MWs is much less than the decrease in dissolved mass observed in the MWs with decreasing trends. It is expected that arsenic and lead concentrations will continue to decrease in the Shallow Aquifer in response to the on-Property soil and perched groundwater interim action removal action. Arsenic and lead concentrations in the Intermediate Aquifer are stable.

All MWs will continue to be sampled annually. Following delineation of the plume using hydropunches, new MWs will be installed following the completion of the ongoing soil and perched groundwater interim action and added to the GWM program.

5. References

- Ecology. 2013. Electronic mail from Marv Coleman to Tim Bingman regarding Ecology approval to separate onproperty soils investigations into a separate Remedial Investigation and Feasibility Study track. January 13.
- Ecology. 2015. Electronic mail from Marv Coleman to Jeff King with the subject "Reduction in groundwater monitoring." November 12.
- Ecology, 2022. Natural Background Groundwater Arsenic Concentrations in Washington State: Study Results. January
- PERC. 2010. Phase I Remedial Investigation Work Plan, for the Superlon Plastics Site, Tacoma, Washington. February.
- PERC. 2012. Phase III Remedial Investigation Work Plan, for the Superlon Plastics Site, Tacoma, Washington. July.
- PERC. 2014. Work Plan: Remedial Investigation for Groundwater Phase IV. February 20.
- PERC. 2015. Letter from Jeff King (PERC) to Marv Coleman (Ecology) regarding Proposed Revisions to the Current Groundwater Monitoring Program at the Superlon Plastics Property. September 14.
- PERC. 2022. Sampling and Analysis Plan & Quality Assurance Project Plan for the Superlon Plastics Site, Tacoma, Washington. February 2022.
- PERC and PIONEER. 2013. Proposed Reduction in Analysis Groundwater Monitoring at the Superlon Plastics Site. September 16.
- PERC and PIONEER. 2015. 2015 Groundwater Monitoring Report Superlon Plastics Property. March 9.
- PERC and PIONEER. 2016. 2016 Groundwater Monitoring Report Superlon Plastics Property. October 26.
- PERC and PIONEER. 2017. 2017 Groundwater Monitoring Report Superlon Plastics Property. October 6.
- PERC and PIONEER. 2018. 2018 Groundwater Monitoring Report Superlon Plastics Property. October 16.
- PERC and PIONEER. 2019. 2019 Groundwater Monitoring Report Superlon Plastics Property. October 21.
- PERC and PIONEER. 2021a. 2020 Groundwater Monitoring Report Superlon Plastics Property. March 3.
- PERC and PIONEER. 2021b. 2021 Groundwater Monitoring Report Superlon Plastics Property. November 30.
- USEPA. 2002. Guidance on Environmental Data Verification and Data Validation. EPA QA/G-8. EPA/240/R-02/004. November 2002.
- USEPA. 2016a. USEPA Contract Laboratory Program, National Functional Guidelines for Superfund Organic Methods Data Review. Final. OSWER 9240.1-45. USEPA/540/R-08/01. September 2016.
- USEPA. 2016b. USEPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Superfund Data Review. Final. OSWER 9240.1-51. EPA 540-R-10-011. September 2016.

This page has been left bl	ank intentionally to allow fo led printing.	O r

This page has been left bl	ank intentionally to allow fo led printing.	O r



Superlon Property Location 2022 Groundwater Monitoring Report Superlon Plastics Property, Tacoma, Washington

Figure 1



Property Features 2022 Groundwater Monitoring Report Superlon Plastics Property, Tacoma, Washington



Monitoring Well Locations 2022 Groundwater Monitoring Report Superlon Plastics Site, Tacoma, Washington



Dissolved Arsenic in Shallow Aquifer 2022 Groundwater Monitoring Report Superlon Plastics Site, Tacoma, Washington




Dissolved Arsenic in Intermediate Aquifer 2022 Groundwater Monitoring Report Superlon Plastics Site, Tacoma, Washington





Dissolved Lead in Shallow Aquifer 2022 Groundwater Monitoring Report Superlon Plastics Site, Tacoma, Washington





Dissolved Lead in Intermediate Aquifer 2022 Groundwater Monitoring Report Superlon Plastics Site, Tacoma, Washington




















Tables

This page has been left bl	ank intentionally to allow fo led printing.	D r



Table 1: Dissolved Arsenic Concentrations by Well and Groundwater Monitoring Event

Well ID	3Q 2011	Qual	4Q 2011	Qual	2Q 2012	Qual	3Q 2012	Qual	4Q 2012	Qual	1Q 2013	Qual	2Q 2013	Qual	3Q 2013	Qual	4Q 2013	Qual	1Q 2014	Qual	2Q 2014	Qual	3Q 2014	Qual	4Q 2014	Qual	1Q 2015	Qual	2Q 2015	Qual
MW-1S	0.0052	J	0.0063	J	0.0026	J	0.0071	J	0.013	UB	0.0093	В	0.0060	UB	0.019		0.010		0.0083		0.011	Ĭ	0.037		0.044	Ĭ	0.057		0.13	
MW-2S	0.049		0.11		0.0063	J	0.0095	J	0.052	UB	0.028	В	0.021	В	0.020		0.075		0.058		0.053		0.040		0.067		0.079		0.24	
MW-3S	4.0		15		11		4.9		5.8	В	5.0	В	4.6	В	4.9		7.8		12		16		16		14		13		14	
MW-4S	0.013	J	0.026		0.0057	J	0.0069	J	0.015	UB	0.0072	UB	0.027	В	0.0073		0.011		0.024		0.028		0.045		0.050		0.055		0.061	
MW-5S	0.36		0.28		0.41		0.51		0.45	В	0.48	В	0.32	В	0.37		0.54		0.34		0.24		0.28		0.40		0.40		0.50	T
MW-6S	1.3		2.0		1.8		1.7		1.8	В	1.8	В	1.4	В	1.9		1.9		1.7		1.6		0.50		1.9		1.8		1.5	T
MW-7S	0.0032	J	0.0041	J	0.020	U	0.0032	J	0.0025	UB	0.0020	UB	0.0016	UB	0.0014		0.0030		0.0019		0.0022		0.0025		0.0047		0.0021		0.0019	T
MW-8S	NS		NS		NS		NS		21	В	13	В	21	В	7.7		8.9		27		0.66		13		25		5.5		40	
MW-9S	NS		NS		NS		NS		NS		NS		5.8		7.4		6.0													
MW-10S	NS		NS		NS		NS		NS		NS		0.42		0.49		0.50													
MW-11S	NS		NS		NS		NS		NS		NS		1.4		2.2		2.2													
MW-12S	NS		NS		NS		NS		NS		NS		100		71		90													
MW-13S	NS		NS		NS		NS		NS		NS		NS		NS		NS													
MW-1I	NS		NS		NS		NS		0.0042	UB	0.0011	UB	0.0031	UB	0.0028		0.0025		0.0024		0.0018		0.0026		0.0011		0.0015		0.0010	
MW-2I	NS		NS		NS		NS		0.0018	UB	0.0010	UB	0.0016	UB	0.00064		0.0027		0.0018		0.0018		0.0024		0.0013		0.0015		0.0012	
MW-3I	NS		NS		NS		NS		1.6	В	0.91	В	0.86	В	0.69		0.56		0.54		0.42		0.48		0.49		0.45		0.32	
MW-4I	NS		NS		NS		NS		0.0078	UB	0.0019	UB	0.0052	В	0.0012		0.0040		0.0023		0.0022		0.0030		0.0021		0.0024		0.0017	
MW-5I	NS		NS		NS		NS		0.0047	UB	0.0034	UB	0.0049	В	0.000088		0.0027		0.0017		0.0017		0.0026		0.0013		0.0014		0.0016	
MW-6I	NS		NS		NS		NS		0.0075	UB	0.0013	UB	0.0023	UB	0.0020		0.0033		0.0021		0.0020		0.0012		0.0014		0.0016		0.0011	
MW-7I	NS		NS		NS		NS		0.0017	UB	0.00073	UB	0.0011	UB	0.00070		0.0029		0.0018		0.0017		0.0027		0.0019		0.0013		0.0010	U
MW-8I	NS		NS		NS		NS		0.021	UB	0.0027	UB	0.0040	UB	0.0017		0.0043		0.0026		0.0023		0.012		0.0063		0.0016		0.0048	
MW-9I	NS		NS		NS		NS		NS		NS		0.0020		0.0023		0.0028													
MW-10I	NS		NS		NS		NS		NS		NS		0.0027		0.0030		0.0018													
MW-11I	NS		NS		NS		NS		NS		NS		0.0025		0.086		0.097													
MW-12I	NS		NS		NS		NS		NS		NS		0.29		0.22		0.15													
MW-13I	NS		NS		NS		NS		NS		NS		NS		NS		NS													

- Results shown are in mg/L.

- The 2021 Annual Groundwater Monitoring Report indicated that the 3Q21 event arsenic concentration in MW-13S was 220 mg/L. This was reported incorrectly. The 3Q21 event arsenic concentration in MW-13S was 22 mg/L as indicated in the laboratory report (see Appendix B of the 2021 Annual Groundwater Monitoring Report dated November 30, 2021). Tables and figures included in this report have been updated accordingly.

NS: Not sampled

Data Qualifiers:

U: Constituent was not detected, reporting limit is shown

J: Constituent was detected, concentration is estimated

B: Constituent was detected in an associated blank sample

⁻ Detection limit changed in 3Q17 event due to the analytical laboratory changing the analytical method for testing.



Table 1: Dissolved Arsenic Concentrations by Well and Groundwater Monitoring Event

Well ID	3Q 2015	Qual	4Q 2015	Qual	3Q 2016	Qual	3Q 2017	Qual	3Q 2018	Qual	3Q 2019	Qual	3Q 2020	Qual	3Q 2021	Qual	3Q 2022	Qual
MW-1S	0.11		1.2		44		57		NS									
MW-2S	0.13		0.13		0.18		0.13		0.24		0.16		0.17		0.078		0.58	
MW-3S	15		13		14		20		NS									
MW-4S	0.083		0.073		0.093		0.15		0.10	U	0.16		0.10		0.24		0.20	
MW-5S	0.49		0.50		1.1		0.86		NS									
MW-6S	1.6		1.4		1.6		1.1		NS									
MW-7S	0.0019		0.0023		0.0050	U	0.10	U	NS									
MW-8S	32		32		40		41		NS									
MW-9S	12		23		80		88		79		38		19		2.9		0.54	
MW-10S	0.64		0.61		0.59		0.61		1.1		0.95		3.3		2.3		1.7	
MW-11S	2.5		1.8		3.6		9.7		NS									
MW-12S	120		110		67		59		NS	·								
MW-13S	NS		9.1		22		19											
MW-1I	0.0012		0.0025		0.83		0.13		NS									
MW-2I	0.0014		0.0010		0.58		0.10	U	0.019		0.012		0.0069		0.0062		0.0069	
MW-3I	0.39		0.39		0.38		0.10	J	NS									
MW-4I	0.0017		0.0029		0.015		0.10	כ	0.12		0.0050	U	0.055		0.0050	J	0.0068	
MW-5I	0.0014		0.0025		0.0050	J	0.10	J	NS									
MW-6I	0.0015		0.0028		0.0050	J	0.13		NS									
MW-7I	0.0012		0.0026		0.0059		0.10	כ	NS									
MW-8I	0.011		0.0012		0.0050	כ	0.10	כ	NS									
MW-9I	0.0061		0.0010		0.18		0.10	U	0.0010	U	0.0050	U	0.019		0.0050	U	0.0050	U
MW-10I	0.0023		0.0038		0.0050	U	0.10	U	0.0010	U	0.0050	U	0.0050	U	0.0050	U	0.0078	
MW-11I	0.067		0.025		0.12		0.80		NS									
MW-12I	0.13		0.22		0.098		1.0		NS									
MW-13I	NS		0.30		0.25		0.16											

NS: Not sampled

Data Qualifiers:

B: Constituent was detected in an associated blank sample

⁻ Results shown are in mg/L.

⁻ Detection limit changed in 3Q17 event due to the analytical laboratory changing the analytical method for testing.

⁻ The 2021 Annual Groundwater Monitoring Report indicated that the 3Q21 event arsenic concentration in MW-13S was 220 mg/L. This was reported incorrectly. The 3Q21 event arsenic concentration in MW-13S was 22 mg/L as indicated in the laboratory report (see Appendix B of the 2021 Annual Groundwater Monitoring Report dated November 30, 2021). Tables and figures included in this report have been updated accordingly.

U: Constituent was not detected, reporting limit is shown

J: Constituent was detected, concentration is estimated



Table 2: Dissolved Lead Concentrations by Well and Groundwater Monitoring Event

Well ID	3Q 2011	Qual	4Q 2011	Qual	2Q 2012	Qual	3Q 2012	Qual	4Q 2012	Qual	1Q 2013	Qual	2Q 2013	Qual	3Q 2013	Qual	4Q 2013	Qual	1Q 2014	Qual	2Q 2014	Qual	3Q 2014	Qual	4Q 2014	Qual	1Q 2015	Qual	2Q 2015	Qual
MW-1S	0.010	U	0.010	U	0.010	U	0.010	U	0.0010	U	0.00010	U	0.00010	U	0.00010	U	0.00040	U												
MW-2S	0.010	U	0.010	U	0.010	U	0.010	U	0.0010	U	0.00010	U	0.00010	U	0.00010	U	0.00040	U												
MW-3S	0.0052	J	0.30		0.28		0.034		0.13		0.11	В	0.15	В	0.090		0.18		0.13		0.083		0.094		0.14		0.15		0.14	
MW-4S	0.010	U	0.0022	J	0.0020	J	0.010	U	0.0010	U	0.00010	U	0.00072	UB	0.00015		0.00040	U	0.00040	U	0.00044		0.00053		0.00097		0.00061		0.00072	
MW-5S	0.010	U	0.010	U	0.010	U	0.010	U	0.0010	J	0.00010	U	0.00010	J	0.00010	U	0.00040	U	0.00040	C	0.00040	J	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-6S	0.022		0.0032	J	0.010	U	0.010	U	0.0031		0.00062	UB	0.00081	В	0.00037		0.00040	U	0.00040	С	0.00064		0.0013		0.00092		0.0012		0.00042	
MW-7S	0.012		0.010	U	0.010	U	0.010	U	0.0010	U	0.00010	U	0.00010	U	0.00010	U	0.00040	U	0.00040	U	0.00040	U	0.00065		0.00040	U	0.0012		0.00040	U
MW-8S	NS		NS		NS		NS		0.0012		0.00010	U	0.00010	U	0.00024		0.00040	U												
MW-9S	NS		0.00040	U	0.00040	U	0.00040	U																						
MW-10S	NS		0.017		0.023		0.027																							
MW-11S	NS		0.027		0.052		0.047																							
MW-12S	NS		0.087		0.010		0.019																							
MW-13S	NS																													
MW-1I	NS		NS		NS		NS		0.0010	U	0.00010	U	0.00010	U	0.00010	U	0.00040	U												
MW-2I	NS		NS		NS		NS		0.0010	U	0.00010	U	0.00010	U	0.00010	U	0.00043		0.00040	U	0.00040	כ	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-3I	NS		NS		NS		NS		0.014		0.00084	UB	0.0010	UB	0.00026		0.00040	U	0.00040	U	0.0011		0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-4I	NS		NS		NS		NS		0.0010	כ	0.00010	כ	0.00010	כ	0.00010	U	0.00040	U	0.00040	U	0.00040	כ	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-5I	NS		NS		NS		NS		0.0010	U	0.00010	UB	0.00011	UB	0.00010	U	0.00040	U	0.00040	U	0.00040	כ	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-6I	NS		NS		NS		NS		0.0010	J	0.00010	J	0.00010	כ	0.00010	U	0.00040	U	0.00040	U	0.00040	J	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-7I	NS		NS		NS		NS		0.0010	J	0.00010	J	0.00010	כ	0.00010	U	0.00040	U	0.00040	U	0.00040	כ	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-8I	NS		NS		NS		NS		0.0010	כ	0.00050	כ	0.00010	UB	0.00010	U	0.00040	U	0.00040	U	0.00040	כ	0.00040	U	0.00040	U	0.00040	U	0.00040	U
MW-9I	NS		0.0031		0.00040	U	0.00040	U																						
MW-10I	NS		0.00040	U	0.00040	U	0.00040	U																						
MW-11I	NS		0.00040	U	0.015		0.023																							
MW-12I	NS		0.00097		0.00040	U	0.00040	U																						
MW-13I	NS																													

- Results shown are in mg/L.

- Detection limit changed in 3Q17 event due to the analytical laboratory changing the analytical method for testing.

NS: Not sampled

Data Qualifiers:

U: Constituent was not detected, reporting limit is shown

J: Constituent was detected, concentration is estimated

B: Constituent was detected, concentration is estimated

B: Constituent was detected in an associated blank sample



Table 2: Dissolved Lead Concentrations by Well and Groundwater Monitoring Event

Well ID	3Q 2015	Qual	4Q 2015	Qual	3Q 2016	Qual	3Q 2017	Qual	3Q 2018	Qual	3Q 2019	Qual	3Q 2020	Qual	3Q 2021	Qual	3Q 2022	Qual
MW-1S	0.00040	U	0.00040	U	0.0020	U	0.080	U	NS	9								
MW-2S	0.00040	U	0.00040	U	0.0020	U	0.080	Ü	0.0010	U	0.0040	U	0.0040	U	0.0020	U	0.0020	U
MW-3S	0.083		0.14		0.10		0.11		NS									
MW-4S	0.00080		0.00070		0.0020	U	0.080	U	0.10	U	0.0040	U	0.0040	U	0.0044		0.019	
MW-5S	0.00040	U	0.00040	U	0.0020	U	0.080	U	NS									
MW-6S	0.0013		0.0012		0.0020	U	0.080	U	NS									
MW-7S	0.00040	U	0.00040	U	0.0020	U	0.080	U	NS									
MW-8S	0.00040	U	0.00040	U	0.0020	U	0.080	U	NS									
MW-9S	0.00040	U	0.00040	U	0.0020	U	0.080	U	0.0010	U	0.0040	U	0.0040	U	0.0020	U	0.0020	U
MW-10S	0.042		0.031		0.018		0.080	U	0.077		0.096		0.25		0.061		0.0078	
MW-11S	0.058		0.087		0.15		0.27		NS									
MW-12S	0.060		0.051		0.0020	J	0.080	U	NS									
MW-13S	NS		0.28		0.31		0.087											
MW-1I	0.00040	U	0.00040	U	0.0020	U	0.080	U	NS									
MW-2I	0.00040	U	0.00040	J	0.0020	J	0.080	U	0.0010	J	0.0040	U	0.0040	U	0.0020	J	0.0020	U
MW-3I	0.00040	U	0.00040	כ	0.0020	J	0.080	U	NS									
MW-4I	0.00040	U	0.00040	J	0.0020	כ	0.080	U	0.0010	כ	0.0040	U	0.0040	J	0.0020	J	0.0020	U
MW-5I	0.00040	U	0.00040	J	0.0020	J	0.080	U	NS									
MW-6I	0.00040	U	0.00040	J	0.0020	J	0.080	U	NS									
MW-7I	0.00040	U	0.00040	J	0.0020	כ	0.080	U	NS									
MW-8I	0.00040	U	0.00040	J	0.0020	כ	0.080	U	NS									
MW-9I	0.00040	U	0.00040	U	0.0020	U	0.080	U	0.0010	U	0.0040	U	0.0040	U	0.0020	U	0.0020	U
MW-10I	0.00040	U	0.00040	U	0.0020	U	0.080	U	0.0010	U	0.0040	U	0.0040	U	0.0020	U	0.0020	U
MW-11I	0.014		0.0040		0.042		0.12		NS									
MW-12I	0.00040	U	0.0011		0.0020	U	0.080	U	NS									
MW-13I	NS		0.0067		0.0020	U	0.0020											

- Results shown are in mg/L.

- Detection limit changed in 3Q17 event due to the analytical laboratory changing the analytical method for testing.

NS: Not sampled

Data Qualifiers:

U: Constituent was not detected, reporting limit is shown

J: Constituent was detected, concentration is estimated

B: Constituent was detected in an associated blank sample



Table 3: pH by Well and Groundwater Monitoring Event

Well ID	3Q11	4Q11	2Q12	3Q12	4Q12	1Q13	2Q13	3Q13	4Q13	1Q14	2Q14	3Q14	4Q14	1Q15	2Q15	3Q15	4Q15	3Q16	3Q17	3Q18	3Q19	3Q20	3Q21	3Q22
MW-1S	6.7	6.6	6.5	6.8	6.8	8.5	6.7	6.5	6.6	7.1	6.0	7.0	6.6	6.5	6.7	7.5	6.3	6.6	6.6	NS	NS	NS	NS	NS
MW-2S	6.8	7.0	6.4	6.7	6.7	8.5	6.7	6.7	6.7	7.0	6.5	6.9	6.6	6.5	6.9	7.5	6.3	6.5	6.5	6.7	6.8	6.4	6.7	6.5
MW-3S	7.5	7.1	7.0	7.6	7.4	8.5	7.2	7.5	7.6	7.6	6.4	7.7	7.0	6.9	7.1	7.9	6.8	7.1	7.1	NS	NS	NS	NS	NS
MW-4S	9.1	6.7	6.5	7.0	6.7	8.3	6.1	6.9	6.5	6.9	6.2	7.0	6.6	6.5	6.7	7.5	6.1	6.7	7.5	6.8	6.9	7.0	6.9	6.9
MW-5S	8.5	6.8	6.1	6.7	6.4	7.9	6.4	6.5	6.4	6.8	5.8	6.9	6.4	6.4	6.7	6.9	6.3	6.7	6.5	NS	NS	NS	NS	NS
MW-6S	7.3	6.9	6.5	7.0	6.8	7.9	6.3	6.3	6.6	8.9	5.9	6.8	6.6	6.5	6.7	7.2	6.1	6.7	6.5	NS	NS	NS	NS	NS
MW-7S	11.0	7.0	6.6	7.3	6.9	9.1	6.9	7.2	6.9	7.2	6.2	7.1	6.8	6.8	6.9	7.6	6.6	6.8	6.5	NS	NS	NS	NS	NS
MW-8S	NS	NS	NS	NS	7.0	NS	7.0	7.4	7.6	7.5	7.5	8.3	7.3	7.5	7.4	8.4	7.1	7.2	6.8	NS	NS	NS	NS	NS
MW-9S	NS	6.7	6.6	6.9	7.7	6.5	6.8	6.5	6.8	7.0	7.0	7.2	4.4											
MW-10S	NS	6.8	6.6	6.9	7.6	6.4	6.8	6.7	6.3	6.8	7.0	6.9	6.9											
MW-11S	NS	6.4	6.5	6.8	7.6	6.4	6.7	7.5	NS	NS	NS	NS	NS											
MW-12S	NS	6.8	6.5	6.7	7.6	6.3	6.5	6.3	NS	NS	NS	NS	NS											
MW-13S	NS	12.0	12.0	12.2																				
MW-1I	NS	NS	NS	NS	7.2	8.1	6.9	6.8	6.9	7.2	6.5	7.3	6.8	6.7	7.0	7.7	6.6	6.9	6.7	NS	NS	NS	NS	NS
MW-2I	NS	NS	NS	NS	7.8	8.6	7.0	7.0	7.1	7.4	7.1	7.4	6.9	6.8	7.2	7.9	6.8	6.9	6.7	7.1	7.6	7.4	7.8	8.1
MW-3I	NS	NS	NS	NS	8.7	9.2	7.6	7.6	7.7	8.0	8.1	8.4	7.5	7.5	7.7	8.5	7.3	7.6	7.5	NS	NS	NS	NS	NS
MW-4I	NS	NS	NS	NS	8.1	7.9	7.0	7.3	7.2	7.4	6.4	7.6	7.3	7.0	7.2	8.0	6.7	7.2	6.9	7.1	7.6	7.5	7.6	7.6
MW-5I	NS	NS	NS	NS	7.7	8.0	9.0	7.2	7.2	7.4	6.1	7.6	7.1	7.0	7.2	7.6	6.7	7.1	6.8	NS	NS	NS	NS	NS
MW-6I	NS	NS	NS	NS	7.4	7.5	7.0	6.5	6.8	7.0	6.5	6.9	6.8	6.0	6.8	7.5	6.4	6.8	6.4	NS	NS	NS	NS	NS
MW-7I	NS	NS	NS	NS	7.2	8.9	7.1	7.2	7.0	7.3	6.6	7.2	6.8	6.8	7.0	8.3	6.6	6.8	6.6	NS	NS	NS	NS	NS
MW-8I	NS	NS	NS	NS	8.0	8.7	7.4	7.3	7.6	7.8	7.1	7.9	7.0	7.2	7.6	8.4	7.3	7.5	7.3	NS	NS	NS	NS	NS
MW-9I	NS	7.2	7.4	7.6	8.6	7.4	7.6	7.1	7.3	8.0	8.1	8.0	8.2											
MW-10I	NS	7.2	7.0	7.4	8.1	7.1	7.2	7.0	7.3	7.1	7.3	7.2	7.3											
MW-11I	NS	7.5	7.4	7.6	NS	7.3	7.1	6.8	NS	NS	NS	NS	NS											
MW-12I	NS	7.5	7.5	7.7	8.5	7.3	7.6	7.2	NS	NS	NS	NS	NS											
MW-13I	NS	7.5	7.8	8.0																				

NS: not sampled

⁻ The YSI meter stopped displaying pH values after the first few readings for MW-9I. The pH shown in this table for MW-9I was recorded after 3 minutes of purging, before stability of the remaining parameters was achieved.

⁻ The YSI meter had a fluctuating second decimal place of the pH reading during the purging of MW-9S.



Table 4: Eh by Well and Groundwater Monitoring Event

Well ID	3Q11	4Q11	2Q12	3Q12	4Q12	1Q13	2Q13	3Q13	4Q13	1Q14	2Q14	3Q14	4Q14	1Q15	2Q15	3Q15	4Q15	3Q16	3Q17	3Q18	3Q19	3Q20	3Q21	3Q22
MW-1S	121	82	66	98	103	96	55	103	82	39	104	-28	81	-6	-16	10	41	30	71	NS	NS	NS	NS	NS
MW-2S	89	55	62	98	100	80	45	82	69	32	48	-20	88	-19	-58	20	41	31	63	143	107	147	104	64
MW-3S	58	78	36	62	112	90	49	48	45	33	60	-47	59	-32	14	-10	5	-1	89	NS	NS	NS	NS	NS
MW-4S	58	92	49	3	97	68	76	32	42	31	27	-27	58	-14	113	6	27	17	82	425	109	79	118	6
MW-5S	69	89	1	102	119	90	53	69	66	42	60	-17	80	-22	6	14	31	24	60	NS	NS	NS	NS	NS
MW-6S	32	60	59	89	77	80	84	100	78	45	81	-22	75	-16	51	8	45	29	69	NS	NS	NS	NS	NS
MW-7S	58	66	76	90	53	82	52	52	64	38	29	-38	81	-7	-6	-5	18	24	87	NS	NS	NS	NS	NS
MW-8S	NS	NS	NS	NS	93	NS	24	56	36	20	-1	-65	38	-49	-65	-20	5	2	61	NS	NS	NS	NS	NS
MW-9S	NS	62	-74	-60	-20	12	10	47	282	54	65	32	169											
MW-10S	NS	92	-92	-34	-6	27	27	63	270	89	77	78	47											
MW-11S	NS	31	-23	-27	-6	21	31	76	NS	NS	NS	NS	NS											
MW-12S	NS	100	15	30	40	45	71	120	NS	NS	NS	NS	NS											
MW-13S	NS	25	-129	-105																				
MW-1I	NS	NS	NS	NS	132	143	94	134	115	77	104	15	126	39	31	24	65	58	262	NS	NS	NS	NS	NS
MW-2I	NS	NS	NS	NS	82	87	50	104	79	45	93	-18	91	-8	-36	-2	30	37	90	270	58	340	400	185
MW-3I	NS	NS	NS	NS	183	30	11	73	31	-5	-34	-66	28	-64	-79	-36	-15	-10	187	NS	NS	NS	NS	NS
MW-4I	NS	NS	NS	NS	138	101	70	68	49	31	54	-32	59	-7	116	-6	40	26	72	469	307	110	68	77
MW-5I	NS	NS	NS	NS	82	89	-72	76	62	32	77	-36	51	-18	55	2	42	34	60	NS	NS	NS	NS	NS
MW-6I	NS	NS	NS	NS	102	122	74	125	95	76	74	5	97	-2	73	6	46	36	86	NS	NS	NS	NS	NS
MW-7I	NS	NS	NS	NS	74	66	41	80	65	39	23	-21	92	-1	7	2	41	50	115	NS	NS	NS	NS	NS
MW-8I	NS	NS	NS	NS	104	79	39	79	53	18	45	-38	46	-17	2	-16	23	5	53	NS	NS	NS	NS	NS
MW-9I	NS	57	-129	-81	-56	-23	-21	46	366	18	11	36	NR											
MW-10I	NS	89	-30	1	-14	29	21	71	365	306	77	93	NR											
MW-11I	NS	21	-42	-30	NS	13	45	91	NS	NS	NS	NS	NS											
MW-12I	NS	37	-72	-70	-36	-15	-7	50	NS	NS	NS	NS	NS											
MW-13I	NS	99	151	76																				

- Activity of Electrons (Eh) values were calculated from the final field oxidation reduction potential results during water quality parameter stabilization (see Appendix A) by adding the correction factor of 200. Eh values are shown in millivolts (mV).

NS: not sampled NR: no reading

Appendix A

This page has been left bl	ank intentionally to allow fo led printing.	D r

PIONEER TECHNOLOGIES CORPORATION (PIONEER) GROUNDWATER MONITORING FORM

Stabilization:

SWL < 0.33 ft Turb ± 10% pH ± 0.1 DO ± 0.3 mg/L C, Temp ± 3% ORP ± 10 mV

H. MOY(e / M. KWKOV DATE: 8/20/22

SITE NAME: JUDENION

FIELD TECHNICIAN(S): H. MOTSE / M. KWYKOV

					•					17-1												
		WELL	NFO		Dī	ΓW						F	URGING	3					SAM	IPLE COLLECTION	PUR	GE WATER
					Depth	Depth							St	abilization	1							
	Total	Screen	Current Canditian		to		NAPL		Intake	Elaps.	Flow			Spec.								Disposal /
Well	Depth	Interval	Current Condition (e.g., seal, cover,		NAPL	Water	Thick.	Pump	Depth	Time	Rate	SWL		Cond.	Turb	D.O.	Temp	ORP		Field Kit Results /	Vol	Storage
ID	(ft)	(ft)	cap, casing, lock)	Time	(ft)	(ft)	(ft)	Туре	(ft)	(min)	(L/min)	(ft)	рН	(mS/cm)	(NTU)	(mg/L)	(°C)	(mV)	Time		(gal)	Comments
		<u> </u>								0725		4.73	6.84	2551	9.9	0.90	16.1	-127.4				penden
			good; boits							0728		4.79	6.82	2552		0.87		-150.9	ì	Brown Color,		site
			on cover	NATE		70		n. ·		0731		4.78	684	2.551	58.7	0.89	156	-161.3		No odor		2 gal
45	22.75		too small	0655		4:73		peri		0734		4.81	6.84	2.550	89.6		154	-165.4	10ch			Logoci
			100 3116001							0737		4.81	6.85	2548	110 6	0.79	153	-169.) .	1		
١.	١,			1		ı		l i		0740		4.81	10 05	2.651	20.6	0.14	15.1	-173.0				
								 				4.80	W.86	2.547	29.0	0.70	15.3	177.		1		1.
l I.				₩		$ \downarrow $		↓		0143		4.80	1.00	2.647	500	0.68	149		VR	₩ I		$ \forall $
₩	V		¥	^v		v	-	l Ψ		0749		4.79	9 75	2546	50.0 58.7	0.67	148	-t9i	7			
										0751		479	0.67	2542	67 U	0.65	146	-108	4)			
								1						2541	700	0.64						
								1		0154 0151		4.19	6.97	2,529	72.3	0.63	146	-iau	2			
-				-				 	\vdash			5.85	808	2.134	341	160	19.6	-190.				
			(acod;							0916		592	12.18	2.233	671	0.40	17.2	-254	5	ught brown		
			Wellind							0925			12.19	2.251	10917	V . I V	16 0	.370		Color; Metalli		Pond
135	2399			0906	-	9.85	-	Peri				6.18	12.20	2.268	14241		10.5	-707	0944	odor	1.5	ON-Site
	147,1	1	Rusted in	' ' '				1		0928 0931			12.71	2.205	205 7	0.30		101.		0 210	1	014 0110
	1		1	L								6.18	10.01	2192	2627	0.23	159	-307	3	i	1	1
\vdash	\vdash	-		\vdash	-		_		-	M34			12 22	21/1	263.2			20/			\vdash	
	↓	1	1	I √		$ \psi $				0937		6-18	10.00	2.164	201.23	0.24	100	303	9	\bigvee	$ \ \lor $	V
₩	•		v	Ι'	-	¥	-	V		0940		6.18	16.11	2.159	203.11	0.24	リフウ	-304	9			, i
										1/		1/	1/	1/	1/	\rightarrow	1/	\vee				
										-X		X	I X	X	X	-X	\vee	\wedge				
				1						/\		Λ	/		/	+	\wedge	/ \				
				-	-	-			_	10:0		0.110	0.74	Λ 7Ω	112 07	7 12	10 .	10.	2		_	
		1	Good;							1010		9.40	0.19	0.749	19.86	3.13	18.1	-19:	.5	Noodor		Rand
		1	Nolockon			0 250		na.		1013		9.41	6.50	0.697	12.01	0.52		-141.	,	1000		Pond
25	29.3	\$		1007	-	936	200	Peri	*	1016		9.41	6.54	0.095	16.33	0.31	15.3	-138			1.0	on-fite
1 2	1113	1	well		1			1		1019		9.42	6.54	0.697	12.28	0.81	15.3	-136		,		311 3110
l		1		1						\vee		\sim	X	X-	\rightarrow	V	X	V	102	b l		
												\wedge	/	0.0	7	\ <u>\</u>	/	\wedge				
			Cond					l		1208		993	0.61	0.314 0.313 0.312 0.312	330.10	0.79	21.6	-53.4		Duplicate "Sample A"		Sann
_			Good.	L				0		1211		9.10	5.0	0.313	980.31	0.53	209	36.9		MSample A"		pond
95	21.7	d		1200		8.62		Peri		1714		9.40	5.1	0.312	132.18	0.48	20.4	31.0			1.5	on-site
' -	1000	1								1717		9.47	1.6	0.312	492.3	0.41	20.8	-309	1229	5		010 0110
				1						1223		942	144	0.312	500 72	0.40	215	-30.2	'''			
										1223		9.43	NI	0.311	493.7	0.40	21.4	-31.0				
														V 1((i)	P. Carl					decimals between	een r	eadinas
														1331	INA ANI	L 1,110	יע יעוי		, 1		-	10

PIONEER TECHNOLOGIES CORPORATION (PIONEER) GROUNDWATER MONITORING FORM

Stabilization:

SWL < 0.33 ft

Turb <u>+</u> 10% DO <u>+</u> 0.3 mg/L ORP <u>+</u> 10 mV

pH <u>+</u> 0.1 SC, Temp <u>+</u> 3%

SITE NAME: Superlon FIELD TECHNICIAN(S): Michael Kurkov, Hannah Mosse

DATE: 08/30/2022

		WELL	NEO	1	D.	TW							URGING	<u> </u>				\neg	SAM	PLE COLLECTION	PUR	GE WATER
		WELL !	NFO			Depth						•		abilization					0,		1	
Well	Depth		Current Condition (e.g., seal, cover,		to NAPL	to Water	NAPL Thick.	Pump	Depth	1	Flow Rate	SWL		Spec. Cond.	Turb (NTU)	D.O. (mg/L)	Temp (°C)	ORP	Time	Field Kit Results / General Comments	Vol (gal)	Disposal / Storage
ID.	(ft)	(ft)	cap, casing, lock)	Time	(ft)	(ft)	(ft)	Туре	(ft)	(min)	(L/min)	(ft)	pH	(mS/cm)					Tille	General Comments	(gai)	Comments
Iμ	51.15		good	7:20		5.51			. 1 .5	7:44	0.2 ^0.2	5.61 5.62 5.62 5.62 5.62	7.46 7.53 7.58 7.59 7.59 7.60	2.352 2.354 2.351 2.351 2.343 2.345	44.72 71.25 119.21 157.10 200.71 84.48	0.36	15.1 150 14.9 14.8	- <u>98</u> 5 - <u>97,5</u> -103,9 -109,6 -112,8 -115,4			.2.0	olumpes into site pond
										7:47 7:50 7:53 7:56 7:59	~0.2 ~0.2 ~0.2 ~0.2 ~0.2	5.60 5.60 5.60 5.60	7.60 7.61 7.61 7.61	2.362 2354 2.353 2.346 2.546	270.25 374.50 455.21 508.47 544.12	0.25	ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロシ ロ	-118.1 - 120.5 -122.1 -125.3 -125.3	S:03	Values stabilized, water clear, Turbably sensor wrong?		
13[4905		Jan	9:05	b. '	651				9:23 9:26 9:29 9:32 9:35 9:38	~0.2 ~0.2 ~0.2 ~0.2 ~0.2 ~0.2	6.53 6.54 6.54 6.54 6.50		2.864 2.864 2.868 2.866 2.866	9,0 8,3 8,4 8,2 8,5 7,0	083	134 134 134	74.0 -17.6 -107.8 -114.7 -123.7	9:40	clear	4.5	olympal into 51 te pond
21	4659		apid, but no lact	10:05		9.76			١١.5	10:10 10:13 10:16 10:19 10:22	~ 6.2 ~ 6.2	10.10 9.98 10.00 10.00 10.01	8.24	1.820 1.820 1.824 1.822 1.823	7.1 6.9 6.3 6.0 9.6	4.23 3.78 3.48 3.26	16.1	416	10:23	Water	M.0	" "
aI.	48.96		Long	15:00		9.18			0.1اء	12:10 12:13 12:13 12:13 12:14	~0.2 ~0.2 ~0.2 ~0.2 ~0.2 ~0.2	9.26 9.26 9.27 9.28 9.28	8.17 8.20 -	7.126 7.167 7.167 7.174 7.128	97.1 0.42.4 505.8 91.7 244.1	1.15 *315.71 0.72 0.67		-135.7 -29.7 -		clear	~1.0	60
	q _k			JE-78	1					12:25 12:28 12:31 12:34 12:34 12:92	~0.2 ~0.2 ~0.2	1.29 9.29 9.30 9.32	1 1 1 2	7.082	291.3 393.5 274.1 244.3	0.63	19.8 19.9 19.8 19.9	1111	12:34			

PIONEER TECHNOLOGIES CORPORATION (PIONEER) GROUNDWATER MONITORING FORM

(uperlon

SITE NAME:

FIELD TECHNICIAN(S): +/m/mk

Stabilization:

SWL < 0.33 ft pH ± 0.1 SC, Temp ± 3% Turb <u>+</u> 10% DO <u>+</u> 0.3 mg/L ORP <u>+</u> 10 mV

DATE:

		WELL !	NEO		D.	TW					/		URGING	•					SAM	PLE COLLECTION	PUR	GE WATER
		WELL!	NFU		_	Depth								abilization	1				JAN.	LL COLLEGION		CE WATER
Well ID	Depth	Interval	Current Condition (e.g., seal, cover, cap, casing, lock)	Time	to NAPL	to	NAPL Thick. (ft)	Pump Type	Intake Depth (ft)	Elaps. Time (min)	Flow Rate (L/min)	SWL (ft)	pН	Spec. Cond. (mS/cm)	Turb (NTU)	D.O. (mg/L)				Field Kit Results / General Comments	Vol (gal)	Disposal / Storage Comments
101	V	6.47	cap, casing, lock) 900d; vegetation fully (0 yer well	1310	(ii)	q.69	(13)	Peri	(ii)	13.7M 13.7M 13.7.7 13.30 13.36 13.37 13.47		9 69 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	1.61 1.51 1.61 1.51 1.41 1.29	9.665 9.598 9.564 9.484 9.52 8.491	97.0 201.6 2018 402.8 281.4 91.0	0.95	19.9 18.1 18.1 18.4 18.5 18.4 18.5			PH meter ysi Not recording OBP or PH 1347	2.0	Pono On-site
105	21.	17	good; vegetation tully cover well	131		a,M		Peri		325 328 328 331 334		9.41 9.58 9.57 9.57	7.15 6.91 6.91	2.652 2.753 2.548 2.561	16.67 126.0 142.11 140.1	1.37 0.38 5.38 6.76	71.4 19.8 20.0 19.9	- 5 - - 5 - 5 - 5 - 5 -	91708	1335	1.0	PONO ON- Site
				` .				ľ														
									3			1	20									¥
			1				7			- 75 - 75	7	6				249						

Eurofins Environmental Testing Northwest, LLC

5755 8th Street East Tacoma, WA 98424

Chain of Custody Record



Environment Testing America

Client Information	Sampler: HM/M			La	b PM:					Car	rrier Track	ring No(s):		COC No:	
Client Contact: Nathan Stark	Phone:			E-	Mail:					Sta	te of Orig	in:		Page: Page 1 of 1	
Company: DIONEER Tech notogies			PWSID:		T			Ana	alysis l	Reque	sted			Job #:	
Address: 5205 Corporate Ctr Ct SE	Due Date Request	ed:					П	П	Ť					Preservation C	
City: Olympia	TAT Requested (da					7					11			A - HCL B - NaOH C - Zn Acetate	M - Hexane N - None O - AsNaO2
State, Zip: WA 98503	Stan Compliance Project		A No		- 8	11.69								D - Nitric Acid E - NaHSO4	P - Na2O4S Q - Na2SO3
Phone: 360 570 1700	PO #: Purchase Order													F - MeOH G - Amchlor	R - Na2S2O3 S - H2SO4
Email: Starr N. Cuspioneer. com	WO #:	Tiot roquire			or No	Arsenic								H - Ascorbic Acid I - Ice J - DI Water	T - TSP Dodecahydrate U - Acetone V - MCAA
Project Name: Superion	Project #:				Wes	AVS.							ainers	K - EDTA L - EDA	W - pH 4-5 Z - other (specify)
Site: Tacoma, WA	SSOW#:				Sample								con	Other:	
		Sample	Sample Type (C=comp,	Matrix (W-water, S-solid,	d Filtered	issolved							Number of		
Sample Identification	Sample Date	Time	G=grab)	O-wastn/oil, BT=Tissue, A-A		ã.						\perp	Tota	Special	Instructions/Note:
	2/22/22	2	Name of Street or other Designation	ation Code:	X	X							IX		
MW-25-082022	8/30/22		a		M	X	$\sqcup \sqcup$		11		\sqcup	\perp		Field F	iltered
MW-2I-083022	8/30/22	1023	G	W	A	X							2		
MW-45-083022	8/30/22	901	a	W	Y	X									
MW-4I-083022	8/30/22	803	C1	W	4	X									
MW-105-08-3022	8/30/22	1335	Ci	W	Y	X							8		
MW-10I-083022	0/30/22	1347	G	W	7	1			T				a diameter		
MW-95-083022	8/30/22	1225	G	W	Y	X						\Box		1	
MW-9I-083022	8!30!77		G	W	17	X			\top			\top			
mw-135-083022	8/30/22		Ca	W	Ŋ	X						$\top \top$			
MW-13I-083022	330/22	940	G	W	Y	X									,
MW-SAMPLE A-083022	8/30/22	1275	G	W	Ϋ́	X								,	
Possible Hazard Identification Non-Hazard ☐ Flammable ☐ Skin Irritant ☐ Poison	on B Unkno	wn 🗆 8	Padiological	,0	5	Sample	Disposal etum To C	(A fee	may be	7	sed if s sal By L		are retaine	ed longer than 1	1 month) Months
Deliverable Requested: I, II, III, IV, Other (specify)			adiological		s		nstruction		Requirem		sar by E	au	Aidii	IIV O FOI	INOILIIS
Empty Kit Relinquished by:		Date:			Time	e:	in the second	11			Method o	f Shipmen			
Relinquished by: Hamnam MUF(3)	Date/Time:	135		Company		Recei	ved by:	her	0	_		Date/Vir	3dn	1434	Company
Relinquished by:	Date/Time:			Company		Recei	ved by:	-0-				Date/Tir	me:	,,	Company
Relinquished by:	Date/Time:		-	Company		Recei	ved by:					Date/Tir	ne:		Company
Custody Seals Intact: Custody Seal No.: Δ Yes Δ No						Coole	Temperatu	re(s) °C a	and Other I	Remarks:		WE S	16.4		

Appendix B

This page has been left bl	ank intentionally to allow fo led printing.	D r

QA/QC SOLUTIONS, LLC



James J. Mc Ateer, Jr., BS, MRSC Managing Member 7532 Champion Hill Rd. SE Salem, Oregon 97306

Telephone: 503.763.6948 Facsimile: 503.566.2114 Cellular: 503.881.1501 email: jjmcateer@msn.com

October 13, 2022

Jeff King, L.G. Pacific Environmental and Redevelopment (PERC-NW) 8424 East Meadow Lake Drive Snohomish, WA 98290

Subject: Data Validation Review for the Superlon Plastics Site Annual 2022

Groundwater Monitoring Well Sampling Event

Task Order No.: 22-1

QA/QC Solutions, LLC Project No.: 092622.1

Sent via e-mail to jking@perc-nw.com on October 13, 2022

Dear Jeff:

This letter documents the results of the data validation review for the analysis of dissolved arsenic and dissolved lead completed on groundwater samples associated with Superlon Plastic Site Annual 2022 groundwater monitoring well sampling event.

The data reported were validated to verify applicable laboratory quality assurance and quality control (QA/QC) procedures were documented and of sufficient quality to support its intended purpose(s). A summary of the overall assessment of data quality, the data set, a summary of the analytical methods used to complete the chemical analyses, a summary of the data validation procedures used, and a summary of the reasons why data were qualified (including other items noted during data validation) is presented below.

Overall Assessment of Data Quality

Overall, the data reported are of good quality and the results for the applicable QA/QC procedures that were used by the laboratory during the analysis of the samples were acceptable. During data validation no results required qualification as estimated (J), restatement as undetected (U), or rejection (R).

Data Set

The data set consisted of 11 groundwater samples, (10 filtered samples and 1 filtered field duplicate sample) collected on August 30, 2022. *QA/QC Solutions, LLC* received the abbreviated data summary and electronic data deliverable (EDD) from Pioneer Technologies, Inc. on September 26, 2022.

A summary of the samples collected and analyses completed for dissolved arsenic and dissolved lead is presented in Table 1. All samples were analyzed by Eurofins Seattle located in Tacoma, Washington under Laboratory Job ID 580-117424-1.

Jeff King October 13, 2022 Page 2

Analytical Methods

Analyses for dissolved arsenic and lead was completed by filtration through 0.45-µm filter in the field, the samples pH was adjusted to <2, and the analyses completed by inductively coupled plasma-mass spectrometry (ICP-MS) using U.S. EPA SW-846 Method 6020B (U.S. EPA 2022).

Data Validation Procedures

Data validation procedures included evaluating a summary of the sample results and applicable quality control results that were reported by the laboratory. This level of validation is also referred to as a Stage 2A (U.S. EPA 2009) or also as an abbreviated data review. The analytical data were validated generally following the applicable guidance and requirements specified in:

- Method-specific and laboratory-established quality control requirements, as applicable.
- ➤ Guidance on Environmental Data Verification and Validation (U.S. EPA 2002).
- ➤ Guidance for Labeling Externally Validated Laboratory Analytical Data for Superfund Use. OSWER No. 9200.1-85. EPA 540-R-08-005. (U.S. EPA 2009).
- > National Functional Guidelines for Inorganic Data Superfund Data Review. Final. OLEM 9240.1-66 EPA 542-R-20-006 November 2020. U.S. Environmental Protection Agency (EPA), Office of Superfund Remediation and Technology Innovation (OSRTI), Washington, DC. (U.S. EPA 2020).

The laboratory data deliverables that were validated included the following:

- > Case narrative discussing analytical problems (if any) and procedures.
- > Chain-of-custody (COC) documentation to verify completeness of the data set.
- Laboratory summary result forms to verify analytical holding times were met.
- > Results for the method blank to determine whether an analyte that was reported as detected in any sample was the result of possible contamination introduced at the laboratory.
- Results for laboratory control sample (LCS) (i.e., blank spike), duplicate LCS, matrix spike (MS), and matrix spike duplicate (MSD) recoveries to assess analytical accuracy.
- Results for applicable laboratory duplicate sample, duplicate LCS, and MSD analyses to assess analytical precision.
- > Results for the field duplicate samples to provide additional information in support of the quality assurance review.
- Laboratory summaries of analytical results.

Verification and validation of 100-percent of all applicable laboratory calculations, transcriptions, review of instrument printouts, and review of bench sheets were not completed during the data validation review. There may be analytical problems that could only be identified by reviewing every instrument printouts and associated analytical quality control results. Verification of all possible factors that could result in the degradation of data quality was not completed nor should be inferred at this time. The laboratory case narrative did not indicate any significant problems with data that were not reviewed during data validation. The adequacy of the sampling procedures was not completed during the data validation.

Jeff King October 13, 2022 Page 3

Performance based control limits established by the laboratory, applicable control limits specified in the analytical methods, and best professional judgement were used to evaluate data quality and to determine if specific data required qualification. Data qualifiers were assigned during data validation following guidance specified by U.S. EPA (2002 and 2020) to the EDD when applicable QC measurement criteria were not met, and qualification of the data was warranted.

Reasons for Data Qualification

No sample results required qualification.

General Comments

- ➤ Data users should refer to the laboratory data package for complete information pertinent to the analyses completed.
- Samples were received at the laboratory at 12.5 °C which is above the recommend limit of 6 °C. No samples required qualification because the cooler did not have time to equilibrate from the date and time the last sample was collected (8/30/22 at 1225) and the date and time the cooler was received (8/30/22 at 1435) at the laboratory.
- Data users should note that filtration through 0.45-μm filter is an "operational" definition and is not indicative of a "truly dissolved" aqueous fraction.
- > Some samples were received at the laboratory required additional preservation with acid to bring the pH to <2 as is required for analysis.
- > Results were reported as a non-detect were at the applicable reporting limit.
- > Some sample results were reported from a dilution analysis that was required. In these instances, all other sample results were reported from the undiluted analysis.

This concludes the data validation review. Should you have any questions regarding the information presented herein, please contact me by telephone at 503.763.6948 or by e-mail at jimcateer@msn.com.

Cordially,

James J. Mc Ateer, Jr., BS, MRSC

Managing Member

cc: Brad Grimsted, Pioneer Technologies Corporation via email at grimstedb@uspioneer.com Nathan Starr, Pioneer Technologies Corporation via email at starrn@uspioneer.com

Attachment

Jeff King October 13, 2022 Page 4

References

U.S. EPA 2002. Guidance on Environmental Data Verification and Data Validation. EPA QA/G-8. EPA/240/R-02/004. November 2002. U.S. Environmental Protection Agency, Office of Environmental Information, Washington DC.

U.S. EPA 2009. Guidance for Labeling Externally Validated Laboratory Analytical Data for Superfund Use. OSWER No. 9200.1-85. EPA 540-R-08-005. January 13, 2009.U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response, Washington, DC.

U.S. EPA 2020. National Functional Guidelines for Inorganic Data Superfund Data Review. Final. OLEM 9240.1-66 EPA 542-R-20-006. November 2020. Office of Superfund Remediation and Technology Innovation (OSRTI), U.S. Environmental Protection Agency.

U.S. EPA 2022. SW-846 on-line. Test methods for evaluating solid wastes, physical/chemical methods. https://www.epa.gov/hw-sw846/sw-846-compendium (last updated on June 15, 2022). U.S. Environmental Protection Agency, Office of Solid Waste, Washington, DC.

Table 1. Summary of Samples Collected and Analyses Completed

Sample Number	Laboratory Sample Number	Sample Date	Dissolved Arsenic and Lead by 6020B
MW-2S-083022	580-117424-1	08/30/22	✓
MW-2I-08052020	580-117424-2	08/30/22	✓
MW-4S-08052020	580-117424-3	08/30/22	✓
MW-41-08052020	580-117424-4	08/30/22	✓
MW-10S-08052020	580-117424-5	08/30/22	✓
MW-10I-08052020	580-117424-6	08/30/22	✓
MW-9S-08052020	580-117424-7	08/30/22	✓
MW-9I-08052020	580-117424-8	08/30/22	✓
MW-13S-08052020	580-117424-9	08/30/22	✓
MW-13I-08052020	580-117424-10	08/30/22	✓
MW-SAMPL A-083022	580-117424-11	08/30/22	✓

This page has been left bl	ank intentionally to allow fo led printing.	D r



America

Eurofins Seattle 5755 8th Street East Tacoma, WA 98424 Tel: (253)922-2310

Laboratory Job ID: 580-117424-1 Client Project/Site: Superlon Plastics

For:

eurofins

Pioneer Technologies Corp 5205 Corporate Center Ct SE Suite A Olympia, Washington 98503

Attn: Nathan Starr

Knistine D. allen

Authorized for release by: 9/14/2022 3:32:29 PM Kristine Allen, Client Service Manager (253)433-0390 Kristine.Allen@et.eurofinsus.com

Designee for

Katie Grant, Project Manager I (253)922-2310 Katie.Grant@et.eurofinsus.com

results through

EOL

Have a Question?

Ask
The

·····LINKS ······

Review your project

Visit us at:
www.eurofinsus.com/Env

This report has been electronically signed and authorized by the signatory. Electronic signature is intended to be the legally binding equivalent of a traditionally handwritten signature.

Client: Pioneer Technologies Corp Project/Site: Superlon Plastics Laboratory Job ID: 580-117424-1

Table of Contents

Cover Page	1
Table of Contents	2
Case Narrative	3
Definitions	
Client Sample Results	5
QC Sample Results	16
Chronicle	18
Certification Summary	20
Sample Summary	21
Chain of Custody	22
Receipt Checklists	23

4

9

Case Narrative

Client: Pioneer Technologies Corp Project/Site: Superlon Plastics

Job ID: 580-117424-1

Job ID: 580-117424-1

Laboratory: Eurofins Seattle

Narrative

Job Narrative 580-117424-1

Comments

No additional comments.

Receipt

The samples were received on 8/30/2022 2:35 PM. Unless otherwise noted below, the samples arrived in good condition, and where required, properly preserved and on ice. The temperature of the cooler at receipt was 12.5° C.

Receipt Exceptions

The reference method requires samples to be preserved to a pH of <2. The following samples were received with insufficient preservation at a pH of <~7. All of the samples were preserved to the appropriate pH in the laboratory with 3244512. These samples were received field filtered.

Metals

No analytical or quality issues were noted, other than those described in the Definitions/Glossary page.

Definitions/Glossary

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Glossary

MDC

Abbreviation	These commonly used abbreviations may or may not be present in this report.
n	Listed under the "D" column to designate that the result is reported on a dry weight basis
%R	Percent Recovery
CFL	Contains Free Liquid
CFU	Colony Forming Unit
CNF	Contains No Free Liquid
DER	Duplicate Error Ratio (normalized absolute difference)
Dil Fac	Dilution Factor
DL	Detection Limit (DoD/DOE)
DL, RA, RE, IN	Indicates a Dilution, Re-analysis, Re-extraction, or additional Initial metals/anion analysis of the sample
DLC	Decision Level Concentration (Radiochemistry)
EDL	Estimated Detection Limit (Dioxin)
LOD	Limit of Detection (DoD/DOE)
LOQ	Limit of Quantitation (DoD/DOE)
MCL	EPA recommended "Maximum Contaminant Level"
MDA	Minimum Detectable Activity (Radiochemistry)

MDL Method Detection Limit
ML Minimum Level (Dioxin)
MPN Most Probable Number
MQL Method Quantitation Limit

NC Not Calculated

ND Not Detected at the reporting limit (or MDL or EDL if shown)

Minimum Detectable Concentration (Radiochemistry)

 NEG
 Negative / Absent

 POS
 Positive / Present

 PQL
 Practical Quantitation Limit

PRES Presumptive
QC Quality Control

RER Relative Error Ratio (Radiochemistry)

RL Reporting Limit or Requested Limit (Radiochemistry)

RPD Relative Percent Difference, a measure of the relative difference between two points

TEF Toxicity Equivalent Factor (Dioxin)
TEQ Toxicity Equivalent Quotient (Dioxin)

TNTC Too Numerous To Count

Eurofins Seattle

9/14/2022

6

0

10

10

1-

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Date Collected: 08/30/22 10:23 Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) -	Dissolved								
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.58		0.0050		mg/L		09/09/22 19:04	09/12/22 14:48	5
Lead	ND		0.0020		mg/L		09/09/22 19:04	09/12/22 14:48	5

5

£

9

10

Client: Pioneer Technologies Corp Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-2I-083022 Lab Sample ID: 580-117424-2 Date Collected: 08/30/22 10:23

Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS)	- Dissolved								
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.0069		0.0050		mg/L		09/09/22 19:04	09/12/22 14:51	5
Lead	ND		0.0020		mg/L		09/09/22 19:04	09/12/22 14:51	5

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-4S-083022 Lab Sample ID: 580-117424-3

Date Collected: 08/30/22 08:01 Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) -	Dissolved								
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.20		0.0050		mg/L		09/09/22 19:04	09/12/22 14:55	5
Lead	0.019		0.0020		mg/L		09/09/22 19:04	09/12/22 14:55	5

6

8

9

10

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-4I-083022 Lab Sample ID: 580-117424-4

Date Collected: 08/30/22 08:03 Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) - Dissolved										
	Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
	Arsenic	0.0068		0.0050		mg/L		09/09/22 19:04	09/12/22 14:58	5
	Lead	ND		0.0020		mg/L		09/09/22 19:04	09/12/22 14:58	5

J

10

4 -

Client: Pioneer Technologies Corp Job ID: 580-117424-1

Project/Site: Superlon Plastics

Date Received: 08/30/22 14:35

Client Sample ID: MW-10S-083022

Lab Sample ID: 580-117424-5 Date Collected: 08/30/22 13:35

Matrix: Water

Method: 6020B - Metals (ICP/MS) - Dissolved

motarour vozos motaro (rer /me)	210001100								
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	1.7		0.0050		mg/L		09/09/22 19:04	09/12/22 15:02	5
Lead	0.0078		0.0020		mg/L		09/09/22 19:04	09/12/22 15:02	5

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-10I-083022 Lab Sample ID: 580-117424-6

Matrix: Water

Date Collected: 08/30/22 13:47 Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) -	Dissolved								
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.0078		0.0050		mg/L		09/09/22 19:16	09/13/22 00:38	5
Lead	ND		0.0020		mg/L		09/09/22 19:16	09/13/22 00:38	5

5

6

<u>۾</u>

9

10

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Date Collected: 08/30/22 12:25 Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) -	Dissolved						
Analyte	Result Qualifier	RL	MDL Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.54	0.0050	mg/L		09/09/22 19:16	09/13/22 01:17	5
Lead	ND	0.0020	mg/L		09/09/22 19:16	09/13/22 01:17	5

ی

5

7

8

Client: Pioneer Technologies Corp Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-9I-083022 Lab Sample ID: 580-117424-8

Matrix: Water

Date Collected: 08/30/22 12:36 Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) - Dissolved MDL Unit Dil Fac Result Qualifier RLPrepared Analyzed Arsenic ND 0.0050 09/09/22 19:16 09/13/22 01:20 5 mg/L 5 ND 0.0020 09/09/22 19:16 09/13/22 01:20 Lead mg/L

4

5

7

0

10

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Date Collected: 08/30/22 09:44

Date Received: 08/30/22 14:35

Matrix: Water

Method: 6020B - Metals (ICP/MS) - Dissolved									
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	19		0.0050		mg/L		09/09/22 19:16	09/13/22 01:24	5
Lead	0.087		0.0020		mg/L		09/09/22 19:16	09/13/22 01:24	5

5

6

8

9

10

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-13I-083022 Lab Sample ID: 580-117424-10

Date Collected: 08/30/22 09:40 Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) - Dissolved									
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.16		0.0050		mg/L		09/09/22 19:16	09/13/22 01:27	5
Lead	0.0020		0.0020		mg/L		09/09/22 19:16	09/13/22 01:27	5

6

8

9

10

Client Sample Results

Client: Pioneer Technologies Corp Job ID: 580-117424-1

Project/Site: Superlon Plastics

Client Sample ID: MW-SAMPLE A-083022

Lab Sample ID: 580-117424-11 Date Collected: 08/30/22 12:25

Matrix: Water

Date Received: 08/30/22 14:35

Method: 6020B - Metals (ICP/MS) -									
Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	0.53		0.0050		mg/L		09/09/22 19:16	09/13/22 01:31	5
Lead	ND		0.0020		mg/L		09/09/22 19:16	09/13/22 01:31	5

Prep Type: Total Recoverable

Client Sample ID: Lab Control Sample Dup

%Rec

Limits

100

80 - 120

80 - 120

Client Sample ID: Lab Control Sample

Client Sample ID: Lab Control Sample Dup

Prep Type: Total Recoverable

Client Sample ID: MW-10I-083022

Prop Batch: 403465

Prep Type: Dissolved

Client Sample ID: Method Blank

Prep Batch: 403463

RPD

0

0

RPD

Limit

20

20

Lab Sample ID: MB 580-403463/26-A

Matrix: Water

Analyte

Arsenic

Lead

Analysis Batch: 403662

Client Sample ID: Method Blank **Prep Type: Total Recoverable Prep Batch: 403463**

MB MB MDL Unit Result Qualifier RLD Prepared Analyzed Dil Fac ND 0.0010 mg/L 09/09/22 19:04 09/12/22 13:03 ND 0.00040 mg/L 09/09/22 19:04 09/12/22 13:03

Lab Sample ID: LCS 580-403463/27-A

Lab Sample ID: LCS 580-403463/27-A			Client Sample ID: Lab Control Sample
Matrix: Water			Prep Type: Total Recoverable
Analysis Batch: 403662			Prep Batch: 403463
	Snika	ICS ICS	%Pac

_	Spike	LCS	LCS				%Rec
Analyte	Added	Result	Qualifier L	Jnit	D	%Rec	Limits
Arsenic	1.00	0.995	n	ng/L		100	80 - 120
Lead	1.00	1.01	n	ng/L		101	80 - 120

1 00

Lab Sample ID: LCSD 580-403463/28-A

Matrix: Water

Analysis Batch: 403662							
	Spike	LCSD	LCSD				
Analyte	Added	Result	Qualifier	Unit	D	%Rec	
Arsenic	1.00	0.991		mg/L		99	

Lab Sample ID: MB 580-403465/14-A

Matrix: Water

Lead

Analysis Batch: 403688

	Chort Campic ID: Miction Blank
	Prep Type: Total Recoverable
	Prep Batch: 403465
11D 11D	

mg/L

Analyte	Result	Qualifier	RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
Arsenic	ND		0.0050		mg/L		09/09/22 19:16	09/13/22 00:34	5
Lead	ND		0.0020		mg/L		09/09/22 19:16	09/13/22 00:34	5

1 00

Lab Sample ID: LCS 580-403465/15-A

Matrix: Water			Prep Type: Total Recoverable
Analysis Batch: 403688			Prep Batch: 403465
	Spike	LCS LCS	%Rec
Amalista	Added	Desuit Qualifier Unit	D 0/ Doo Limite

	Spike	LCS	LCS				%Rec	
Analyte	Added	Result	Qualifier	Unit	D	%Rec	Limits	
Arsenic	1.00	0.999		mg/L		100	80 - 120	
Lead	1.00	1.00		mg/L		100	80 - 120	

Lab Sample ID: LCSD 580-403465/16-A **Matrix: Water**

Analysis Batch: 403688

Analysis Dateil. 400000							ı ı c p	Daten. 4	00400
	Spike	LCSD	LCSD				%Rec		RPD
Analyte	Added	Result	Qualifier	Unit	D	%Rec	Limits	RPD	Limit
Arsenic	 1.00	0.997		mg/L		100	80 - 120	0	20
Lead	1.00	1.01		mg/L		101	80 - 120	1	20

Lab Sample ID: 580-117424-6 MS

Matrix: Water

Analysis Batch: 403688									Prep	Batch: 403465
	Sample	Sample	Spike	MS	MS				%Rec	
Analyte	Result	Qualifier	Added	Result	Qualifier	Unit	D	%Rec	Limits	
Arsenic	0.0078		1.00	1.06		mg/L		105	80 - 120	
Lead	ND		1.00	1.04		mg/L		104	80 - 120	

Eurofins Seattle

QC Sample Results

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Project/Site: Superlon Plastics

Method: 6020B - Metals (ICP/MS)

Lab Sample ID: 580-117424-6 MSD

Analysis Batch: 403688

nple ID: M	W-10I-083022
Prep Typ	e: Dissolved
Prep E	Batch: 403465
%Rec	RPD
	Prep Typ Prep B

	Sample	Sample	Spike	MSD	MSD				%Rec		RPD
Analyte	Result	Qualifier	Added	Result	Qualifier	Unit	D	%Rec	Limits	RPD	Limit
Arsenic	0.0078		1.00	1.05		mg/L		105	80 - 120	1	20
Lead	ND		1.00	1.05		mg/L		105	80 - 120	1	20

Lab Sample ID: 580-117424-6 DU

Matrix: Water

Matrix: Water

Analysis Batch: 403688

Client Sample ID: MW-10I-083022
Prep Type: Dissolved
Prop Ratch: 403465

Sample Sample DU DU RPD Analyte Result Qualifier Result Qualifier Unit RPD Limit 0.0078 Arsenic 0.00780 0.4 20 mg/L ND ND NC Lead mg/L

9

4

6

9

10

4

Client: Pioneer Technologies Corp Project/Site: Superlon Plastics

Client Sample ID: MW-2S-083022

Date Collected: 08/30/22 10:23 Date Received: 08/30/22 14:35 Lab Sample ID: 580-117424-1

Matrix: Water

Matrix: Water

Job ID: 580-117424-1

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Type	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403463	JLS	EET SEA	09/09/22 19:04
Dissolved	Analysis	6020B		5	403662	FCW	EET SEA	09/12/22 14:48

Client Sample ID: MW-2I-083022 Lab Sample ID: 580-117424-2

Date Collected: 08/30/22 10:23 Matrix: Water

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Type	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403463	JLS	EET SEA	09/09/22 19:04
Dissolved	Analysis	6020B		5	403662	FCW	EET SEA	09/12/22 14:51

Lab Sample ID: 580-117424-3 Client Sample ID: MW-4S-083022

Date Collected: 08/30/22 08:01 **Matrix: Water**

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A		- -	403463	JLS	EET SEA	09/09/22 19:04
Dissolved	Analysis	6020B		5	403662	FCW	EET SEA	09/12/22 14:55

Client Sample ID: MW-4I-083022 Lab Sample ID: 580-117424-4

Date Collected: 08/30/22 08:03

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403463	JLS	EET SEA	09/09/22 19:04
Dissolved	Analysis	6020B		5	403662	FCW	EET SEA	09/12/22 14:58

Client Sample ID: MW-10S-083022 Lab Sample ID: 580-117424-5

Date Collected: 08/30/22 13:35 **Matrix: Water**

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403463	JLS	EET SEA	09/09/22 19:04
Dissolved	Analysis	6020B		5	403662	FCW	EET SEA	09/12/22 15:02

Client Sample ID: MW-10I-083022 Lab Sample ID: 580-117424-6

Date Collected: 08/30/22 13:47 **Matrix: Water**

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Type	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 00:38

Eurofins Seattle

Client: Pioneer Technologies Corp Project/Site: Superion Plastics

Client Sample ID: MW-9S-083022 Lab Sample ID: 580-117424-7

Matrix: Water

Job ID: 580-117424-1

Date Collected: 08/30/22 12:25 Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Type	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 01:17

Client Sample ID: MW-9I-083022 Lab Sample ID: 580-117424-8

Date Collected: 08/30/22 12:36

Matrix: Water

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 01:20

Client Sample ID: MW-13S-083022 Lab Sample ID: 580-117424-9

Date Collected: 08/30/22 09:44

Matrix: Water

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 01:24

Client Sample ID: MW-13I-083022 Lab Sample ID: 580-117424-10

Date Collected: 08/30/22 09:40 Matrix: Water

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Туре	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A		- <u> </u>	403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 01:27

Client Sample ID: MW-SAMPLE A-083022 Lab Sample ID: 580-117424-11

Date Collected: 08/30/22 12:25 Matrix: Water

Date Received: 08/30/22 14:35

	Batch	Batch		Dilution	Batch			Prepared
Prep Type	Type	Method	Run	Factor	Number	Analyst	Lab	or Analyzed
Dissolved	Prep	3005A			403465	JLS	EET SEA	09/09/22 19:16
Dissolved	Analysis	6020B		5	403688	FCW	EET SEA	09/13/22 01:31

Laboratory References:

EET SEA = Eurofins Seattle, 5755 8th Street East, Tacoma, WA 98424, TEL (253)922-2310

Accreditation/Certification Summary

Client: Pioneer Technologies Corp
Project/Site: Superlon Plastics
Job ID: 580-117424-1

Laboratory: Eurofins Seattle

The accreditations/certifications listed below are applicable to this report.

Authority	Program	Identification Number	Expiration Date
Washington	State	C788	07-13-23

4

Ω

9

10

Sample Summary

Project/Site: Superlon Plastics

Client: Pioneer Technologies Corp

Job ID: 580-117424-1

Lab Sample ID	Client Sample ID	Matrix	Collected	Received
580-117424-1	MW-2S-083022	Water	08/30/22 10:23	08/30/22 14:35
580-117424-2	MW-2I-083022	Water	08/30/22 10:23	08/30/22 14:35
580-117424-3	MW-4S-083022	Water	08/30/22 08:01	08/30/22 14:35
580-117424-4	MW-4I-083022	Water	08/30/22 08:03	08/30/22 14:35
580-117424-5	MW-10S-083022	Water	08/30/22 13:35	08/30/22 14:35
580-117424-6	MW-10I-083022	Water	08/30/22 13:47	08/30/22 14:35
580-117424-7	MW-9S-083022	Water	08/30/22 12:25	08/30/22 14:35
580-117424-8	MW-9I-083022	Water	08/30/22 12:36	08/30/22 14:35
580-117424-9	MW-13S-083022	Water	08/30/22 09:44	08/30/22 14:35
580-117424-10	MW-13I-083022	Water	08/30/22 09:40	08/30/22 14:35
580-117424-11	MW-SAMPLE A-083022	Water	08/30/22 12:25	08/30/22 14:35

Chain of Custody Record

\\$\sigma\$ eurofins Environment Testing America

Phone: Prone: Prone:
Perform MSMSD (Yes or No) Dissolved Arsenic/Lead Analysis
TX 1

Login Sample Receipt Checklist

Client: Pioneer Technologies Corp

Job Number: 580-117424-1

Login Number: 117424 List Source: Eurofins Seattle

List Number: 1

Creator: Vallelunga, Diana L

Question	Answer	Comment
Radioactivity wasn't checked or is = background as measured by a survey meter.</td <td>N/A</td> <td></td>	N/A	
The cooler's custody seal, if present, is intact.	True	
Sample custody seals, if present, are intact.	N/A	
The cooler or samples do not appear to have been compromised or tampered with.	True	
Samples were received on ice.	True	
Cooler Temperature is acceptable.	True	
Cooler Temperature is recorded.	True	Thermal preservation not required.
COC is present.	True	
COC is filled out in ink and legible.	True	
COC is filled out with all pertinent information.	True	
Is the Field Sampler's name present on COC?	True	
There are no discrepancies between the containers received and the COC.	True	
Samples are received within Holding Time (excluding tests with immediate HTs)	True	
Sample containers have legible labels.	True	
Containers are not broken or leaking.	True	
Sample collection date/times are provided.	True	
Appropriate sample containers are used.	True	
Sample bottles are completely filled.	True	
Sample Preservation Verified.	False	Refer to Job Narrative for details.
There is sufficient vol. for all requested analyses, incl. any requested MS/MSDs	True	
Containers requiring zero headspace have no headspace or bubble is <6mm (1/4").	N/A	
Multiphasic samples are not present.	True	
Samples do not require splitting or compositing.	True	
Residual Chlorine Checked.	N/A	

3

5

6

Ö

10

11

This page has been left bl	ank intentionally to allow fo led printing.	O r

Appendix C

This page has been left bl double-sid	ank intentionally to allow fo	or

