



TECHNICAL MEMORANDUM

TO: Bill Preston, City of Yakima
CC: Dana Kallevig, City of Yakima
FROM: Weston Boardman, GIT, and Shane Kostka, LG
DATE: February 7, 2025
RE: Interim Action Groundwater Injection Summary
Former Tiger Oil Site
1808 North 1st Street
Yakima, Washington
Landau Project No. 1148010.010

INTRODUCTION

This document was prepared by Landau Associates, Inc. (Landau) on behalf of the City of Yakima (City) and presents a summary of *in situ* chemical oxidation (ISCO) injection work at the former Tiger Oil gas station property located at 1808 North 1st Street in Yakima, Washington (Site; Facility ID No. 477; Cleanup Site ID No. 4922). This work was conducted in accordance with Agreed Order (AO) No. DE19882 between the City and the Washington State Department of Ecology (Ecology) and is consistent with the revised Scope of Work for the AO provided by Ecology in December 2021. The purpose of the ISCO treatment is to remediate remaining petroleum hydrocarbon contamination in groundwater and smear zone soils from historical releases from underground storage tanks (USTs) associated with former gas station operations at the Site.

SITE DESCRIPTION AND BACKGROUND

The primary Site property is owned by the City but is under a Lease-to-Own agreement between the City and the current Lessee. The property is currently occupied by a former convenience store building in the southwest corner and a drive-through coffee kiosk in the east central portion of the property. The Site is located at the northern end of the City, proximate to the south of the confluence of the Yakima and Naches rivers (Figure 1). The Site includes a 0.65-acre parcel that was used as a gasoline station and convenience store between 1979 and 2001. Gasoline, diesel, waste oil, and heating oil were stored in USTs at the property. Three gasoline tanks (20,000-, 8,000-, and 10,000-gallon), one 6,000-gallon diesel tank, and associated fueling islands/piping were removed in 2005. In 1982, a release of approximately 12,000 to 22,000 gallons of leaded and unleaded gasoline from the delivery lines between the USTs and fuel dispensers (GeoEngineers 2017) was reported. Several phases of investigation have been completed at the Site following the release. The heating and waste oil tanks, both of unknown size, were removed in 2019. No other USTs are known to have been present at the Site.

The Site boundaries (i.e., the known extent of remaining contamination based on the 2017 GeoEngineers remedial investigation (RI) and the October 2021 pre-ISCO injection investigation performed by Landau [discussed below]) extend onto the southeast corner of the neighboring property to the north (currently occupied by an auto repair shop), and into the City right-of-way (North 1st Street); see Figure 2.

Previous Investigations

An RI report completed in 2017 documented the presence of petroleum-contaminated vadose zone and smear zone soils associated with the UST systems (GeoEngineers 2017). During the RI, monitoring wells N1MW-6, N1MW-7, and N1MW-8 were installed at the Site along with soil borings N1DP-9 through N1DP-19, in addition to monitoring wells N1MW-1, N1MW-2, N1MW-3, N1MW-4, and N1MW-5, which were installed as a part of a Phase II environmental site assessment, along with soil borings N1DP-1 through N1DP-8, performed by GeoEngineers in 2014 (GeoEngineers 2015). Refer to Table 1 for soil boring and well construction details. A UST assessment report in 2019 documented one sidewall sample from the heating oil UST excavation pit and one bottom sample from the waste oil UST excavation pit that contained elevated petroleum concentrations (Fulcrum 2019). Data from the RI and Tank Assessment report indicated total petroleum hydrocarbon (TPH) concentrations in Site soils were above the applicable Model Toxics Control Act (MTCA) Method A cleanup levels (CULs), and exceedances of groundwater CULs were present in the vicinity of the former gasoline and diesel USTs and dispenser islands.

Landau Supplemental Investigation

A supplemental investigation was conducted by Landau in October 2021 to evaluate current Site conditions prior to proceeding with remedy planning. The investigation included drilling and sampling soil from eight soil borings (HSB-1 through HSB-5; N1MW-6R, N1MW-7R, and N1MW-9) and installing monitoring wells in three of the borings (N1MW-6R, N1MW-7R, and N1MW-9). Investigation locations are shown on Figure 2 along with investigation locations from the GeoEngineers RI. Refer to Appendix A for supplemental investigation borings logs and Table 1 for soil boring and well construction details. Monitoring wells N1MW-6R and N1MW-7R were replacement wells for former monitoring wells N1MW-6 and N1MW-7, which appear to have been destroyed or paved over during redevelopment of the Site with a coffee kiosk. N1MW-9 was installed to provide monitoring near the eastern property boundary between N1MW-6R and N1MW-7R. Top of casing and ground surface elevations, as well as horizontal coordinates of new and existing monitoring wells were surveyed by a licensed land surveyor following installation of the new monitoring wells. Groundwater was sampled from all monitoring wells at the Site including these three new/replacement monitoring wells and existing monitoring wells N1MW-2, N1MW-3, N1MW-4, N1MW-5, N1MW-8, and groundwater grab samples were collected from temporary wells installed in soil borings HSB-1, HSB-2, and HSB-3.

Soil and groundwater samples were analyzed for TPH in the gasoline-range (TPH-G), diesel-range (TPH-D), and oil-range (TPH-O), as well as benzene, toluene, ethylbenzene, and xylenes (BTEX). The results of the supplemental investigation indicate that soil TPH concentrations appear to have declined

since the RI but remain above CULs in the smear zone in the northeastern portion of the Site; however, no CUL exceedances were identified in soil at the former heating or waste oil UST locations where HSB-4 and

HSB-5 were drilled (see Figures 2 and 3A and Table 2). Groundwater concentrations in the northeastern portion of the Site also continue to exceed TPH and BTEX CULs, but contaminants were not detected further downgradient across 1st Street in the sample collected from monitoring well N1MW-2.

Soil and groundwater data from the supplemental investigation are shown on Figures 3A and 3B, respectively. Supplemental investigation groundwater analytical results and groundwater quality parameters are summarized in Tables 3 and 4, respectively.

Data from the RI and supplemental investigation indicate that the water table has been encountered at approximate depths of just over 10 feet (ft) below ground surface (bgs) to a maximum of 14 ft bgs (Table 5). The data also indicate that the residual petroleum contamination is primarily located in the smear zone at or near the water table, generally at depths below 12 ft bgs and declining sharply with depth, with photoionization detector readings indicating minimal impact present below approximately 18 ft bgs.

GROUNDWATER INJECTION SUMMARY

Eighteen groundwater injection wells (IW-1 through IW-18) were installed in August and September of 2022 to accommodate the ISCO injections. Refer to Figure 4 for Site investigation locations, including injection well locations, and Figure 5 for injection and groundwater monitoring locations. Prior to injection wells being installed and injection work commencing, the injection wells were rule authorized by Ecology's Underground Injection Control (UIC) program per Chapter 173-218 of the Washington Administrative Code (UIC Site Number 36713). All of the injection wells were developed at least 24 hours after construction.

Three injections of Klozur® One, a soluble activated persulfate,¹ were performed at the Site in October 2022, July 2023, and September 2024, all in general accordance with Landau's Ecology-approved Injection Work Plan (Landau 2022).

The target injection solution concentration for each injection was 67 grams of Klozur One activated persulfate (persulfate) per liter. During all Site injections, persulfate was pre-mixed with tap water in 55-gallon polyurethane (poly) drums before being pumped, using a compressed air-driven dual diaphragm pump, into a 6,500-gallon poly tank containing tap water. The solution was then mixed in the poly tank to achieve the design concentration for the injections. Up to four injection wells received injectate simultaneously and the pressure at each injection well was monitored and kept below 10 to 20 pounds per square inch (psi) to prevent short circuiting of fluid to the surface ("daylighting") or nearby storm drains, or damaging the injection well screens. To monitor temporary groundwater mounding, depth-to-water was measured in monitoring wells and other injection wells proximate to the wells

¹ Klozur One is produced by Evonik and is a proprietary blend of sodium persulfate and activator agents, including chelated iron and trace levels of permanganate.

receiving injection solution before injecting and during injections. Injections were temporarily stopped if mounding exceeded 5 ft to prevent contact of injection solution with underground utilities. Injections were then resumed at a decreased flow rate after the observed mounding decreased. Following each ISCO injection, approximately 100 gallons of tap water were injected into injection wells to push the injection fluid into the aquifer matrix and to flush the injection well screens to prevent clogging.

Depth-to-water was also measured in all injection wells and monitoring wells prior to starting the second and third injections to determine baseline water levels for monitoring mounding during injections to evaluate groundwater flow direction at the time of the injections. Groundwater flow direction at the Site is generally to the east with a flat gradient of approximately 0.0017 ft/ft. Figures 7A and 7B are groundwater contour maps associated with measurements taken in monitoring wells prior to the second and third injections. Injection wells were not used to calculate groundwater elevation contours. Irrigation season in the Yakima area generally begins each year on April 1 and ends on October 15 or earlier. Irrigation in the Yakima River basin generally has the greatest influence on shallow groundwater levels in the area throughout the year; shallow groundwater elevations are generally higher during the irrigation season and lower during the period when no irrigation is occurring.

Baseline groundwater samples were collected in September 2022 to characterize initial conditions within and downgradient of the source zone prior to the first injection event (October 2022). Post-injection groundwater monitoring was performed in January 2023 and November 2023, approximately 3 to 4 months after completion of the first (October 2022) and second (July 2023) injection events to evaluate post-injection groundwater conditions and to determine whether additional treatment may be necessary. Groundwater sampling locations and analytes for all monitoring events were determined in coordination with Ecology. Groundwater samples were collected using low-flow sampling techniques, and field parameters were measured including temperature, dissolved oxygen (DO), conductivity, pH, turbidity, and oxidation-reduction potential (ORP). Table 6 summarizes the baseline and post-injection groundwater quality field parameters. All samples were submitted to Eurofins TestAmerica of Spokane, Washington, for TPH-G analysis using Ecology-approved method NWTPH-Gx. Groundwater analytical results are summarized in Table 5.

Laboratory analytical data underwent US Environmental Protection Agency (EPA) Level IIA-equivalent validation and verification. Validation of data was performed in accordance with guidance from applicable portions of the National Functional Guidelines for Organic Superfund Methods Data Review (EPA 2020), analytical methods, and Landau data validation standard operating procedures. All samples were received by the laboratory in good condition and prepared and analyzed within holding times. The groundwater analytical results were compared with the MTCA Method A CUL for gasoline-range organics (GRO), assumed to be 800 micrograms per liter ($\mu\text{g}/\text{L}$) based previous sampling events identifying benzene being present in groundwater at the Site.

The sections below provide a more detailed summary of the completed groundwater injection activities that have occurred at the Site to date, including installation of groundwater injection wells, baseline groundwater sampling, three groundwater injections, and two post-injection groundwater sampling events.

Installation of Groundwater Injection Wells

Groundwater injection wells IW-1 through IW-18 were installed in August and September of 2022 in preparation for the ISCO injection events. To ensure adequate overlap of the injection radius of influence at each injection well, the well locations were designed with a nominal well spacing of approximately 20 ft in the direction of groundwater flow and approximately 17 ft perpendicular to flow, and injection wells were placed at least 10 ft from all Site monitoring wells. Injection wells were generally installed to a total depth of 20 ft bgs with 10 ft of 0.020-inch slot screen placed from 10 to 20 ft bgs with 12/20 silica sand backfilled up to at least 2 ft above the top of the well screen. The annular space above the sand pack was sealed using hydrated bentonite chips and concrete and all injection wells were completed with a flush-mount monument. All Injection wells were developed at least 24 hours after construction using surge and pump methodology and a centrifugal submersible pump. Injection wells were not surveyed after being installed; the locations of injection wells shown on Figures 4, 5, 6A, 6B, 6C, 7A, and 7B are approximate. Refer to Appendix B for injection well borings logs and Table 1 for soil boring and well construction details. Figure 5 shows the locations of groundwater injection wells including the treatment area and the radius of influence of each injection well.

Investigation derived waste (IDW) soil cuttings were characterized as non-hazardous waste and were disposed of at Subtitle D disposal facility. Development water IDW from installation of the groundwater injection wells was characterized in conjunction with the pre-injection baseline groundwater sampling event (see below).

Pre-injection Baseline Groundwater Sampling

On September 7 and 8, 2022, groundwater samples were collected from monitoring wells N1MW-6R, N1MW-7R, N1MW-8, and N1MW-9, and injection wells IW-1, IW-2, IW-3, IW-4, IW-8, IW-9, IW-10, IW-12, IW-14, IW-15, IW-17, and IW-18.

Detections of TPH-G were reported above the laboratory reporting limit (RL) and above the CUL in each groundwater sample with concentrations ranging from 1,100 µg/L (IW-1) to 44,000 µg/L (IW-18). Concentrations were generally the highest both within and to the east of the former UST excavation area (Figure 6A). The sample collected from IW-9 was also analyzed for total lead by EPA Method 6010D and for BTEX by EPA Method 8260D for waste characterization purposes. Analysis for benzene and lead is required by the Subtitle D disposal facility for IDW related to gasoline releases. Lead was not detected above the laboratory RL and BTEX compounds were detected at levels both below their respective CULs and below the applicable hazardous waste designation thresholds (40 Code of Federal Regulations [CFR] Part 261.24 Table 1).

Purge water IDW from the pre-injection baseline groundwater sampling event as well as development water IDW from the installation of the groundwater injection wells was characterized as non-hazardous waste based on the analytical results described above and was disposed of at a Subtitle D disposal facility.

Injection 1: October 2022

The first persulfate injection performed at the Site took place from October 11 through October 19, 2022 (Injection 1). It should be noted that the irrigation shutoff occurred during this injection event on October 14, 2022 (Smith 2022). Depth-to-water in monitoring wells was not measured prior to beginning injections and, therefore, groundwater elevations are not included in Table 5 and groundwater contours were not produced. Injection 1 was designed such that each of the Site injection wells (IW-1 through IW-18) was to receive 2,500 gallons of injection solution (45,000 gallons total) mixed at the concentration specified above. The injection generally proceeded from downgradient (east; beginning with IW-3, IW-6, IW-7, and IW-16) to upgradient (west) with the three injection wells that had the highest concentrations of TPH-G during the pre-injection baseline groundwater sampling event (IW-8, IW-14, and IW-18) injected last.

A total of approximately 25,080 pounds (lbs) of persulfate in 45,410 gallons of solution (a concentration of approximately 66 gallons per liter [g/L]) was injected. Additional injection solution volume was placed into injection wells IW-2, IW-4, IW-5, IW-6, IW-7, IW-9, IW-11, IW-16, and IW-18 due to injection wells IW-1, IW-8, IW-12, IW-14, and IW-17 receiving less than the design volume of injection solution due to slow injection rates and/or high pressures. The wells that received additional volume of injection solution were selected based on pre-injection groundwater analytical results as well as flow rates and pressures observed during the injection. Table 8 summarizes the actual volume injected into each injection well.

Daylighting of injection fluids occurred at the gravel surface of the adjacent property to the north of the Site when injecting into IW-3. Injection solution which daylighted was immediately recovered using a wet-dry vacuum, placed in 55-gal poly drums, and was later filtered to remove dirt/gravel and re-injected. Minor daylighting occurred at IW-18 and IW-10 during injections, but either infiltrated into the subsurface immediately or evaporated quickly after injections were paused.

Post-Injection 1 Groundwater Sampling

On January 18 and 19, 2023, approximately 3 months following Injection 1, groundwater samples were collected from injection wells IW-1, IW-2, IW-3, IW-4, IW-8, IW-9, IW-10, IW-12, IW-14, IW-15, IW-17, and IW-18 and monitoring wells N1MW-6R, N1MW-7R, N1MW-8, and N1MW-9 to evaluate post-Injection 1 Site conditions. Evidence that the injection solution was still present in groundwater, such as low pH and elevated conductivity values in groundwater, was observed during this event.

Detections of TPH-G were reported above the laboratory RL and above the CUL in groundwater samples collected from injection wells IW-2, IW-3, IW-4, IW-8, IW-9, IW-10, IW-12, and IW-18 and monitoring wells N1MW-6R and N1MW-9, with concentrations ranging from 840 µg/L (IW-3) to 15,000 µg/L (IW-4). Detections of TPH-G were reported above the laboratory RL but below the CUL in samples collected from injection wells IW-1, IW-15, and IW-17 and monitoring wells N1MW-7R and N1MW-8, with concentrations ranging from 190 µg/L (IW-17) to 690 µg/L (N1MW-7R). TPH-G was not detected above the laboratory RL, which is below the CUL, in the sample collected from IW-14. Concentrations were

generally the highest within and to the east (downgradient) of the former UST excavation area (Figure 6B).

TPH-G concentrations were observed to have decreased from above to below the CUL after Injection 1 in injection wells IW-1, IW-14, IW-15, and IW-17 and monitoring wells N1MW-7R and N1MW-8. TPH-G concentrations decreased, but not to below the CUL, after Injection 1 in injection wells IW-2, IW-3, IW-8, IW-12 and IW-18 and monitoring wells N1MW-6R and N1MW-9. TPH-G concentrations increased from the pre-injection baseline sampling event in groundwater samples collected from injection wells IW-4 (from 2,300 µg/L to 15,000 µg/L), IW-9 (from 1,700 µg/L to 1,900 µg/L), and IW-10 (from 7,800 µg/L to 8,400 µg/L).

Injection 2: July 2023

The second persulfate injection performed at the Site took place from July 10 through July 13, 2023, (Injection 2) and occurred during irrigation season (high-groundwater season). Figure 4B shows groundwater contours based on depth-to-water measurements from Site monitoring wells on July 10, 2023, before injection activities began. Injection 2 was designed for injection wells IW-2, IW-4, IW-5, IW-9, IW-10, IW-11, IW-12, IW-13, IW-14, and IW-18 to receive 2,500 gallons of injection solution (25,000 gallons total) mixed at the design concentration specified above. These injection points were selected based on the groundwater analytical data following Injection 1 and their proximity to historical USTs. Injection 2 focused treatment on the area of the former UST excavation as most of the elevated TPH-G concentrations reported following Injection 1 were either within or immediately east/downgradient of this area. Injections generally progressed from the perimeter of the former UST excavation area toward the center of the excavation. A total of approximately 13,860 lbs of persulfate in 25,030 gallons of solution (a concentration of approximately 66 g/L) was injected. Additional injection solution volume was placed into injection wells IW-1 and IW-8 due to injection wells IW-10, IW-12, and IW-14 receiving less than the design volume of injection solution due to slow injection rates and/or high pressures. Minor daylighting, which either infiltrated into the subsurface immediately or evaporated quickly after injections were paused, occurred at IW-10, IW-14, and IW-18 during injections. Table 8 summarizes the actual volume injected into each injection well.

Post-Injection 2 Groundwater Sampling

On November 28 and 29, 2023, approximately 4 months following Injection 2, groundwater samples were collected from monitoring wells N1MW-6R, N1MW-7R, N1MW-8, and N1MW-9 as well as injection wells IW-1, IW-2, IW-3, IW-4, IW-8, IW-9, IW-10, IW-12, IW-14, IW-15, IW-17, and IW-18. Because the injection solution appeared to be present and active during the post-Injection 1 groundwater sampling event (conducted 3 months after the injection), the post-Injection 2 sampling event was conducted 4 months after the second injection to allow the persulfate additional time to react with *in situ* contamination. However, evidence that the injection solution was still present and active in groundwater, such as low pH and elevated conductivity values, was again observed during this event.

In addition to TPH-G by NWTPH-Gx, groundwater samples were analyzed for BTEX using EPA Method 8260D. The groundwater analytical results for benzene, toluene, ethylbenzene, and total xylenes were compared to their MTCA Method A CULs of 5 µg/L, 1,000 µg/L, 700 µg/L, and 1,000 µg/L, respectively.

Detections of TPH-G were reported above the laboratory RL and above the CUL in groundwater samples collected from injection wells IW-3, IW-4, IW-8, IW-10, and IW-17 and monitoring wells N1MW-6R, N1MW-7R, and N1MW-9, with concentrations ranging from 870 µg/L (IW-10) to 4,000 µg/L (IW-8). Detections of TPH-G were reported above the laboratory RL, but below the CUL, in samples collected from injection wells IW-1, IW-2, IW-9, IW-12 and IW-18 and monitoring well N1MW-8, with concentrations ranging from 310 µg/L (IW-1) to 690 µg/L (IW-9). TPH-G was not detected above the laboratory RL, which is below the CUL, in the samples collected from IW-14 and IW-15. Concentrations were generally highest at the eastern/downgradient end of the Site with all three monitoring wells in that area (N1MW-6R, N1MW-7R, and N1MW-9) having concentrations of TPH-G over the CUL as well as injection wells IW-3 and IW-8, which are located upgradient of N1MW-6R and N1MW-9, respectively (Figure 6C).

TPH-G concentrations decreased from above to below the CUL after Injection 2 in injection wells IW-2, IW-9, IW-12, and IW-18. TPH-G concentrations decreased from their post-Injection 1 values, but not below the CUL, after Injection 2 in injection wells IW-4 and IW-10. TPH-G concentrations increased from their post-Injection 1 values in injection wells IW-3 (from 840 µg/L to 3,900 µg/L), IW-8 (from 3,100 µg/L to 4,000 µg/L), and IW-17 (from 190 µg/L to 1,100 µg/L) and monitoring wells N1MW-6R (from 2,200 µg/L to 3,700 µg/L), N1MW-7R (from 690 µg/L to 1,200 µg/L), and N1MW-9 (from 1,400 µg/L to 1,500 µg/L).

A detection of benzene was reported above the laboratory RL and above the CUL in the groundwater sample collected from injection well IW-8 at a concentration of 7.2 µg/L. Detections of benzene were reported above the laboratory RL but below the CUL in all other groundwater samples, with concentrations ranging from 0.59 µg/L (IW-14) to 4.3 µg/L (IW-10), except the sample collected from IW-15 in which benzene was not detected above the laboratory RL. Toluene was detected above the laboratory RL but below the CUL in groundwater samples collected from injection wells IW-3, IW-8, and IW-17 and monitoring wells N1MW-6R, N1MW-7R, and N1MW-9, with concentrations ranging from 1.1 µg/L (IW-17) to 200 µg/L (IW-8). Toluene was not detected above the laboratory RL, which is below the CUL, in any other groundwater samples. Ethylbenzene was detected above the laboratory RL but below the CUL in all groundwater samples with concentrations ranging from 1.7 µg/L (IW-12) to 360 µg/L (IW-3). Total xylenes were detected above the laboratory RL and above the CUL in groundwater samples collected from injection wells IW-3 (1,800 µg/L) and IW-8 (1,000 µg/L). Total xylenes were detected above the laboratory RL but below the CUL in all groundwater samples except the samples collected from IW-12 and N1MW-8, where total xylenes were not detected above the laboratory RL, with concentrations ranging from 3.6 µg/L (IW-14) to 460 µg/L (N1MW-9).

Injection 3: September 2024

The third persulfate injection performed at the Site took place from September 9 through September 13, 2024 (Injection 3), during irrigation season (high-groundwater season). Figure 4B shows

groundwater contours based on depth-to-water measurements from Site monitoring wells on September 10, 2024, before injection activities began. Injection 3 was designed for injection wells IW-3, IW-4, IW-6, IW-7, IW-8, IW-10, IW-15, IW-16, IW-17, and IW-18 to receive 2,500 gallons of injection solution (25,000 gallons total) mixed at the design concentration specified above. These injection points were selected based on the groundwater analytical data collected following Injection 2. This injection focused treatment on the eastern/downgradient area of the Site where most of the TPH-G concentrations above the CUL were located following Injection 2 (IW-3, IW-6, IW-7, IW-8, IW-15, and IW-16). Treatment was also applied to injection wells where TPH-G concentrations were above the CUL following Injection 2 (IW-4, IW-10, and IW-17). IW-18 was also injected (TPH-G following Injection 2 was below the CUL) given that its TPH-G concentration in the pre-injection baseline sampling event was the highest (44,000 µg/L) reported in Site wells. A total of approximately 13,940 lbs of persulfate in 25,680 gallons of solution (a concentration of approximately 65 g/L) was injected. Each injection well received +/- 10 percent of the design volume (2,500 gallons) with no injection solution needing to be placed in other injection wells. Minor daylighting, which either infiltrated into the subsurface immediately or evaporated quickly after injections were paused, occurred at IW-10 and IW-18 during injections. Table 8 summarizes the actual volume injected into each injection well.

Continued Groundwater Monitoring and Reporting

Post-Injection 3 groundwater sampling is expected to be conducted up to 1 year after Injection 3 was completed to allow the persulfate ample time to react with *in situ* contamination. Groundwater analytical results are more likely to be representative of actual post-injection conditions when injection solution is not present and active in groundwater. Groundwater samples will be collected using low-flow sampling techniques. Groundwater sampling locations are anticipated to be determined in coordination with Ecology and each groundwater sample is anticipated to be submitted to the laboratory for TPH-G analysis using Ecology-approved method NWTPH-Gx as well as analysis for BTEX using EPA Method 8260. Depth-to-water measurements will be taken in Site monitoring wells concurrent with the sampling event before groundwater samples are collected to evaluate groundwater flow direction and gradient at the Site at the time of the sampling event. Groundwater quality field parameters including temperature, DO, conductivity, pH, turbidity, and ORP will be measured at all groundwater sampling locations.

Based on communications from Ecology, Landau understands that Ecology will assess the need for additional post-injection groundwater monitoring and determine whether there is sufficient data to support a No Further Action (NFA) determination for the Site (Ecology 2024). Landau also anticipates preparing an interim action completion report further detailing previous investigations, monitoring well replacement, injection well installation, and injection activities, as well as all groundwater monitoring results following Ecology's review of the post-injection monitoring event data.

DISCUSSION

A total of approximately 52,880 lbs of persulfate in 96,120 gallons of solution (an average concentration of approximately 66 g/L) was injected at the Site during the course of the three injection events between October 2022 and September 2024. Post-Injection 2 groundwater monitoring results indicate

that on average, GRO concentrations have decreased 71 percent from baseline sampling conducted prior to the injections. However, it is likely that injection solution was still present and active in groundwater during the post-Injection 2 monitoring event, indicating that treatment was likely still occurring. The third persulfate injection is expected to further decrease GRO concentrations. The post-Injection 3 groundwater monitoring event is planned to be conducted up to 1 year after completion of Injection 3 to more accurately determine post-injection groundwater quality and conditions. The sufficiency of data to support an NFA determination will be determined by Ecology following review of the data from the post-Injection 3 monitoring event as well as any subsequent post-injection monitoring.

USE OF THIS TECHNICAL MEMORANDUM

This technical memorandum has been prepared for the exclusive use of the City for specific application to the Former Tiger Oil Site. No other party is entitled to rely on the information, conclusions, and recommendations included in this document without the express written consent of Landau. Further, the reuse of information, conclusions, and recommendations provided herein for extensions of the project or for any other project, without review and authorization by Landau, shall be at the user's sole risk. Landau warrants that within the limitations of scope, schedule, and budget, our services have been provided in a manner consistent with that level of care and skill ordinarily exercised by members of the profession currently practicing in the same locality under similar conditions as this project. Landau makes no other warranty, either express or implied.

This document has been prepared under the supervision and direction of the following key staff.

LANDAU ASSOCIATES, INC.



Weston Boardman, GIT
Project GIT



Shane Kostka, LG
Associate Geologist

PMR/SRK/WMB/kee
[P:\1148\010\R\INJECTION TECH MEMO\LANDAU TIGER OIL GROUNDWATER INJECTION SUMMARY_TM 020725.DOCX]

Attachments

Figure 1. Vicinity Map

Figure 2. Site Boundaries and RI and Supplemental Investigation Exploration Locations

Figure 3A. 2021 Supplemental Investigation Soil Analytical Results Map

Figure 3B. 2021 Supplemental Investigation Groundwater Analytical Results Map

Figure 4. Site Investigation Locations

Figure 5. Injection and Groundwater Monitoring Locations

Figure 6A. Pre-Injection Baseline Groundwater Analytical Results Map

Figure 6B. Post-Injection 1 Groundwater Analytical Results Map

Figure 6C. Post-Injection 2 Groundwater Analytical Results Map

Figure 7A. Injection 2 Groundwater Contours

Figure 7B. Injection 3 Groundwater Contours

Table 1. Soil Boring and Well Construction Details

Table 2. Supplemental Investigation Soil Analytical Results

Table 3. Supplemental Investigation Groundwater Analytical Results

Table 4. Supplemental Investigation Groundwater Field Parameters

Table 5. Cumulative Groundwater Level Elevation Measurements

Table 6. Groundwater Field Parameters

Table 7. Groundwater Analytical Results

Table 8. Groundwater Injection Summary

Appendix A. Supplemental Investigation Boring Logs

Appendix B. Injection Well Boring Logs

References

Ecology. 2024. "Re: Tiger Oil Groundwater Sampling." From Frank P. Winslow, LHG, Washington State Department of Ecology, to Shane Kostka, LG, Landau Associates, Inc. July 24.

EPA. 2020. National Functional Guidelines for Organic Superfund Methods Data Review. OLEM 9240.0-51; EPA-540-R-20-005. US Environmental Protection Agency. November.
https://www.epa.gov/sites/default/files/2021-03/documents/nfg_for_organic_superfund_methods_data_review_november_2020.pdf.

Fulcrum. 2019. Memorandum: Preliminary Results—Underground Storage Tank Site Assessment, Former Tiger Oil Site, 1808 North 1st Street, Yakima, Washington. Fulcrum Environmental Consulting, Inc. October 22.

GeoEngineers. 2015. Phase II Site Assessment Report: Tiger Oil, 1808 North 1st Street, Yakima, Washington. File No. 0504-101-00. GeoEngineers, Inc. February 11.


GeoEngineers. 2017. Remedial Investigation: Tiger Oil, 1808 North 1st Street, Yakima, Washington. File No. 0504-101-03. GeoEngineers, Inc. May 22.

Landau. 2022. Tiger Oil Injection Work Plan, 1808 North 1st Street, Yakima, Washington. Landau Associates, Inc. May 9.

Smith, Kate. 2022. "Irrigation Season Ends Oct. 14 in Yakima." *Yakima Herald-Republic*. October 8.
https://www.yakimaherald.com/news/local/irrigation-season-ends-oct-14-in-yakima/article_60010af4-4665-11ed-9b88-b70f607674e3.html.




G:\Projects\1148\01\010\015\TigerOil\TigerOil.aprx 10/8/2024



Data Source: Esri.

G:\Projects\1148\010\010\015\InjectionTechMemo\F02RISupplementalInvestigationExplorationLocations.mxd 11/26/2024 | abarton





- Legend**
- Monitoring Well (Landau 2021)
 - Monitoring Well (GeoEngineers 2014 and 2016)
 - Former Monitoring Well
 - ▲ Soil Boring (Landau 2021)
 - RI Boring (GeoEngineers 2016)
 - Extent of UST Excavation
 - Estimated Extent of Impacted Soil and Groundwater Associated with the Site

Acronyms/Abbreviations
 N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well
 N1DP = North 1st Direct Push
 HSB = Hollow-Stem Boring
 RI = Remedial Investigation

Note
 1. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021; GeoEngineers, 2015, 2017

G:\Projects\1148\01\010\015\InjectionTechMemo\F03ASupplementalInvestigationSoilPetroleum.mxd 12/3/2024 | abarton



Legend

- Monitoring Well (Landau 2021)
- Former Monitoring Well
- ▲ Soil Boring (Landau 2021)
- Soil Concentrations Exceed
MTCA Method A Cleanup Level

Acronyms/Abbreviations

N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well
 HSB = Hollow-Stem Boring
 GRO = Gasoline range organics
 DRO = Diesel range organics
 ORO = Oil range organics
 ND = Not Detected
 MTCA = Model Toxics Control Act

Notes

1. Analytical results for benzene, toluene, ethylbenzene, and xylenes not shown.
2. Results in mg/kg (milligrams per kilogram).
3. **Bold** indicates analyte exceedance.
4. Green shading indicates detected analyte exceeds MTCA Method A cleanup level.
5. J = The result is an estimated quantity. The associated numerical value is the approximate concentration of the analyte in the sample.
6. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.



N1MW-5	10/4/2021
GRO	ND
DRO	ND
ORO	ND

N1MW-6R	10/6/2021
GRO	14,000
DRO	3,300 J
ORO	ND

HSB-2	10/5/2021
GRO	43,000
DRO	7,800 J
ORO	ND

N1MW-8	10/4/2021
GRO	400
DRO	1,400 J
ORO	ND

N1MW-9	10/6/2021
GRO	21,000
DRO	4,200 J
ORO	ND

N1MW-2	10/4/2021
GRO	ND
DRO	ND
ORO	ND


N1MW-4	10/4/2021
GRO	ND
DRO	ND
ORO	ND

HSB-3	10/6/2021
GRO	23,000
DRO	6,400 J
ORO	ND

N1MW-7R	10/6/2021
GRO	11,000
DRO	2,700 J
ORO	ND

HSB-1	10/5/2021
GRO	19,000
DRO	7,600 J
ORO	ND

N1MW-3	10/4/2021
GRO	ND
DRO	ND
ORO	ND



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- ▲ Soil Boring (Landau 2021)
- Groundwater Concentrations Exceed MTCA Method A Cleanup Level


Acronyms/Abbreviations

N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well
 HSB = Hollow-Stem Boring
 GRO = Gasoline range organics
 DRO = Diesel range organics
 ORO = Oil range organics
 ND = Not Detected
 MTCA = Model Toxics Control Act

Notes

1. Analytical results for benzene, toluene, ethylbenzene, and xylenes not shown.
2. Results in µg/L (micrograms per liter).
3. **Bold** indicates analyte exceedance.
4. **Green** shading indicates detected analyte exceeds MTCA Method A cleanup level.
5. J = The result is an estimated quantity. The associated numerical value is the approximate concentration of the analyte in the sample.
6. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- Injection Well (Landau 2022)
- ▲ Soil Boring (Landau 2021)
- RI Boring (GeoEngineers 2016)
- W Water
- P Power
- S Sewer/SW
- ⊖ Comm
- ⊕ Unknown
- Continuance

Acronyms/Abbreviations


- N1MW = North 1st Monitoring Well
- N1MW-#R = North 1st Replacement Monitoring Well
- N1DP = North 1st Direct Push
- HSB = Hollow-Stem Boring
- RI = Remedial Investigation

Notes

1. Injection wells not surveyed and locations are approximate.
2. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.

G:\Projects\1148\010\010\015\InjectionTechMemo\F05InjectionLocations.mxd 11/26/2024 | abarton




- Legend**
- Monitoring Well (Landau 2021)
 - Monitoring Well (GeoEngineers 2014 and 2016)
 - Former Monitoring Well
 - Injection Well (Landau 2022)
 - W Water
 - P Power
 - S Sewer/SW
 - ⊖ Comm
 - ⊕ Unknown
 - Continuance
 - ▨ Extent of UST Excavation
 - ▭ Target Treatment Area
 - Designed Injection Radius of Influence

Acronyms/Abbreviations
 N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well

- Notes**
1. Injection wells not surveyed and locations are approximate.
 2. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.

G:\Projects\1148\01\010\015\InjectionTechMemo\F06APreInjectionGRO.mxd 11/26/2024 | abarton



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- Injection Well (Landau 2022)
- Groundwater Concentrations Exceed MTCA Method A Cleanup Level
- ▨ Extent of UST Excavation
- ▭ Target Treatment Area
- Designed Injection Radius of Influence

Acronyms/Abbreviations


- N1MW = North 1st Monitoring Well
- N1MW-#R = North 1st Replacement Monitoring Well
- GRO = Gasoline range organics
- MTCA = Model Toxics Control Act
- NS = Not sampled

Notes

1. Analytical results for benzene, toluene, ethylbenzene, and xylenes not shown.
2. Results in µg/L (micrograms per liter).
3. **Bold** indicates analyte exceedance.
4. **Green** shading indicates detected analyte exceeds MTCA Method A cleanup level.
5. Injection wells not surveyed and locations are approximate.
6. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.


G:\Projects\1148\01\010\015\InjectionTechMemo\F06BPostInjection1GRO.mxd 11/26/2024 | abarton



- Legend**
- Monitoring Well (Landau 2021)
 - Monitoring Well (GeoEngineers 2014 and 2016)
 - Former Monitoring Well
 - Injection Well (Landau 2022)
 - Groundwater Concentrations Exceed MTCA Method A Cleanup Level
 - ▨ Extent of UST Excavation
 - ▭ Target Treatment Area
 - Designed Injection Radius of Influence


Acronyms/Abbreviations
 N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well
 GRO = Gasoline range organics
 MTCA = Model Toxics Control Act
 NS = Not sampled

- Notes**
1. Analytical results for benzene, toluene, ethylbenzene, and xylenes not shown.
 2. Results in µg/L (micrograms per liter).
 3. **Bold** indicates analyte exceedance.
 4. **Green** shading indicates detected analyte exceeds MTCA Method A cleanup level.
 5. Injection wells not surveyed and locations are approximate.
 6. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.



Source: Google Earth Pro, 2021; GeoEngineers, 2017

G:\Projects\1148\01\010\015\InjectionTechMemo\F06CPostInjection2GRO.mxd 11/26/2024 | abarton



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- Injection Well (Landau 2022)
- Groundwater Concentrations Exceed MTCA Method A Cleanup Level
- ▨ Extent of UST Excavation
- ▭ Target Treatment Area
- Designed Injection Radius of Influence



Acronyms/Abbreviations

N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well
 GRO = Gasoline range organics
 MTCA = Model Toxics Control Act
 NS = Not sampled

Notes

1. Analytical results for benzene, toluene, ethylbenzene, and xylenes not shown.
2. Results in µg/L (micrograms per liter).
3. **Bold** indicates analyte exceedance.
4. **Green** shading indicates detected analyte exceeds MTCA Method A cleanup level.
5. Injection wells not surveyed and locations are approximate.
6. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021; GeoEngineers, 2017



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- Injection Well (Landau 2022)
- Groundwater Elevation Contour
- Target Treatment Area

Acronyms/Abbreviations

- N1MW = North 1st Monitoring Well
- N1MW-#R = North 1st Replacement Monitoring Well



Notes

1. Depth-to-water measurements taken on 7/10/2023 prior to injection beginning.
2. Elevations calculated based on TOC elevations surveyed by Gray Surveying under contract with Landau Associates in November 2021 and elevations reference NAVD88.
3. Injection wells were not used to calculate groundwater elevation contours.
4. Injection wells not surveyed and locations are approximate.
5. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.

G:\Projects\1148\010\010\015\InjectionTechMemo\F07A\Injection2GWContours.mxd 11/26/2024 | abarton

G:\Projects\1148\010\010\015\InjectionTechMemo\F07BInjection3GWContours.mxd 11/26/2024 | abarton



Legend

- Monitoring Well (Landau 2021)
- Monitoring Well (GeoEngineers 2014 and 2016)
- Former Monitoring Well
- Injection Well (Landau 2022)
- Groundwater Elevation Contour
- Target Treatment Area

Acronyms/Abbreviations

N1MW = North 1st Monitoring Well
 N1MW-#R = North 1st Replacement Monitoring Well

Notes

1. Depth-to-water measurements taken on 9/9/2024 prior to injection beginning.
2. Elevations calculated based on TOC elevations surveyed by Gray Surveying under contract with Landau Associates in November 2021 and elevations reference NAVD88.
3. Injection wells were not used to calculate groundwater elevation contours.
4. Injection wells not surveyed and locations are approximate.
5. Black and white reproduction of this color original may reduce its effectiveness and lead to incorrect interpretation.

Source: Google Earth Pro, 2021.

Table 1
Soil Boring and Well Construction Details
Former Tiger Oil Site
Yakima, Washington

Location ID	Boring Type	Date Installed	X Coordinate (easting)	Y Coordinate (northing)	Drilling Method	Total Boring Depth (ft bgs)	Ground Surface Elevation (ft NAVD88)	Total Well Depth (ft bgs)	Well Diameter/ Material/ Monument Type (inches)	Length of Screen (ft)	Top of Screen Interval (ft bgs)	Bottom of Screen Interval (ft bgs)	TOC Elevation (ft NAVD88)
N1DP-1	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-2	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-3	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-4	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-5	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-6	Soil Boring	4/16/2014	NS	NS	Direct Push	15	NS	--	--	--	--	--	--
N1DP-7	Soil Boring	4/16/2014	NS	NS	Direct Push	15	NS	--	--	--	--	--	--
N1DP-8	Soil Boring	4/16/2014	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-9	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-10	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-11	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-12	Soil Boring	8/4/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-13	Soil Boring	8/4/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-14	Soil Boring	8/4/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-15	Soil Boring	8/4/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-16	Soil Boring	8/4/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-17	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-18	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
N1DP-19	Soil Boring	8/3/2016	NS	NS	Direct Push	20	NS	--	--	--	--	--	--
HSB-1 (c)	Soil Boring	10/5/2021	1637359.308	470583.971	Hollow-Stem Auger	20	1085.158	--	--	--	--	--	--
HSB-2 (c)	Soil Boring	10/5/2021	1637360.617	470603.488	Hollow-Stem Auger	20	1084.976	--	--	--	--	--	--
HSB-3 (c)	Soil Boring	10/6/2021	1637343.428	470591.606	Hollow-Stem Auger	19.5	1085.516	--	--	--	--	--	--
HSB-4 (c)	Soil Boring	10/6/2021	1637267.273	470515.372	Hollow-Stem Auger	17	1085.831	--	--	--	--	--	--
HSB-5 (c)	Soil Boring	10/6/2021	1637242.545	470564.059	Hollow-Stem Auger	16.5	1086.533	--	--	--	--	--	--
N1MW-1* (a)	Monitoring Well	8/7/2014	1637341.7	470569	Rotosonic	20	1058.19	19.5	2 / PVC / Flush	10	9.5	19.5	1084.85
N1MW-2 (c)	Monitoring Well	8/7/2014	1637480.028	470616.604	Rotosonic	20	1084.289	20	2 / PVC / Flush	10	10	20	1083.90
N1MW-3 (c)	Monitoring Well	8/6/2014	1637358.732	470475.202	Rotosonic	20	1084.855	20	2 / PVC / Flush	10	10	20	1084.54
N1MW-4 (c)	Monitoring Well	8/7/2014	1637199.855	470595.117	Rotosonic	20	1082.449	17	2 / PVC / Flush	10	7	17	1082.11
N1MW-5 (c)	Monitoring Well	8/6/2014	1637362.962	470681.530	Rotosonic	20	1083.554	19	2 / PVC / Flush	10	9	19	1083.34
N1MW-6* (b)	Monitoring Well	10/17/2016	1637363.5	470639	Hollow-Stem Auger	20.5	1083.96	20	2 / PVC / Flush	10	10	20	1083.54
N1MW-6R (c)	Monitoring Well	10/4/2021	1637367.775	470639.445	Hollow-Stem Auger	20.5	1084.671	20	2 / PVC / Flush	10	10	20	1084.26
N1MW-7* (b)	Monitoring Well	10/18/2016	1637370.7	470586.4	Hollow-Stem Auger	19	1085.18	18.8	2 / PVC / Flush	10	8.8	18.8	1084.84
N1MW-7R (c)	Monitoring Well	10/4/2021	1637362.962	470581.530	Hollow-Stem Auger	20.5	1084.948	20	2 / PVC / Flush	10	10	20	1084.54
N1MW-8 (c)	Monitoring Well	10/17/2016	1637328.275	470623.300	Hollow-Stem Auger	21	1085.517	20	2 / PVC / Flush	10	10	20	1084.42
N1MW-9 (c)	Monitoring Well	10/5/2021	1637369.489	470614.814	Hollow-Stem Auger	20.5	1084.754	20	2 / PVC / Flush	10	10	20	1084.36

**Table 1
Soil Boring and Well Construction Details
Former Tiger Oil Site
Yakima, Washington**

Location ID	Boring Type	Date Installed	X Coordinate (easting)	Y Coordinate (northing)	Drilling Method	Total Boring Depth (ft bgs)	Ground Surface Elevation (ft NAVD88)	Total Well Depth (ft bgs)	Well Diameter/ Material/ Monument Type (inches)	Length of Screen (ft)	Top of Screen Interval (ft bgs)	Bottom of Screen Interval (ft bgs)	TOC Elevation (ft NAVD88)
IW-1	Injection Well	8/1/2022	NS	NS	Rotosonic	20.9	NS	20.9	2 / PVC / Flush	10	10.9	20.9	NS
IW-2	Injection Well	8/1/2022	NS	NS	Rotosonic	20.8	NS	20.8	2 / PVC / Flush	10	10.8	20.8	NS
IW-3	Injection Well	8/1/2022	NS	NS	Rotosonic	20.4	NS	20.4	2 / PVC / Flush	10	10.4	20.4	NS
IW-4	Injection Well	8/2/2022	NS	NS	Rotosonic	20.4	NS	20.4	2 / PVC / Flush	10	10.4	20.4	NS
IW-5	Injection Well	8/2/2022	NS	NS	Rotosonic	20.7	NS	20.7	2 / PVC / Flush	10	10.7	20.7	NS
IW-6	Injection Well	8/2/2022	NS	NS	Rotosonic	20	NS	20	2 / PVC / Flush	10	10	20	NS
IW-7	Injection Well	8/2/2022	NS	NS	Rotosonic	20.6	NS	20	2 / PVC / Flush	10	10	20	NS
IW-8	Injection Well	8/31/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-9	Injection Well	8/29/2022	NS	NS	Hollow-Stem Auger	21	NS	20	2 / PVC / Flush	10	10	20	NS
IW-10	Injection Well	8/29/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-11	Injection Well	8/29/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-12	Injection Well	8/30/2022	NS	NS	Hollow-Stem Auger	20	NS	20	2 / PVC / Flush	10	10	20	NS
IW-13	Injection Well	8/30/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-14	Injection Well	8/30/2022	NS	NS	Hollow-Stem Auger	21	NS	20	2 / PVC / Flush	10	10	20	NS
IW-15	Injection Well	8/31/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-16	Injection Well	8/31/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS
IW-17	Injection Well	9/1/2022	NS	NS	Hollow-Stem Auger	18.5	NS	18.5	2 / PVC / Flush	10	8.5	18.5	NS
IW-18	Injection Well	9/1/2022	NS	NS	Hollow-Stem Auger	20.5	NS	20	2 / PVC / Flush	10	10	20	NS

Notes:

- (a) Elevations and coordinates surveyed by PLS under contract with GeoEngineers in August 2014.
- (b) Elevations and coordinates surveyed by PLS under contract with GeoEngineers in October 2016.
- (c) Elevations and coordinates surveyed by Gray Surveying under contract with Landau Associates in November 2021.
- = Not applicable

Vertical elevations are with respect to NAVD88. Horizontal northings and eastings are with respect to the Washington State Plane coordinate system, south zone (NAD83-1996).

* N1MW-1, N1MW-6, and N1MW-7 are presumed to have been paved over and/or underneath the current drive-through coffee hut at the Site and there is no record of these wells being decommissioned.

Acronyms and Abbreviations:

- ft = foot/feet
- NAD83 = North American Datum of 1983
- TOC = top of casing
- N1DP = North 1st Direct Push
- N1MW = North 1st Monitoring Well
- IW = Injection Well
- NS = not surveyed

Table 2
Supplemental Investigation Soil Analytical Results
Former Tiger Oil Site
Yakima, Washington

Sample Location	Sample Depth Interval	Laboratory SDG	Sample Date	Sample Type	Analytical Method, Analyte, Unit of Measurement									
					NWTPH-Gx	NWTPH-Dx		SW-846 8260D						
					Gasoline Range Organics µg/L	Diesel Range Organics µg/L	Residual Range Organics µg/L	Benzene µg/L	Ethylbenzene µg/L	m-&p-Xylenes µg/L	o-Xylene µg/L	Toluene µg/L	Xylenes, Total µg/L	
HSB-1	15.5-17	590-16086-1	10/5/2021	N	2100	210	26 U	0.047 U	33	180	57	9.3	230	
HSB-2	15.5-16	590-16086-1	10/5/2021	N	9.9 U	10 U	26 U	0.040 U	0.035 J	0.14 J	0.052 J	0.030 J	0.19 J	
HSB-3	13.5-14.5	590-16086-1	10/6/2021	N	270 J	19	40	0.037 U	3.2 J	11 J	3.6 J	0.19 U	15 J	
HSB-3	13.5-14.5	590-16086-1	10/6/2021	FD	26 J	24	49	0.057 U	0.090 J	0.32 J	0.13 J	0.28 U	0.45 J	
HSB-4	7-8	590-16086-1	10/6/2021	N	12 U	12 U	29 U	0.049 U	0.25 U	0.99 U	0.49 U	0.25 U	1.5 U	
HSB-4	11-12	590-16086-1	10/6/2021	N	12 U	10 U	25 U	0.047 U	0.23 U	0.93 U	0.47 U	0.23 U	1.4 U	
HSB-5	7.5-9	590-16086-1	10/6/2021	N	11 U	10 U	81	0.045 U	0.22 U	0.90 U	0.45 U	0.22 U	1.3 U	
N1MW-6R	14.5-15	590-16086-1	10/4/2021	N	670	62	29	0.042 U	3.4	12	0.43	0.21 U	12 J	
N1MW-7R	14.5-16	590-16086-1	10/4/2021	N	9700	180	27 U	0.039 U	110 J	550 J	160 J	1.6	710 J	
N1MW-9	16-17.5	590-16086-1	10/5/2021	N	110	11 U	27 U	0.039 U	2.1	7.7	2.6	0.37	10	
MTCA Method A Cleanup Level					30/100 (a)	2,000	2,000	0.03	6	N/A	N/A	7	9	

Notes:

- * = This sample was initially identified as N1MW-1R in field and lab reports but was renamed per Ecology Request
- Bold** text indicates detected analyte
- Green shading indicates detected analyte exceeds applicable cleanup level
- U = the analyte was analyzed for, but was not detected above the level of the reported sample quantitation limit.
- J = The result is an estimated quantity. The associated numerical value is the approximate concentrations of the analyte in the sample.
- (a) MTCA Method A cleanup level is 100 µg/L if benzene is not present and the total of ethylbenzene, toluene, and xylenes is less than 1% of the gasoline mixture; otherwise, the cleanup level is 30 µg/L .

Acronyms/Abbreviations:

- mg/kg = milligrams per kilogram
- NWTPH - Northwest Total Petroleum Hydrocarbon
- N = primary sample
- FD = field duplicate

Table 3
Supplemental Investigation Groundwater Analytical Results
Former Tiger Oil Site
Yakima, Washington

Sample Location	Laboratory SDG	Sample Date	Sample Type	Analytical Method, Analyte, Unit of Measurement								
				NWTPH-Gx	NWTPH-Dx		SW-846 8260D					
				Gasoline Range Organics µg/L	Diesel Range Organics µg/L	Residual Range Organics µg/L	Benzene µg/L	Ethylbenzene µg/L	m-&p-Xylenes µg/L	o-Xylene µg/L	Toluene µg/L	Xylenes, Total µg/L
HSB-1	590-16086-1	10/5/2021	N	19000	7600 J	380 U	2.0 U	940	380	150	550	530
HSB-2	590-16086-1	10/5/2021	N	43000	7800 J	380 U	9.2	2900	8700	3600	180	12000
HSB-3	590-16086-1	10/6/2021	N	23000	6400 J	380 U	4.1	1600	4500	1800	22	6300
HSB-3	590-16086-1	10/6/2021	FD	24000	6000 J	380 U	4.0	1500	4300	1700	22	6000
N1MW-2	590-16086-1	10/4/2021	N	150 U	240 U	390 U	0.40 U	1.0 U	2.0 U	1.0 U	1.0 U	3.0 U
N1MW-3	590-16086-1	10/4/2021	N	150 U	230 U	390 U	0.40 U	1.0 U	2.0 U	1.0 U	1.0 U	3.0 U
N1MW-4	590-16086-1	10/4/2021	N	150 U	240 U	390 U	0.40 U	1.0 U	2.0 U	1.0 U	1.0 U	3.0 U
N1MW-5	590-16086-1	10/4/2021	N	150 U	240 U	390 U	0.40 U	1.0 U	2.0 U	1.0 U	1.0 U	3.0 U
N1MW-6R	590-16086-1	10/6/2021	N	14000	3300 J	380 U	0.85	550	2100	170	1.8	2200
N1MW-7R	590-16086-1	10/6/2021	N	11000	2700 J	380 U	2.0	640	2700	1000	380	3700
N1MW-8	590-16086-1	10/4/2021	N	400	1400 J	390 U	8.1	7.2	23	14	2.5	37
N1MW-9	590-16086-1	10/6/2021	N	21000	4200 J	380 U	6.2	1800	6200	2700	660	8900
MTCA Method A Cleanup Level				800/1000 (a)	500	500	5	700	N/A	N/A	1000	1000

Notes:

* = This sample was initially identified as N1MW-1R in field and lab reports but was renamed per Ecology Request

Bold text indicates detected analyte

Green shading indicates detected analyte exceeds applicable cleanup level

U = the analyte was analyzed for, but was not detected above the level of the reported sample quantitation limit.

J = The result is an estimated quantity. The associated numerical value is the approximate concentrations of the analyte in the sample.

(a) MTCA Method A cleanup level is 1000 µg/L if benzene is not present in groundwater and 800 µg/L if benzene is present in groundwater.

Acronyms/Abbreviations:

mg/kg = milligrams per kilogram

NWTPH - Northwest Total Petroleum Hydrocarbon

N = primary sample

FD = field duplicate

Table 4
Supplemental Investigation Groundwater Field Parameters
Former Tiger Oil Site
Yakima, Washington

Sample Location	Date Measured	Field Parameters					
		Temp (°C)	Specific Conductance (µS/cm)	Dissolved Oxygen (mg/L)	pH	Oxidation Reduction Potential (mV)	Turbidity (NTU)
October 2021 Sampling Event							
NIMW-2	10/4/2021	18.2	361.2	1.23	6.21	70.7	--
NIMW-3	10/4/2021	18.5	345.1	3.48	6.29	71.2	--
NIMW-4	10/4/2021	17.0	284.6	4.30	6.33	76.8	--
NIMW-5	10/4/2021	19.9	341.2	0.89	5.79	69.5	--
NIMW-8	10/4/2021	18.7	7.4	2.08	6.11	31.3	--
NIMW-1R	10/6/2021	18.8	492.5	2.01	6.66	-86.5	--
NIMW-6R	10/6/2021	19.1	436.6	3	6.52	-66.7	--
NIMW-7R	10/6/2021	17.8	505	2.54	6.53	-74.3	--
HSB-1	10/5/2021	20.8	553	1.85	6.70	20.9	--
HSB-2	10/5/2021	21.7	705	0.38	6.57	-93.8	--
HSB-3	10/6/2021	21.3	788	0.56	6.58	-115.9	--
HSB-3	10/6/2021	21.1	788	0.55	6.57	-116.1	--

Notes:

-- = not sampled

NA = not available

Abbreviations and Acronyms:

°C = degrees Celsius

µS/cm = microsiemens per centimeter

mg/L = milligrams per liter

mV = millivolts

NTU = nephelometric turbidity units

**Table 5
Cumulative Groundwater-Level Elevation Measurements
Former Tiger Oil Site
Yakima, Washington**

Monitoring Well TOC Elevation (ft) (a)	N1MW-2 1,083.90		N1MW-3 1,084.54		N1MW-4 1,082.11		N1MW-5 1,083.34		N1MW-6R 1,084.26		N1MR-7R 1,084.54		N1MW-8 1,084.42		N1MW-9 1,084.36	
	Date Measured	Depth	Elevation	Depth	Elevation	Depth	Elevation	Depth	Elevation	Depth	Elevation	Depth	Elevation	Depth	Elevation	
10/4/2021	13.70	1,070.20	14.16	1,070.38	11.48	1,070.63	12.77	1,070.57	Well not yet installed		Well not yet installed		13.90	1,070.52	Well not yet installed	
10/6/2021	-	-	-	-	-	-	-	-	13.66	1,070.60	14.03	1,070.51	-	-	13.80	1,070.56
9/8/2022	-	-	-	-	-	-	-	-	14.23	1,070.03	14.60	1,069.94	14.45	1,069.97	14.37	1,069.99
1/18/2023	-	-	-	-	-	-	-	-	13.71	1,070.55	14.03	1,070.51	13.36	1,071.06	13.85	1,070.51
7/10/2023	13.80	1,070.10	14.23	1,070.31	11.59	1,070.52	12.87	1,070.47	13.82	1,070.44	14.17	1,070.37	14.00	1,070.42	13.96	1,070.40
11/28/2023	14.28	1,069.62	14.77	1,069.77	12.24	1,069.87	13.39	1,069.95	14.30	1,069.96	14.71	1,069.83	14.53	1,069.89	14.45	1,069.91
9/9/2024	13.27	1,070.63	13.67	1,070.87	10.99	1,071.12	12.62	1,070.72	13.20	1,071.06	13.62	1,070.92	13.45	1,070.97	13.37	1,070.99

Notes:

(a) TOC elevation surveyed by Gray Surveying under contract with Landau Associates in November 2021.

- = Not measured

Depth measured in ft below TOC.

Elevation datum = NAVD88

Acronyms and Abbreviations:

ft = foot/feet

NAVD88 = North American Vertical Datum of 1988

TOC = top of casing

**Table 6
Groundwater Field Parameters
Former Tiger Oil Site
Yakima, Washington**

Sample Location	Date Measured	Field Parameters																	
		Temp (°C)			Specific Conductance (µS/cm)			Dissolved Oxygen (mg/L)			pH			Oxidation Reduction Potential (mV)			Turbidity (NTU)		
		Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)	Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)	Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)	Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)	Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)	Pre-injection Baseline Sampling (a)	Post Injection 1 (b)	Post Injection 2 (c)
IW-1	9/7/2022	16.82	--	--	569	--	--	6.15	--	--	6.55	--	--	-50.1	--	--	4.61	--	--
	1/18/2023	--	14.52	--	--	10326	--	--	0.94	--	--	1.69	--	--	534	--	--	2.62	--
	11/28/2023	--	--	15.20	--	--	8970	--	--	1.04	--	--	2.74	--	--	447.5	--	--	0.00
IW-2	9/7/2022	16.27	--	--	353	--	--	3.89	--	--	6.63	--	--	-52.1	--	--	1.93	--	--
	1/18/2023	--	14.85	--	--	2817	--	--	1.71	--	--	3.15	--	--	415.2	--	--	1.88	--
	11/28/2023	--	--	15.27	--	--	4180	--	--	0.44	--	--	3.28	--	--	440.9	--	--	0.93
IW-3	9/7/2022	16.16	--	--	359	--	--	2.34	--	--	6.69	--	--	-64.3	--	--	6.70	--	--
	1/19/2023	--	14.30	--	--	5688	--	--	0.33	--	--	3.19	--	--	471.7	--	--	3.87	--
	11/29/2023	--	--	14.77	--	--	3327	--	--	0.88	--	--	4.37	--	--	124.5	--	--	11.43
IW-4	9/7/2022	17.63	--	--	537	--	--	5.59	--	--	6.48	--	--	-100.8	--	--	1.25	--	--
	1/18/2023	--	15.35	--	--	6111	--	--	0.56	--	--	1.87	--	--	354.8	--	--	1.30	--
	11/28/2023	--	--	16.15	--	--	10853	--	--	0.40	--	--	2.69	--	--	517.9	--	--	3.89
IW-8	9/8/2022	16.83	--	--	473	--	--	1.32	--	--	6.46	--	--	-74.2	--	--	3.73	--	--
	1/19/2023	--	15.29	--	--	8030	--	--	1.60	--	--	3.35	--	--	358.4	--	--	2.52	--
	11/29/2023	--	--	15.52	--	--	4594	--	--	0.35	--	--	3.38	--	--	275.5	--	--	5.82
IW-9	9/8/2022	16.62	--	--	374	--	--	2.56	--	--	5.81	--	--	-29.5	--	--	1.22	--	--
	1/18/2023	--	14.35	--	--	845	--	--	0.50	--	--	5.14	--	--	-102.7	--	--	2.29	--
	11/28/2023	--	--	14.72	--	--	572	--	--	0.32	--	--	5.51	--	--	9.50	--	--	5.13
IW-10	9/7/2022	17.32	--	--	352	--	--	3.25	--	--	6.44	--	--	-50.6	--	--	1.22	--	--
	1/19/2023	--	14.54	--	--	3563	--	--	7.46	--	--	3.07	--	--	340.0	--	--	2.65	--
	11/30/2023	--	--	15.80	--	--	9206	--	--	0.21	--	--	2.79	--	--	415.0	--	--	10.05
IW-12	9/8/2022	16.92	--	--	609	--	--	1.46	--	--	6.34	--	--	-58.6	--	--	0.58	--	--
	1/19/2023	--	14.84	--	--	12605	--	--	2.47	--	--	3.23	--	--	499.2	--	--	4.52	--
	11/30/2023	--	--	15.13	--	--	9374	--	--	0.21	--	--	3.00	--	--	452.6	--	--	9.12
IW-14	9/8/2022	16.57	--	--	536	--	--	1.63	--	--	6.45	--	--	-73.6	--	--	2.81	--	--
	1/19/2023	--	15.05	--	--	2101	--	--	0.95	--	--	5.35	--	--	35	--	--	15.99	--
	11/29/2023	--	--	15.23	--	--	2623	--	--	0.22	--	--	4.41	--	--	164.1	--	--	42.13
IW-15	9/8/2022	17.09	--	--	460	--	--	1.57	--	--	6.37	--	--	-89.8	--	--	3.56	--	--
	1/19/2023	--	15.12	--	--	1015	--	--	0.46	--	--	3.86	--	--	369.7	--	--	4.61	--
	11/29/2023	--	--	15.74	--	--	712	--	--	0.34	--	--	5.39	--	--	-23.8	--	--	7.02
IW-17	9/8/2022	16.38	--	--	438	--	--	1.48	--	--	6.41	--	--	-8.6	--	--	2.79	--	--
	1/19/2023	--	12.75	--	--	1829	--	--	0.58	--	--	5.25	--	--	11.9	--	--	NA	--
	11/29/2023	--	--	14.38	--	--	3226	--	--	1.00	--	--	4.66	--	--	22.5	--	--	24.24
IW-18	9/8/2022	17.36	--	--	559	--	--	2.18	--	--	6.36	--	--	-70.3	--	--	2.06	--	--
	1/19/2023	--	14.17	--	--	6900	--	--	1.12	--	--	3.32	--	--	497.0	--	--	10.54	--
	11/28/2023	--	--	14.78	--	--	3479	--	--	0.83	--	--	4.07	--	--	381.6	--	--	6.66
N1MW-6R	9/8/2022	16.55	--	--	876	--	--	2.20	--	--	6.24	--	--	-50.9	--	--	2.64	--	--
	1/19/2023	--	14.09	--	--	5017	--	--	0.48	--	--	3.15	--	--	422.9	--	--	10.75	--
	11/29/2023	--	--	14.34	--	--	2504	--	--	1.36	--	--	4.27	--	--	-1.90	--	--	--

**Table 6
Groundwater Field Parameters
Former Tiger Oil Site
Yakima, Washington**

		Field Parameters																	
		Temp (°C)			Specific Conductance (µS/cm)			Dissolved Oxygen (mg/L)			pH			Oxidation Reduction Potential (mV)			Turbidity (NTU)		
N1MW-7R	9/8/2022	14.83	--	--	709	--	--	3.94	--	--	6.50	--	--	27.0	--	--	1.61	--	--
	1/18/2023	--	14.17	--	--	2779	--	--	1.06	--	--	2.48	--	--	455.5	--	--	58.35	--
	11/28/2024	--	--	14.70	--	--	2262	--	--	0.66	--	--	4.06	--	--	271.6	--	--	35.35
N1MW-8	9/7/2022	16.03	--	--	547	--	--	4.00	--	--	6.45	--	--	-35.5	--	--	2.68	--	--
	1/18/2023	--	14.74	--	--	1916	--	--	0.41	--	--	4.38	--	--	93	--	--	7.15	--
	11/30/2023	--	--	15.35	--	--	10907	--	--	0.46	--	--	2.78	--	--	505.8	--	--	8.81
N1MW-9	9/8/2022	15.77	--	--	803	--	--	2.12	--	--	6.46	--	--	-29.8	--	--	4.13	--	--
	1/19/2023	--	13.86	--	--	3554	--	--	0.99	--	--	1.34	--	--	422.7	--	--	1.47	--
	11/29/2023	--	--	15.04	--	--	1219	--	--	0.65	--	--	4.75	--	--	-67.1	--	--	10.04

Notes:

-- = not measured
NA = not available

- (a) Parameters recorded during pre-injection baseline groundwater sampling took place on September 7 and 8, 2022 after injection wells were installed and developed prior to any injections occurring at the Site.
- (b) Parameters recorded during groundwater sampling on January 18 and 19, 2023 following the 1st ISCO injection at the site which occurred October 11-19, 2023.
- (c) Parameters recorded during groundwater sampling on November 28 and 29, 2023 following the 2nd ISCO injection at the site which occurred July 10-13, 2023.

Abbreviations and Acronyms:

°C = degrees Celsius
µS/cm = microsiemens per centimeter
mg/L = milligrams per liter
mV = millivolts
NTU = nephelometric turbidity units

**Table 7
Groundwater Analytical Results
Former Tiger Oil Site
Yakima, Washington**

Sample Location	Field Sample ID	Laboratory SDG	Sample Date	Analytical Method, Analyte, Unit of Measurement, Sampling Event									
				NWTPH-Gx			SW-846 6010D	SW-846 8260D					
				Gasoline Range Organics µg/L			Lead	Benzene	Ethylbenzene	m-&p-Xylenes	o-Xylene	Toluene	Xylenes, Total
				Pre-Injection Baseline Sampling (a)	Post-Injection 1 (b)	Post-Injection 2 (c)	mg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L
IW-1	IW-1	590-18585-1	9/7/2022	1,100	--	--	--	--	--	--	--	--	--
		590-19667-1	1/18/2023	--	600	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	310	--	0.96	6.0	4.6	1.6	1.0 U	6.2
IW-2	IW-2	590-18585-1	9/7/2022	6,100	--	--	--	--	--	--	--	--	--
		590-19667-1	1/18/2023	--	2,200	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	580	--	0.94	3.8	9.7	3.5	1.0 U	13
IW-3	IW-3	590-18585-1	9/7/2022	4,700	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	840	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	3,900	--	2.8	360	1,300	520	100	1,800
IW-4	IW-4	590-18585-1	9/7/2022	2,300	--	--	--	--	--	--	--	--	--
		590-19667-1	1/18/2023	--	15,000	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	840	--	1.3	12	5.8	1.8	1.0 U	7.6
IW-8	IW-8	590-18585-1	9/8/2022	20,000	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	3,100	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	4,000	--	7.2	320	730	280	200	1,000
IW-9	IW-9	590-18585-1	9/8/2022	1,700	--	--	0.060 U	3.5	77	120 J	18	1.0 U	140 J
		590-19667-1	1/18/2023	--	1,900	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	690	--	2.6	35	64	8.6	1.0 U	73
IW-10	IW-10	590-18585-1	9/7/2022	7,800	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	8,400	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	870	--	4.3	36	19	2.6	1.0 U	21
IW-12	IW-12	590-18585-1	9/8/2022	16,000	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	2,800	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	420 J	--	0.94	1.7	2.0 U	1.0 U	1.0 U	3.0 U
IW-14	IW-14	590-18585-1	9/8/2022	17,000	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	150 U	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	150 U	--	0.59	10	2.2	1.3	1.0 U	3.6
IW-15	IW-15	590-18585-1	9/8/2022	9,200	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	450	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	150 U	--	0.40 U	4.8	4.1	1.8	1.0 U	5.9
IW-17	IW-17	590-18585-1	9/8/2022	6,300	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	190	--	--	--	--	--	--	--	--
		590-22377-1	11/29/2023	--	--	1,100	--	1.2	91	89	13	1.1	100
IW-18	IW-18	590-18585-1	9/8/2022	44,000	--	--	--	--	--	--	--	--	--
		590-19667-1	1/19/2023	--	2,600	--	--	--	--	--	--	--	--
		590-22377-1	11/28/2023	--	--	420	--	0.75	4.8	4.9	1.9	1.0 U	6.8

**Table 7
Groundwater Analytical Results
Former Tiger Oil Site
Yakima, Washington**

Sample Location	Field Sample ID	Laboratory SDG	Sample Date	Analytical Method, Analyte, Unit of Measurement, Sampling Event										
				NWTPH-Gx			SW-846 6010D	SW-846 8260D						
				Gasoline Range Organics µg/L			Lead	Benzene	Ethylbenzene	m-&p-Xylenes	o-Xylene	Toluene	Xylenes, Total	
				Pre-Injection Baseline Sampling (a)	Post-Injection 1 (b)	Post-Injection 2 (c)	mg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	
N1MW-6R	MW-6R	590-18585-1	9/8/2022	5,900	--	--	--	--	--	--	--	--	--	--
	NMW-6R	590-19667-1	1/19/2023	--	2,200	--	--	--	--	--	--	--	--	--
	MW-6R	590-22377-1	11/29/2023	--	--	3,700	--	1.1	140	280	25	1.2	300	--
N1MW-7R	MW-7R	590-18585-1	9/8/2022	1,900	--	--	--	--	--	--	--	--	--	--
	NMW-7R	590-19667-1	1/18/2023	--	690	--	--	--	--	--	--	--	--	--
	MW-7R	590-22377-1	11/28/2023	--	--	1,200	--	1.7	40	74	66	38	140	--
N1MW-8	MW-8	590-18585-1	9/7/2022	2,400	--	--	--	--	--	--	--	--	--	--
	NMW-8	590-19667-1	1/18/2023	--	230	--	--	--	--	--	--	--	--	--
	MW-8	590-22377-1	11/29/2023	--	--	430	--	1.1 J	1.4 J	2.0 UJ	1.0 UJ	1.0 UJ	3.0 UJ	--
N1MW-9	MW-1R	590-18585-1	9/8/2022	2,300	--	--	--	--	--	--	--	--	--	--
	NMW-9	590-19667-1	1/19/2023	--	1,400	--	--	--	--	--	--	--	--	--
	MW-9	590-22377-1	11/29/2023	--	--	1,500	--	1.1	94	340	130	33	460	--
MTCA Method A Cleanup Level				800/1,000 (d)			0.015	5	700	NL	NL	1,000	1,000	

Notes:

- Bold** text indicates detected analyte.
- Green shading indicates detected exceedance of associated screening level.
- = Not analyzed
- U = The analyte was analyzed for, but was not detected above the level of the reported sample quantitation limit.
- J = The result is an estimated quantity. The associated numerical value is the approximate concentration of the analyte in the sample.
- UJ = The analyte was analyzed for but was not detected. The reported quantitation limit is approximate and may be inaccurate or imprecise.
- (a) Pre-injection baseline groundwater sampling took place on September 7 and 8, 2022 after injection wells were installed and developed prior to any injections occurring at the Site.
- (b) Samples collected on January 18 and 19, 2023 were collected following the 1st ISCO injection at the site which occurred October 11-19, 2023.
- (c) Samples collected on November 28 and 29, 2023 were collected following the 2nd ISCO injection at the site which occurred July 10-13, 2023.
- (d) MTCA Method A cleanup level is 1000 µg/L if benzene is not present in groundwater and 800 µg/L if benzene is present in groundwater.

Acronyms/Abbreviations:

- µg/L = micrograms per liter
- mg/L = milligrams per liter
- NL = not listed

Table 8
Groundwater Injection Summary
Former Tiger Oil Site
Yakima, Washington

Injection Well ID	Volume Injected (gal)											
	Injection 1 (10/11/22 - 10/19/22)			Injection 2 (7/10/23 - 7/13/23)			Injection 3 (9/9/24 - 9/13/24)			Totals		
	Design Volume	Volume Injected	Percent of Design Volume (%)	Design Volume	Volume Injected	Percent of Design Volume (%)	Design Volume	Volume Injected	Percent of Design Volume (%)	Design Volume	Volume Injected	Percent of Total Design Volume
IW-1	2,500	1,114	45%	NA	1,805	NA	NA	NA	NA	2,500	2,919	117%
IW-2	2,500	3,196	128%	2,500	2,988	120%	NA	NA	NA	5,000	6,184	124%
IW-3	2,500	2,147	86%	NA	0	NA	2,500	2,452	98%	5,000	4,599	92%
IW-4	2,500	3,215	129%	2,500	3,453	138%	2,500	2,430	97%	7,500	9,098	121%
IW-5	2,500	3,135	125%	2,500	2,661	106%	2,500	NA		7,500	5,796	77%
IW-6	2,500	3,770	151%	NA	0	NA	2,500	2,735	109%	5,000	6,506	130%
IW-7	2,500	3,214	129%	NA	0	NA	2,500	2,759	110%	5,000	5,972	119%
IW-8	2,500	1,319	53%	NA	626	NA	2,500	2,549	102%	5,000	4,494	90%
IW-9	2,500	3,182	127%	2,500	2,805	112%	NA	NA	NA	5,000	5,986	120%
IW-10	2,500	2,505	100%	2,500	1,554	62%	2,500	2,333	93%	7,500	6,393	85%
IW-11	2,500	3,386	135%	2,500	2,736	109%	NA	NA	NA	5,000	6,122	122%
IW-12	2,500	780	31%	2,500	1,967	79%	NA	NA	NA	5,000	2,747	55%
IW-13	2,500	2,559	102%	2,500	2,712	108%	NA	NA	NA	5,000	5,271	105%
IW-14	2,500	886	35%	2,500	1,335	53%	NA	NA	NA	5,000	2,221	44%
IW-15	2,500	3,174	127%	NA	0	NA	2,500	2,709	108%	5,000	5,883	118%
IW-16	2,500	3,344	134%	NA	0	NA	2,500	2,581	103%	5,000	5,925	119%
IW-17	2,500	972	39%	NA	0	NA	2,500	2,355	94%	5,000	3,327	67%
IW-18	2,500	3,511	140%	2,500	390	16%	2,500	2,440	98%	7,500	6,341	85%
Totals:	45,000	45,410		25,000	25,032		27,500	25,343		97,500	95,785	

Notes:

NA = Injection well either not included in given injection design or not injected into during given injection.

Supplemental Investigation Boring Logs

Soil Classification System

	MAJOR DIVISIONS	CLEAN GRAVEL (Little or no fines)	GRAPHIC SYMBOL	USCS LETTER SYMBOL ⁽¹⁾	TYPICAL DESCRIPTIONS ⁽²⁾⁽³⁾
COARSE-GRAINED SOIL (More than 50% of material is larger than No. 200 sieve size)	GRAVEL AND GRAVELLY SOIL (More than 50% of coarse fraction retained on No. 4 sieve)	CLEAN GRAVEL (Little or no fines)		GW	Well-graded gravel; gravel/sand mixture(s); little or no fines
		GRAVEL WITH FINES (Appreciable amount of fines)		GP	Poorly graded gravel; gravel/sand mixture(s); little or no fines
	SAND AND SANDY SOIL (More than 50% of coarse fraction passed through No. 4 sieve)	CLEAN SAND (Little or no fines)		GM	Silty gravel; gravel/sand/silt mixture(s)
			GRAVEL WITH FINES (Appreciable amount of fines)		GC
		SAND WITH FINES (Appreciable amount of fines)		SW	Well-graded sand; gravelly sand; little or no fines
				SP	Poorly graded sand; gravelly sand; little or no fines
FINE-GRAINED SOIL (More than 50% of material is smaller than No. 200 sieve size)	SILT AND CLAY (Liquid limit less than 50)		ML	Inorganic silt and very fine sand; rock flour; silty or clayey fine sand or clayey silt with slight plasticity	
			CL	Inorganic clay of low to medium plasticity; gravelly clay; sandy clay; silty clay; lean clay	
			OL	Organic silt; organic, silty clay of low plasticity	
	SILT AND CLAY (Liquid limit greater than 50)		MH	Inorganic silt; micaceous or diatomaceous fine sand	
			CH	Inorganic clay of high plasticity; fat clay	
			OH	Organic clay of medium to high plasticity; organic silt	
	HIGHLY ORGANIC SOIL		PT	Peat; humus; swamp soil with high organic content	

OTHER MATERIALS	GRAPHIC SYMBOL	LETTER SYMBOL	TYPICAL DESCRIPTIONS
PAVEMENT		AC or PC	Asphalt concrete pavement or Portland cement pavement
ROCK		RK	Rock (See Rock Classification)
WOOD		WD	Wood, lumber, wood chips
DEBRIS		DB	Construction debris, garbage


- Notes:
- USCS letter symbols correspond to symbols used by the Unified Soil Classification System and ASTM classification methods. Dual letter symbols (e.g., SP-SM for sand or gravel) indicate soil with an estimated 5-15% fines. Multiple letter symbols (e.g., ML/CL) indicate borderline or multiple soil classifications.
 - Soil descriptions are based on the general approach presented in the Standard Practice for Description and Identification of Soils (Visual-Manual Procedure), outlined in ASTM D 2488. Where laboratory index testing has been conducted, soil classifications are based on the Standard Test Method for Classification of Soils for Engineering Purposes, as outlined in ASTM D 2487.
 - Soil description terminology is based on visual estimates (in the absence of laboratory test data) of the percentages of each soil type and is defined as follows:
 - Primary Constituent: > 50% - "GRAVEL," "SAND," "SILT," "CLAY," etc.
 - Secondary Constituents: > 30% and < 50% - "very gravelly," "very sandy," "very silty," etc.
 - > 15% and < 30% - "gravelly," "sandy," "silty," etc.
 - Additional Constituents: > 5% and < 15% - "with gravel," "with sand," "with silt," etc.
 - < 5% - "with trace gravel," "with trace sand," "with trace silt," etc., or not noted.
 - Soil density or consistency descriptions are based on judgement using a combination of sampler penetration blow counts, drilling or excavating conditions, field tests, and laboratory tests, as appropriate.

Drilling and Sampling Key		Field and Lab Test Data
SAMPLER TYPE	SAMPLE NUMBER & INTERVAL	
Code	Description	Code
a	3.25-inch O.D., 2.42-inch I.D. Split Spoon	PP = 1.0
b	2.00-inch O.D., 1.50-inch I.D. Split Spoon	TV = 0.5
c	Shelby Tube	PID = 100
d	Grab Sample	W = 10
e	Single-Tube Core Barrel	D = 120
f	Double-Tube Core Barrel	-200 = 60
g	2.50-inch O.D., 2.00-inch I.D. WSDOT	GS
h	3.00-inch O.D., 2.375-inch I.D. Mod. California	AL
i	Other - See text if applicable	GT
1	300-lb Hammer, 30-inch Drop	CA
2	140-lb Hammer, 30-inch Drop	
3	Pushed	
4	Vibrocore (Rotasonic/Geoprobe)	
5	Other - See text if applicable	

Groundwater

Approximate water level at time of drilling (ATD)
 Approximate water level at time after drilling/excavation/well


HSB-1



- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

HSB-2




Boring Completed 10/05/21
Total Depth of Boring = 20.0 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

HSB-3



Boring Completed 10/06/21
Total Depth of Boring = 19.5 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

HSB-4

SAMPLE DATA

SOIL PROFILE

GROUNDWATER

Depth (ft)	Sample Number & Interval	Sampler Type	Blows/Foot	Test Data	Graphic Symbol	USCS Symbol	Soil Profile	Water Level
0							Drilling Method: <u>Hollow-Stem Auger</u> Ground Elevation (ft): _____	
					GM SM		Gravel Brown, silty, fine SAND with cobbles (no odor, no sheen) (loose to medium dense, damp) (FILL)	
5		a1	14	0.0				
	HSB-4-7-8-100621	a1	50	0.0		SP- SM	Brown, fine to medium SAND with silt and cobbles (no odor, no sheen) (dense, dry) Soil Sample: HSB-4-7-8-100621	
10		a1	50/6	0.0				
	HSB-4-11-12-100621	a1	50/6	0.0			Soil Sample: HSB-4-11-12-100621	
		a1	50/6	0.0				
		a1	50/6	0.0		SP- SM	Brown, gravelly, medium to coarse SAND with silt (no odor, no sheen) (dense, wet)	
15		a1	60	0.0				▽ ATD

Boring Completed 10/06/21
Total Depth of Boring = 17.0 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ SOIL BORING LOG

HSB-5

SAMPLE DATA

SOIL PROFILE

GROUNDWATER


Depth (ft)	Sample Number & Interval	Sampler Type	Blows/Foot	Test Data	Graphic Symbol	USCS Symbol	Drilling Method: <u>Hollow-Stem Auger</u>	Water Level
							Ground Elevation (ft): _____	
0					GM		Coarse gravel	
0.0					SM		Brown, silty, fine to medium SAND (no odor, no sheen) (loose, damp) (FILL)	
0.5	a1	a1	4	0.0				
1.0	a1	a1	6	0.0				
1.5	a1	a1	4	0.0				
2.0	a1	a1	4	0.0				
7.5-9.0	HSB-5-7.5-9-100621		50/6	0.0	SP-SM		- with gravel Brown to gray, medium SAND with silt and cobbles (no odor, no sheen) (dense, dry) Soil Sample: HSB-5-7.5-9-100621	
9.0	a1	a1	50/6	0.0				
10.0	a1	a1	50/4	0.0				
13.5-14.5	HSB-5-13.5-14.5-100621		57	0.0	SW		Brown to light brown, gravelly, medium to coarse SAND with trace silt (no odor, no sheen) (dense, dry) Soil Sample: HSB-5-13.5-14.5-100621	
14.5	a1	a1	50/0	0.0				
15.0								▽ ATD
16.5	a1	a1	60	0.0				

Boring Completed 10/06/21
Total Depth of Boring = 16.5 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ SOIL BORING LOG

NIMW-6R




Boring Completed 10/04/21
Total Depth of Boring = 20.5 ft

Monitoring Well Completed 10/04/21
Total Depth of Monitoring Well = 20.0 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

NIMW-7R




Boring Completed 10/04/21
Total Depth of Boring = 20.5 ft

Monitoring Well Completed 10/04/21
Total Depth of Monitoring Well = 20.0 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

NIMW-9



Boring Completed 10/05/21
Total Depth of Boring = 20.5 ft

Monitoring Well Completed 10/05/21
Total Depth of Monitoring Well = 20.0 ft

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01 1/4/22 N:\PROJECTS\1148010.010.GPJ WELL LOG

Injection Well Boring Logs

Soil Classification System


	MAJOR DIVISIONS	CLEAN GRAVEL (Little or no fines)	GRAPHIC SYMBOL	LETTER SYMBOL ⁽¹⁾	TYPICAL DESCRIPTIONS ⁽²⁾⁽³⁾
COARSE-GRAINED SOIL (More than 50% of material is larger than No. 200 sieve size)	GRAVEL AND GRAVELLY SOIL (More than 50% of coarse fraction retained on No. 4 sieve)	CLEAN GRAVEL (Little or no fines)		GW	Well-graded gravel; gravel/sand mixture(s); little or no fines
		GRAVEL WITH FINES (Appreciable amount of fines)		GP	Poorly graded gravel; gravel/sand mixture(s); little or no fines
		GRAVEL WITH FINES (Appreciable amount of fines)		GM	Silty gravel; gravel/sand/silt mixture(s)
	SAND AND SANDY SOIL (More than 50% of coarse fraction passed through No. 4 sieve)	CLEAN SAND (Little or no fines)		SW	Well-graded sand; gravelly sand; little or no fines
		CLEAN SAND (Little or no fines)		SP	Poorly graded sand; gravelly sand; little or no fines
		SAND WITH FINES (Appreciable amount of fines)		SM	Silty sand; sand/silt mixture(s)
FINE-GRAINED SOIL (More than 50% of material is smaller than No. 200 sieve size)	SILT AND CLAY (Liquid limit less than 50)	CLEAN SAND (Little or no fines)		SC	Clayey sand; sand/clay mixture(s)
		SILT AND CLAY (Liquid limit less than 50)		ML	Inorganic silt and very fine sand; rock flour; silty or clayey fine sand or clayey silt with low plasticity
		SILT AND CLAY (Liquid limit less than 50)		CL	Inorganic clay of low to medium plasticity; gravelly clay; sandy clay; silty clay; lean clay
	SILT AND CLAY (Liquid limit greater than 50)	SILT AND CLAY (Liquid limit greater than 50)		OL	Organic silt; organic, silty clay of low plasticity
		SILT AND CLAY (Liquid limit greater than 50)		MH	Inorganic silt; micaceous or diatomaceous fine sand; elastic silt
		SILT AND CLAY (Liquid limit greater than 50)		CH	Inorganic clay of high plasticity; fat clay
	HIGHLY ORGANIC SOIL		OH	Organic clay of medium to high plasticity; organic silt	
	HIGHLY ORGANIC SOIL		PT	Peat; humus; swamp soil with high organic content	

OTHER MATERIALS	GRAPHIC SYMBOL	LETTER SYMBOL	TYPICAL DESCRIPTIONS
PAVEMENT		AC or PC	Asphalt concrete pavement or Portland cement pavement
ROCK		RK	Rock (See Rock Classification)
WOOD		WD	Wood, lumber, wood chips
DEBRIS		DB	Construction debris, garbage

- Notes:
- USCS letter symbols correspond to symbols used by the Unified Soil Classification System and ASTM classification methods. Dual letter symbols (e.g., SP-SM for sand or gravel) indicate soil with an estimated 5-15% fines. Multiple letter symbols (e.g., ML/CL) indicate borderline or multiple soil classifications.
 - Soil descriptions are based on the general approach presented in the Standard Practice for Description and Identification of Soils (Visual-Manual Procedure), outlined in ASTM D 2488. Where laboratory index testing has been conducted, soil classifications are based on the Standard Test Method for Classification of Soils for Engineering Purposes, as outlined in ASTM D 2487.
 - Soil description terminology is based on visual estimates (in the absence of laboratory test data) of the percentages of each soil type and is defined as follows:
 - Primary Constituent: > 50% - "GRAVEL," "SAND," "SILT," "CLAY," etc.
 - Secondary Constituents: > 30% and < 50% - "very gravelly," "very sandy," "very silty," etc.
 - > 15% and < 30% - "gravelly," "sandy," "silty," etc.
 - Additional Constituents: > 5% and < 15% - "with gravel," "with sand," "with silt," etc.
 - < 5% - "with trace gravel," "with trace sand," "with trace silt," etc., or not noted.
 - Soil density or consistency descriptions are based on judgement using a combination of sampler penetration blow counts, drilling or excavating conditions, field tests, and laboratory tests, as appropriate.

Drilling and Sampling Key		Field and Lab Test Data																																																																																
SAMPLER TYPE & METHOD	SAMPLE NUMBER & INTERVAL																																																																																	
<table style="width: 100%;"> <tr> <th style="width: 10%;">Graphic</th> <th style="width: 10%;">Code</th> <th style="width: 80%;">Description</th> </tr> <tr> <td></td> <td>a</td> <td>3.25-in OD, 2.42-in ID Split Spoon</td> </tr> <tr> <td></td> <td>b</td> <td>2.00-in OD, 1.50-in ID Split Spoon</td> </tr> <tr> <td></td> <td>c</td> <td>Thin-Wall Sampler (aka Shelby Tube)</td> </tr> <tr> <td></td> <td>d</td> <td>Grab Sample</td> </tr> <tr> <td></td> <td>e</td> <td>Single-Tube Core Barrel</td> </tr> <tr> <td></td> <td>f</td> <td>Double-Tube Core Barrel</td> </tr> <tr> <td></td> <td>g</td> <td>2.50-in OD, 2.00-in ID WSDOT</td> </tr> <tr> <td></td> <td>h</td> <td>3.00-in OD, 2.37-in ID Mod. Calif.</td> </tr> <tr> <td></td> <td>i</td> <td>Other - See text if applicable</td> </tr> <tr> <td></td> <td>1</td> <td>300-lb Hammer, 30-inch Drop</td> </tr> <tr> <td></td> <td>2</td> <td>140-lb Hammer, 30-inch Drop</td> </tr> <tr> <td></td> <td>3</td> <td>Direct Push</td> </tr> <tr> <td></td> <td>4</td> <td>Vibrocore</td> </tr> <tr> <td></td> <td>5</td> <td>Other - See text if applicable</td> </tr> <tr> <td></td> <td>6</td> <td>Piston Extraction</td> </tr> </table>	Graphic	Code	Description		a	3.25-in OD, 2.42-in ID Split Spoon		b	2.00-in OD, 1.50-in ID Split Spoon		c	Thin-Wall Sampler (aka Shelby Tube)		d	Grab Sample		e	Single-Tube Core Barrel		f	Double-Tube Core Barrel		g	2.50-in OD, 2.00-in ID WSDOT		h	3.00-in OD, 2.37-in ID Mod. Calif.		i	Other - See text if applicable		1	300-lb Hammer, 30-inch Drop		2	140-lb Hammer, 30-inch Drop		3	Direct Push		4	Vibrocore		5	Other - See text if applicable		6	Piston Extraction	<div style="text-align: center;"> </div> <div style="text-align: center; border: 1px solid black; padding: 5px;"> <p>Groundwater</p> <p> Approximate water level at time of drilling (ATD)</p> <p> Approximate water level at time after drilling/excavation/well</p> </div>	<table style="width: 100%;"> <tr> <th style="width: 30%;">Code</th> <th style="width: 70%;">Description</th> </tr> <tr> <td>WOR</td> <td>Weight of Rod</td> </tr> <tr> <td>WOH</td> <td>Weight of Hammer</td> </tr> <tr> <td>PP = 1.0</td> <td>Pocket Penetrometer, tsf</td> </tr> <tr> <td>TV = 0.5</td> <td>Torvane, tsf</td> </tr> <tr> <td>PID = 100</td> <td>Photoionization Detector VOC screening, ppm</td> </tr> <tr> <td>W = 10</td> <td>Moisture Content, %</td> </tr> <tr> <td>D = 120</td> <td>Dry Density, pcf</td> </tr> <tr> <td>-200 = 60</td> <td>Material smaller than No. 200 sieve, %</td> </tr> <tr> <td>GS</td> <td>Grain Size - See separate figure for data</td> </tr> <tr> <td>AL</td> <td>Atterberg Limits - See separate figure for data</td> </tr> <tr> <td>UU</td> <td>Triaxial Unconsolidated Undrained (UU) Strength</td> </tr> <tr> <td>CU</td> <td>Triaxial Consolidated Undrained (CU) Strength</td> </tr> <tr> <td>Consol</td> <td>1-D Consolidation Test</td> </tr> <tr> <td>Perm</td> <td>Permeability Test</td> </tr> <tr> <td>CA</td> <td>Chemical Analysis</td> </tr> </table>	Code	Description	WOR	Weight of Rod	WOH	Weight of Hammer	PP = 1.0	Pocket Penetrometer, tsf	TV = 0.5	Torvane, tsf	PID = 100	Photoionization Detector VOC screening, ppm	W = 10	Moisture Content, %	D = 120	Dry Density, pcf	-200 = 60	Material smaller than No. 200 sieve, %	GS	Grain Size - See separate figure for data	AL	Atterberg Limits - See separate figure for data	UU	Triaxial Unconsolidated Undrained (UU) Strength	CU	Triaxial Consolidated Undrained (CU) Strength	Consol	1-D Consolidation Test	Perm	Permeability Test	CA	Chemical Analysis
Graphic	Code	Description																																																																																
	a	3.25-in OD, 2.42-in ID Split Spoon																																																																																
	b	2.00-in OD, 1.50-in ID Split Spoon																																																																																
	c	Thin-Wall Sampler (aka Shelby Tube)																																																																																
	d	Grab Sample																																																																																
	e	Single-Tube Core Barrel																																																																																
	f	Double-Tube Core Barrel																																																																																
	g	2.50-in OD, 2.00-in ID WSDOT																																																																																
	h	3.00-in OD, 2.37-in ID Mod. Calif.																																																																																
	i	Other - See text if applicable																																																																																
	1	300-lb Hammer, 30-inch Drop																																																																																
	2	140-lb Hammer, 30-inch Drop																																																																																
	3	Direct Push																																																																																
	4	Vibrocore																																																																																
	5	Other - See text if applicable																																																																																
	6	Piston Extraction																																																																																
Code	Description																																																																																	
WOR	Weight of Rod																																																																																	
WOH	Weight of Hammer																																																																																	
PP = 1.0	Pocket Penetrometer, tsf																																																																																	
TV = 0.5	Torvane, tsf																																																																																	
PID = 100	Photoionization Detector VOC screening, ppm																																																																																	
W = 10	Moisture Content, %																																																																																	
D = 120	Dry Density, pcf																																																																																	
-200 = 60	Material smaller than No. 200 sieve, %																																																																																	
GS	Grain Size - See separate figure for data																																																																																	
AL	Atterberg Limits - See separate figure for data																																																																																	
UU	Triaxial Unconsolidated Undrained (UU) Strength																																																																																	
CU	Triaxial Consolidated Undrained (CU) Strength																																																																																	
Consol	1-D Consolidation Test																																																																																	
Perm	Permeability Test																																																																																	
CA	Chemical Analysis																																																																																	

IW-1




Boring Completed 08/01/22
Total Depth of Boring = 20.9 ft.

Injection Well Completed 08/01/22
Total Depth of Injection Well = 20.9 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-2




Boring Completed 08/01/22
Total Depth of Boring = 20.8 ft.

Injection Well Completed 08/01/22
Total Depth of Injection Well = 20.8 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-3



Boring Completed 08/01/22
Total Depth of Boring = 20.4 ft.

Injection Well Completed 08/01/22
Total Depth of Injection Well = 20.4 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG



Tiger Oil
Yakima, WA

Log of Injection Well IW-3


Figure
B-4

IW-4

SAMPLE DATA

SOIL PROFILE

GROUNDWATER




Boring Completed 08/02/22
 Total Depth of Boring = 20.4 ft.

Injection Well Completed 08/02/22
 Total Depth of Injection Well = 20.4 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-5



Boring Completed 08/02/22
Total Depth of Boring = 20.7 ft.

Injection Well Completed 08/02/22
Total Depth of Injection Well = 20.7 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-5

Figure
B-6

IW-6




Boring Completed 08/02/22
Total Depth of Boring = 20.0 ft.

Injection Well Completed 08/02/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-7




Boring Completed 08/02/22
Total Depth of Boring = 20.6 ft.

Injection Well Completed 08/03/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-8




Boring Completed 08/31/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/31/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-9



Boring Completed 08/29/22
Total Depth of Boring = 21.0 ft.

Injection Well Completed 08/29/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24_N:\PROJECTS\1148010.GPJ_WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-9

Figure
B-10

IW-10



Boring Completed 08/29/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/29/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-10

Figure
B-11

IW-11



Boring Completed 08/29/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/29/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-11

Figure
B-12

IW-12




Boring Completed 08/30/22
Total Depth of Boring = 20.0 ft.

Injection Well Completed 08/30/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-13



Boring Completed 08/30/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/30/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-13

Figure
B-14

IW-14




Boring Completed 08/30/22
Total Depth of Boring = 21.0 ft.

Injection Well Completed 08/30/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-15




Boring Completed 08/31/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/31/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-16




Boring Completed 08/31/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 08/31/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG

IW-17



Boring Completed 09/01/22
Total Depth of Boring = 18.5 ft.

Injection Well Completed 09/01/22
Total Depth of Injection Well = 18.5 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG




Tiger Oil
Yakima, WA

Log of Injection Well IW-17

Figure
B-18

IW-18



Boring Completed 09/01/22
Total Depth of Boring = 20.5 ft.

Injection Well Completed 09/02/22
Total Depth of Injection Well = 20.0 ft.

- Notes:
1. Stratigraphic contacts are based on field interpretations and are approximate.
 2. Reference to the text of this report is necessary for a proper understanding of subsurface conditions.
 3. Refer to "Soil Classification System and Key" figure for explanation of graphics and symbols.

1148010.01_10/28/24 N:\PROJECTS\1148010.GPJ WELL LOG



Tiger Oil
Yakima, WA

Log of Injection Well IW-18

Figure
B-19