

**Monitoring Well Installation
Technical Memorandum**

Everett Smelter Cleanup Site
FSID 2744, ISIS Cleanup Site ID 4298

Lowland Area
Everett, Washington

for
Washington State Department of Ecology

May 20, 2013



**Monitoring Well Installation
Technical Memorandum
Everett Smelter Cleanup Site
FSID 2744, ISIS Cleanup Site ID 4298
Lowland Area
Everett, Washington
Project No. 0504-068-00
May 15, 2013**

Prepared for:

Washington State Department of Ecology
Toxics Cleanup Program
3190 160th Avenue SE
Bellevue, Washington 98008-5452


Attention: Sandra Matthews and David South

Prepared by:


GeoEngineers, Inc.
Plaza 600 Building
600 Stewart Street, Suite 1700
Seattle, Washington 98101
206.728.2674



John M. Herzog, PhD
Principal



Garrett R. Leque, LG
Geologist



Iain H. Wingard
Associate

GRL:IHW:JMH:cn

Disclaimer: Any electronic form, facsimile or hard copy of the original document (email, text, table, and/or figure), if provided, and any attachments are only a copy of the original document. The original document is stored by GeoEngineers, Inc. and will serve as the official document of record.

Copyright© 2013 by GeoEngineers, Inc. All rights reserved.

Table of Contents

1.0 INTRODUCTION	1
1.1. Site History and Background.....	1
2.0 FIELD INVESTIGATION	2
2.1. Monitoring Well and Soil Boring Installation	2
2.2. Monitoring Well Development.....	4
2.3. Decontamination.....	4
2.4. Disposal of Investigation-Derived Materials.....	4
2.5. Deviations From the SAP.....	5
3.0 RESULTS.....	5
3.1. Observed Stratigraphy and Subsurface Conditions.....	5
3.2. Data Validation.....	6
3.3. Soil Analytical Results.....	6
4.0 LIMITATIONS	7
5.0 REFERENCES	8

LIST OF FIGURES

Figure 1. Vicinity Map

Figure 2. Lowland Area

Figure 3. Lowland Area Investigation Locations

Figure 4. Boring/Monitoring Well Locations: Soil Results – Arsenic

Figure 5. Boring/Monitoring Well Locations: Soil Results – Lead

LIST OF TABLES

Table 1. Summary of Monitoring Well and Soil Boring Construction Information

Table 2. Chemical Analytical Results – Soil

Table 3. Soil Total Organic Carbon

Table 4. Samples Submitted for Grain Size Analysis

APPENDICES

Appendix A. Boring and Monitoring Well Construction Logs

Appendix B. Survey Data

Appendix C. Data Quality Assessment Report

Appendix D. Laboratory Deliverables (on attached CD)

Appendix E. Results of Grain Size Analyses

Appendix F. Report Limitations and Guidelines for Use

1.0 INTRODUCTION

This memorandum summarizes field investigation activities completed at the Everett Smelter Lowland Area. The Lowland Area is a part of the Everett Smelter Cleanup Site and generally located in northeast Everett, Washington (Figure 1). The Lowland Area includes multiple parcels and the rights-of-way adjacent to the parcels as shown in Figure 2.

The purpose of the Lowland Area study is to characterize metals concentrations in soil and groundwater within and near the Lowland Area in order to evaluate potential environmental impacts from the historical smelter activities. Soil boring, soil sampling and analysis and monitoring well installation were performed in December 2012 and January 2013. A total of 54 monitoring wells and three soil borings were installed to characterize metals concentrations in soil throughout the Lowland Area. The activities were completed in general accordance with the Washington State Department of Ecology (Ecology)-approved Final Sampling and Analysis Plan (SAP), Quality Assurance Project Plan (QAPP) and Health and Safety Plan (HASP) for the project dated August 31, 2012.

The purpose of this technical memorandum is to describe field activities completed as part of the investigation of the Lowland Area and summarize the resulting data. The results of this and future field activities will be used to develop a preliminary Feasibility Study so that a Cleanup Action Plan can be developed for the Lowland Area that is protective of human health and the environment.

1.1. Site History and Background

The Everett Smelter Lowland Area is part of the Everett Smelter Cleanup Site. The Everett Smelter Cleanup Site has been divided into an Upland Area and Lowland Area. Historically, a smelter was located in the Upland Area, west of the Lowland Area. Beginning in the 1890s, the smelter produced lead, copper, gold and silver from ore. An arsenic extraction plant was added in 1901. The entire smelter was shut down by 1912 and dismantled by 1915.

The historic smelting activities resulted in the release of metals including arsenic and lead to the soil, groundwater and air. The arsenic extraction plant where arsenic trioxide was produced was demolished. However, arsenic trioxide remained on site in the former plant area. This portion of the Everett Smelter Cleanup Site has been referred to as the former arsenic trioxide processing area and as the fenced area.¹ This area underwent environmental cleanup in approximately 2004 through 2006 to remove and consolidate soil that had been contaminated by smelter operations.

Historically, slag waste from former smelter activities was poured down the bluff located on the east side of the Upland portion of the Everett Smelter Site and onto an adjacent property, currently known as the Benson Property. Slag present on the Benson Property was historically used for the manufacture of "rock wool". Additionally, slag was excavated from the Benson Property and

¹ The former arsenic trioxide processing area has sufficiently high contamination that it was purchased by Asarco soon after the Site was rediscovered, the homes vacated, and the area fenced off.

transported for use on and off site. Although slag was historically reused, not all of it was removed. Slag still remains on the Benson Property and potentially in other parts of the Lowland Area.

Air emissions from the former smelter stacks are likely to have deposited of particulates containing metals onto the historic land surface surrounding the Smelter Site. The extent of contamination from the smelter has been characterized in the Upland portion of the Everett Smelter Cleanup Site and is currently under remedial action. The extent of contamination in the Lowland portion of the Site is being investigated to evaluate potential environmental impacts from historical smelter activities.

Multiple soil and groundwater investigations have been performed in the Lowland Area since the 1990s related to the Everett Smelter contamination. Groundwater monitoring in the late 1990s identified metals-contaminated groundwater east of the former smelter in the Lowland Area. In 2011 and 2012, GeoEngineers installed 20 wells (in ten well pairs - "shallow" and "deep" wells BP-01S/D through BP-10S/D) along the eastern portion of the Benson Property and collected soil and groundwater samples from the borings/wells. Additionally, GeoEngineers collected groundwater samples from three existing wells (EV-20B and EV-22A/B). Soil and groundwater samples were analyzed for arsenic, lead, cadmium, mercury, antimony and thallium. Results indicated soil and groundwater contain elevated metals concentrations (predominantly arsenic and lead). Of note, the metals concentrations in groundwater identified in the late 1990s were similar to the metals concentrations detected in 2012.

2.0 FIELD INVESTIGATION

2.1. Monitoring Well and Soil Boring Installation

Investigation activities included installation of 54 groundwater monitoring wells (23 "shallow" wells, 30 "deep" wells and one "deeper deep" well) throughout the Lowland Area using hollow-stem auger (HSA) drill rigs. Forty six of the monitoring wells were installed in shallow/deep well pairs at twenty three locations as shown on Figure 3. Seven of the wells were installed as deep wells, either adjacent to existing shallow wells or where shallow groundwater was not encountered. One deeper, deep well (BP-05D2) was installed adjacent to an existing shallow/deep well pair (BP-05S/D) on the Benson Property to further characterize the vertical extent of metals in soil and groundwater. The shallow and deep wells in each pair are spaced approximately 4 to 5 feet apart. Soil samples were collected from each deep well boring completed during the monitoring well installation activities.

The investigation locations were selected to characterize metals concentrations in soil and groundwater throughout the Lowland Area. The monitoring well installations were completed between December 4, 2012 and January 24, 2013. The horizontal coordinates and vertical elevations of each well were surveyed after well installation was completed.

In general accordance with the objectives of the SAP, shallow wells were installed in what previous investigations of the Everett Smelter Area characterize as the "shallow aquifer." The top of the well screens were installed at depths ranging from 3.5 feet to 8 feet below ground surface (bgs) and the bottom of the well screens were installed at depths ranging from 6 to 18 feet bgs. The only exception to this is well LLMW-23S, which was installed on top of a dike along the Snohomish River

at a higher surface elevation than the surrounding Lowland Area and was screened from 14 to 24 feet bgs. The bottom of the shallow well screens within the Lowland Area were installed approximately 1 foot above the historic native surface of the silt/channel deposits, where encountered. Shallow wells installed within the Upland Area along Marine View Drive were typically installed at or just above the top of the Vashon Till unit (described below in Section 3.0) with the exception of LLMW-27S, which was installed between 31 and 36 feet bgs at a potential water bearing zone within the Vashon Till unit. Shallow wells were installed with screen lengths ranging from 2.5 to 10 feet.

Deep wells were installed in what previous investigations of the Everett Smelter Area characterize as the “deep aquifer.” The top of the well screens within the Lowland Area were installed at depths ranging from 11 to 30 feet bgs and the bottom of the well screens were installed at depths ranging from 21 feet to 40 feet bgs. The deep wells installed in the Upland Area had top of screen depths ranging from 35 to 63.5 feet bgs and the bottom of the screens were installed between approximately 45 to 73.5 feet bgs. All of the deep well screens were ten feet in length. The deep well screens were installed with a minimum 1-foot separation between the bottom of the silt/channel deposits or Vashon Till unit and the top of the well screens.

The deeper deep well BP-05D2 was installed with a 5-foot-long screen set from 67 feet to 72 feet bgs.

Three soil borings were completed using direct-push technologies at the locations shown on Figure 3. These borings were each completed to 20 feet bgs on January 7, 2013.

All borings were logged by qualified geologists and the wells were installed by licensed drillers in general accordance with Washington Administrative Code (WAC) 173-160. Wells were constructed of 2-inch-diameter PVC with either flush mount or stick-up monuments. Wells with stick-up monuments have steel bollards set in concrete around the wells for protection. Boring and monitoring well construction logs are provided in Appendix A. Each monitoring well and boring location was surveyed by a certified land survey company, David Evans and Associates. A summary of monitoring well and soil boring construction information is provided in Table 1. The survey data and surveyor’s field notes are provided in Appendix B.

Continuous soil samples were collected from each boring advanced to install the deep wells using a split-spoon sampler (i.e., Standard Penetration Test sampler or “California spoon” sampler). Soil samples were only collected from the deep well borings at locations where the deep well borings were co-located with a shallow well boring. Well construction details for the shallow wells were based on observations of soil in the adjacent deep well. Field screening was completed as described in the Ecology-approved SAP (GeoEngineers, 2012), and at least one soil sample was collected from each deep well in each of the following four soil horizons:

- Fill comprising the shallow aquifer;
- Historic native surface (i.e., the top of the native silt deposits or till);
- From deeper within the native deposits; and

- Soil from within the deep aquifer (alluvium or advance outwash) that was within the elevation where the well screen was installed.

Soil samples were collected, logged on a chain-of-custody form in general accordance with the QAPP, placed in laboratory-supplied jars and stored in coolers on ice for transport and delivery to the analytical laboratory. A total of 151 samples were analyzed for metals including antimony, arsenic, cadmium, lead, mercury, and thallium by Environmental Protection Agency (EPA) Methods 6010/200.8/7470.

Chemical analysis of the soil samples was completed by Analytical Resources, Inc. (ARI) in Tukwila, Washington.

2.2. Monitoring Well Development

The monitoring wells were developed in December 2012 and January 2013. Well development was completed to remove water that may have been introduced into the well during drilling, stabilize the filter pack and formation materials surrounding the well screen and restore the hydraulic connection between the well screen and the surrounding soil. Each well screen interval was gently surged with a decontaminated stainless steel bailer and groundwater in the well was removed using a decontaminated, submersible pump and tubing. Approximately 20 to 50 gallons of water was removed from each well at a rate of approximately 20 gallons per hour. The initial turbidity readings of water removed from the wells during development were greater than 1,000 Nephelometric turbidity units (NTUs) and final turbidity readings were less than 500 NTUs in all but six wells. The soil within the well screen intervals of the six wells with higher turbidities generally included a higher fines content and/or organics/wood which may have contributed to the higher turbidities.

2.3. Decontamination

Drilling and non-disposable sampling equipment was decontaminated using the procedures specified in the QAPP.

2.4. Disposal of Investigation-Derived Materials

Soil cuttings from borings advanced for soil sampling and monitoring well installation were placed in labeled and sealed 55-gallon drums pending characterization for disposal. Approximately 3,500 gallons of development and purge water removed from the monitoring wells and decontamination water generated during all Lowland activities was placed in one 6,500 gallon upright aboveground polyethylene storage tank pending characterization for disposal. Both the soil drums and aboveground storage tank were stored within a fenced staging area on a property owned by the Port of Everett and made available for the investigation. The soil was disposed of at Republic Services Landfill in Roosevelt, Washington and water was disposed of at Emerald Services Airport Way Facility in Seattle, Washington based on the results of the characterization for disposal and approval by the disposal facilities. Incidental waste (i.e., gloves, paper towels, etc.) were disposed of off site as solid waste.

2.5. Deviations From the SAP

Field activities were performed in general accordance with the SAP, QAPP and HASP created for this project, with the exceptions listed below. All deviations were discussed with and approved by a representative of Ecology prior to implementation. Deviations included the following:

- Monitoring wells LLMW-24D, LLMW-25D, LLMW-31D were installed as deep wells only due to the absence of shallow groundwater at those locations.
- The actual location for monitoring well pair LLMW-17S/D was moved approximately 100 feet east-northeast from the planned location based on a request by Ecology. Pentachlorophenol (PCP) was previously observed at an investigation location west of the actual location of LLMW-17S/D. These wells were sampled for PCP in groundwater independent of the original scope of the Lowland (i.e., metals) investigation. The groundwater samples for PCP analysis were collected as “splits” and provided to Weyerhaeuser and Ecology.
- The actual location for monitoring well pair LLMW-21S/D is approximately 150 feet northeast of the planned location due to a request by the property owner for access reasons.
- The actual location for monitoring well LLMW-31D was on the east side of East Marine View Drive due to underground and overhead utility conflicts at the planned location.
- The actual locations for monitoring well pairs LLMW-12S/D, LLMW-14S/D and LLMW-15S/D were adjusted slightly (each less than approximately 100 feet from the planned locations) based on a request by the property owner for access reasons.

3.0 RESULTS

3.1. Observed Stratigraphy and Subsurface Conditions

In general, soils encountered during this investigation were similar to what has been described in previous investigations of the Lowland Area. The following is a description of four soil units observed in the Lowland Area:

- **Fill:** In general, approximately 7 feet of fill was observed at the surface of the Lowland Area. However, up to 19 feet of fill was observed in LLMW-13D and LLMW-23D. Fill predominantly consisted of soft/loose silty sands to silts with occasional wood and debris such as glass, metal and concrete. Groundwater within the fill unit was measured at depths ranging from approximately 3 to approximately 12 feet bgs during groundwater investigation activities. Results of groundwater investigation activities will be provided in a separate groundwater monitoring technical memorandum.
- **Silt:** Silt deposits were identified beneath the fill, typically as a layer of silt, silt with organics, and/or peat. The top of the silt is likely the historic native surface present during the time of smelter operations. The silt deposits have been described as forming a somewhat leaky confining layer between the shallow, unconfined aquifer and underlying deep aquifer. Where present, the silt deposits were generally observed to be between approximately 1.5 and 13 feet thick. The silt deposits were generally observed to be thicker in monitoring wells in the western portion of the Lowland Area, and thinner toward the east (i.e., towards the Snohomish River). A silt layer was not observed to be present at wells LLMW-01 or LLMW-02 at an

elevation consistent with the elevation of the silt layer in other Lowland Area investigation locations. However, a thin silt layer was observed at LLMW-01 and LLMW-02 at an elevation substantially lower than observed in the remainder of the Lowland Area. It is likely the silt observed in LLMW-01 and LLMW-02 may represent a thin interbed within the alluvium unit (described below).

- Alluvium: Wet, loose to medium dense sand was observed beneath the silt confining layer. The sand present beneath the confining layer is interpreted to be comprised of alluvium that has been described in previous investigations (ASARCO Incorporated, 2000).
- Lower Silt: A lower silt unit with sand interbeds was observed beneath the deep aquifer sand unit at the deeper deep location of BP-05D2. This silt was observed from approximately 46 feet to the total depth of the boring at 72 feet bgs. A five-foot well screen was set across the thickest sand interbed observed in the boring. The sand was observed at a depth of 68 to 71 feet bgs and the well screen was set at a depth of 67 to 72 feet bgs.

Soils encountered along the boundary between the Upland and Lowland Areas (LLMW-24D, LLMW-25D, LLMW-27D, LLMW-29D, LLMW-31D, LLMW-33D, and LLMW-34D) consisted of four principal geologic units:

- Fill/colluvium deposits: Approximately 1.5 to 6 feet of fill/colluvium deposits were observed at the surface in the borings performed along the boundary between the Upland and Lowland Areas. The soil was generally comprised of silt to cobble size material and occasionally contained organic matter, charred wood and other debris typically associated with fill.
- Weathered glacial till: Approximately 1.5 to 10 feet of weathered glacial till was observed underlying the surface fill/colluviums. The soil was generally comprised of silt to cobble size material. The soil was similar in appearance to the glacial till described below. However, the color of the weathered glacial till was generally brown and the density was lower than glacial till.
- Glacial till: Approximately 15 to 30 feet of glacial till was observed underlying the weathered glacial till. The soil was generally comprised of a dense mixture of silt to cobble sized material. Our interpretation of this soil is that it is Vashon till.
- Advance outwash sand: Advance outwash sand was observed underlying the glacial till to the full depth of the explorations. Soil consisted of fine to medium sand with trace amounts of silt. Our interpretation of this soil is that it is Vashon Advance Outwash Sand.

3.2. Data Validation

A data quality assessment was performed on all data in general conformance with an EPA “Stage-2B” validation. The data quality assessment report is provided in Appendix C. The laboratory analytical reports are provided in Appendix D. The data were deemed acceptable for use as qualified.

3.3. Soil Analytical Results

One hundred and fifty one soil samples from 31 deep borings were analyzed. Soil samples were only collected as part of the deep well installation and not from the co-located shallow monitoring well installations due to the close proximity (i.e., within 4 or 5 feet) of the well pairs. The soil

samples collected were submitted for metals analysis including antimony, arsenic, cadmium, lead, mercury and thallium. Selected soil samples were also submitted for analysis of grain size and total organic carbon (TOC).

The results for metals in soil are presented in Table 2 and Figures 4 and 5 present the arsenic and lead soil results, respectively.

The following summarizes the results for soil samples:

- Antimony was detected in one soil sample collected from the fill layer at LLMW-17 at a concentration of 19 milligrams per kilogram (mg/kg). Antimony was not detected in any other soil samples.
- Arsenic was detected in all samples at concentrations ranging from 1.7 mg/kg up to 1,330 mg/kg (LLMW-27 from 3.5 to 4.5 feet bgs). In general, the highest soil arsenic concentrations were observed in samples collected from the historic native surface of the silt deposits, followed by samples collected from the fill layer above the silt deposits.
- Cadmium was detected in all but 12 of the soil samples at concentrations ranging from 0.2 mg/kg to 4.5 mg/kg. Cadmium concentrations were higher in samples collected from the fill as well as the historic native surface of the silt. Cadmium concentrations also tended to be higher in samples with higher lead and/or arsenic concentrations.
- Lead was detected in the majority of samples at concentrations ranging from 2 mg/kg to 395 mg/kg. Lead concentrations tended to be higher in samples collected from the fill as well as the historic native surface of the silt.
- Mercury was detected in approximately half the samples at concentrations ranging from 0.02 mg/kg to 0.81 mg/kg.
- Thallium was not detected in any of the soil samples analyzed.

Soil total organic carbon results are presented in Table 3. The samples selected for grain size analysis are shown in Table 4 and the results are contained in Appendix E.

4.0 LIMITATIONS

We have prepared this report for the exclusive use of Washington State Department of Ecology and their authorized agents.

Within the limitations of scope, schedule and budget, our services have been executed in accordance with generally accepted practices in the field of environmental investigation in this area at the time this report was prepared. No warranty or other conditions express or implied should be understood.

Please refer to Appendix F titled "Report Limitations and Guidelines for Use" for additional information pertaining to use of this report.

5.0 REFERENCES

ASARCO Incorporated, 2000. Draft Comprehensive Lowland Area Remedial Investigation Report for the Everett Smelter Site, Everett, Washington. January 2000.

Table 1
Summary of Monitoring Well and Soil Boring Construction Information
Everett Lowland
Everett, Washington

Location ID	Ecology Well Tag	Location Coordinates ¹		Elevations ²		Flush / Stickup	Screened Interval Depth (feet bgs)
		Northing (Y)	Easting (X)	Ground Surface Elevation (feet)	Top of Casing Elevation (feet)		
Monitoring Well							
BP-05D2	BHR-977	371472.5693	1308791.7070	15.83	19.26	Stickup	67-72
LLMW-01D	BHU-093	373911.1708	1307952.9290	16.08	15.74	Flush	27.5-37.5
LLMW-02D	BHU-027	372887.0090	1307921.3900	15.38	15.15	Flush	22-32
LLMW-03S	BHU-088	372968.4709	1308355.5780	14.52	17.45	Stickup	3.5-8.5
LLMW-03D	BHU-087	372965.5718	1308351.5110	14.43	17.45	Stickup	21-31
LLMW-04S	BHU-090	372644.2517	1308249.7640	18.61	21.91	Stickup	4-14
LLMW-04D	BHU-089	372642.8382	1308246.2520	18.89	21.98	Stickup	22-32
LLMW-05S	BHU-011	372938.3312	1309085.1330	14.42	14.05	Flush	4-9
LLMW-05D	BHU-010	372934.1281	1309088.2700	14.39	13.92	Flush	15-25
LLMW-06S	BHU-091	372477.6634	1309132.4260	12.73	12.49	Flush	4-7
LLMW-06D	BHU-092	372472.7325	1309133.8720	12.71	12.29	Flush	18-28
LLMW-07S	BHU-008	372578.2673	1309467.0870	14.06	13.82	Flush	4-9
LLMW-07D	BHU-009	372580.8285	1309464.7630	14.09	13.81	Flush	15-25
LLMW-08S	BHU-013	372213.2542	1309788.2490	13.21	16.21	Stickup	5-10
LLMW-08D	BHU-012	372209.3701	1309788.5690	13.45	16.26	Stickup	15-25
LLMW-09S	BHU-007	371929.4722	1309290.9450	13.15	12.57	Flush	3.5-6
LLMW-09D	BHU-006	371933.0232	1309291.5300	13.18	12.79	Flush	17-27
LLMW-10S	BHU-015	371722.2934	1309357.7910	13.18	15.91	Stickup	4-6.5
LLMW-10D	BHU-014	371725.4255	1309359.4070	13.14	15.97	Stickup	21-31
LLMW-11S	BHU-041	371826.1136	1310349.2310	16.00	19.76	Stickup	3.5-9.5
LLMW-11D	BHU-040	371822.9079	1310350.2610	16.03	19.71	Stickup	12-22
LLMW-12S	BHU-017	371520.5241	1309412.4360	13.84	15.61	Stickup	3-7
LLMW-12D	BHU-016	371523.5091	1309414.2800	13.63	15.71	Stickup	17-27
LLMW-13S	BHU-044	371682.6131	1309796.9300	18.43	21.49	Stickup	8-18
LLMW-13D	BHU-045	371682.4624	1309793.1490	18.48	21.24	Stickup	25-35
LLMW-14S	BHU-019	371374.1753	1309446.9460	12.49	14.74	Stickup	3.5-6
LLMW-14D	BHU-018	371375.9911	1309449.1600	12.49	14.80	Stickup	20-30
LLMW-15S	BHU-021	371051.1506	1309535.4190	13.21	15.94	Stickup	3.5-9.5
LLMW-15D	BHU-020	371053.2175	1309536.6120	13.10	16.07	Stickup	24-34
LLMW-16S	BHU-043	371159.2967	1310164.4520	17.19	20.02	Stickup	4-12
LLMW-16D	BHU-042	371158.1660	1310160.4370	17.14	20.14	Stickup	24-34
LLMW-17S	BHU-039	371320.3207	1310602.2830	15.32	18.27	Stickup	4-11
LLMW-17D	BHU-038	371317.6575	1310603.0720	15.27	18.29	Stickup	15-25
LLMW-18S	BHU-023	370389.0772	1309715.2920	13.27	15.70	Stickup	3.5-7.5
LLMW-18D	BHU-022	370391.7580	1309718.7140	13.11	15.91	Stickup	20-30
LLMW-19D	BHU-005	370189.3895	1310224.8460	11.64	14.22	Stickup	17-27
LLMW-20D	BHU-037	370542.4429	1310748.1780	11.32	14.92	Stickup	11-21
LLMW-21S	BHU-026	370010.9467	1309885.4530	13.62	16.04	Stickup	3.5-7
LLMW-21D	BHU-025	370011.1759	1309881.2800	13.29	16.03	Stickup	23-33
LLMW-22S	BHU-004	369173.0090	1310445.6340	13.18	12.87	Flush	3.5-7
LLMW-22D	BHU-003	369167.8357	1310446.0910	13.14	12.80	Flush	17-27
LLMW-23S	BHU-002	368222.1107	1310277.4480	25.95	25.54	Flush	14-24
LLMW-23D	BHU-001	368226.9076	1310278.8900	25.91	25.30	Flush	30-40
LLMW-24D	BHU-030	371665.5506	1308321.7200	54.66	54.28	Flush	43.5-53.5
LLMW-25D	BHU-024	371489.9394	1308367.7590	61.98	61.76	Flush	55-65
LLMW-27S	BHU-032	371254.3715	1308467.3450	61.87	61.46	Flush	31-36
LLMW-27D	BHU-031	371259.2652	1308465.4350	61.93	61.71	Flush	50-60
LLMW-29S	BHU-029	370978.6854	1308557.0080	55.91	55.66	Flush	5-15
LLMW-29D	BHU-028	370982.4647	1308556.2150	56.04	55.62	Flush	50-60
LLMW-31D	BHR-886	370452.8170	1308669.7760	59.00	58.41	Flush	54-64
LLMW-33S	BHU-095	369957.8312	1308912.9560	37.73	37.42	Flush	3.5-10.5
LLMW-33D	BHU-094	369961.9490	1308914.5250	37.57	37.24	Flush	35-45
LLMW-34S	BHU-047	368693.8425	1308931.7710	53.22	52.71	Flush	4-12
LLMW-34D	BHU-046	368696.1556	1308930.6690	53.30	53.03	Flush	63.5-73.5
Soil Boring							
LLSB-1	Not Applicable	373990.7175	1306949.75	12.6436	Not Applicable	Not Applicable	Not Applicable
LLSB-2	Not Applicable	373634.9832	1307691.419	14.7497	Not Applicable	Not Applicable	Not Applicable
LLSB-3	Not Applicable	373543.2766	1308050.649	15.0686	Not Applicable	Not Applicable	Not Applicable

Notes

BP = Benson Property

LLMW = Lowland Monitoring Well

¹ Northing (Y) and Easting(X) are in Washington State Plane North Coordinate System, 83/91 grid values

² Vertical datum is NAVD88, US survey feet

Survey performed by David Evans and Associates, Everett, Washington

Table 2
Chemical Analytical Result - Soil¹

Everett Lowland
Everett, Washington

Location ID	Sample ID	Analyte	Antimony	Arsenic	Cadmium	Lead	Mercury	Thallium
		Units	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
		Stratigraphic Unit						
LLMW01	LLMW01-3-4	Fill	5 U	5.6	0.2	2	0.02 U	0.2 U
	LLMW01-25-25.2	Native Surface	8 U	16.4	0.6	14	0.18	0.3 U
	LLMW01-26-26.5	Silt Deposits	8 U	13.3	0.6	12	0.16	0.3 U
	LLMW01-32.5-33.5	Alluvium	6 U	2.7	0.2 U	2 U	0.03 U	0.2 U
LLMW02	LLMW02-6-7	Fill	6 U	5.3	0.3	3	0.02 U	0.2 U
	LLMW02-17.4-17.6	Native Surface	8 U	64.6	1.9	50	0.21	0.3 U
	LLMW02-20-21	Silt Deposits	6 U	7.5	0.3	3	0.03 U	0.2 U
	LLMW02-27-28	Alluvium	6 U	5.3	0.3	3	0.02 U	0.2 U
LLMW03	LLMW03-9-10	Fill	6 U	6.4	0.3	5	0.02 U	0.2 U
	LLMW03-10.5-10.6	Native Surface	8 U	20.9	0.6	21	0.09 J	0.3 U
	LLMW03-13.5-14.5	Silt Deposits	8 U	12.6	0.7	7	0.09 J	0.3 U
	LLMW03-28-29	Alluvium	6 U	3.2	0.3	2 U	0.03 U	0.2 U
LLMW04	LLMW04-2-3	Fill	5 U	7.3	0.5	11	0.05	0.2 U
	LLMW04-2-3D	Duplicate	5 U	6.7	0.5	10	0.05	0.2 U
	LLMW04-14.3-14.5	Native Surface	7 U	24.9	0.6	11	0.08	0.3 U
	LLMW04-18-19	Silt Deposits	8 U	15.7	0.7	6	0.09	0.3 U
	LLMW04-30-31	Alluvium	5 U	4.4	0.3	2 U	0.02 U	0.2 U
LLMW05	LLMW05-6-7	Fill	6 U	9.8	0.3	4	0.02 U	0.2 U
	LLMW05-10-10.2	Native Surface	8 U	49.8	0.8	53	0.1	0.3 U
	LLMW05-12-13	Silt Deposits	7 U	9.8	0.5	6	0.06	0.3 U
	LLMW05-12-13-D	Duplicate	7 U	9.8	0.5	5	0.06	0.3 U
	LLMW05-20-21	Alluvium	6 U	4.4	0.3	3	0.03 U	0.2 U
LLMW06	LLMW06-6.5-7.5	Fill	6 U	59.5	0.3	3	0.02 U	0.2 U
	LLMW06-8-8.2	Native Surface	9 U	28	0.8	15	0.08	0.3 U
	LLMW06-11-12	Silt Deposits	7 U	13.7	0.6	6	0.09	0.3 U
	LLMW06-23-24	Alluvium	6 U	5.3	0.3	2 U	0.03	0.3 U
LLMW07	LLMW07-3-4	Fill	6 U	5.7	0.5	16	0.02 U	0.2 U
	LLMW07-10-10.2	Native Surface	8 U	12.9	0.3	4	0.05	0.3 U
	LLMW07-10.5-11	Silt Deposits	7 U	13.5	0.4	5	0.06	0.3 U
	LLMW07-18-19	Alluvium	6 U	2.6	0.2 U	2 U	0.02 U	0.2 U
LLMW08	LLMW08-3-4	Fill	10 U	26.8	0.8	81	0.06	0.2 U
	LLMW08-12-13	Native Surface	20 U	29.2	1.1	386	0.07	0.3 U
	LLMW08-20-21	Alluvium	6 U	5.4	0.3	4	0.02 U	0.2 U
LLMW09	LLMW09-4.5-5.5	Fill	6 U	15.1	0.3	4	0.02 U	0.2 U
	LLMW09-8.3-8.5	Native Surface	10 U	103	1.7	169	0.26	0.4 U
	LLMW09-10.5-11	Silt Deposits	8 U	16.5	0.5	8	0.08	0.3 U
	LLMW09-18-19	Alluvium	6 U	5.9	0.2 U	2 U	0.02 U	0.2 U
LLMW10	LLMW10-6-7	Fill	6 U	2.8	0.3	3	0.03 U	0.2 U
	LLMW10-7.5-7.7	Native Surface	7 U	22.3	2.5	37	0.1	0.3 U
	LLMW10-12-13	Silt Deposits	8 U	15.4	0.6	8	0.09	0.3 U
	LLMW10-27-28	Alluvium	6 U	3.4	0.2	2 U	0.03 U	0.2 U
LLMW11	LLMW11-5-6	Fill	10 U	26	0.6 U	15	0.05	0.2 U
	LLMW11-10.5-10.7	Native Surface	7 U	13.9	0.4	12	0.05	0.3 U
	LLMW11-11-11.5	Silt Deposits	6 U	10.8	0.5	6	0.06	0.3 U
	LLMW11-19.5-20.5	Alluvium	6 U	28.9	0.3	3	0.03 U	0.3 U
LLMW12	LLMW12-5-5.5	Fill	6 U	3.8	0.3	3	0.02 U	0.2 U
	LLMW12-8.5-8.7	Native Surface	8 U	32.1	0.8	12	0.07	0.3 U
	LLMW12-10-10.5	Silt Deposits	8 U	12.6	0.5	8	0.09	0.3 U
	LLMW12-21-22	Alluvium	6 U	9.4	0.3	3	0.02 U	0.2 U
LLMW13	LLMW13-10.5-11.5	Fill	7 U	47.2	0.3	49	0.03 U	0.3 U
	LLMW13-18.7-19	Native Surface	7 U	15.7	0.5	12	0.09	0.3 U
	LLMW13-23-24	Silt Deposits	6 U	6.7	0.4	5	0.02 U	0.2 U
	LLMW13-32-33	Alluvium	6 U	4.2	0.3	3	0.02 U	0.2 U
LLMW14	LLMW14-5.5-6	Fill	6 U	8.4	0.4	16	0.03	0.2 U
	LLMW14-7-7.2	Native Surface	10 U	203	4.5	395	0.23	0.4 U
	LLMW14-13.5-14.5	Silt Deposits	7 U	12.9	0.6	7	0.07	0.3 U
	LLMW14-29-30	Alluvium	6 U	2.8	0.3	2 U	0.03 U	0.2 U
LLMW15	LLMW15-2-3	Fill	6 U	2.6	0.3	4	0.02	0.2 U
	LLMW15-2-3 DUP	Duplicate	6 U	2.5	0.3	3	0.03 U	0.2 U
	LLMW15-11.5-11.7	Native Surface	10 U	63.8	1.5	105	0.2	0.4 U
	LLMW15-14-15	Silt Deposits	8 U	12.9	0.6	7	0.1	0.3 U
	LLMW15-30.5-31.5	Alluvium	6 U	5.1	0.2	2 U	0.03 U	0.2 U
LLMW16	LLMW16-13-13.5	Fill	6 U	15	0.3	6	0.03	0.2 U
	LLMW16-13.5-13.7	Native Surface	7 U	21	0.5	8	0.06	0.3 U
	LLMW16-15-16	Silt Deposits	7 U	10.5	0.5	6	0.07	0.3 U
	LLMW16-29.5-30.5	Alluvium	5 U	4	0.3	3	0.02 U	0.2 U
LLMW17	LLMW17-5-6	Fill	19	43.7	0.4	47	0.04	0.2 U
	LLMW17-12-12.2	Native Surface	6 U	10.8	0.4	5	0.05	0.3 U
	LLMW17-12.5-13	Silt Deposits	6 U	12.2	0.4	5	0.05	0.3 U
	LLMW17-21-22	Alluvium	6 U	3.7	0.3	2	0.03 U	0.2 U
LLMW18	LLMW18-6-7	Fill	6 U	3.9	0.2	3	0.03 U	0.2 U
	LLMW18-8.5-8.7	Native Surface	10 U	313	3.1	212	0.54	0.4 U
	LLMW18-11-12	Silt Deposits	9 U	18.8	0.5	9	0.08	0.4 U
	LLMW18-21-22	Alluvium	6 U	3.4	0.3 U	3 U	0.03 U	0.3 U
LLMW19	LLMW19-3-4	Fill	6 U	142	0.4	86	0.04	0.2 U
	LLMW19-7.8-8	Native Surface	8 U	31.2	0.5	131	0.09	0.3 U
	LLMW19-9-10	Silt Deposits	8 U	19.8	0.5	13	0.08	0.3 U
	LLMW19-25-26	Alluvium	6 U	2.7	0.2 U	2 U	0.03 U	0.2 U

Location ID	Sample ID	Analyte	Antimony	Arsenic	Cadmium	Lead	Mercury	Thallium
		Units	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg	mg/Kg
		Stratigraphic Unit						
LLMW20	LLMW20-4.5-5.5	Fill	5 U	30.2	0.3	12	0.03	0.2 U
	LLMW20-7.2-7.4	Native Surface	7 U	64.6	0.5	9	0.06	0.3 U
	LLMW20-9-9.5	Silt Deposits	6 U	19.4	0.4	5	0.03	0.2 U
	LLMW20-13.5-14.5	Alluvium	6 U	22.9	0.3	19	0.03 U	0.3 U
LLMW21	LLMW21-6-7	Fill	6 U	15.4	0.3	5	0.02 U	0.2 U
	LLMW21-7.7-7.9*	Native Surface	10 U	121	2	96	0.22	0.4 U
	LLMW21-12-13	Silt Deposits	8 U	21.3	0.6	9	0.07	0.3 U
	LLMW21-15-16	Silt Deposits	10 U	17	0.6	10	0.07	0.4 U
	LLMW21-24-25	Alluvium	6 U	5.1	0.3	3 U	0.02 U	0.2 U
LLMW22	LLMW22-3-4	Fill	6 U	6.1	0.2 U	2 U	0.02 U	0.2 U
	LLMW22-8-8.2	Native Surface	9 U	24.6	0.4	8	0.1	0.3 U
	LLMW22-10.5-11.5	Silt Deposits	8 U	16.9	0.4	9	0.09	0.3 U
	LLMW22-20-21	Alluvium	6 U	2.6	0.2	2 U	0.03 U	0.2 U
LLMW23	LLMW23-17-18	Fill	6 U	5.6	0.2 U	4	0.02 U	0.2 U
	LLMW23-20-21	Fill	6 U	5.7	0.2 U	5	0.03 U	0.2 U
	LLMW23-22.9-23.1	Native Surface	7 U	11.2	0.3	7	0.04	0.3 U
	LLMW23-26-26.5	Silt Deposits	8 U	16.3	0.4	6	0.1	0.3 U
	LLMW23-35-36	Alluvium	6 U	2.3	0.2 U	2 U	0.02 U	0.2 U
LLMW24	LLMW24-1.3-1.5	Native Surface	6 U	14.6 J	1.1	69	0.07	0.2 U
	LLMW24-6-6.5	Till	6 U	3.2 J	0.5	4	0.04	0.2 U
	LLMW24-30-31	Outwash	5 U	2.1 J	0.4	2	0.03 U	0.2 U
	LLMW24-45-46	Outwash	5 U	2.5 J	0.3	2 U	0.02	0.2 U
LLMW25	LLMW25-3-4	Fill	5 U	2.7	0.6	5	0.04	0.2 U
	LLMW25-8-8.2	Native Surface	5 U	2.1	0.3	2 U	0.02 U	0.2 U
	LLMW25-10.5-11	Till	5 U	2	0.3	2	0.03 U	0.2 U
	LLMW25-55-56	Outwash	6 U	2.2	0.3	2 U	0.03 U	0.2 U
LLMW27	LLMW27-3.5-4.5	Fill	6 U	1,330	0.2 U	2 U	0.08	0.2 U
	LLMW27-4.5-5.5	Native Surface	5 U	274	0.7	2 U	0.02 U	0.2 U
	LLMW27-8-9	Weathered Till	6 U	84.2	0.8	2 U	0.02 U	0.2 U
	LLMW27-15.5-16	Weathered Till	6 U	2.4	0.3	2 U	0.02 U	0.2 U
	LLMW27-25-26	Till	5 U	3.1	0.4	2	0.02 U	0.2 U
	LLMW27-30-31	Outwash	5 U	2.3	0.4	2 U	0.02 U	0.2 U
	LLMW27-37-37.5	Outwash	6 U	58.7	0.7	19	0.08	0.2 U
	LLMW27-40-41	Outwash	5 U	2.3	0.3	2 U	0.02 U	0.2 U
	LLMW27-50-51	Outwash	6 U	28.8	0.4	2 U	0.03 U	0.2 U
LLMW27-60-61	Outwash	5 U	38.9	0.3	2 U	0.03 U	0.2 U	
LLMW29	LLMW29-6-7	Fill	10 U	6.9	0.5 U	5 U	0.05	0.2 U
	LLMW29-12.5-13.5	Native Surface	5 U	85.7	0.4	2	0.02	0.2 U
	LLMW29-20-21	Till	5 U	52.6	0.3	2	0.02	0.2 U
	LLMW29-30-31	Outwash	5 U	30.1	0.3	2 U	0.02 U	0.2 U
	LLMW29-55-56	Outwash	6 U	6.7	0.3	2 U	0.03 U	0.2 U
LLMW31	LLMW31-3-4	Fill	5 U	58.8	0.8	271	0.13	0.2 U
	LLMW31-9.1-9.3	Native Surface	5 U	12.7	0.4	34	0.07	0.2 U
	LLMW31-25-25.5	Till	5 U	4.3	0.4	3	0.02 U	0.2 U
	LLMW31-45-46	Outwash	5 U	2.2	0.4	3	0.03	0.2 U
	LLMW31-55-56	Outwash	6 U	2.1	0.4	2 U	0.02 U	0.2 U
LLMW33	LLMW33-3-4	Fill	6 U	121	1	301	0.81	0.2 U
	LLMW33-4.5-4.7	Native Surface	6 U	10.9	0.5	18	0.17	0.2 U
	LLMW33-10.5-11.5	Weathered Till	6 U	2.6	0.3	2 U	0.03 U	0.2 U
	LLMW33-39-40	Outwash	6 U	1.7	0.3	2 U	0.02 U	0.2 U
LLMW34	LLMW34-4.5-5.5	Fill	6 U	5.7 J	0.4	7	0.05	0.2 U
	LLMW34-6-6.2	Native Surface	6 U	4.6 J	0.3	6	0.06	0.2 U
	LLMW34-11.5-11.7	Weathered Till	6 U	2.7 J	0.3	2 U	0.02 U	0.2 U
	LLMW34-70-70.5	Outwash	5 U	2.2 J	0.4	2 U	0.02 U	0.2 U
LLSB01	LLSB01-6-7	Fill	8 U	11.3	0.5	26 J	0.06	0.3 U
	LLSB01-10.8-11	Native Surface	9 U	13.4	1.2	50 J	0.4	0.4 U
	LLSB01-13-14	Silt Deposits	8 U	14.9	0.6	12 J	0.15	0.3 U
	LLSB01-19-20	Alluvium	6 U	3.9	0.3	3 J	0.03 U	0.2 U
LLSB02	LLSB02-3-4	Fill	5 U	9.8	0.4	37	0.02	0.2 U
	LLSB02-10-10.2	Native Surface	9 U	36.4	1	133	0.1	0.3 U
	LLSB02-10.6-10.8	Silt Deposits	8 U	14.7	0.6	7	0.07	0.3 U
	LLSB02-12-13	Silt Deposits	7 U	15	0.7	7	0.09	0.3 U
	LLSB02-15-16	Alluvium	6 U	9.4	0.4	4	0.04	0.2 U
LLSB03	LLSB03-3-4	Fill	5 U	6.9	0.3	3	0.02 U	0.2 U
	LLSB03-11-11.2	Native Surface	8 U	31.1	0.7	14	0.12	0.3 U
	LLSB03-13-14	Silt Deposits	7 U	18.3	0.6	7	0.07	0.3 U
	LLSB03-19-20	Alluvium	6 U	6.9	0.3	3	0.03 U	0.2 U
	LLSB-DUP	Duplicate	5 U	5.4	0.3	3 J	0.02 U	0.2 U
BP05D2	BP05D2-40-41	Alluvium	6 U	10.7	0.3	6	0.03 U	0.2 U
	BP05D2-50-51	Silt Deposits	6 U	8.2	0.5	4	0.03	0.2 U
	BP05D2-62-62.5	Silt Deposits	7 U	11.9	0.7	5	0.04	0.3 U
	BP05D2-65-66	Silt Deposits	6 U	12.3	0.6	3	0.03 U	0.3 U
	BP05D2-70.5-71	Alluvium	6 U	6.4	0.3	2 U	0.02 U	0.2 U

Notes

¹ Chemical analysis performed by Analytical Resources, Inc., of Tukwila, Washington.

mg/Kg = milligram per Kilogram

U = Analyte was not detected at or greater than the listed reporting limit.

J = The indicated result is an estimate.

A "D" or "Dup" at the end of the sample ID indicates a field duplicate sample.

Bold type indicates the analyte was detected.

* = Sample LLMW21-7.7-7.9 was mislabeled in the field and reported as LLMW21-7.7-9. The correct sample ID (LLMW21-7.7-7.9) is displayed in this table.

Table 3
Soil Total Organic Carbon
Everett Lowland
Everett, Washington

Sample ID	Analyte	Total Solids	Total Organic Carbon
	Units	Percent	Percent
	Stratigraphic Unit		
LLMW03-5-5.2	Native Surface	67.3	2.93
LLMW04-30-31	Alluvium	88.3	0.264
LLMW05-6-7	Fill	84.2	0.247
LLMW06-6.5-7.5	Fill	87.8	0.368
LLMW07-18-19	Alluvium	82.2	0.222
LLMW08-20-21	Alluvium	82.6	0.741
LLMW10-6-7	Fill	83	0.296
LLMW11-19.5-20.5	Alluvium	84.6	3.06
LLMW12-21-22	Alluvium	83.8	0.765
LLMW13-10.5-11.5	Fill	65.7	28.2
LLMW14-5.5-6	Fill	82.8	3.36
LLMW16-29.5-30.5	Alluvium	87.5	0.549
LLMW17-5-6	Fill	88	11.6
LLMW18-6-7	Fill	83.2	0.433
LLMW18-21-22	Alluvium	78.30	1.29
LLMW20-4.5-5.5	Fill	88.6	3.42
LLMW27-50-51	Outwash	79.8	0.129
LLMW29-55-56	Outwash	78.9	0.538

Table 4
Samples Submitted for Grain Size Analysis
Everett Lowland
Everett, Washington


Sample ID
LLMW03-5-5.2
LLMW03-28-29
LLMW06-6.5-7.5
LLMW06-23-24
LLMW07-18-19
LLMW08-20-21
LLMW11-3.5-4.5
LLMW11-19.5-20.5
LLMW12-5-5.5
LLMW12-21-22
LLMW13-10.5-11.5
LLMW13-32-33
LLMW18-6-7
LLMW18-21-22

Note:

See Appendix E for results of grain size analyses.



Path: \\sea\projects\0\0504068\GIS\050406800_VicinityMap_Lowland.mxd Map Revised: 07 February, 2013 amanza




Notes:




1. The locations of all features shown are approximate.
2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. can not guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.
3. It is unlawful to copy or reproduce all or any part thereof, whether for personal use or resale, without permission.

Data Sources: ESRI Data & Maps
 Projection: NAD 1983 UTM Zone 10N

Vicinity Map	
Everett Smelter - Lowland Area	
GEOENGINEERS	Figure 1




Legend


-  Lowland Area
-  Snohomish County Parcel Boundary
-  Approximate WSDOT Right of Way

Notes:
 1. The locations of all features shown are approximate.
 2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.

Data Source: Aerials Express Seattle, 2009. Snohomish County GIS, 2012.



Lowland Area	
Everett Smelter - Lowland Area	
GEOENGINEERS 	Figure 2



- Legend**
- Lowland Area
 - Snohomish County Parcel Boundary
 - Existing Shallow Aquifer Monitoring Well
 - Existing Deep Aquifer Monitoring Well
 - Existing Shallow and Deep Aquifer Monitoring Well Pair

- Investigation Locations (2012-2013)**
- Shallow and Deep Aquifer Monitoring Well Pair
 - Deep Aquifer Monitoring Well
 - Deeper Deep Aquifer Monitoring Well (to determine vertical extent)
 - Soil Boring




Lowland Area Investigation Locations

Everett Smelter - Lowland Area



Figure 3

Notes:
 1. The locations of all features shown are approximate.
 2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.



Greater than four soil samples were analyzed from a limited number of borings. In cases where more than one soil sample was analyzed for a given stratigraphic layer, the highest concentration is shown. See Table 2 for all sample results.

Legend

- Lowland Area
- Snohomish County Parcel Boundary
- Existing Shallow Aquifer Monitoring Well
- Existing Deep Aquifer Monitoring Well
- Existing Shallow and Deep Aquifer Monitoring Well Pair

Investigation Locations (2012-2013)

- Shallow and Deep Aquifer Monitoring Well Pair
- Deep Aquifer Monitoring Well
- Deeper Deep Aquifer Monitoring Well (to determine vertical extent)
- Soil Boring

Key to Soil Results

- Fill (Shallow Aquifer)
- Native Surface
- Silt/Till
- Alluvium/Outwash (Deep Aquifer)
- Arsenic Concentration in mg/kg ("J" indicates estimate)
- Sample Not Obtained

Notes:
 1. The locations of all features shown are approximate.
 2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.

Data Source: Aerials Express Seattle, 2009. Snohomish County GIS, 2012.




**Boring/Monitoring Well Locations:
Soil Results - Arsenic**


Everett Smelter - Lowland Area



Figure 4



<p>Legend</p> <ul style="list-style-type: none"> Lowland Area Snohomish County Parcel Boundary Existing Shallow Aquifer Monitoring Well Existing Deep Aquifer Monitoring Well Existing Shallow and Deep Aquifer Monitoring Well Pair <p><small>Notes:</small></p> <p>1. The locations of all features shown are approximate. 2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.</p> <p><small>Data Source: Aerials Express Seattle, 2009. Snohomish County GIS, 2012.</small></p>	<p>Investigation Locations (2012-2013)</p> <ul style="list-style-type: none"> Shallow and Deep Aquifer Monitoring Well Pair Deep Aquifer Monitoring Well Deeper Deep Aquifer Monitoring Well (to determine vertical extent) Soil Boring <p>Key to Soil Results</p> <ul style="list-style-type: none"> Fill (Shallow Aquifer) Native Surface Silt/Till Alluvium/Outwash (Deep Aquifer) <p>Arsenic Concentration in mg/kg ("U" indicates not detected, "J" indicates estimate)</p> <ul style="list-style-type: none"> 5.7J Sample Not Obtained 		<p>Boring/Monitoring Well Locations: Soil Results - Lead</p> <p>Everett Smelter - Lowland Area</p> <p>GEOENGINEERS</p>	<p>Figure 5</p>
--	---	--	--	------------------------



APPENDIX A
Boring and Monitoring Well Construction Logs

SOIL CLASSIFICATION CHART

MAJOR DIVISIONS			SYMBOLS		TYPICAL DESCRIPTIONS
			GRAPH	LETTER	
COARSE GRAINED SOILS	GRAVEL AND GRAVELLY SOILS	CLEAN GRAVELS <small>(LITTLE OR NO FINES)</small>		GW	WELL-GRADED GRAVELS, GRAVEL - SAND MIXTURES
		GRAVELS WITH FINES <small>(APPRECIABLE AMOUNT OF FINES)</small>		GP	POORLY-GRADED GRAVELS, GRAVEL - SAND MIXTURES
		GRAVELS WITH FINES <small>(APPRECIABLE AMOUNT OF FINES)</small>		GM	SILTY GRAVELS, GRAVEL - SAND - SILT MIXTURES
	SAND AND SANDY SOILS	CLEAN SANDS <small>(LITTLE OR NO FINES)</small>		SW	WELL-GRADED SANDS, GRAVELLY SANDS
		SANDS WITH FINES <small>(APPRECIABLE AMOUNT OF FINES)</small>		SP	POORLY-GRADED SANDS, GRAVELLY SAND
		SANDS WITH FINES <small>(APPRECIABLE AMOUNT OF FINES)</small>		SM	SILTY SANDS, SAND - SILT MIXTURES
FINE GRAINED SOILS	SILTS AND CLAYS	LIQUID LIMIT LESS THAN 50		ML	INORGANIC SILTS, ROCK FLOUR, CLAYEY SILTS WITH SLIGHT PLASTICITY
		LIQUID LIMIT LESS THAN 50		CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
		LIQUID LIMIT LESS THAN 50		OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY
	SILTS AND CLAYS	LIQUID LIMIT GREATER THAN 50		MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS SILTY SOILS
		LIQUID LIMIT GREATER THAN 50		CH	INORGANIC CLAYS OF HIGH PLASTICITY
		LIQUID LIMIT GREATER THAN 50		OH	ORGANIC CLAYS AND SILTS OF MEDIUM TO HIGH PLASTICITY
HIGHLY ORGANIC SOILS			PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS	

NOTE: Multiple symbols are used to indicate borderline or dual soil classifications

Sampler Symbol Descriptions

	2.4-inch I.D. split barrel
	Standard Penetration Test (SPT)
	Shelby tube
	Piston
	Direct-Push
	Bulk or grab

Blowcount is recorded for driven samplers as the number of blows required to advance sampler 12 inches (or distance noted). See exploration log for hammer weight and drop.

A "P" indicates sampler pushed using the weight of the drill rig.

ADDITIONAL MATERIAL SYMBOLS

SYMBOLS		TYPICAL DESCRIPTIONS
GRAPH	LETTER	
	AC	Asphalt Concrete
	CC	Cement Concrete
	CR	Crushed Rock/Quarry Spalls
	TS	Topsoil/Forest Duff/Sod

Groundwater Contact



Measured groundwater level in exploration, well, or piezometer



Groundwater observed at time of exploration



Perched water observed at time of exploration



Measured free product in well or piezometer

Graphic Log Contact



Distinct contact between soil strata or geologic units



Approximate location of soil strata change within a geologic soil unit

Material Description Contact



Distinct contact between soil strata or geologic units



Approximate location of soil strata change within a geologic soil unit

Laboratory / Field Tests

%F	Percent fines
AL	Atterberg limits
CA	Chemical analysis
CP	Laboratory compaction test
CS	Consolidation test
DS	Direct shear
HA	Hydrometer analysis
MC	Moisture content
MD	Moisture content and dry density
OC	Organic content
PM	Permeability or hydraulic conductivity
PI	Plasticity index
PP	Pocket penetrometer
PPM	Parts per million
SA	Sieve analysis
TX	Triaxial compression
UC	Unconfined compression
VS	Vane shear


Sheen Classification

NS	No Visible Sheen
SS	Slight Sheen
MS	Moderate Sheen
HS	Heavy Sheen
NT	Not Tested

NOTE: The reader must refer to the discussion in the report text and the logs of explorations for a proper understanding of subsurface conditions. Descriptions on the logs apply only at the specific exploration locations and at the time the explorations were made; they are not warranted to be representative of subsurface conditions at other locations or times.

KEY TO EXPLORATION LOGS

Drilled	Start 1/8/2013	End 1/8/2013	Total Depth (ft)	72	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850 Track Rig		A 2 (in) well was installed on 1/8/2013 to a depth of 72 (ft).			
Surface Elevation (ft)	16.46				Top of Casing Elevation (ft)						
Vertical Datum	NAVD88							Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)	
Easting (X)	371367.4523				Horizontal Datum	WA State Plane North 83/91					
Northing (Y)	1308612.59										
Notes:											




Log of Boring BP-05D2



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-2
 Sheet 1 of 2



Note: Please see Figure A-1 for explanation of symbols

Log of Boring BP-05D2 (continued)




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-2
 Sheet 2 of 2

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-068-00.GPJ DB Template: I:\Template: GEOENGINEERS8.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 1/2/2013	End 1/2/2013	Total Depth (ft)	38	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Mobile B-59 Track Rig		DOE Well I.D.: BHU-093 A 2 (in) well was installed on 1/2/2013 to a depth of 38 (ft).		
Surface Elevation (ft) Vertical Datum	16.0827 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	373911.1708 1307952.929				Horizontal Datum	WA State Plane North 83/91		1/2/2013	7.5	8.6
Notes:										



Log of Monitoring Well LLMW-01D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-068-00.GPJ DB Template: I:\Template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA							MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Interval	Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level	Graphic Log				
35	4		33								
							Dark gray fine to coarse sand with mica, trace silt, occasional gravel, trace organic matter (~1%) (medium dense, wet)				


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-01D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/21/2012	End 12/21/2012	Total Depth (ft) 32	Logged By Checked By GRL	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Mobile B-59 Track Rig		DOE Well I.D.: BHU-027 A 2 (in) well was installed on 12/21/2012 to a depth of 32 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 15.384	Top of Casing Elevation (ft)		Groundwater Date Measured 12/21/2012		
Easting (X) Northing (Y) 372887.009 1307921.39	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 3.3		Elevation (ft) 12.1
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-02D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-4
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LibTemplate: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Start Drilled 12/26/2012	End 12/26/2012	Total Depth (ft) 31	Logged By Checked By GRL	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-087 A 2 (in) well was installed on 12/26/2012 to a depth of 31 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 14.4339	Top of Casing Elevation (ft)		Groundwater Date Measured 12/26/2012		
Easting (X) Northing (Y) 372965.5718 1308351.511	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 3.0		Elevation (ft) 11.4
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-03D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-5
 Sheet 1 of 1

Drilled	Start 12/26/2012	End 12/26/2012	Total Depth (ft)	8.5	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-50 Turbo Track Rig			DOE Well I.D.: BHU-088 A 2 (in) well was installed on 12/26/2012 to a depth of 31 (ft).	
Surface Elevation (ft) Vertical Datum	14.5247 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	372968.4709 1308355.578				Horizontal Datum	WA State Plane North 83/91				
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-03S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-6
 Sheet 1 of 1

Start Drilled 12/28/2012	End 12/28/2012	Total Depth (ft) 33	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-089 A 2 (in) well was installed on 12/28/2012 to a depth of 33 (ft).		
Surface Elevation (ft) Vertical Datum 18.8925 NAVD88	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y) 372642.8382 1308246.252	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)					
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-04D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-7
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 12/28/2012	End 12/28/2012	Total Depth (ft)	14	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-090 A 2 (in) well was installed on 12/28/2012 to a depth of 33 (ft).		
Surface Elevation (ft) Vertical Datum	18.6052 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	372644.2517 1308249.764				Horizontal Datum	WA State Plane North 83/91				
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-04S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-8
 Sheet 1 of 1

Start Drilled 12/10/2012	End 12/10/2012	Total Depth (ft) 25	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-010 A 2 (in) well was installed on 12/10/2012 to a depth of 25 (ft).	
Surface Elevation (ft) Vertical Datum 14.3948 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured 12/10/2012	
Easting (X) Northing (Y) 372934.1281 1309088.27		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 5.0 Elevation (ft) 9.4	
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-05D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-9
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: L:\Template\GEOENGINEERS\GDT\GELB_ENVIRONMENTAL_WELL

Drilled	<u>Start</u> 12/10/2012	<u>End</u> 12/10/2012	Total Depth (ft)	9	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-011 A 2 (in) well was installed on 12/10/2012 to a depth of 25 (ft).		
Surface Elevation (ft) Vertical Datum	14.4241 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	372938.3312 1309085.133				Horizontal Datum	WA State Plane North 83/91				
<u>Groundwater</u> Date Measured Depth to Water (ft) Elevation (ft)										
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-05S



Project: Everett Lowland
Project Location: Everett, Washington
Project Number: 0504-068-00

Figure A-10
Sheet 1 of 1

Start Drilled 12/27/2012	End 12/27/2012	Total Depth (ft) 28.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-092 A 2 (in) well was installed on 12/27/2012 to a depth of 28.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 12.7123	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y) 372472.7325 1309133.872	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft)		
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-06D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-11
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LibTemplate: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 12/27/2012	End 12/27/2012	Total Depth (ft)	7	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-091 A 2 (in) well was installed on 12/27/2012 to a depth of 28.5 (ft).		
Surface Elevation (ft) Vertical Datum	12.7338 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	372477.6634 1309132.426				Horizontal Datum	WA State Plane North 83/91				
Notes:										




Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\Template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-06S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/7/2012	End 12/7/2012	Total Depth (ft) 25	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-009 A 2 (in) well was installed on 12/7/2012 to a depth of 25 (ft).	
Surface Elevation (ft) Vertical Datum NAVD88 14.088		Top of Casing Elevation (ft)		Groundwater Date Measured	
Easting (X) Northing (Y) 372580.8285 1309464.763		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft)	
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-07D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: L:\Template\ENVIRONMENTAL_WELL

Drilled	Start 12/7/2012	End 12/7/2012	Total Depth (ft)	9	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-50 Turbo Track Rig		DOE Well I.D.: BHU-008 A 2 (in) well was installed on 12/7/2012 to a depth of 25 (ft).		
Surface Elevation (ft) Vertical Datum	14.057 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	372578.2673 1309467.087				Horizontal Datum	WA State Plane North 83/91				
Notes:										

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
0										
5							See LLMW-07D for sampling and material description			
9.0'										

Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-07S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-14
 Sheet 1 of 1

Start Drilled 12/10/2012	End 12/11/2012	Total Depth (ft) 25.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-012 A 2 (in) well was installed on 12/10/2012 to a depth of 25.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 13.4459	Top of Casing Elevation (ft)		Groundwater Date Measured 12/10/2012		
Easting (X) Northing (Y) 372209.3701 1309788.569	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 5.5 Elevation (ft) 7.9		
Notes:					




Log of Monitoring Well LLMW-08D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\TEMPLATE\ENVIRONMENTAL_WELL

Start Drilled 12/10/2012	End 12/11/2012	Total Depth (ft) 10	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-013 A 2 (in) well was installed on 12/10/2012 to a depth of 25.5 (ft).	
Surface Elevation (ft) Vertical Datum 13.2146 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured	
Easting (X) Northing (Y) 372213.2542 1309788.249		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft)	
Notes:					




Log of Monitoring Well LLMW-08S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-16
 Sheet 1 of 1

Drilled	Start 12/6/2012	End 12/6/2012	Total Depth (ft)	27	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-006 A 2 (in) well was installed on 12/6/2012 to a depth of 27 (ft).		
Surface Elevation (ft) Vertical Datum	13.1786 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	371933.0232 1309291.53				Horizontal Datum	WA State Plane North 83/91				
Notes:										



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-09D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB: Template\lib\Template\GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Drilled	Start 12/6/2012	End 12/6/2012	Total Depth (ft)	6	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-007 A 2 (in) well was installed on 12/6/2012 to a depth of 27 (ft).		
Surface Elevation (ft) Vertical Datum	13.1484 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured		
Easting (X) Northing (Y)	371929.4722 1309290.945				Horizontal Datum	WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)										
Notes:										

Elevation (feet)	FIELD DATA							MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level	Graphic Log				
0								See LLMW-09D for sampling and material description			
5											


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-09S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/11/2012	End 12/11/2012	Total Depth (ft) 31.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-014 A 2 (in) well was installed on 12/11/2012 to a depth of 31.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 13.1425	Top of Casing Elevation (ft)		Groundwater Date Measured 12/11/2012		
Easting (X) Northing (Y) 371725.4255 1309359.407	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 24.0 Elevation (ft) -10.9		
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-10D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB: Template: LIB\TEMPLATE\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 12/11/2012	End 12/11/2012	Total Depth (ft)	6.5	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-015 A 2 (in) well was installed on 12/11/2012 to a depth of 31.5 (ft).			
Surface Elevation (ft) Vertical Datum	13.183 NAVD88			Top of Casing Elevation (ft)						
Easting (X) Northing (Y)	371722.2934 1309357.791			Horizontal Datum	WA State Plane North 83/91					
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-10S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-20
 Sheet 1 of 1

Start Drilled 12/13/2012	End 12/13/2012	Total Depth (ft) 22.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-040 A 2 (in) well was installed on 12/13/2012 to a depth of 22.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 16.0257	Top of Casing Elevation (ft)		Groundwater Date Measured 1/2/2013		
Easting (X) Northing (Y) 371822.9079 1310350.261	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 4.5		Elevation (ft) 11.5
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-11D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: L:\Template\GEOENGINEERS\GDT\GEBL_ENVIRONMENTAL_WELL

Drilled	Start 12/13/2012	End 12/13/2012	Total Depth (ft)	9.5	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment	CME 850 Track Rig			DOE Well I.D.: BHU-041 A 2 (in) well was installed on 12/13/2012 to a depth of 22.5 (ft).		
Surface Elevation (ft) Vertical Datum	15.999 NAVD88			Top of Casing Elevation (ft)				Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	371826.1136 1310349.231			Horizontal Datum	WA State Plane North 83/91					
Notes:										




Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-11S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/12/2012	End 12/12/2012	Total Depth (ft) 27.5	Logged By Checked By PDR	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-016 A 2 (in) well was installed on 12/12/2012 to a depth of 27.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 13.6305	Top of Casing Elevation (ft)		Groundwater Date Measured 12/12/2012		
Easting (X) Northing (Y) 371523.5091 1309414.28	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 4.5 Elevation (ft) 9.1		
Notes:					




Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-12D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 12/12/2012	End 12/12/2012	Total Depth (ft)	7	Logged By Checked By	PDR	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-017 A 2 (in) well was installed on 12/12/2012 to a depth of 27.5 (ft).			
Surface Elevation (ft) Vertical Datum	13.8405 NAVD88				Top of Casing Elevation (ft)			<u>Groundwater</u>	Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	371520.5241 1309412.436				Horizontal Datum	WA State Plane North 83/91					
Notes:											



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-12S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-24
 Sheet 1 of 1

Start Drilled 12/17/2012	End 12/17/2012	Total Depth (ft) 37	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-045 A 2 (in) well was installed on 12/17/2012 to a depth of 37 (ft).		
Surface Elevation (ft) Vertical Datum 18.4782 NAVD88	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y) 371682.4624 1309793.149	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)					
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-13D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-25
 Sheet 1 of 2

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB: Template\LIB\Template:GEOENGINEERS.GDT\GEBL_ENVIRONMENTAL_WELL

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA							MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG	
	Interval	Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level	Graphic Log				Group Classification	
35	17	61							NS		35.0'	
											37.0'	


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-13D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 12/17/2012	End 12/17/2012	Total Depth (ft)	18	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850 Track Rig		DOE Well I.D.: BHU-044 A 2 (in) well was installed on 12/17/2012 to a depth of 37 (ft).		
Surface Elevation (ft) Vertical Datum	18.4337 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	371682.6131 1309796.93				Horizontal Datum	WA State Plane North 83/91				
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-13S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-26
 Sheet 1 of 1

Start Drilled 12/12/2012	End 12/12/2012	Total Depth (ft) 31	Logged By PDR Checked By	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-018 A 2 (in) well was installed on 12/12/2012 to a depth of 31 (ft).		
Surface Elevation (ft) Vertical Datum 12.4895 NAVD88	Top of Casing Elevation (ft)		Groundwater Date Measured 12/12/2012		
Easting (X) Northing (Y) 371375.9911 1309449.16	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 4.5		Elevation (ft) 8.0
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-14D



Project: Everett Lowland
Project Location: Everett, Washington
Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 12/12/2012	End 12/12/2012	Total Depth (ft)	6	Logged By Checked By	PDR	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-019 A 2 (in) well was installed on 12/12/2012 to a depth of 31 (ft).		
Surface Elevation (ft) Vertical Datum	12.4877 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured		
Easting (X) Northing (Y)	371374.1753 1309446.946				Horizontal Datum	WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)										
Notes:										




Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\Template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-14S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/13/2012	End 12/13/2012	Total Depth (ft)	34	Logged By Checked By	PDR	Driller Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-020 A 2 (in) well was installed on 12/13/2012 to a depth of 34 (ft).	
Surface Elevation (ft) Vertical Datum	13.0987 NAVD88			Top of Casing Elevation (ft)			<u>Groundwater</u> Date Measured	Depth to Water (ft) Elevation (ft)
Easting (X) Northing (Y)	371053.2175 1309536.612			Horizontal Datum	WA State Plane North 83/91		12/13/2012	6.0 7.1
Notes:								



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-15D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB: Template\lib\Template:GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Start Drilled 12/13/2012	End 12/13/2012	Total Depth (ft)	9.5	Logged By Checked By	PDR	Driller Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data		140 (lbs) / 30 (in) Drop		Drilling Equipment		Diedrich D-120		
Surface Elevation (ft)		13.2143		Top of Casing Elevation (ft)		DOE Well I.D.: BHU-021 A 2 (in) well was installed on 12/13/2012 to a depth of 34 (ft).		
Vertical Datum		NAVD88				Groundwater		
Easting (X)		371051.1506		Horizontal Datum		WA State Plane North 83/91		
Northing (Y)		1309535.419				Date Measured		
						Depth to Water (ft)		
						Elevation (ft)		
Notes:								




Log of Monitoring Well LLMW-15S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-30
 Sheet 1 of 1

Start Drilled 12/14/2012	End 12/14/2012	Total Depth (ft) 34	Logged By PDR	Checked By	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-042 A 2 (in) well was installed on 12/14/2012 to a depth of 34 (ft).			
Surface Elevation (ft) Vertical Datum NAVD88	17.1441	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y)	371158.166 1310160.437	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft)	Elevation (ft)	
Notes:						



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-16D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENV\IRONMINTAL_WELL

Drilled	Start 12/14/2012	End 12/14/2012	Total Depth (ft)	12	Logged By Checked By	PDR	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850 Track Rig		DOE Well I.D.: BHU-043 A 2 (in) well was installed on 12/14/2012 to a depth of 34 (ft).		
Surface Elevation (ft) Vertical Datum	17.1917 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	371159.2967 1310164.452				Horizontal Datum	WA State Plane North 83/91		Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-16S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-32
 Sheet 1 of 1

Start Drilled 12/12/2012	End 12/13/2012	Total Depth (ft) 25.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-038 A 2 (in) well was installed on 12/12/2012 to a depth of 25.5 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 15.2671	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y) 371317.6575 1310603.072	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)					
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-17D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB: Template\1b\Template\ENVIRONMENTAL_WELL

Drilled	Start 12/12/2012	End 12/13/2012	Total Depth (ft)	11	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850 Track Rig		DOE Well I.D.: BHU-039 A 2 (in) well was installed on 12/12/2012 to a depth of 25.5 (ft).		
Surface Elevation (ft) Vertical Datum	15.3209 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	371320.3207 1310602.283				Horizontal Datum	WA State Plane North 83/91		Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:										




Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\Template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-17S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/13/2012	End 12/13/2012	Total Depth (ft) 30	Logged By PDR Checked By	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-022 A 2 (in) well was installed on 12/13/2012 to a depth of 30 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88	13.1053	Top of Casing Elevation (ft)		Groundwater Date Measured 12/13/2012	
Easting (X) Northing (Y)	370391.758 1309718.714	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 4.0	Elevation (ft) 9.1
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-18D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Drilled	Start 12/13/2012	End 12/13/2012	Total Depth (ft)	7.5	Logged By Checked By	PDR	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-023 A 2 (in) well was installed on 12/13/2012 to a depth of 30 (ft).		
Surface Elevation (ft) Vertical Datum	13.2735 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured		
Easting (X) Northing (Y)	370389.0772 1309715.292				Horizontal Datum	WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)										
Notes:										



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-18S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-36
 Sheet 1 of 1

Start Drilled 12/6/2012	End 12/6/2012	Total Depth (ft) 27	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-005 A 2 (in) well was installed on 12/6/2012 to a depth of 27 (ft).		
Surface Elevation (ft) Vertical Datum NAVD88 11.642	Top of Casing Elevation (ft)		Groundwater Date Measured		
Easting (X) Northing (Y) 370189.3895 1310224.846	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)					
Notes:					



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-19D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-06800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Start Drilled 12/12/2012	End 12/12/2012	Total Depth (ft) 21	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-037 A 2 (in) well was installed on 12/12/2012 to a depth of 21 (ft).	
Surface Elevation (ft) Vertical Datum 11.3205 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured 12/12/2012	
Easting (X) Northing (Y) 370542.4429 1310748.178		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 3.0 Elevation (ft) 8.3	
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-20D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-38
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LibTemplate: GEOENGINEERS.GDT Template: LIB\ENVIRONMENTAL_WELL

Start Drilled 12/20/2012	End 12/20/2012	Total Depth (ft) 33	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-025 A 2 (in) well was installed on 12/20/2012 to a depth of 33 (ft).		
Surface Elevation (ft) Vertical Datum 13.2943 NAVD88	Top of Casing Elevation (ft)		Groundwater Date Measured 12/20/2012		
Easting (X) Northing (Y) 370011.1759 1309881.28	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 5.0		Elevation (ft) 8.3
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-21D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GEI6_ENVIRONMENTAL_WELL

Drilled	<u>Start</u> 12/20/2012	<u>End</u> 12/20/2012	Total Depth (ft)	7	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		A 2 (in) well was installed on 12/20/2012 to a depth of 33 (ft).		
Surface Elevation (ft) Vertical Datum	13.6214 NAVD88				Top of Casing Elevation (ft)			<u>Groundwater</u>	<u>Depth to</u> <u>Water (ft)</u>	<u>Elevation (ft)</u>
Easting (X) Northing (Y)	370010.9467 1309885.453				Horizontal Datum	WA State Plane North 83/91		<u>Date Measured</u>		
Notes:										

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
0										
5							See LLMW-21D for sampling and material description			

Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-21S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-40
 Sheet 1 of 1

Drilled	Start 12/5/2012	End 12/5/2012	Total Depth (ft)	27	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120			DOE Well I.D.: BHU-003 A 2 (in) well was installed on 12/5/2012 to a depth of 27 (ft).		
Surface Elevation (ft) Vertical Datum	13.1426 NAVD88				Top of Casing Elevation (ft)				Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)	369167.8357 1310446.091				Horizontal Datum	WA State Plane North 83/91					
Notes:											



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-22D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-41
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-06800.GPJ DB: Template\LIB\Template:GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Drilled	Start 12/5/2012	End 12/5/2012	Total Depth (ft)	7	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-004 A 2 (in) well was installed on 12/5/2012 to a depth of 27 (ft).		
Surface Elevation (ft) Vertical Datum	13.1787 NAVD88				Top of Casing Elevation (ft)			Groundwater Date Measured		
Easting (X) Northing (Y)	369173.009 1310445.634				Horizontal Datum	WA State Plane North 83/91		Depth to Water (ft)		
Elevation (ft)										
Notes:										

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
0										
5							See LLMW-22D for sampling and material description			

Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-22S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-42
 Sheet 1 of 1

Start Drilled 12/4/2012	End 12/5/2012	Total Depth (ft) 40	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment Diedrich D-120		DOE Well I.D.: BHU-001 A 2 (in) well was installed on 12/4/2012 to a depth of 40 (ft).	
Surface Elevation (ft) Vertical Datum 25.9105 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured	
Easting (X) Northing (Y) 368226.9076 1310278.89		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft)	
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-23D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
35	18	31		35-36				NS		<p>2-inch Schedule 40 PVC screen, 0.01-inch slot width</p>
	12	37						NS		
40										


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-23D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 12/4/2012	End 12/5/2012	Total Depth (ft)	24	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment	Diedrich D-120		DOE Well I.D.: BHU-002 A 2 (in) well was installed on 12/4/2012 to a depth of 40 (ft).			
Surface Elevation (ft) Vertical Datum	25.9515 NAVD88			Top of Casing Elevation (ft)						
Easting (X) Northing (Y)	368222.1107 1310277.448			Horizontal Datum	WA State Plane North 83/91		Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)	
Notes:										



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-23S




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-44
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LibTemplate: GEOENGINEERS.GDT\GEBL_ENVIRONMENTAL_WELL

Start Drilled 12/20/2012	End 12/20/2012	Total Depth (ft) 56.5	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment CME 850 Track Rig		A 2 (in) well was installed on 12/21/2012 to a depth of 56.5 (ft).	
Surface Elevation (ft) Vertical Datum 54.6587 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured 12/20/2012	
Easting (X) Northing (Y) 371665.5506 1308321.72		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft) 45.0 9.7	
Notes:					




Log of Boring LLMW-24D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LibTemplate: GEOENGINEERS.GDT\GEI6_ENVIRONMENTAL_WELL



Note: Please see Figure A-1 for explanation of symbols


Log of Boring LLMW-24D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-45
 Sheet 2 of 2

Start Drilled 12/19/2012	End 12/19/2012	Total Depth (ft) 65	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop		Drilling Equipment CME 850 Track Rig		A 2 (in) well was installed on 12/19/2012 to a depth of 65 (ft).	
Surface Elevation (ft) Vertical Datum 61.9771 NAVD88		Top of Casing Elevation (ft)		Groundwater Date Measured 12/19/2012	
Easting (X) Northing (Y) 371489.9394 1308367.759		Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) Elevation (ft) 55.0 7.0	
Notes:					



Note: Please see Figure A-1 for explanation of symbols

Log of Boring LLMW-25D




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB Template: GEOENGINEERS.GDT\GEI6_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
35		11	50/5"				Grades moist			
40		18	78	40-41		SP	Brown fine to medium sand, trace silt (dense, moist) (outwash) Grades very dense	NS		
45		11	50/5"					NS		
50		9	50/3"				Grades to fine sand, trace silt (very dense, moist) Grades fine to medium sand, trace silt Grades wet			
55		11	50/5"	55-56				NS		
60		12	50/6"							
65										

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\Template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Note: Please see Figure A-1 for explanation of symbols




Log of Boring LLMW-25D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-46
 Sheet 2 of 2

Drilled	Start 1/9/2013	End 1/9/2013	Total Depth (ft)	61.5	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment			Mobile B-59 Track Rig		DOE Well I.D.: BHU-031 A 2 (in) well was installed on 1/10/2013 to a depth of 61.5 (ft).		
Surface Elevation (ft)			61.9264		Top of Casing Elevation (ft)						
Vertical Datum			NAVD88					Groundwater			
Easting (X)			371259.2652		Horizontal Datum			WA State Plane North 83/91			
Northing (Y)			1308465.435					Date Measured		Depth to Water (ft)	Elevation (ft)
Notes:											




Log of Monitoring Well LLMW-27D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-27D (continued)




Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-47
 Sheet 2 of 2

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Drilled	Start 1/9/2013	End 1/9/2013	Total Depth (ft)	36	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Mobile B-59 Track Rig			DOE Well I.D.: BHU-032 A 2 (in) well was installed on 1/9/2013 to a depth of 61.5 (ft).		
Surface Elevation (ft) Vertical Datum	61.8712 NAVD88				Top of Casing Elevation (ft)						
Easting (X) Northing (Y)	371254.3715 1308467.345				Horizontal Datum	WA State Plane North 83/91			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:											



Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\05040680\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-27S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template:GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA							MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Interval	Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level	Graphic Log				
35											
											36.0'


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-27S (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 1/8/2013	End 1/8/2013	Total Depth (ft)	61.5	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop		Drilling Equipment		Mobile B-59 Track Rig		DOE Well I.D.: BHU-028 A 2 (in) well was installed on 1/8/2013 to a depth of 61.5 (ft).			
Surface Elevation (ft)		56.0371		Top of Casing Elevation (ft)						
Vertical Datum		NAVD88		Groundwater Date Measured		1/8/2013		Depth to Water (ft)	11.9	
Easting (X)		370982.4647		Horizontal Datum		WA State Plane North 83/91				
Northing (Y)		1308556.215								
Notes:										




Log of Monitoring Well LLMW-29D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB Template: GEOENGINEERS.GDT/GEI6_ENVIRONMENTAL_WELL

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: Lib\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-29D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 1/8/2013	End 1/8/2013	Total Depth (ft)	10	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	Mobile B-59 Track Rig			DOE Well I.D.: BHU-029 A 2 (in) well was installed on 1/8/2013 to a depth of 61.5 (ft).	
Surface Elevation (ft) Vertical Datum	55.9093 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	370978.6854 1308557.008				Horizontal Datum	WA State Plane North 83/91				
Notes:										

Elevation (feet)	FIELD DATA							MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level	Graphic Log				
0											
5											
10											

Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-29S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-50
 Sheet 1 of 1

Drilled	Start 1/23/2013	End 1/23/2013	Total Depth (ft)	64	Logged By Checked By	GRL	Driller	Holocene	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850		A 2 (in) well was installed on 1/23/2013 to a depth of 64 (ft).		
Surface Elevation (ft) Vertical Datum	59				Top of Casing Elevation (ft)			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Easting (X) Northing (Y)					Horizontal Datum			1/23/2013	46.0	13.0
Notes:										




Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-31D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: I:\Template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-31D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-51
 Sheet 2 of 2

Drilled	Start 1/3/2013	End 1/7/2013	Total Depth (ft)	45.5	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger	
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment			Mobile B-59 Track Rig		DOE Well I.D.: BHU-094 A 2 (in) well was installed on 1/7/2013 to a depth of 45.5 (ft).		
Surface Elevation (ft) Vertical Datum			37.5673 NAVD88		Top of Casing Elevation (ft)						
Easting (X) Northing (Y)			369961.949 1308914.525		Horizontal Datum			WA State Plane North 83/91			
Groundwater Date Measured			Depth to Water (ft)		Elevation (ft)						
Notes:											



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-33D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GEB_ENVIRONMENTAL_WELL

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	WELL LOG
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name	Water Level				
35							dense, wet) (advance outwash)			
35	35.0	14	50/4"					NS		
40	39.0	13	50/3"	39-40				NS		
45	45.0	18	77				Becomes dense	NS		


Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-33D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Drilled	Start 1/3/2013	End 1/7/2013	Total Depth (ft)	10.5	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop			Drilling Equipment	Mobile B-59 Track Rig			DOE Well I.D.: BHU-095 A 2 (in) well was installed on 1/7/2013 to a depth of 45.5 (ft).		
Surface Elevation (ft) Vertical Datum	37.7314 NAVD88			Top of Casing Elevation (ft)				Groundwater Date Measured		
Easting (X) Northing (Y)	369957.8312 1308912.956			Horizontal Datum	WA State Plane North 83/91			Depth to Water (ft)		
Elevation (ft)										
Notes:										




Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-33S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Start Drilled 12/20/2012	End 12/20/2012	Total Depth (ft) 75.3	Logged By Checked By AMW	Driller Holocene Drilling	Drilling Method Hollow-stem Auger
Hammer Data 140 (lbs) / 30 (in) Drop	Drilling Equipment CME 850 Track Rig		DOE Well I.D.: BHU-046 A 2 (in) well was installed on 12/19/2012 to a depth of 75.3 (ft).		
Surface Elevation (ft) Vertical Datum 53.2995 NAVD88	Top of Casing Elevation (ft)		Groundwater Date Measured 12/19/2012		
Easting (X) Northing (Y) 368696.1556 1308930.669	Horizontal Datum WA State Plane North 83/91		Depth to Water (ft) 70.0 Elevation (ft) -16.7		
Notes:					




Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well LLMW-34D



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-06800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL



Note: Please see Figure A-1 for explanation of symbols


Log of Monitoring Well LLMW-34D (continued)



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: LIB\Template: GEOENGINEERS.GDT\GEI6_ENVIRONMENTAL_WELL

Drilled	Start 12/20/2012	End 12/20/2012	Total Depth (ft)	12	Logged By Checked By	AMW	Driller	Holocene Drilling	Drilling Method	Hollow-stem Auger
Hammer Data	140 (lbs) / 30 (in) Drop				Drilling Equipment	CME 850 Track Rig		DOE Well I.D.: BHU-047 A 2 (in) well was installed on 12/20/2012 to a depth of 75.3 (ft).		
Surface Elevation (ft) Vertical Datum	53.2239 NAVD88				Top of Casing Elevation (ft)					
Easting (X) Northing (Y)	368693.8425 1308931.771				Horizontal Datum	WA State Plane North 83/91				
Notes:										



Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\template\GEOENGINEERS.GDT\GELB_ENVIRONMENTAL_WELL

Log of Monitoring Well LLMW-34S



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-55
 Sheet 1 of 1

Drilled	Start 1/7/2013	End 1/7/2013	Total Depth (ft)	20	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Direct Push
Surface Elevation (ft) Vertical Datum	12.6436 NAVD88			Hammer Data	Pneumatic			Drilling Equipment	AMS Powerprobe 9500 D	
Easting (X) Northing (Y)	373990.7175 1306949.75			System Datum	WA State Plane North 83/91			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:										

Elevation (feet)	FIELD DATA					Water Level	Graphic Log	Group Classification	MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	REMARKS
	Interval	Recovered (in)	Blows/foot	Collected Sample	Sample Name Testing							
0		36					GP	Gray fine to coarse gravel with sand, trace silt (moist) (fill)	NS			
10							Wood	Brown wood debris				
5		40		4-5			SP-SM	Brown fine to coarse sand with silt and gravel, trace wood debris (moist) (fill) Grades to wet at 5 feet	NS			
5				6-7			Wood	Brown wood debris with brown fine to medium sand with silt, occasional gravel (wet) (fill)	NS			
10		40					SP-SM	Brown fine to coarse sand with silt and gravel, trace wood debris (wet) (fill)	NS			
10				10.8-11			ML	Brown silt, trace organics (wet) (native)	NS			
15				13-14				Grades with 1 inch sand interbeds Grades with wood, trace sand	NS			
15		48					SP	Gray fine to medium sand, trace silt, trace wood (wet)	NS			
20				19-20					NS			

Note: Please see Figure A-1 for explanation of symbols

Log of Boring LLSB-01



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Figure A-56
 Sheet 1 of 1

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template: I:\Template\GEOENGINEERS.GDT\GEL_ENVIRONMENTAL_STANDARD

Drilled	Start 1/7/2013	End 1/7/2013	Total Depth (ft)	20	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Direct Push
Surface Elevation (ft) Vertical Datum	14.7497 NAVD88			Hammer Data	Pneumatic			Drilling Equipment	AMS Powerprobe 9500 D	
Easting (X) Northing (Y)	373634.9832 1307691.419			System Datum	WA State Plane North 83/91			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:										

Elevation (feet)	FIELD DATA					Water Level	Graphic Log	Group Classification	MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	REMARKS
	Interval Depth (feet)	Recovered (in)	Blows/foot	Collected Sample	Sample Name Testing							
0	30						SP	Dark brown fine to coarse sand, trace silt, occasional gravel (moist) (fill)				
							SP	Brown-orange fine to medium sand (moist) (fill)				
				3-4				Gravel				
5	48							Grades to brown				
								Grades to wet				
								Grades to medium to coarse sand				
10	48						ML	Gray silt, trace organics (wet) (native)				
				10-10.2			Wood	Wood (wet)				
				10.6-10.8				Gray silt, trace organics, trace sand (wet)				
				12-13			ML	Grades sandy silt				
15	40						SP	Gray fine sand, trace silt, trace wood (wet)				
				15-16				Grades fine to medium				
								Lacks wood				
								Grades <1cm layers of wood				
20												

Note: Please see Figure A-1 for explanation of symbols

Log of Boring LLSB-02



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504-068\GINT\0504-06800.GPJ DB Template: Lib\Template: GEOENGINEERS.GDT\GEL_ENVIRONMENTAL_STANDARD

Drilled	Start 1/7/2013	End 1/7/2013	Total Depth (ft)	20	Logged By Checked By	GRL	Driller	Holocene Drilling	Drilling Method	Direct Push
Surface Elevation (ft) Vertical Datum	15.0686 NAVD88			Hammer Data	Pneumatic			Drilling Equipment	AMS Powerprobe 9500 D	
Easting (X) Northing (Y)	373543.2766 1308050.649			System Datum	WA State Plane North 83/91			Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
Notes:										

Elevation (feet)	FIELD DATA						MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)	REMARKS			
	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name Testing	Water Level					Graphic Log	Group Classification	
0	44						SP			Brown fine to medium sand (moist) (fill)			
				2-3							NS		
				3-4							NS		
5	46									Grades to brown-orange			
											NS		
	48												
10				9.5-10.5			SP			Gray fine to coarse sand trace silt (wet) (fill)			
				11-11.2							NS		
	40						ML			Gray silt, trace organics (wet) (native)			
				13-14							NS		
15													
	44						SP			Gray fine to medium sand, trace silt (wet)			
											NS		
				19-20							NS		
20										Refusal due to heaving sands (wet)			

Seattle: Date: 5/16/13 Path: W:\SEATTLE\PROJECTS\0504068\GINT\050406800.GPJ DB Template\lib\Template\GEOENGINEERS.GDT\GEL_ENVIRONMENTAL_STANDARD

Note: Please see Figure A-1 for explanation of symbols

Log of Boring LLSB-03



Project: Everett Lowland
 Project Location: Everett, Washington
 Project Number: 0504-068-00



APPENDIX B
Survey Data

Garrett R. Leque

From: Garrett R. Leque
Sent: Monday, February 11, 2013 9:05 AM
To: Aaron M. Waggoner
Subject: FW: Monitor Wells-Everett Smelter
Attachments: GEOE0020-FIELD NOTES.pdf

From: Gil Laas [<mailto:GJLA@deainc.com>]
Sent: Wednesday, January 23, 2013 12:34 PM
To: Garrett R. Leque
Subject: Monitor Wells-Everett Smelter

Garrett,

Attached is a spread sheet with all the wells we located over the last few days. The format is as such: Point number, Northing, Easting, Elevation, and description. The descriptions are as follows: TOP CASE= top of metal lid to well. PVC NORTH=north edge of pvc pipe inside the well. GROUND= a ground shot elevation adjacent to well in areas in which the well case is NOT flush with the ground. In areas in which the lid was flush with the ground we did not measure a separate ground elevation.

Wells LLMW-31S and LLMW-31D were not set at the time of this survey.

I also included a copy of the surveyor's field notes for your reference.

The coordinate system is Washington State Plane North coordinate system 83/91 in grid values. Vertical datum is NAVD88. US survey feet.

Please call with any comments or questions.

Thanks


Gil Laas, P.L.S., C.Fed.S,

Project Surveyor | Associate

David Evans and Associates, Inc. | Surveying and Geomatics

1620 W, Marine View Dr, Suite 200 | Everett, WA 98201 | www.deainc.com

d: 425.405.1513 | c: 360.739.9853 | gjla@deainc.com



LLMW-31D was surveyed January 28, 2013 and has been included in the table below. LLMW-31S was not installed.

Carly Nadasky

From: Garrett R. Leque
Sent: Monday, February 11, 2013 9:04 AM
To: Aaron M. Waggoner
Subject: FW: Monitor Wells-Everett Smelter
Attachments: GRID-GEOE0118-0121CAG-WITH DESCRIPTION.csv

From: Gil Laas [<mailto:GJLA@deainc.com>]
Sent: Monday, January 28, 2013 10:43 AM
To: Garrett R. Leque
Subject: RE: Monitor Wells-Everett Smelter

Garrett,

Here is the updated spreadsheet with the last well.

Stop by anytime for the keys.

Gil

From: Garrett R. Leque [<mailto:glogue@geoengineers.com>]
Sent: Monday, January 28, 2013 9:35 AM
To: Gil Laas
Subject: RE: Monitor Wells-Everett Smelter

ok sounds good. There is one well; LLMW31D, and it is located across the street (east of) from the location shown on the Figure I sent you. It is located just north of the little City park that overlooks the industrial area. It is a flush well with one stickup bollard...

Thanks,
G

From: Gil Laas [<mailto:GJLA@deainc.com>]
Sent: Monday, January 28, 2013 9:33 AM
To: Garrett R. Leque
Subject: RE: Monitor Wells-Everett Smelter

Garrett,

We will shoot the two new wells this morning. I will send you the updated info by the end of the day. No worries about budget.

You can have someone pick up the keys this afternoon or tomorrow.

Thanks

Gil

From: Garrett R. Leque [<mailto:glogue@geoengineers.com>]
Sent: Monday, January 28, 2013 9:12 AM
To: Gil Laas
Subject: RE: Monitor Wells-Everett Smelter

Thanks!

After DEA did the work we installed one more well; LLMW31. Do you think it would be possible to get that included within the budget?

Thanks,
G

From: Gil Laas [<mailto:GJLA@deainc.com>]
Sent: Wednesday, January 23, 2013 12:34 PM
To: Garrett R. Leque
Subject: Monitor Wells-Everett Smelter

Garrett,

Attached is a spread sheet with all the wells we located over the last few days. The format is as such: Point number, Northing, Easting, Elevation, and description. The descriptions are as follows: TOP CASE= top of metal lid to well. PVC NORTH=north edge of pvc pipe inside the well. GROUND= a ground shot elevation adjacent to well in areas in which the well case is NOT flush with the ground. In areas in which the lid was flush with the ground we did not measure a separate ground elevation.

Wells LLMW-31S and LLMW-31D were not set at the time of this survey.

I also included a copy of the surveyor's field notes for your reference.

The coordinate system is Washington State Plane North coordinate system 83/91 in grid values. Vertical datum is NAVD88. US survey feet.

Please call with any comments or questions.

Thanks

Gil Laas, P.L.S., C.Fed.S,

Project Surveyor | Associate

David Evans and Associates, Inc. | Surveying and Geomatics

1620 W. Marine View Dr. Suite 200 | Everett, WA 98201 | www.deainc.com

d: 425.405.1513 | c: 360.739.9853 | gjla@deainc.com

Confidentiality: This message is confidential and intended solely for use of the individual or entity to whom it is addressed. If you are not the person for whom this message is intended, please delete it and notify me immediately, and please do not copy or send this message to anyone else.

Appendix B
Survey Data

Point Number	Northing	Easting	Elevation	Description
10000	373999.5776	1306940.8470	12.46	1501R-TOP CASE
10001	373999.2866	1306940.8230	11.94	1501R PVC NORTH
10002	373990.7175	1306949.7500	12.64	LLSB-1
10003	373634.9832	1307691.4190	14.75	LLSB-2
10004	373543.2766	1308050.6490	15.07	LLSB-3
10005	373911.1708	1307952.9290	16.08	01D-TOP CASE
10006	373910.9344	1307952.7240	15.74	01D-PVC NORTH
10007	373726.9180	1307221.6340	20.54	MW-UNK-TOP CASE
10008	373726.7456	1307221.4940	20.05	MW-UNK-PVC NORTH
10009	373729.7908	1307217.3640	15.98	MW-UNK-GROUND
10010	373617.7071	1307454.3610	17.19	MW-UNK-2-TOP BASE AT GROUND-BENT
10011	372887.0090	1307921.3900	15.38	02D-TOP CASE
10012	372886.6753	1307921.1850	15.15	02D PVC NORTH
10013	372968.6297	1308356.2020	17.64	03S-TOP CASE
10014	372968.3797	1308356.3800	17.45	03S-PVC NORTH
10015	372968.4709	1308355.5780	14.52	03S-GROUND
10016	372965.2847	1308351.9080	17.79	03D-TOP CASE
10017	372965.2972	1308351.7320	17.45	03D-PVC NORTH
10018	372965.5718	1308351.5110	14.43	03D-GROUND
10019	372938.3312	1309085.1330	14.42	05S-TOP CASE
10020	372938.0230	1309084.8030	14.05	05S-PVC NORTH
10021	372934.1281	1309088.2700	14.39	05D-TOP CASE
10022	372933.9143	1309087.9300	13.92	05D-PVC NORTH
10023	372578.2673	1309467.0870	14.06	07S-TOP CASE
10024	372578.1202	1309467.2720	13.82	07S-PVC NORTH
10025	372580.8285	1309464.7630	14.09	07D-TOP CASE
10026	372580.6617	1309464.9380	13.81	07D-PVC NORTH
10027	372477.6634	1309132.4260	12.73	06S-TOP CASE
10028	372477.2658	1309132.4950	12.49	06S-PVC NORTH
10029	372472.7325	1309133.8720	12.71	06D-TOP CASE
10030	372472.4759	1309133.8230	12.29	06D-PVC NORTH
10031	371929.4722	1309290.9450	13.15	09S-TOP CASE
10032	371929.1754	1309290.9440	12.57	09S-PVC NORTH
10033	371933.0232	1309291.5300	13.18	09D-TOP CASE
10034	371932.7400	1309291.5290	12.79	09D-PVC NORTH
10035	372212.5643	1309788.4460	16.65	08S-TOP CASE
10036	372212.3650	1309788.4670	16.21	08S-PVC NORTH
10037	372213.2542	1309788.2490	13.21	08S-GROUND
10038	372208.8338	1309788.8870	16.62	08D-TOP CASE
10039	372208.7778	1309789.0540	16.26	08D-PVC NORTH
10040	372209.3701	1309788.5690	13.45	08D-GROUND
10041	371825.3721	1310349.5720	19.88	11S-TOP CASE
10042	371825.3634	1310349.5860	19.76	11S-PVC NORTH
10043	371826.1136	1310349.2310	16.00	11S-GROUND
10044	371822.0995	1310350.8190	19.86	11D-TOP CASE
10045	371821.8957	1310350.7800	19.71	11D-PVC NORTH
10046	371822.9079	1310350.2610	16.03	11D-GROUND
10050	371319.7638	1310602.2140	18.53	17S-TOP CASE
10051	371319.6439	1310602.2280	18.27	17S-PVC NORTH
10052	371320.3207	1310602.2830	15.32	17S-GROUND
10053	371317.1396	1310602.9420	18.63	17D-TOP CASE
10054	371317.0587	1310602.9620	18.29	17D-PVC NORTH
10055	371317.6575	1310603.0720	15.27	17D-GROUND
10056	370542.1375	1310748.1650	15.11	20D-TOP CASE
10057	370541.8637	1310748.3440	14.92	20D-PVC NORTH
10058	370542.4429	1310748.1780	11.32	20D-GROUND

Point Number	Northing	Easting	Elevation	Description
10059	370543.0710	1310753.2670	11.23	PZ-3B-PVC NORTH
10060	370542.7696	1310753.2970	11.75	PZ-3B-TOP CASE
10061	370504.9847	1310755.1880	14.16	PZ-3A-PVC NORTH
10062	370504.7144	1310755.0800	14.74	PZ-3A-TOP CASE
10063	370188.7720	1310224.8770	14.60	19D-TOP CASE
10064	370188.5613	1310224.9320	14.22	19D-PVC NORTH
10065	370189.3895	1310224.8460	11.64	19D-GROUND
10066	370205.8714	1310306.7650	11.34	PZ-1B-PVC NORTH
10067	370205.6506	1310306.9870	13.74	PZ-1B-TOP CASE
10068	370216.1134	1310344.1870	13.33	PZ-1A-PVC NORTH
10069	370089.9137	1310537.2860	12.99	PZ-2A-PVC NORTH
10070	370089.9303	1310537.3100	13.50	PZ-2A-TOP CASE
10071	370050.4818	1310539.9430	12.02	PZ-2B-PVC NORTH
10072	370050.6105	1310539.6630	12.87	PZ-2B-TOP CASE
10073	370215.8348	1310344.3790	14.47	PZ-1A-TOP CASE
10074	369172.9406	1310445.5870	12.87	22S-PVC NORTH
10075	369173.0090	1310445.6340	13.18	22S-TOP CASE
10076	369167.8989	1310446.1630	12.80	22D-PVC NORTH
10077	369167.8357	1310446.0910	13.14	22D-TOP CASE
10078	368222.2067	1310277.6010	25.54	23S-PVC NORTH
10079	368222.1107	1310277.4480	25.95	23S-TOP CASE
10080	368226.9611	1310279.1070	25.30	23D-PVC NORTH
10081	368226.9076	1310278.8900	25.91	23D-TOP CASE
10082	370010.9723	1309884.8390	16.36	21S-TOP CASE
10083	370010.7034	1309884.8900	16.04	21S-PVC NORTH
10084	370010.9467	1309885.4530	13.62	21S-GROUND
10085	370011.2226	1309881.9670	16.15	21D-TOP CASE
10086	370011.1111	1309881.9240	16.03	21D-PVC NORTH
10087	370011.1759	1309881.2800	13.29	21D-GROUND
10088	370388.7121	1309715.0820	16.26	18S-TOP CASE
10089	370388.7626	1309715.2030	15.70	18S-PVC NORTH
10090	370389.0772	1309715.2920	13.27	18S-GROUND
10091	370391.6628	1309718.2390	16.22	18D-TOP CASE
10092	370391.6398	1309718.1620	15.91	18D-PVC NORTH
10093	370391.7580	1309718.7140	13.11	18D-GROUND
10094	371050.7465	1309535.3570	16.22	15S-TOP CASE
10095	371050.5776	1309535.3370	15.94	15S-PVC NORTH
10096	371051.1506	1309535.4190	13.21	15S-GROUND
10097	371052.7439	1309536.7510	16.25	15D-TOP CASE
10098	371052.5926	1309536.6760	16.07	15D-PVC NORTH
10099	371053.2175	1309536.6120	13.10	15D-GROUND
10100	371373.4417	1309447.0550	15.31	14S-TOP CASE
10101	371373.4769	1309447.0670	14.74	14S-PVC NORTH
10102	371374.1753	1309446.9460	12.49	14S-GROUND
10103	371375.7095	1309449.0750	15.29	14D-TOP CASE
10104	371375.6023	1309449.1470	14.80	14D-PVC TOP
10105	371375.9911	1309449.1600	12.49	14D-GROUND
10106	371520.1755	1309412.6120	16.19	12S-TOP CASE
10107	371520.0860	1309412.6630	15.61	12S-PVC NORTH
10108	371520.5241	1309412.4360	13.84	12S-GROUND
10109	371522.9645	1309414.2950	16.23	12D-TOP CASE
10110	371523.0150	1309414.2620	15.71	12D-PVC NORTH
10111	371523.5091	1309414.2800	13.63	12D-GROUND
10112	371721.7620	1309357.6080	16.40	10S-TOP CASE
10113	371721.7809	1309357.9690	15.91	10S-PVC NORTH
10114	371722.2934	1309357.7910	13.18	10S-GROUND
10115	371725.0606	1309359.3290	16.34	10D-TOP CASE
10116	371724.8375	1309359.5870	15.97	10D-PVC NORTH
10117	371725.4255	1309359.4070	13.14	10D-GROUND
10118	371682.0940	1309796.8330	21.74	13S-TOP CASE

Point Number	Northing	Easting	Elevation	Description
10119	371682.0263	1309796.7690	21.49	13S-PVC NORTH
10120	371682.6131	1309796.9300	18.43	13S-GROUND
10121	371682.0029	1309793.1160	21.67	13D-TOP CASE
10122	371681.8513	1309793.0410	21.24	13D-PVC NORTH
10123	371682.4624	1309793.1490	18.48	13D-GROUND
10124	371159.1791	1310165.4720	20.23	16S-TOP CASE
10125	371158.9693	1310165.5270	20.02	16S-PVC NORTH
10126	371159.2967	1310164.4520	17.19	16S-GROUND
10127	371157.7625	1310161.3970	20.35	16D-TOP CASE
10128	371157.6532	1310161.3680	20.14	16D-PVC NORTH
10129	371158.1660	1310160.4370	17.14	16D-GROUND
10130	372644.2048	1308250.2640	22.14	04S-TOP CASE
10131	372644.1374	1308250.3910	21.91	04S-PVC NORTH
10132	372644.2517	1308249.7640	18.61	04S-GROUND
10133	372642.4795	1308246.2400	22.62	04D-TOP CASE
10134	372642.3485	1308246.3590	21.98	04D-PVC NORTH
10135	372642.8382	1308246.2520	18.89	04D-GROUND
10136	372106.4788	1308333.6660	28.82	EV-22A-TOP CASE
10137	372106.2793	1308333.5780	28.59	EV-22A-PVC NORTH
10138	372106.9332	1308333.6120	26.33	EV-22A-GROUND
10139	372111.6804	1308337.1410	29.41	EV-22B-TOP CASE
10140	372111.4369	1308337.1550	29.02	EV-22B-PVC NORTH
10141	372112.0293	1308337.8310	26.35	EV-22B-GROUND
10142	371460.1320	1308563.1640	60.96	EV-6A-PVC NORTH-SOUTHERLY
10143	371460.1068	1308563.2560	61.56	EV-6A-TOP CASE-SOUTHERLY
10144	371466.2733	1308565.2580	60.91	EV-6B-PVC NORTH-NORTHERLY
10145	371466.2012	1308565.2320	61.44	EV-6B-TOP CASE-NORTHERLY
10146	371451.3097	1308568.5600	61.65	PIEZ-PVC NORTH
10147	371451.1763	1308568.6050	61.76	PIEZ-TOP CASE
10148	371406.8325	1308516.4780	64.67	EV-20-TOP CASE
10149	371406.5816	1308516.5360	64.28	EV-20-PVC NORTH
10150	371407.2479	1308516.1020	62.05	EV-20-GROUND
10151	371355.0783	1308496.2820	61.46	EV-19B-PVC NORTH
10152	371355.0687	1308496.3590	62.02	EV-19B-TOP CASE
10153	371254.5214	1308467.3680	61.46	27S-PVC NORTH
10154	371254.3715	1308467.3450	61.87	27S-TOP CASE
10155	371259.3534	1308465.4100	61.71	27D-PVC NORTH
10156	371259.2652	1308465.4350	61.93	27D-TOP CASE
10157	371490.1217	1308367.6460	61.76	25D-PVC NORTH
10158	371489.9394	1308367.7590	61.98	25D-TOP CASE
10159	371665.5296	1308321.6810	54.28	24D-PVC NORTH
10160	371665.5506	1308321.7200	54.66	24D-TOP CASE
10161	371472.5693	1308791.7070	19.41	BP-05D2-TOP CASE
10162	371472.4120	1308791.7130	19.26	BP-05D2-PVC NORTH
10163	371472.6348	1308791.6740	15.82	BP-05D2-GROUND
10164	368693.8487	1308931.6630	52.71	34S-PVC NORTH
10165	368693.8425	1308931.7710	53.22	34S-TOP CASE
10166	368696.1675	1308930.6570	53.03	34D-PVC NORTH
10167	368696.1556	1308930.6690	53.30	34D-TOP CASE
10168	369957.9657	1308912.9620	37.42	33S-PVC NORTH
10169	369957.8312	1308912.9560	37.73	33S-TOP CASE
10170	369962.0849	1308914.4660	37.24	33D-PVC NORTH
10171	369961.9490	1308914.5250	37.57	33D-TOP CASE
10172	370978.8889	1308556.9360	55.66	29S-PVC NORTH
10173	370978.6854	1308557.0080	55.91	29S-TOP CASE
10174	370982.4785	1308556.1280	55.62	29D-PVC NORTH
10175	370982.4647	1308556.2150	56.04	29D-TOP CASE
10180	370453.0750	1308669.7880	58.41	31D-PVC NORTH
10181	370452.8170	1308669.7760	59.00	31D-TOP CASE

1-18-13 CIA JRS

Mod Code

w/ Grad 6562 564

2 286

2 286

1 113

FLUSH w/ Ground 4 564

4 4

4 4

4 4

4 270

4 564

4 4


4 4

4 270

4 564

4 4

4 270



FLUSH w/ Ground 4 4

4 4

4 4

4 4

4 270

4 564

4 4

4 270

GEOE 18CAG

DECK

10,000 MW 150 IR NORTH Rim FLUSH

10,001 " TOP N. Rim PVC - 0.2 TO PVC

10,002 SOIL Log 6562-1

10,003 " " 6562-2

10,004 " " 6562-3

8 EGGS COE MON / SHOT

10,005 LL MW - OLD NORTH Rim LID

10,006 " " " PVC

10,007 MON FOR WCH DNK N. Rim LID

10,008 " " " N. Rim PVC

10,009 " " " GROUND

10,010 " " UNK-2 SHOT @ BASE OF

STEEL @ TOP OF CONC. PIPE BEAT 45 N.

10,011 MON FOR WCH LUMINED N. Rim LID

10,012 " " " N. Rim PVC

10,013 " " LL MW 035 N. Rim LID

10,014 " " " N. Rim PVC

10,015 " " " GROUND

10,016 " " LL MW 035 N. Rim LID

10,017 " " " N. Rim PVC

10,018 " " " GROUND

Return to the Rain

GEOELIBGS

NIR

DESK

10,019	LLMIN-55	N. RIM	LID
10,020	"	N. RIM	PVC
10,021	"	N. RIM	LID
10,022	"	N. RIM	PVC
10,023	LLMIN-075	N. RIM	LID
10,024	"	N. RIM	PVC
10,025	"-07D	N. RIM	LID
10,026	"-07D	N. RIM	PVC
10,027	LLMIN-065	N. RIM	LID
10,028	"	N. RIM	PVC
10,029	"-06D	N. RIM	LID
10,030	"	N. RIM	PVC
10,031	LLMIN-095	N. RIM	LID (NO LOCK)
10,032	"	N. RIM	PVC
10,033	"-09D	N. RIM	LID (NO LOCK)
10,034	"	N. RIM	PVC

1-18-13

CR-286

	Flush w/ GARD		
	"		
	"		
	"		
	Flush w/ GARD		
	"		
	"		
	"		
	Flush w/ GARD		
	"		
	"		
	"		
	Flush w/ GARD		
	"		
	"		
	"		

Rate in the Rain

10035 LLMW-08 S N. RIM CASING
 10036 " " N. RIM PVC
 10037 " " Ground
 10038 " -08 D N. RIM CASING
 10039 " " N. RIM PVC
 10040 " " Ground

10041 LLMW-11 S N. RIM CASING
 10042 " " N. RIM PVC
 10043 " " Ground
 10044 " 11 D N. RIM CASING
 10045 " " N. RIM PVC
 10046 " " Ground

0562 564
 " "
 " 270
 " 564
 " "
 " 270
 " 564
 " "
 " 270
 " 564
 " "
 " 270

Reto en 200 Rain

GEDERZIGAS

NIC

DRS

8 CEDE-08

10050 LLMW-17 S

10051 "

10052 "

10053 LLMW-17 D

10054 "

10055 "

10056 LLMW-20 D

10057 "

10058 "

10059 PE3B

10060 "

10061 PE3A

10062 "

12° BS

1-21-13

SIA JEG

TRed

Code

6.562 111

6.562 564

" "

" 270

" 564

" "

" 270

" 564

" "

" 270

" 564

" "

" "

" "

Reite in die Reihe

12/13

6.562 564
" "
" 170

" 564
" "

" "
" "

" "
" "

" "
" "

" "
" "

" "
" "

" "
" "

Return the Run

10063 CMW 19-D N. LID TIM
" " N. PVC TIM
10065 " " Ground

10066 PE1B N. TIM PVC
10067 " " E LID

10068 PE1A N. TIM PVC
10073 " " E LID

10069 PE2A N. TIM PVC
10070 " " E LID

10071 PE2B N. TIM PVC
10072 " " E LID

10074 CMW 20 S N. TIM PVC
10075 " " E LID @ Ground

10076 " " N. TIM PVC
10077 " " E LID @ Ground

1-21-13

10094 LL MW 15.5" N. Rim CASE

10095 " " " " PVC

10096 " " " " Ground

10097 LL MW 15.0" N. Rim CASE

10098 " " " " PVC

10099 " " " " Ground

10100 LL MW 14.5" N. Rim CASE

10101 " " " " PVC

10102 " " " " Ground

10103 LL MW 14.0" N. Rim CASE

10104 " " " " PVC

10105 " " " " Ground

10106 LL MW 12.5" N. Rim CASE

10107 " " " " PVC

10108 " " " " Ground

10109 LL MW 12.0" N. Rim CASE

10110 " " " " PVC

10111 " " " " Ground

6.564

" " 1

" " 270

" " 564

" " "

" " 270

" " 564

" " "

" " 270

" " 564

" " "

" " 270

" " 564

" " "

" " 270

" " 564

" " "

" " 270

Return to Room

1-21-13

10112	LLMW 10 S	N. Rim	CASE
10113	"	"	PVC
10114	"	Ground	
10115	LLMW 10 D	N. Rim	CASE
10116	"	"	PVC
10117	"	Ground	
10118	LLMW 13 S	N. Rim	CASE
10119	"	"	PVC
10120	"	Ground	
10121	LLMW 13 D	N. Rim	CASE
10122	"	"	PVC
10123	"	Ground	
10124	LLMW 16 S	N. Rim	CASE
10125	"	"	PVC
10126	"	Ground	
10127	LLMW 16 D	N. Rim	CASE
10128	"	"	PVC
10129	"	Ground	

6.564	564
"	"
"	270
"	564
"	"
"	270
"	
"	564
"	"
"	270
"	564
"	"
"	270
"	
"	564
"	"
"	270
"	
"	564
"	"
"	270

Return to the Rain

The background of the page is a topographic map with contour lines. The map is rendered in shades of blue and grey. It shows various geographical features, including several peaks and valleys. A prominent dashed line, likely representing a trail or a specific boundary, winds across the map from the upper left towards the lower right. The contour lines are closely spaced in some areas, indicating steeper slopes, and more widely spaced in others, indicating gentler slopes. The overall layout is clean and professional, with the title text positioned in the upper right quadrant.

APPENDIX C
Data Quality Assessment Report

**DATA QUALITY ASSESSMENT REPORT
METALS BY METHODS SW6010C/ SW7471A/SW200.8**

ARI Laboratory SDG	Samples Validated (Bold indicates the sample was qualified)
VW17 (VY27 by SW200.8)	LLMW05-6-7, LLMW05-10-10.2, LLMW05-12-13, LLMW05-20-21, LLMW08-3-4, LLMW08-12-13, LLMW08-20-21, LLMW10-6-7, LLMW10-7.5-7.7, LLMW10-12-13, LLMW10-27-28, LLMW12-5-5.5, LLMW12-8.5-8.7, LLMW12-10-10.5, LLMW12-21-22, LLMW20-4.5-5.5, LLMW20-7.2-7.4, LLMW20-9-9.5, LLMW20-13.5-14.5
VW08 (VY30 by SW200.8)	LLMW22-3-4, LLMW22-8-8.2, LLMW22-10.5-11.5, LLMW22-20-21, LLMW23-17-18, LLMW23-20-21, LLMW23-22.9-23.1, LLMW23-26-26.5, LLMW23-35-36
VW18 (VY32 by SW200.8)	LLMW07-3-4, LLMW07-10-10.2, LLMW07-10.5-11, LLMW07-18-19, LLMW09-4.5-5.5, LLMW09-8.3-8.5, LLMW09-10.5-11, LLMW09-18-19, LLMW19-3-4, LLMW19-7.8-8, LLMW19-9-10, LLMW19-25-26
VX00 (VY33 by SW200.8)	LLMW14-5.5-6, LLMW14-7-7.2, LLMW14-13.5-14.5, LLMW14-29-30, LLMW15-2-3, LLMW15-11.5-11.7, LLMW15-14-15, LLMW15-30.5-31.5, LLMW17-5-6, LLMW17-12-12.2, LLMW17-12.5-13, LLMW17-21-22, LLMW18-6-7, LLMW18-8.5-8.7, LLMW18-11-12, LLMW18-21-22
VX01 (VY34 by SW200.8)	LLMW11-5-6, LLMW11-10.5-10.7, LLMW11-11-11.5, LLMW11-19.5-20.5, LLMW13-10.5-11.5, LLMW13-18.7-19, LLMW13-23-24, LLMW13-32-33, LLMW16-13-13.5, LLMW16-13.5-13.7, LLMW16-15-16, LLMW16-29.5-30.5
VX78 (VY35 by SW200.8)	LLMW02-6-7, LLMW02-17.4-17.6, LLMW02-20-21, LLMW02-27-28, LLMW21-6-7, LLMW21-7.7-9, LLMW21-12-13, LLMW21-15-16, LLMW21-24-25, LLMW25-3-4, LLMW25-8-8.2, LLMW25-10.5-11, LLMW25-55-56
VX79 (VY36 by SW200.8)	LLMW24-1.3-1.5, LLMW24-6-6.5, LLMW24-30-31, LLMW24-45-46 LLMW34-4.5-5.5, LLMW34-6-6.2, LLMW34-11.5-11.7, LLMW34-70-70.5
VZ01	LLMW29-6-7, LLMW29-12.5-13.5, LLMW29-20-21, LLMW29-30-31, LLMW29-55-56, LLSB01-6-7, LLSB01-10.8-11, LLSB01-13-14, LLSB01-19-20, LLSB-DUP LLSB02-3-4, LLSB02-10-10.2, LLSB02-10.6-10.8, LLSB02-12-13, LLSB02-15-16, LLSB03-3-4, LLSB03-11-11.2, LLSB03-13-14, LLSB03-19-20
VZ07	LLMW01-3-4, LLMW01-25-25.2, LLMW03-9-10, LLMW03-10.5-10.6, LLMW03-13.5-14.5, LLMW03-28-29, LLMW04-2-3, LLMW04-2-3D, LLMW04-14.3-14.5, LLMW04-18-19, LLMW04-30-31, LLMW06-6.5-7.5, LLMW06-8-8.2, LLMW06-11-12, LLMW06-23-24
VZ08	LLMW01-26-26.5, LLMW01-32.5-33.5, LLMW33-3-4, LLMW33-4.5-4.7, LLMW33-10.5-11.5, LLMW33-39-40 BP05D2-40-41, BP05D2-50-51, BP05D2-62-62.5, BP05D2-65-66, BP05D2-70.5-71
VZ68	LLMW27-3.5-4.5, LLMW27-4.5-5.5, LLMW27-8-9, LLMW27-15.5-16, LLMW27-25-26, LLMW27-30-31, LLMW27-37-37.5, LLMW27-40-41, LLMW27-50-51, LLMW27-60-61
WA93	LLMW31-3-4, LLMW31-9.1-9.3, LLMW31-25-25.5, LLMW31-45-46, LLMW31-55-56

PROJECT: LOWLAND AREA (0504-068-00)

This report documents the results of an Environmental Protection Agency (EPA) level 2b data validation of analytical data from the analyses of soil boring samples and the associated laboratory and field quality control (QC) samples. The review included the following:

- Chain of Custody
- Holding Times and Sample Preservation
- Instrument Calibration
- ICP Interference Check Sample
- Method and Calibration Blanks
- Laboratory Control Samples
- Matrix Spikes
- Laboratory Duplicates
- Field Duplicates
- Internal Standards/Tunes

OBJECTIVE

The objective of the data validation was to review laboratory analytical procedures and quality control (QC) results to evaluate whether:

- The samples were analyzed using well-defined and acceptable methods that provide detection limits below applicable regulatory criteria;
- The precision and accuracy of the data are well defined and sufficient to provide defensible data; and
- The quality assurance/quality control (QA/QC) procedures utilized by the laboratory meet acceptable industry practices and standards.

One hundred and fifty-one (151) soil samples were analyzed by one or more of the analytical methods listed in the title of this appendix.

DATA PACKAGE COMPLETENESS

Analytical Resources Incorporated (ARI), located in Tukwila, Washington, analyzed the soil samples evaluated as part of this data quality assessment. The laboratory provided all required deliverables for the assessment according to the National Functional Guidelines. The laboratory followed adequate corrective action processes and all identified anomalies were discussed in the case narrative.



DATA QUALITY ASSESSMENT SUMMARY

The results for each of the QC elements are summarized below. The data assessment was performed using guidance in the USEPA Contract Laboratory Program *National Functional Guidelines for Inorganic Data Review* (USEPA, 2010).

Chain-of-Custody Documentation

Chain-of-custody (COC) forms were provided with the laboratory analytical reports. There were no anomalies noted on the COC forms; proper COC protocols appear to have been followed for this sampling event.

Holding Times and Sample Preservation

The holding time is defined as the time that elapses between sample collection and sample analysis. The maximum holding time criteria of 6 months is prescribed for the two metals analytical methods to help ensure that the analyte concentrations found at the time of analysis reflect the concentration present at the time of sample collection. Established holding times of 6 months were met for all analyses.

Instrument Calibration

The laboratory followed the method requirements for satisfactory instrument calibration. Instrument calibration is necessary in order to ensure that the instrument is capable of producing acceptable quantitative data for the metals on the target analyte list in the QAPP. Initial Calibration Verification (ICV) demonstrates that the instrument is capable of acceptable performance at the beginning of the analytical run. The Continuing Calibration Verification (CCV) demonstrates that the initial calibration is still valid by checking the performance of the instrument on any given day that samples are being analyzed.

Each calibration curve was made up of a blank and at least five calibration standards with all measurements being within the working range of the instrument. The calibration curves were fitted using linear regression and each curve had a correlation coefficient of ≥ 0.995 .

The ICV/CCV standards were within 90% to 110% of the true value in all cases.

ICP Interference Check Sample

The Interference Check Sample verifies the analytical instrument's ability to overcome isobaric interferences typical of those found in samples. The laboratory analyzed this QC sample at the proper frequency and location of the analytical run. All solution mixtures were within the control limit of 20% of the true value.

Method Blanks

Method blanks are analyzed to ensure that laboratory procedures and reagents do not introduce measurable concentrations of the analytes of interest. Method blanks were analyzed with each batch of samples, at a frequency of 1 per 20 samples. For all sample batches, method blanks were analyzed at the required frequency. None of the analytes of interest were detected above the reporting limits in any of the method blanks.

Matrix Spikes

Because the actual analyte concentration in an environmental sample is not known, the accuracy of a particular analysis is usually inferred by performing a matrix spike (MS) analysis. One aliquot of sample is



analyzed in the normal manner, and then a second aliquot of the sample is spiked with a known amount of analyte concentration and analyzed. From these analyses, a percent recovery (%R) is calculated. In the event that a particular element is out of the recovery value control limits in the matrix spiked sample, the laboratory is required to analyze a “post-spiked” sample in order to further isolate any potential quality control issues with the given element.

Matrix spike analyses should be performed once per analytical batch or every 20 field samples, whichever is more frequent. The recovery criteria for matrix spikes are 75% to 125% for all of the elements in this report.

The frequency requirements were met for all analyses, with the following exceptions:

All SDGs: In all of the matrix spike samples, the %R value for antimony was less than the control limit of 80%. Appropriately, in each case the laboratory properly conducted a post-spiked sample. These post-spiked samples were spiked with a higher concentration of element solution as the matrix spike, however, they do not interact with acid and are never heated in the digestion process. The %R values for each of the post spike samples were within the 75% to 125% control limits.

In the process of determining the appropriate action for these potential outliers, it was also noted that there were no positive detections for antimony in the associated field samples in this sampling event. The reporting limits for antimony, even though biased low, were consistently three to five times less than the screening level and target reporting limit prescribed in the project QAPP. Based on professional judgment, the antimony reporting limits were not qualified, as there is no effect on the usefulness of the antimony data for this project.

SDG VZ07: The laboratory performed a matrix spike on Sample LLMW03-9-10. The %R value for mercury was greater than the control limit. The positive results for mercury were qualified as estimated (J) in the following samples from this geological boring: LLMW03-10.5-10.6, and LLMW03-13.5-14.5.

SDG VZ68: The laboratory performed a matrix spike on Sample LLMW27-3.5-4.5. The %R value for arsenic was less than the control limit. However, in this case the parent sample concentration was greater than four times the amount spiked into the matrix spike. For this reason, no qualification was necessary.

Laboratory Control Samples (LCS)

A laboratory control sample is essentially a blank sample that is spiked with a known amount of analyte concentration and analyzed. It is to be treated much like a matrix spike, without the possibility for matrix interference. As there is no actual sample matrix in the analysis, the analytical expectations for accuracy and precision are usually more rigorous and qualification would apply to all samples in the batch, instead of the parent sample only.

Laboratory control sample analyses should be performed once per analytical batch or every 20 field samples, whichever is more frequent. The recovery criteria for laboratory control samples are specified in the laboratory documents as are the relative percent difference values. The frequency requirements were met for all analyses, and the %R/RPD values were within the proper control limits.

Laboratory Duplicates

Internal laboratory duplicate analyses are performed to monitor the precision of the analyses. Two separate aliquots of a sample are analyzed as distinct samples in the laboratory, and the RPD between



the two results is calculated. Duplicate analyses should be performed once per analytical batch. If one or more of the samples used has a concentration greater than five times the reporting limit for that sample, the absolute difference is used instead of the RPD.

Laboratory duplicates were analyzed at the proper frequency and the specified acceptance criteria were met in all cases, with the following exceptions:

SDG VX01: The laboratory performed an internal duplicate on Sample LLMW11-5-6. The absolute difference value for antimony was greater than the control limit. There were no positive results for antimony in any of the field samples from the LLMW11 boring. The antimony reporting limits were qualified as estimated (UJ) in all samples from this geological boring: LLMW11-5-6, LLMW11-10.5-10.7, LLMW11-11-11.5, and LLMW11-19.5-20.5.

SDG VZ01: The laboratory performed an internal duplicate on Sample LLSB01-13-14. The absolute difference value for lead was greater than the control limit. The positive results for lead were qualified as estimated (J) in all samples from this geological boring: LLSB01-6-7, LLSB01-10.8-11, LLSB01-13-14, LLSB01-19-20, and LLSB-DUP.

Field Duplicates

Field duplicate samples were collected and analyzed along with the reviewed sample batches. The duplicate samples were analyzed for the same parameters as the associated parent samples. As mentioned above for the laboratory duplicates the RPD is used as the criteria for assessing precision, unless one or more of the samples used has a concentration greater than five times the reporting limit for that sample, the absolute difference is used instead of the RPD.

The RPD control limits for soil samples is 50%, while the RPD control limits for water samples is 35%. The absolute difference control limits for soil samples is twice the PQL value, while the absolute difference control limits for water samples is the same as the PQL value.

SDG VW17: One set of field duplicates, Samples LLMW05-12-13 & LLMW05-12-13D, was submitted to the laboratory. The precision criteria were met for all target analytes.

SDG VX00: One set of field duplicates, Samples LLMW15-2-3 & LLMW15-2-3 DUP, was submitted to the laboratory. The precision criteria were met for all target analytes.

SDG VZ01: One set of field duplicates, Samples LLSB01-19-20 & LLSB-DUP, was submitted to the laboratory. The precision criteria were met for all target analytes.

SDG VZ07: One set of field duplicates, Samples LLMW04-2-3 & LLMW04-2-3DUP, was submitted to the laboratory. The precision criteria were met for all target analytes.

Reporting Limits and Miscellaneous

SDG VW17, VW08, VW18, VX00, VX01, VX78, VX79: The reporting limits of arsenic and thallium in certain samples exceeded the screening levels and/or target reporting limits prescribed in the QAPP when originally analyzed by method SW6010C. The samples in these SDGs were all re-analyzed by method SW200.8 in order to achieve the target reporting limits.

Internal Standards/Tunes

The laboratory appropriately added an internal standard into each sample, with the exception of the instrument tune. The intensity of the internal standard response in each sample was monitored and

compared to the intensity of the response for that internal standard in the calibration blank. The percent relative intensity (%RI) in the samples were within 60-125% of the response in the calibration blank for the appropriate analytical run.

OVERALL ASSESSMENT

As was determined by this data quality assessment, the laboratory followed the specified analytical methods. Accuracy was acceptable, as demonstrated by the LCS and MS %R values, with the exceptions mentioned above. Precision was acceptable, as demonstrated by the laboratory duplicate and field duplicate RPD values, with the exceptions noted above.

Data were qualified as estimated because of laboratory duplicate precision outliers.

The data are acceptable for use.



A topographic map background with blue contour lines of varying thickness and a dashed blue line path. The map is partially visible on the left side of the page.

APPENDIX D
Laboratory Deliverables
(on attached CD)



APPENDIX E
Results of Grain Size Analyses

GeoEngineers
0504-068-00
Lowland

Percent Finer (Passing) Than the Indicated Size

Sieve Size (microns)	3"	2"	1 1/2"	1"	3/4"	1/2"	3/8"	#4 (4750)	#10 (2000)	#20 (850)	#40 (425)	#60 (250)	#100 (150)	#200 (75)	32	22	13	9	7	3.2	1.3
LLMW06-23-24	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.9	99.8	97.3	81.1	57.6	31.4	14.8	9.0	6.0	5.0	4.5	4.0	2.5	1.5
	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.6	97.1	80.4	56.9	31.6	14.9	9.0	6.0	5.0	4.5	4.0	2.5	1.5
	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.6	99.2	96.4	79.2	55.3	29.5	13.5	9.0	6.0	5.0	4.5	4.0	2.5	1.5
LLMW03-5-5.2	100.0	100.0	100.0	100.0	100.0	99.1	99.0	98.3	97.1	94.8	91.3	84.7	73.9	60.7	42.8	32.5	24.0	20.1	14.9	9.1	5.2
LLMW03-28-29	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.2	92.8	76.5	48.1	29.9	16.6	7.3	5.7	4.1	3.1	2.6	1.6	0.5	0.5
LLMW06-6.5-7.5	100.0	100.0	100.0	100.0	100.0	97.7	93.0	83.0	67.9	38.7	9.1	2.8	1.9	1.5	1.4	1.0	0.7	0.3	0.3	0.0	0.0
LLMW07-18-19	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.9	98.5	74.8	14.2	6.4	3.4	2.0	1.5	1.5	1.0	0.5	0.0	0.0	0.0
LLMW08-20-21	100.0	100.0	100.0	100.0	100.0	100.0	100.0	98.2	96.2	75.3	23.5	14.7	11.6	7.4	5.3	3.9	2.9	2.4	1.9	0.5	0.5
LLMW11-3.5-4.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.3	98.1	93.0	65.0	26.2	12.0	6.8	5.9	5.0	4.0	3.5	2.5	1.5	0.5
LLMW11-19.5-20.5	100.0	100.0	100.0	100.0	100.0	100.0	99.4	94.9	85.9	73.8	48.0	16.1	9.0	5.4	5.2	3.9	2.6	2.2	1.3	0.4	0.0
LLMW12-5-5.5	100.0	100.0	100.0	100.0	100.0	100.0	98.9	97.1	92.5	68.9	29.4	8.1	3.8	2.6	2.3	1.8	1.4	1.4	0.9	0.5	0.5
LLMW12-21-22	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.0	89.9	51.4	18.0	12.0	8.6	6.0	4.5	3.6	2.7	2.3	2.3	0.9	0.5
LLMW13-10.5-11.5	100.0	100.0	100.0	100.0	100.0	90.2	85.2	78.5	69.7	54.8	31.5	18.0	13.2	9.8	9.6	7.5	5.9	4.8	3.7	1.6	0.5
LLMW13-32-33	100.0	100.0	100.0	100.0	100.0	100.0	98.5	94.5	84.8	52.4	15.8	7.5	4.5	2.8	2.6	2.1	1.3	0.9	0.4	0.0	0.0
LLMW18-6-7	100.0	100.0	100.0	100.0	100.0	98.2	98.2	97.0	91.4	72.9	34.7	10.8	5.4	3.0	2.8	2.3	1.4	1.4	0.9	0.5	0.5
LLMW18-21-22	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.2	98.6	87.9	57.0	17.2	8.8	6.0	5.0	4.5	3.0	2.5	1.5	0.5	0.0

Testing performed according to ASTM D421/D422

099000 · 257 · 099000

GeoEngineers
0504-068-00
Lowland

Percent Retained in Each Size Fraction

Description	% Coarse Gravel				% Gravel			% Coarse Sand	% Medium Sand		% Fine Sand			% Very Coarse Silt	% Coarse Silt	% Medium Silt	% Fine Silt	% Fine Silt	% Very Fine Silt	% Clay	
	3-2"	2-1 1/2"	1 1/2"-1"	1-3/4"	3/4-1/2"	1/2-3/8"	3/8"-4750	4750-2000	2000-850	850-425	425-250	250-150	150-75	75-32	32-22	22-13	13-9	9-7	7-3 2	3 2-1.3	<1 3
LLMW06-23-24	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	2.4	16.3	23.5	26.2	16.6	5.8	3.0	1.0	0.5	0.5	1.5	1.0	1.5
	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.4	2.5	16.7	23.4	25.4	16.6	5.9	3.0	1.0	0.5	0.5	1.5	1.0	1.5
	0.0	0.0	0.0	0.0	0.0	0.0	0.4	0.5	2.8	17.2	23.9	25.8	15.9	4.6	3.0	1.0	0.5	0.5	1.5	1.0	1.5
LLMW03-5-5 2	0.0	0.0	0.0	0.0	0.9	0.1	0.7	1.2	2.2	3.5	6.7	10.8	13.1	17.9	10.4	8.4	3.9	5.2	5.8	3.9	5.2
LLMW03-28-29	0.0	0.0	0.0	0.0	0.0	0.0	0.8	6.4	16.3	28.4	18.2	13.3	9.3	1.6	1.6	1.0	0.5	1.0	1.0	0.0	0.5
LLMW06-6 5-7 5	0.0	0.0	0.0	0.0	2.3	4.7	10.0	15.1	29.2	29.6	6.2	0.9	0.4	0.1	0.3	0.3	0.3	0.0	0.3	0.0	0.0
LLMW07-18-19	0.0	0.0	0.0	0.0	0.0	0.0	0.1	1.4	23.7	60.7	7.8	3.0	1.4	0.5	0.0	0.5	0.5	0.5	0.0	0.0	0.0
LLMW08-20-21	0.0	0.0	0.0	0.0	0.0	0.0	1.8	2.0	20.9	51.8	8.9	3.0	4.2	2.1	1.5	1.0	0.5	0.5	1.5	0.0	0.5
LLMW11-3.5-4.5	0.0	0.0	0.0	0.0	0.0	0.0	0.7	1.3	5.0	28.0	38.8	14.2	5.2	0.9	1.0	1.0	0.5	1.0	1.0	1.0	0.5
LLMW11-19 5-20 5	0.0	0.0	0.0	0.0	0.0	0.6	4.6	9.0	12.1	25.8	31.9	7.1	3.6	0.2	1.3	1.3	0.4	0.9	0.9	0.4	0.0
LLMW12-5-5 5	0.0	0.0	0.0	0.0	0.0	1.1	1.9	4.6	23.6	39.5	21.3	4.3	1.3	0.3	0.5	0.5	0.0	0.5	0.5	0.0	0.5
LLMW12-21-22	0.0	0.0	0.0	0.0	0.0	0.0	1.0	9.0	38.5	33.5	6.0	3.4	2.6	1.4	0.9	0.9	0.5	0.0	1.4	0.5	0.5
LLMW13-10.5-11.5	0.0	0.0	0.0	0.0	9.8	5.0	6.8	8.7	14.9	23.4	13.5	4.7	3.4	0.2	2.1	1.6	1.1	1.1	2.1	1.1	0.5
LLMW13-32-33	0.0	0.0	0.0	0.0	0.0	1.5	3.9	9.7	32.4	36.6	8.3	3.0	1.7	0.3	0.4	0.9	0.4	0.4	0.4	0.0	0.0
LLMW18-6-7	0.0	0.0	0.0	0.0	1.8	0.0	1.2	5.6	18.5	38.2	23.9	5.3	2.4	0.2	0.5	0.9	0.0	0.5	0.5	0.0	0.5
LLMW18-21-22	0.0	0.0	0.0	0.0	0.0	0.0	0.8	0.6	10.8	30.9	39.8	8.4	2.8	1.0	0.5	1.5	0.5	1.0	1.0	0.5	0.0

1999 0821 1574

Client	GeoEngineers	Project No	0504-068-00
ARI Tnplicate Sample ID	VZ67F	Project	Lowland
Client Tnplicate Sample ID	LLMW06-23-24	Batch No	VZ67-01
		Page	1 of 1

Relative Standard Deviation, By Size


Sample ID	75000	50000	37500	25000	19000	12500	9500	4750	2000	850	425	250	150	75	32	22	13	9	7	3.2	1.3
LLMW06-23-24	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.9	99.8	97.3	81.1	57.6	31.4	14.8	9.0	6.0	5.0	4.5	4.0	2.5	1.5
LLMW06-23-24	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.6	97.1	80.4	56.9	31.6	14.9	9.0	6.0	5.0	4.5	4.0	2.5	1.5
LLMW06-23-24	100.0	100.0	100.0	100.0	100.0	100.0	100.0	99.6	99.2	96.4	79.2	55.3	29.5	13.5	9.0	6.0	5.0	4.5	4.0	2.5	1.5
AVE	100.00	100.00	100.00	100.00	100.00	100.00	100.00	99.85	99.52	96.94	80.23	56.60	30.81	14.43	9.01	6.00	5.00	4.50	4.00	2.50	1.50
STDEV	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.19	0.30	0.50	0.93	1.17	1.15	0.77	0.03	0.02	0.02	0.01	0.01	0.01	0.00
%RSD	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.19	0.30	0.51	1.16	2.07	3.74	5.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32

This Tnplicate applies to the Batch Containing the Following Samples

Sample ID	Date Sampled	Date Set up	Date Started	Date Complete	Data Qualifiers
LLMW06-23-24	12/27/2012	1/15/2013	1/21/2013	1/23/2013	
	12/27/2012	1/15/2013	1/21/2013	1/23/2013	
	12/27/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW03-5-5.2	12/26/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW03-28-29	12/26/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW06-6-5-7.5	12/27/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW07-18-19	12/7/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW08-20-21	12/10/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW11-3-5-4.5	12/13/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW11-19-5-20.5	12/13/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW12-5-5.5	12/12/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW12-21-22	12/12/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW13-10-5-11.5	12/17/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW13-32-33	12/17/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW18-6-7	12/13/2012	1/15/2013	1/21/2013	1/23/2013	
LLMW18-21-22	12/13/2012	1/15/2013	1/21/2013	1/23/2013	

23000 . 2570

Grain Size Distribution by Hydrometer



—◆— LLMW06-23-24


—■— LLMW06-23-24

—▲— LLMW06-23-24

ES000012570

15000 1520


Grain Size Distribution by Hydrometer




- ◆ LLMW03-5-5.2
- LLMW03-28-29
- ▲ LLMW06-6.5-7.5
- LLMW07-18-19

55000 : 2970

Grain Size Distribution by Hydrometer



Grain Size Distribution by Hydrometer



◆ LLMW12-21-22


■ LLMW13-10.5-11.5

▲ LLMW13-32-33

○ LLMW18-6-7


VZ57:00005

Grain Size Distribution by Hydrometer



◆ LLMW18-21-22

2.5000 1.920



APPENDIX F
Report Limitations and Guidelines for Use

APPENDIX F REPORT LIMITATIONS AND GUIDELINES FOR USE²

This appendix provides information to help you manage your risks with respect to the use of this report.

Environmental Services are Performed for Specific Purposes, Persons and Projects

GeoEngineers has performed this investigation of the Everett Smelter – Lowland Area in general accordance with the scope and limitations of our proposal, dated July 3, 2012. This report has been prepared for the exclusive use of Washington State Department of Ecology, and their authorized agents. This report is not intended for use by others, and the information contained herein is not applicable to other properties.

GeoEngineers structures our services to meet the specific needs of our clients. For example, an ESA study conducted for a property owner may not fulfill the needs of a prospective purchaser of the same property. Because each environmental study is unique, each environmental report is unique, prepared solely for the specific client and property. No one except Washington State Department of Ecology should rely on this environmental report without first conferring with GeoEngineers. Use of this report is not recommended for any purpose or project except the one originally contemplated.

This Environmental Report is Based on a Unique Set of Project-Specific Factors

This report has been prepared for the Everett Smelter – Lowland Area. GeoEngineers considered a number of unique, project-specific factors when establishing the scope of services for this project and report. Unless GeoEngineers specifically indicates otherwise, it is important not to rely on this report if it was:

- not prepared for you,
- not prepared for your project,
- not prepared for the specific site explored, or
- completed before important project changes were made.

If important changes are made to the project or property after the date of this report, we recommend that GeoEngineers be given the opportunity to review our interpretations and recommendations. Based on that review, we can provide written modifications or confirmation, as appropriate.

² Developed based on material provided by ASFE, Professional Firms Practicing in the Geosciences; www.asfe.org.

Reliance Conditions for Third Parties

Our report was prepared for the exclusive use of our Client. No other party may rely on the product of our services unless we agree to such reliance in advance and in writing. This is to provide our firm with reasonable protection against open-ended liability claims by third parties with whom there would otherwise be no contractual limits to their actions. Within the limitations of scope, schedule and budget, our services have been executed in accordance with our Agreement with the Client and generally accepted environmental practices in this area at the time this report was prepared.

Environmental Regulations are Always Evolving

Some substances may be present in the vicinity of the subject property in quantities or under conditions that may have led, or may lead, to contamination of the subject property, but are not included in current local, state or federal regulatory definitions of hazardous substances or do not otherwise present current potential liability. GeoEngineers cannot be responsible if the standards for appropriate inquiry, or regulatory definitions of hazardous substances, change or if more stringent environmental standards are developed in the future.

Conditions Can Change

This environmental report is based on conditions that existed at the time the study was performed. The findings and conclusions of this report may be affected by the passage of time, by man-made events such as construction on or adjacent to the subject property, by new releases of hazardous substances, or by natural events such as floods, earthquakes, slope instability or groundwater fluctuations. Please contact GeoEngineers before applying this report for its intended purpose so that GeoEngineers may evaluate whether changed conditions affect the continued applicability of the report.

Most Environmental Findings are Professional Opinions

Our interpretations of site conditions are based on field observations and analytical data from widely spaced sampling locations at the subject property. Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. GeoEngineers reviewed field and laboratory data and then applied our professional judgment to render an informed opinion about subsurface conditions throughout the property. Actual subsurface conditions may differ, sometimes significantly, from those indicated in this report. Our report, conclusions and interpretations should not be construed as a warranty of the subsurface conditions.

Read These Provisions Closely

It is important to recognize that the geoscience practices (geotechnical engineering, geology and environmental science) are less exact than other engineering and natural science disciplines. Without this understanding, there may be expectations that could lead to disappointments, claims and disputes. GeoEngineers includes these explanatory “limitations” provisions in our reports to help reduce such risks. Please confer with GeoEngineers if you need to know more about how these “Report Limitations and Guidelines for Use” apply to your project or property.