GeoEngineers
Plaza 600 Building
600 Stewart Street, Suite 1700
Seattle, Washington 98101
206.728.2674

June 8, 2018

Washington State Department of Ecology
Southwest Region – Toxics Cleanup Program
300 Desmond Drive SE
Lacey, Washington 98503

Attention: Tim Mullin

Subject: Groundwater Monitoring Well Decommissioning Plan
Former Olympia Manufactured Gas Plant (MGP) Property (Columbia Square Properties)
320 Columbia Street NW
Olympia, Washington
File No. 0186-774-05

INTRODUCTION

On the behalf of Puget Sound Energy (PSE), this letter describes plans to decommission five existing groundwater monitoring wells on or directly adjacent to the property located at 320 Columbia Street in Olympia, Washington (Property; Figure 1), also known as the Columbia Square Properties. Predecessors of PSE previously owned and operated a manufactured gas plant (MGP) on the Property. PSE completed a cleanup on the property in 2012 to address contamination related to the former MGP.[1] In general, the cleanup removed contaminated soil to a depth of approximately 6 feet below ground surface (bgs) within the Property boundaries. The Washington State Department of Ecology (Ecology) issued a property-specific "no further action" (NFA) determination in 2015. An environmental covenant (EC) is in place to address contaminated soil that remains beneath the Property at depths greater than 6 feet.

As a requirement of the EC, groundwater conditions on and near the property are being monitored in five groundwater monitoring wells (MW-6, MW-10, and MW-14 through MW-16; Figure 2) in accordance with the Groundwater Compliance Monitoring Plan (GWCMP) dated October 8, 2013 and an associated Addendum #1 dated November 5, 2014. We understand that the current property owner (The Rants Group) plans to redevelop the Property and will need to decommission all existing wells on and near the Property in preparation for redevelopment construction activities scheduled to start in August 2018. Existing groundwater monitoring well details and the proposed groundwater monitoring well decommissioning plan is described below.

[1] The cleanup was conducted under Ecology's Voluntary Cleanup Program (VCP number SW0984). The cleanup site identification number is 6851.

GROUNDWATER MONITORING WELL DECOMMISSIONING PLAN

Five groundwater monitoring wells (MW-6, MW-10, and MW-14 through MW-16; Figure 2) exist on and near the Property that will require decommissioning prior to Property redevelopment construction. Existing groundwater monitoring well boring logs are provided as an attachment and well details are summarized below.

Monitoring Well ID	Depth of Well Casing (ft bgs)	Measured Range for Depth to Groundwater (ft below TOC)	Depth of Screened Interval (ft below TOC)	Well Construction Details
MW-6	11	4.31 to 5.37[1]	Unknown (Boring log not available; well installed by others)	Flush mounted 2-in Schedule 40 PVC casing, otherwise unknown casing and screen construction details
MW-10	14	4.66 to 5.31[1]	Unknown (Boring log not available; well installed by others)	
MW-14	20	5.53 to 6.24[2]	4-20	Flush mounted 2-in Schedule 40 PVC casing with 0.01-in slot screen
MW-15	20	4.98 to 5.81[2]	4-20	
MW-16	20	4.01 to 4.98[2]	4-20	

Notes:

[1]Depth to water measurement range represents August 2008 through February 2018.

[2]Depth to water measurement range represents August 2013 through February 2018.

TOC = top of casing

PVC = polyvinyl chloride

A Washington State licensed well driller will be subcontracted to decommission all five groundwater monitoring wells prior to redevelopment construction activities. The methods for well decommissioning will be in accordance with Washington Administrative Code (WAC) 173-160-460.

Decommissioned groundwater monitoring wells (that are abandoned in place) may be encountered and a portion of the decommissioned well may be required to be removed during Property redevelopment construction activities, such as shallow grading or shallow soil excavation is conducted within or outside of the Property boundary. In this case, the WAC allows for the Property redevelopment contractor the ability to cut and remove exposed portions of the decommissioned groundwater monitoring well casings to match existing ground surface conditions, leaving decommissioned subgrade portions of the groundwater monitoring well casing in place.

After Property redevelopment is complete, new groundwater monitoring wells will be installed on or surrounding the Property to monitor groundwater as part of the EC. The number and location of new monitoring wells will be determined in consultation with Ecology at a later date.

SCHEDULE FOR FUTURE GROUNDWATER MONITORING

The current groundwater compliance monitoring events are conducted once every 18 months, and the last monitoring event was completed in February 2018 (GeoEngineers, 2018). The sampling event was conducted in accordance with the GWCMP, and no constituents were detected in the groundwater samples.

Property redevelopment is scheduled to start August 2018 and last approximately 18 months. This time period falls greater than the 18-month window between the last monitoring event in February 2018 and the next compliance event scheduled in August 2019. New monitoring wells will be installed, at a minimum, around the redeveloped Property and before the next groundwater compliance monitoring event scheduled for August 2019. The groundwater compliance monitoring program will then proceed according to the 18-month interval schedule outlined in the GWCMP.

The footprint of the building that will be constructed on the Property during redevelopment is anticipated to cover nearly the entire Property, and it is unclear whether it will be possible to install any of the replacement groundwater monitoring wells inside the Property boundary. We will evaluate potential locations for the replacement monitoring wells after details of the new building (footprint and design) are known, and discuss the proposed monitoring well location(s) with Ecology.

REFERENCES

GeoEngineers 2018. Groundwater Monitoring Technical Memorandum, February 2018 Monitoring Event, PSE Former Olympia MGP Site, 320 Columbia Street NW, Olympia, Washington. Prepared for Puget Sound Energy. April 5, 2018.

LIMITATIONS

We have prepared this letter for the exclusive use of Puget Sound Energy, their authorized agents and regulatory agencies. This letter is not intended for use by others, and the information contained herein is not applicable to other sites. No other party may rely on the product of our services unless we agree in advance, and in writing, to such reliance. This is to provide our firm with reasonable protection against open-ended liability claims by third parties with whom there would otherwise be no contractual limits to their actions.

Our interpretations of site conditions are based on field observations and limited sampling events. Within the limitations of scope, schedule and budget, our services have been executed in accordance with our general agreement with PSE (Contract No. 4600007908) and generally accepted environmental science practices in this area at the time this letter was prepared. No warranty or other conditions, express or implied, should be understood.

Any electronic form of this document (email, text, table, and/or figure), if provided, and any attachments are only a copy of a master document. The master hard copy is stored by GeoEngineers, Inc. and will serve as the official document of record.

Sincerely,
GeoEngineers, Inc.

Nick E. Rohrbach
Project Manager

Steve C. Woodward, LG
Principal

SJB:NER:SCW:lw

Attachments:
Figure 1. Vicinity Map
Figure 2. Existing Monitoring Well Locations to be Decommissioned
Existing Groundwater Monitoring Well Boring Logs and Driller Logs – MW-14 through MW-16

cc: Greg Andrina – PSE

Notes:
1. The locations of all features shown are approximate.
2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. can not guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.
3. It is unlawful to copy or reproduce all or any part thereof, whether for personal use or resale, without permission.

Data Sources: ESRI Data & Maps, Street Maps 2005

Transverse Mercator, Zone 10 N North, North American Datum 1983
North arrow oriented to grid north

Vicinity Map

Former Olympia MGP Site
Olympia, Washington

GeoEngineers

Figure 1

Office: SEA Path: \\sea\projects\0\0186774\GIS\0186774GIS_F1_VM.mxd Map Revised: 14 October 2011 amanza



Legend

- Property boundary
- Existing building
- Existing fence
- MW-10 Monitoring well to be decommissioned

N
W E
S

20 0 20
Feet

Notes:

1. The locations of all features shown are approximate.
2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication

Data Source:
Background from Barghausen Consulting Engineers, dated 3/28/2012.

Existing Monitoring Well Locations to be Decommissioned

Former Olympia MGP Site
Olympia, Washington

GeoEngineers

Figure 2

SOIL CLASSIFICATION CHART

MAJOR DIVISIONS			SYMBOLS GRAPH	SYMBOLS LETTER	TYPICAL DESCRIPTIONS
COARSE GRAINED SOILS	GRAVEL AND GRAVELLY SOILS	CLEAN GRAVELS (LITTLE OR NO FINES)		GW	WELL-GRADED GRAVELS, GRAVEL - SAND MIXTURES
				GP	POORLY-GRADED GRAVELS, GRAVEL - SAND MIXTURES
	MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE	GRAVELS WITH FINES (APPRECIABLE AMOUNT OF FINES)		GM	SILTY GRAVELS, GRAVEL - SAND - SILT MIXTURES
				GC	CLAYEY GRAVELS, GRAVEL - SAND - CLAY MIXTURES
MORE THAN 50% RETAINED ON NO. 200 SIEVE	SAND AND SANDY SOILS	CLEAN SANDS (LITTLE OR NO FINES)		SW	WELL-GRADED SANDS, GRAVELLY SANDS
				SP	POORLY-GRADED SANDS, GRAVELLY SAND
	MORE THAN 50% OF COARSE FRACTION PASSING NO. 4 SIEVE	SANDS WITH FINES (APPRECIABLE AMOUNT OF FINES)		SM	SILTY SANDS, SAND - SILT MIXTURES
				SC	CLAYEY SANDS, SAND - CLAY MIXTURES
FINE GRAINED SOILS	SILTS AND CLAYS	LIQUID LIMIT LESS THAN 50		ML	INORGANIC SILTS, ROCK FLOUR, CLAYEY SILTS WITH SLIGHT PLASTICITY
				CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
				OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY
MORE THAN 50% PASSING NO. 200 SIEVE	SILTS AND CLAYS	LIQUID LIMIT GREATER THAN 50		MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS SILTY SOILS
				CH	INORGANIC CLAYS OF HIGH PLASTICITY
				OH	ORGANIC CLAYS AND SILTS OF MEDIUM TO HIGH PLASTICITY
HIGHLY ORGANIC SOILS				PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS

NOTE: Multiple symbols are used to indicate borderline or dual soil classifications

Sampler Symbol Descriptions

- **2.4-inch I.D. split barrel**
- **Standard Penetration Test (SPT)**
- **Shelby tube**
- **Piston**
- **Direct-Push**
- **Bulk or grab**
- **Continuous Coring**

Blowcount is recorded for driven samplers as the number of blows required to advance sampler 12 inches (or distance noted). See exploration log for hammer weight and drop.

A "P" indicates sampler pushed using the weight of the drill rig.

ADDITIONAL MATERIAL SYMBOLS

SYMBOLS GRAPH	SYMBOLS LETTER	TYPICAL DESCRIPTIONS
	AC	Asphalt Concrete
	CC	Cement Concrete
	CR	Crushed Rock/ Quarry Spalls
	TS	Topsoil/ Forest Duff/Sod

Groundwater Contact

Measured groundwater level in exploration, well, or piezometer

Measured free product in well or piezometer

Graphic Log Contact

Distinct contact between soil strata or geologic units

Approximate location of soil strata change within a geologic soil unit

Material Description Contact

Distinct contact between soil strata or geologic units

Approximate location of soil strata change within a geologic soil unit

Laboratory / Field Tests

%F	Percent fines
AL	Atterberg limits
CA	Chemical analysis
CP	Laboratory compaction test
CS	Consolidation test
DS	Direct shear
HA	Hydrometer analysis
MC	Moisture content
MD	Moisture content and dry density
OC	Organic content
PM	Permeability or hydraulic conductivity
PI	Plasticity index
PP	Pocket penetrometer
PPM	Parts per million
SA	Sieve analysis
TX	Triaxial compression
UC	Unconfined compression
VS	Vane shear

Sheen Classification

NS	No Visible Sheen
SS	Slight Sheen
MS	Moderate Sheen
HS	Heavy Sheen
NT	Not Tested

NOTE: The reader must refer to the discussion in the report text and the logs of explorations for a proper understanding of subsurface conditions. Descriptions on the logs apply only at the specific exploration locations and at the time the explorations were made; they are not warranted to be representative of subsurface conditions at other locations or times.

KEY TO EXPLORATION LOGS

GeoEngineers

FIGURE A-1

Drilled Start	End	Total Depth (ft)	Logged By / Checked By	Driller	Drilling Method
8/15/2015	8/15/2015	20	ARJ / NER	Cascade Drilling	Hollow Stem Auger

Hammer Data	140 Pound Auto Hammer	Drilling Equipment	CME Auger Drill Rig
Surface Elevation (ft) Vertical Datum	20.44	Top of Casing Elevation (ft)	20.09
Easting (X) / Northing (Y)	1041521.464 / 634097.3957	Horizontal Datum	NAD83

A 2 (in) well was installed on 8/15/2015 to a depth of 20 (ft).

Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
8/15/2015	7.0	13.1

Notes: Slight odor observed at 8 feet below ground surface

Elevation (feet)	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name Testing	Water Level	Graphic Log	Group Classification	MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)
	0							CR	Crushed rock (5/8")		
								SP	Brown fine to medium sand with trace silt and gravel (medium dense, moist) (fill)		
	5	18	49		1	▼				NS	<1
		18	17		2			SP	Gray fine to medium sand with trace silt and organics (shell fragments) (loose, wet)	NS	<1
	10	18	10		3					NS	<1
								SM	Dark gray silty fine to medium sand with gravel and trace organics (shell fragments) (loose, wet)		
		18	20		4			SP	Gray fine to medium sand with gravel (trace shell fragments) (loose, wet)	NS	<1
									No shell fragments between 13.5 and 14 feet		
	15	18	29		5				Becomes medium dense, wet	NS	<1
		18	16		6				Brownish gray fine sand with trace gravel (loose, wet)	NS	<1
									With increasing gravel content		
	20										

WELL LOG



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well MW-14

GeoEngineers

Project:	Former Columbia Street MGP Property
Project Location:	Olympia, Washington
Project Number:	0186-774-03

Figure A-2
Sheet 1 of 1

Seattle: Date:4/6/15 Path:W:\SEATTLE\PROJECTS\0\0186774\GINT\0186774.GPJ DBTemplate/LibTemplate:GEOENGINEERS8.GDT/GEI8_ENVIRONMENTAL_WELL

Drilled Start	End	Total Depth (ft)	Logged By / Checked By	Driller	Drilling Method
8/15/2015	8/15/2015	20	ARJ / NER	Cascade Drilling	Hollow Stem Auger

Hammer Data	140 Pound Auto Hammer	Drilling Equipment	CME Auger Drill Rig
Surface Elevation (ft) Vertical Datum	20.1	Top of Casing Elevation (ft)	19.65
Easting (X) / Northing (Y)	1041482.007 / 634052.9873	Horizontal Datum	NAD83

A 2 (in) well was installed on 8/15/2015 to a depth of 20 (ft).

Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
8/15/2015	6.5	13.2

Notes:

Elevation (feet)	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample	Sample Name Testing	Water Level	Graphic Log	Group Classification	MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)
20	0							CR	Crushed rock (5/8")		
								SP	Brown fine to medium sand with occasional gravel (moist) (fill)		
15	5	18	11		1					NS	<1
						▼		SP	Gray fine sand with organics and trace silt (shell fragments) (loose, wet)	SS	<1
		18	12		2				Gray fine to medium sand with organics (shell fragments), trace silt and trace gravel (loose, wet)	NS	<1
										NS	<1
10	10	18	13		3					NS	<1
		18	13		4				Increasing shell fragments	NS	<1
										NS	<1
5	15	18	14		5				Gray fine to medium sand with trace silt, gravel and organics (shell fragments) (loose, wet)	NS	<1
								GW	Gray fine to coarse gravel with sand (loose, wet)		
		18	20		6					NS	<1
	20										



Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well MW-15

GeoEngineers

Project: Former Columbia Street MGP Property
Project Location: Olympia, Washington
Project Number: 0186-774-03

Figure A-3
Sheet 1 of 1

Drilled Start	End	Total Depth (ft)	Logged By / Checked By	Driller	Drilling Method
8/15/2015	8/15/2015	20	ARJ / NER	Cascade Drilling	Hollow Stem Auger

Hammer Data	140 Pound Auto Hammer	Drilling Equipment	CME Auger Drill Rig
Surface Elevation (ft) Vertical Datum	19.14	Top of Casing Elevation (ft)	18.84
Easting (X) / Northing (Y)	1041411.807 / 634068.3031	Horizontal Datum	NAD83

A 2 (in) well was installed on 8/15/2015 to a depth of 20 (ft).

Groundwater Date Measured	Depth to Water (ft)	Elevation (ft)
8/15/2015	5.5	13.3

Notes:

Elevation (feet)	Depth (feet)	Interval Recovered (in)	Blows/foot	Collected Sample / Sample Name Testing	Water Level	Graphic Log	Group Classification	MATERIAL DESCRIPTION	Sheen	Headspace Vapor (ppm)
	0						AC	Approximately 3 inches asphalt concrete pavement		
							SP	Brown fine to sand with trace gravel		
									SS	<1
15										
	5	18	16	1	▼				SS	<1
							SP	Gray medium sand with organics (clam shells)	NS	<1
								Gray fine to medium sand with organics (smaller clam shells) and trace silt (loose, wet)	NS	<1
		18	11	2				With decreasing organics (clam shells)	NS	<1
10										
	10	18	15	3				Gray fine to medium sand with trace organics (shell fragments) (loose, wet)	NS	<1
		18	19	4				With trace silt	NS	<1
5							ML	Gray sandy silt with trace organics (shell fragments)		
	15	18	19	5					NS	<1
							SP	Gray fine to medium sand with organics (shell fragments) and trace silt (loose, wet)	NS	<1
0							ML	Gray sandy silt with organics (shell fragments and highly decayed wood fragments) (very stiff, wet)		
		18	30	6					NS	<1
	20									

WELL LOG

Steel surface monument
Concrete surface seal
1.5'
Bentonite
3.0'
2-inch Schedule 40 PVC well casing
4.0'
10/20 Silica sand
2-inch Schedule 40 PVC screen, 0.01-inch slot width
20.0'

Note: Please see Figure A-1 for explanation of symbols

Log of Monitoring Well MW-16

GeoEngineers

Project: Former Columbia Street MGP Property
Project Location: Olympia, Washington
Project Number: 0186-774-03

Figure A-4
Sheet 1 of 1

Seattle: Date:4/6/15 Path:W:\SEATTLE\PROJECTS\0\0186774\GINT\0186774.GPJ DBTemplate/LibTemplate:GEOENGINEERS8.GDT/GEI8_ENVIRONMENTAL_WELL

GeoEngineers Well ID: MW-14

RESOURCE PROTECTION WELL REPORT

(SUBMIT ONE WELL REPORT PER WELL INSTALLED)

Construction/Decommission 497234

[X] Construction

[ ] Decommission *ORIGINAL INSTALLATION Notice of Intent Number* _____

Consulting Firm **GeoEngineers**

Unique Ecology Well ID Tag No BIC 709

WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.

[X] Driller [ ] Trainee Name (Print) **James Goble**

Driller/Trainee Signature _____

Driller/Trainee License No **3131**

If trainee, licensed driller's Signature and License No _____

CURRENT

Notice of Intent No **RE08807**

Type of Well

[X] Resource Protection

[ ] Geotechnical Soil Boring

Property Owner **Evergreen Olympic Properties Inc**

Site Address **320 Columbia St NW**

City **Olympia** County **Thurston**

Location 1/4 **NW** NE **SW** Sec **14** TWN **18N** R **2W** EWM or WWM

Lat/Long (s,t,r still Required) Lat Deg x Lat Min/Sec x Long Deg x Long Min/Sec x

Tax Parcel No **78500200100**

Cased or Uncased Diameter 8" Static Level 6'

Work/Decommision Start Date 8-15-13

Work/Decommision End Date 8-15-13

Construction/Design — Well Data W3-480 — Formation Description



Concrete Surface Seal Depth	1½' FT
Blank Casing (dia x dep)	2"x 4'
Material	PVC
Backfill	1½ FT
Type	Bent. Chips
Seal	
Material	
Gravel Pack	17' FT
Material	2-12 Sand
Screen (dia x dep)	2"x 16'
Slot Size	010
Material	PVC
Well Depth	20' FT
Backfill	
Material	
Total Hole Depth	20' FT

0 - 6' FT (Fill) light brown Sand w/ very small gravels

0 6' - 20' FT Med. to Fine light grey Sand w/ Sea Shells

0 - FT

RECEIVED
OCT 04 2013
WA State Department of Ecology (SWRO)

Scale 1" = _____ Page _____ of _____

ECY 050-12 (Rev=v 2/01)

GeoEngineers Well ID: MW-15

RESOURCE PROTECTION WELL REPORT

(SUBMIT ONE WELL REPORT PER WELL INSTALLED)

Construction/Decommission 497233

[X] Construction

[ ] Decommission *ORIGINAL INSTALLATION Notice of Intent Number* _____

CURRENT

Notice of Intent No RE08807

Type of Well

[X] Resource Protection

[ ] Geotechnical Soil Boring

Consulting Firm **GeoEngineers**

Property Owner **Evergreen Olympic Properties Inc**

Site Address **320 Columbia St NW**

City **Olympia** County **Thurston**

Unique Ecology Well ID Tag No BIC 708

Location 1/4 **NW** NE **SW** Sec **14** TWN **18N** R **2W** EWM or WWM

Lat/Long (s,t,r still Required) Lat Deg x Lat Min/Sec x Long Deg x Long Min/Sec x

WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.

Tax Parcel No **78500200100**

[X] Driller [ ] Trainee Name (Print) **James Goble**

Driller/Trainee Signature _____

Driller/Trainee License No **3131**

Cased or Uncased Diameter 8" Static Level 6'

Work/Decommission Start Date 8-15-13

If trainee, licensed driller's Signature and License No _____

Work/Decommission End Date 8-15-13

Construction/Design



Well Data W3-480

Concrete Surface Seal Depth	1½'	FT
Blank Casing (dia x dep)	2"x 4'	
Material	PVC	
Backfill	1½	FT
Type	Bent. chips	
Seal		
Material		
Gravel Pack	17'	FT
Material	2-12 Sand	
Screen (dia x dep)	2"x 16'	
Slot Size	010	
Material	PVC	
Well Depth	20'	FT
Backfill		
Material		
Total Hole Depth	20'	FT

Formation Description

0 - 6' FT (Fill) light brown sand w/ very small gravels

0 6' - 20' FT Med. to Fine light grey sand w/ sea shells

0 - FT

RECEIVED
OCT 04 2013
WA State Department of Ecology (SWRO)

Scale 1" = _____ Page _____ of _____

ECY 050-12 (Rev 2/01)

GeoEngineers Well ID: MW-16

RESOURCE PROTECTION WELL REPORT

(SUBMIT ONE WELL REPORT PER WELL INSTALLED)

Construction/Decommission 497232

[X] Construction

[ ] Decommission *ORIGINAL INSTALLATION Notice of Intent Number* _____

Consulting Firm **GeoEngineers**

Unique Ecology Well ID Tag No BLC 707.

WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.

[X] Driller [ ] Trainee Name (Print) **James Goble**

Driller/Trainee Signature _____

Driller/Trainee License No **3131**

If trainee, licensed driller's Signature and License No _____

CURRENT

Notice of Intent No **RE08807**

Type of Well

[X] Resource Protection

[ ] Geotechnical Soil Boring

Property Owner **Evergreen Olympic Properties Inc**

Site Address **320 Columbia St NW**

City **Olympia** County **Thurston**

Location 1/4 **NW** NE **SW** Sec **14** TWN **18N** R **2W** EWM or WWM

Lat/Long (s,t,r still Required) Lat Deg x Lat Min/Sec x Long Deg x Long Min/Sec x

Tax Parcel No **78500200100**

Cased or Uncased Diameter 8" Static Level 6'

Work/Decommision Start Date 8-15-13

Work/Decommision End Date 8-15-13

Construction/Design — Well Data W3-480 — Formation Description



Concrete Surface Seal Depth	1½' FT
Blank Casing (dia x dep)	2"x 4'
Material	PVC
Backfill	1½ FT
Type	Bent. Chips
Seal	
Material	
Gravel Pack	17' FT
Material	2-12 Sand
Screen (dia x dep)	2"x 16'
Slot Size	010
Material	PVC
Well Depth	20' FT
Backfill	
Material	
Total Hole Depth	20' FT

Formation Description

0 - 6' FT (Fill) light brown Sand w/ very small gravels

0 6' - 20' FT Med. to Fine light grey Sand w/ Sea Shells

0 - FT

RECEIVED
OCT 04 2013
WA State Department of Ecology (SWRO)

Scale 1" = _____ Page _____ of _____

ECY 050 12 (Rec=v 2/01)