

AECOM 111 SW Columbia Portland OR, 97201 USA aecom.com

April 2, 2020

Panjini Balaraju, P.E. Environmental Engineer Washington State Department of Ecology Toxics Cleanup Program Southwest Regional Office PO Box 47775 Olympia, WA 98504-7775 Distributed via electronic mail only: PBAL461@ecy.wa.gov

Re: Monitoring Well Decommissioning Summary Letter – GL-7 Former Automotive Services, Inc. Site Port of Vancouver USA 2327 West Mill Plain Boulevard Vancouver, Washington AECOM Job No. 60624310

Dear Mr. Balaraju:

On behalf of Port of Vancouver USA (the Port), AECOM is pleased to provide the Washington Department of Ecology (Ecology) with this letter report summarizing the decommissioning of monitoring well GL-7 at the Former Automotive Services, Inc. (ASI) Site (herein referred to as the Site) (Figures 1 and 2). In 2010, Ecology agreed that the remaining wells were deemed sufficient to monitor the localized area of diesel impacts in groundwater near GL-2 (Ecology, 2014).

AECOM subcontracted with Pacific Soil and Water, Inc., (PSW) a Washington State licensed well driller, to decommission GL-7 on October 8, 2019 following Ecology's well abandonment guidelines outlined in Chapter 173-160 of the Washington Administrative Code (WAC), Minimum Standards for Construction and Maintenance of Wells. AECOM provided oversight for the well abandonment.

The proposed and actual decommissioning methods are listed on the table below.

Well ID		GL-7	
Ground Surface		Gravel/dirt	
Decommissioning Plan	Proposed Method	Decommission in place	
	Decommissioning Date	10/8/2019	
	Actual Method	Decommissioned in place	
	Department of Ecology Notice of Intent for the Decommissioning	AE57246	
	Actual Surface Patching Method	Monument removed and gravel laid down	
	Depth Measured During Decommissioning (feet bgs)	28.5	
Monitoring Well Details	Department of Ecology Notice of Intent for the Installation	R063769	
	Ecology Well Tag	AHE 594	
	Install Date	12/30/2002	
	Install Total Depth (feet bgs)	30.0	
	Diameter (inches)	2	
	Monument Type	Flush	
	Screen Interval (feet bgs)	10 - 30	



PSW decommissioned the well in place by filling the casing from bottom to land surface with bentonite. The Ecology well decommissioning log is attached.

AECOM is pleased to present this letter to Ecology on behalf of the Port. If you have any questions regarding the well decommissioning activities, please contact the undersigned at (971) 323-6324.

Yours sincerely, AECOM

lun

Nicky Moody Project Manager



Attachments:

Figure 1. Vicinity Map Figure 2. Site Map Ecology Resource Protection Well Reports

References:

Ecology, 2014. Letter from Washington State Department of Ecology to Port of Vancouver. *No Further Action for the Former Automotive Services Inc Site.* March 7.

cc: Craig Rankine, RG, LHG, Cleanup Project Manager/Hydrogeologist, Washington Department of Ecology, Toxics Cleanup Program, Vancouver Field Office, 12121 NE 99th Street, Suite 2100, Vancouver, WA 98682, <u>cran461@ecy.wa.gov</u>

Matt Graves, LG, Environmental Manager, Port of Vancouver USA, 3103 NW Lower River Road, Vancouver, WA 98660, <u>mgraves@Portvanusa.com</u>



VICINITY MAP

FORMER AUTOMOTIVE SERVICES, INC. SITE PORT OF VANCOUVER USA 2327 WEST MILL PLAIN BOULEVARD, VANCOUVER, WA

FIGURE 1

1,000

AECOM

0

SCALE IN FEET

1,000

2,000





AECOM

FORMER AUTOMOTIVE SERVICES, INC. SITE PORT OF VANCOUVER USA 2327 WEST MILL PLAIN BOULEVARD, VANCOUVER, WA

FIGURE 2

SITE MAP

Resource Protection Well Report

CURRENT Notice of Intent No. RG3769 (SUBMIT ONE WELL REPORT PER WELL INSTALLED) Type of Well ("x" in circle) Construction/Decommission ("x" in circle) **X** Resource Protection ✗ Construction 0 Geotech Soil Boring Decommission ORGINAL INSTALLATION Notice of Intent Number 126776 Consulting Fum Coles Environmenter Consulting Property Owner Port of Vuncauker Unique Ecology Well ID Sile Address 2327 West Mill Plain AHE 694 Tag No City Vancouver County Clark WELL CONTRUCTION CERTIFICATION I constructed and/or accept for Location SE 1/4 Sec 21 Twn 2N R 1 construction of this well, and it compliance with all Washington construction EWD standards Materials used and the information reported above are true to my WWM bost knowledge and belief HUriller I'ngineer I France Name (Print galey to jeberd (yhit REQUIRED) Lat Deg _____ Lat Mun/Sec _____ Driller/Engineer/Tramee Signature Lat Deg _____ Long Min/Sec _____ Duller or Trainee Lacense No _____2406 Tax Parcel No Nonc If trainec, licensed driller's Cased or Uncased Diameter Static Level Signature and License no. Work/Decommission Start Date 12-30-02 Work/Decommission Completed Date 12-3-02 Well DaRECEIVED Construction/Design Formation Description FFB 0 3 2003 Water-tight cover Surface flush vault DEPARTMENT OF ECOLOGY WELL DRILLING UNIT Locking Cap\Lock 0 ft to 22 ft Vault Silb & Cherrys Casing Diameter ____ m with Sands PUL Material Welded Threaded Glucd 22 ft to 30 ft Well Seal Δ Sand R To 9 From Material Bentonito Amount 46045 ____ ft to _____ ft Drilling Method X Hollow-Stem Auger Air Rotary Mud Rotary ____ Other Borchole diameter _____ ft to _____ ft 8 m Screen Material PUL Interval(s) From 10 To 30 From To 50 Slot Size 100 m _____ ft_to _____ ft. Filter Pack Completed Depth 30

Page _____ of



Submit one well report per well installed. See page ty	port	Notice of Intent No. AE57246		
	vo for instructions.	Type of Well:		
Type of Work:		Resource Protection Well 🔲 Injection Point		
Construction	769	Remediation Well	Grounding Well	
Easlow Wall ID Tax No. AHE 594		Geotechnical Soil	Boring Ground Source Heat Pump	
Ecology well ID Tag No. 7412 004			ring U Other	
Site well Name <u>SL-7</u>		Soil- Vapor	- 🗆 Water-sampling	
Consulting Firm		Property Owner Port of		
Was a variance approved for this well/boring?	🗆 Yes 🔳 No	Well Street Address 2327 West Mill Plain Blvd		
If yes, what was the variance for?		City VancouverCounty Clark		
		Tax Parcel No.		
		Location (see instructio	ns): WWM 🗆 or EWM 🔳	
WELL CONSTRUCTION CERTIFICATION:	I constructed and/or	SE 1/4-1/4 SW 1/4, Section 21 Town 2N Range 1		
Washington well construction standards. Materials used and	d the information	Latitude (Example: 47.12345)		
Priller Trainee Fngineer		Longitude (Example: -120.12345)		
Name (Print Last, First Name) Watson, Colin		(WGS 84 Coordinate System)		
Driller/Engineer/Trainee Signature	2	Borehole diameter inches Casing diameter inches		
License No. 2963	Contract Contract Contract	Static water level 24.8 ft below top of casing Date 10/8/2019		
Company Name Pacific Soil and Water		□ Above-ground completion with bollards □ Flush monument		
If trainee box is checked, sponsor's license num	ber:	Stick-up of top of well casing ft above ground surface		
Sponsor's signature		Start Date 10/8/2019	Completed Date 10/8/2019	
Construction Design	V	Vell Data	Driller's Log	
	2" well, Total dept	h 30'		
Abandon well in place with bentonite to	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		
Abandon well in place with bentonite to surface. Remove monument and concrete. Repair surface.	Screened 10' to 3	0'		