

Underground Storage Tank System Summary

UST ID: 7681

Site Name: CIRCLE K #9660					Glossary		
UST ID:	7681	Facility/Site ID:	64241737	Latitude:	46.98262	Active Tag(s):	A4311
Address:	220 LINCOLN ST			Longitude:	-123.88546	Responsible Unit:	Southwest
	HOQUIAM, WA 98550			County:	Grays Harbor		

Tank Summary		
Tank Name	Tank Status	Tank Install Date
1A	Operational	9/24/2004
2A	Operational	9/24/2004
1	Removed	6/1/1972
2	Removed	6/1/1972
4	Removed	6/1/1972
22	Removed	6/1/1972

Tank Name: 1A		Tank Status: Operational	
Tank Installation:	9/24/2004	Tank Upgrade:	Business License Endorsement Expiration: 2/28/2026
Tank Status Date:	11/30/2004	Piping Installation:	Tank Permanently Closed Date:
Tank Information		Piping Information	
Material:	Fiberglass Reinforced Plastic	Material:	Fiberglass
Construction:	Double Wall Tank	Construction:	Double Wall Pipe
Corrosion Protection:	Corrosion Resistant	Corrosion Protection:	Corrosion Resistant
Manifolded Tank:		SFC* at Tank:	Single Wall Sump
Release Detection:	Interstitial Monitoring	SFC* at Dispenser/Pump:	Single Wall Sump
Tank Manufacturer:		Primary Release Detection:	Automatic Line Leak Detector (ALLD)
Spill Prevention:	Single Wall Spill Bucket	Secondary Release Detection:	Annual Line Tightness Test (LTT)
Overfill Prevention:	Overfill Alarm	Pumping System:	Pressurized System
Actual Capacity:	8,000 Gallons	Piping Manufacturer:	
Capacity Range:	5,000 to 9,999 Gallons	*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Unleaded Gasoline	Motor Fuel for Vehicles	8,000 Gallons

Underground Storage Tank System Summary

UST ID: 7681

Tank Name: 2A		Tank Status: Operational	
Tank Installation:	9/24/2004	Tank Upgrade:	Business License Endorsement Expiration: 2/28/2026
Tank Status Date:	11/30/2004	Piping Installation:	Tank Permanently Closed Date:
Tank Information		Piping Information	
Material:	Fiberglass Reinforced Plastic	Material:	Fiberglass
Construction:	Double Wall Tank	Construction:	Double Wall Pipe
Corrosion Protection:	Corrosion Resistant	Corrosion Protection:	Corrosion Resistant
Manifolded Tank:		SFC* at Tank:	Single Wall Sump
Release Detection:	Interstitial Monitoring	SFC* at Dispenser/Pump:	Single Wall Sump
Tank Manufacturer:		Primary Release Detection:	Automatic Line Leak Detector (ALLD)
Spill Prevention:	Single Wall Spill Bucket	Secondary Release Detection:	Annual Line Tightness Test (LTT)
Overfill Prevention:	Overfill Alarm	Pumping System:	Pressurized System
Actual Capacity:	15,000 Gallons	Piping Manufacturer:	
Capacity Range:	10,000 to 19,999 Gallons	*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Unleaded Gasoline	Motor Fuel for Vehicles	15,000 Gallons

Tank Name: 1		Tank Status: Removed	
Tank Installation:	6/1/1972	Tank Upgrade:	Business License Endorsement Expiration: 2/28/2005
Tank Status Date:	9/8/2004	Piping Installation:	Tank Permanently Closed Date: 2/14/2005
Tank Information		Piping Information	
Material:	Steel	Material:	Fiberglass
Construction:	Single Wall Tank	Construction:	Single Wall Pipe
Corrosion Protection:	Sacrificial Anode	Corrosion Protection:	Corrosion Resistant
Manifolded Tank:		SFC* at Tank:	
Release Detection:	Statistical Inventory Reconciliation	SFC* at Dispenser/Pump:	
Tank Manufacturer:		Primary Release Detection:	Automatic Line Leak Detector (ALLD)
Spill Prevention:	Single Wall Spill Bucket	Secondary Release Detection:	
Overfill Prevention:	Ball Float Valve (vent line)	Pumping System:	Pressurized System
Actual Capacity:	8,000 Gallons	Piping Manufacturer:	
Capacity Range:	5,000 to 9,999 Gallons	*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Unleaded Gasoline	Motor Fuel for Vehicles	8,000 Gallons

Underground Storage Tank System Summary

UST ID: 7681

Tank Name: 2		Tank Status: Removed	
Tank Installation: 6/1/1972	Tank Upgrade: 7/28/1994	Business License Endorsement Expiration: 2/28/2005	
Tank Status Date: 9/8/2004	Piping Installation:	Tank Permanently Closed Date: 2/14/2005	
Tank Information		Piping Information	
Material: Steel		Material: Fiberglass	
Construction: Single Wall Tank		Construction: Single Wall Pipe	
Corrosion Protection: Sacrificial Anode		Corrosion Protection: Corrosion Resistant	
Manifolded Tank:		SFC* at Tank:	
Release Detection: Statistical Inventory Reconciliation		SFC* at Dispenser/Pump:	
Tank Manufacturer:		Primary Release Detection: Automatic Line Leak Detector (ALLD)	
Spill Prevention: Single Wall Spill Bucket		Secondary Release Detection:	
Overfill Prevention: Ball Float Valve (vent line)		Pumping System: Pressurized System	
Actual Capacity: 8,000 Gallons		Piping Manufacturer:	
Capacity Range: 5,000 to 9,999 Gallons		*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Leaded Gasoline	Motor Fuel for Vehicles	8,000 Gallons

Tank Name: 4		Tank Status: Removed	
Tank Installation: 6/1/1972	Tank Upgrade: 7/28/1994	Business License Endorsement Expiration: 2/28/2005	
Tank Status Date: 9/8/2004	Piping Installation:	Tank Permanently Closed Date: 2/14/2005	
Tank Information		Piping Information	
Material: Steel		Material: Fiberglass	
Construction: Single Wall Tank		Construction: Single Wall Pipe	
Corrosion Protection: Sacrificial Anode		Corrosion Protection: Corrosion Resistant	
Manifolded Tank:		SFC* at Tank:	
Release Detection: Statistical Inventory Reconciliation		SFC* at Dispenser/Pump:	
Tank Manufacturer:		Primary Release Detection: Automatic Line Leak Detector (ALLD)	
Spill Prevention: Single Wall Spill Bucket		Secondary Release Detection:	
Overfill Prevention: Ball Float Valve (vent line)		Pumping System: Pressurized System	
Actual Capacity: 6,000 Gallons		Piping Manufacturer:	
Capacity Range: 10,000 to 19,999 Gallons		*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Unleaded Gasoline	Motor Fuel for Vehicles	6,000 Gallons

Underground Storage Tank System Summary

UST ID: 7681

Tank Name: 22		Tank Status: Removed	
Tank Installation: 6/1/1972	Tank Upgrade: 7/28/1994	Business License Endorsement Expiration: 2/28/2005	
Tank Status Date: 9/8/2004	Piping Installation:	Tank Permanently Closed Date: 2/14/2005	
Tank Information		Piping Information	
Material: Steel		Material: Fiberglass	
Construction: Single Wall Tank		Construction: Single Wall Pipe	
Corrosion Protection: Sacrificial Anode		Corrosion Protection: Corrosion Resistant	
Manifolded Tank:		SFC* at Tank:	
Release Detection: Statistical Inventory Reconciliation		SFC* at Dispenser/Pump:	
Tank Manufacturer:		Primary Release Detection: Automatic Line Leak Detector (ALLD)	
Spill Prevention: Single Wall Spill Bucket		Secondary Release Detection:	
Overfill Prevention: Ball Float Valve (vent line)		Pumping System: Pressurized System	
Actual Capacity: 10,000 Gallons		Piping Manufacturer:	
Capacity Range: 10,000 to 19,999 Gallons		*SFC = Steel Flex Connector	
Compartment	Substance Stored	Substance Used	Capacity
1	Unleaded Gasoline	Motor Fuel for Vehicles	10,000 Gallons