

***** Section 1 - IDENTIFICATION*****

Product Identifier:

UP-23 Gen 2

Recommended Use

Various industrial applications. Wood treatment.

Restrictions on Use

Product needs to be kept above 50°F in storage and transportation.

Manufactured for:

Viance, LLC.
8001-IBM Drive
Charlotte, NC 28262

Phone: 704-522-0825
Fax: 704-527-8232
Emergency #: CHEMTREC: (800) 424-9300, 1-703-527-3887 for U.S. and Canadian shipments ONLY

General Comments

NOTE: Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

***** Section 2 - HAZARD(S) IDENTIFICATION*****

Classification in accordance with 29 CFR 1910.1200.

Eye damage/irritation, Category 1
Sensitization - Skin, Category 1A
Skin corrosion/irritation, Category 1C
Carcinogenicity, Category 2
Specific Target Organ Toxicity – Single Exposure (Respiratory), Category 3

GHS LABEL ELEMENTS

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Causes serious eye damage.
May cause an allergic skin reaction.
Causes severe skin burns and eye damage.
Suspected of causing cancer.

May cause respiratory irritation.

Precautionary Statement(s)

Prevention

Wear eye protection/ face protection.
Avoid breathing dust/fume/gas/mist/spray.
Wash exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protective/face protection.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use only outdoors or in a well-ventilated area.

Response

IF ON SKIN: Take off immediately contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation persists: Get medical advice attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified

None

* * * Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS * * *

CAS #	Component	Percent
67784-80-9	Soybean Oil, Methyl Ester	45 - 55
64359-81-5	4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one	20 - 25
Not Available	Polymer	14 -18
104-76-7	2-Ethylhexanol	2.5 - 3.5
64742-94-5	Solvent Naphtha (Petroleum), Heavy Aromatic	4 - 6

Component Information/Information on Non-Hazardous Components

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication), and the criteria specified in the Canadian Workplace Hazardous Materials Information System (WHMIS).

*** Section 4 - FIRST-AID MEASURES ***

Description of Necessary Measures

Inhalation

IF INHALED: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin Contact

IF ON SKIN (or hair): Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing. Seek medical attention if symptoms occur or irritation persists. Wash clothing before reuse. Suitable emergency safety shower facility should be immediately available.

Eye Contact

IF IN EYES: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion

IF SWALLOWED: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: MATERIAL IS SEVERELY IRRITATING. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Maintain adequate ventilation and oxygenation of the patient. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

*** Section 5 - FIRE-FIGHTING MEASURES ***

Suitable Extinguishing Media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. General purpose synthetic foams (including AFFF type) or protein foams are preferred if available. Alcohol resistant foams (ATC type) may function.

Unsuitable Extinguishing Media

No data available.

Specific Hazards Arising from the Chemical

Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous Decomposition Products

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

Special Protective Equipment and Precautions for Firefighters

Keep people away. Isolate fire and deny unnecessary entry. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Fire Fighting Measures

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire-fighting clothing (includes fire-fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

NFPA Ratings: Health: 3 Fire: 1 Reactivity: 0 Other: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe



*** Section 6 - ACCIDENTAL RELEASE MEASURES ***

Personal Precautions, Protective Equipment and Emergency Procedures

Evacuate area. Refer to section 7, Handling, for additional precautionary measures. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spills or discharge to natural waterways is likely to kill aquatic organisms.

Methods and Materials for Containment

Avoid release to the environment. Keep runoff from getting into sewers and waterways

Methods and Materials for Containment and Cleaning Up

Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

*** Section 7 - HANDLING AND STORAGE ***

Precautions for Safe Handling

Do not get in eyes. Do not get on skin or clothing. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Do not swallow. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. Product shipped/handled hot can cause thermal burns. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for Safe Storage, including any Incompatibilities

Product needs to be kept above 50°F in storage and transportation.
Store in a cool, dry, locked, well-ventilated area. Store away from direct sunlight and any sources of heat. Do not freeze. Do not store this material in open or unlabeled containers. See product label for more information.

Incompatibilities

Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Halogens. Metal oxides

*** Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION***

Component Exposure Limits

Exposure limits for this product or the individual components have not been established.

Appropriate Engineering Controls

Whenever possible, engineering controls should be used to minimize the need for personal protective equipment. Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual Protection Measures, such as Personal Protective Equipment

Eyes/Face Protection

Use chemical goggles. When handling hot material: Wear a face-shield which allows use of chemical goggles, or wear a full-face respirator, to protect face and eyes when there is any likelihood of splashes.

Skin Protection

Use gloves chemically resistant to this material. Use gloves with insulation for thermal protection, when needed. Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. When handling hot material, protect skin from thermal burns. Selection of specific items will depend on the operation.

Respiratory Protection

If ventilation is not sufficient to effectively prevent buildup of large quantities of dust or prolonged exposure is possible, appropriate approved NIOSH respiratory protection must be provided. Respirators should be selected by and used under the direction of a trained health and safety professional following the requirements found in OSHA's respirator standard (29 CFR 1901.134) and ANSI's standard for respiratory protection (Z88.2-1992), applicable U.S. regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. A written respiratory protection program, including provisions for medical certification, training, fit-testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage, must be implemented.

PPE Pictograms:



*** Section 9 - PHYSICAL AND CHEMICAL PROPERTIES***

Safety Data Sheet

UP-23 Gen 2

SDS ID: VIA-292

Appearance:	Pale Yellow	Odor:	Mild
Physical State:	Liquid	Odor Threshold:	Not Available
Vapor Pressure:	Not available	pH:	Not available
Vapor Density:	Not available	Specific Gravity:	0.94-0.96
Boiling Point / Boiling Range:	Not available	Evaporation Rate:	Not Available
Melting Point / Freezing Point:	Not available	Relative Density:	Not Available
Solubility (H₂O):	Compatible	Auto-ignition Temperature:	Not available
Flash Point:	>95C	Decomposition Temperature:	Not available
Upper Flammable Limit (UFL):	Not available	Lower Flammable Limit (LFL):	Not available
Viscosity:	Not available	Partition Coefficient (n-octanol / water):	Not available
Flammability (solid, gas):	Not applicable		

*** Section 10 - STABILITY AND REACTIVITY ***

Chemical Stability

This is a stable material under normal conditions of temperature and pressure.

Possibility of Hazardous Reactions

Does not occur.

Conditions to Avoid

Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

Incompatible Materials

Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Halogens. Metal oxides

Hazardous Decomposition Products

Decomposition products depend upon temperature, air supply and the presence of other materials.

*** Section 11 - TOXICOLOGICAL INFORMATION ***

Product Toxicity

Not available

Component Analysis - LD50/LC50

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

Dermal LD50 Rabbit: >2,000 mg/kg

Inhalation LC50 Rat: 4,778 mg/m³ 4 hr (aerosol)

Oral LD50 Rat: >5,000 mg/kg

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Oral LD50 Rat: 1,636 mg/kg

Dermal LD50: >1,000 mg/kg (estimated)

Inhalation LC50 Rat (male and female): 0.26 mg/L 4 hr (dust/mist)

2-Ethylhexanol (104-76-7)

Oral LD50 Rat: 3,290 mg/kg

Inhalation LC50 Rat: 1.2 mg/L 6 hr

Dermal LD50 (Rat): >3,000 mg/kg

Information on Likely Routes of Exposure

Inhalation

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs. May cause central nervous system effects.

Ingestion

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage.

Skin Contact

Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

Eye Contact

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur. Vapor may cause eye irritation experienced as mild discomfort and redness.

Immediate Effects

Serious eye damage and skin irritation.

Delayed Effects

Repeated or prolonged skin contact may result in dermatitis or dermal sensitization.

Medical Conditions Aggravated by Exposure

No data Available.

Irritation/Corrosivity Data

Respiratory tract irritation, skin irritation, eye irritation

Respiratory Sensitization

No data available.

Dermal Sensitization

May cause an allergic skin reaction.

Germ Cell Mutagenicity

No data available.

Carcinogenicity

Component Carcinogenicity

Solvent naphtha (petroleum), heavy aromatic (64742-94-5)

Contains naphthalene (91-20-3) which has caused cancer in some laboratory animals. IARC 1, IARC 2B

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No information available for the product. Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3 – May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure

No information available for the product.

Aspiration Hazard

Not classified as an Aspiration Hazard.

* * * Section 12 - ECOLOGICAL INFORMATION * * *

Ecotoxicity

This product can be harmful to both terrestrial and aquatic plant or animal life.

Component Analysis - Aquatic Toxicity

Polyurethane Resin (Not available)

Not expected to be acutely toxic, but material in pellet or bead form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

Avian: Coilinus virginianus LD50: >2,250 mg/kg; Coilinus virginianus LC50 5 days: >6,500 ppm

Fish: Pimephales promelas LC50 96 hr: 19 mg/L [static]; Oncrhynchus mykiss LC50 96 hr: 2.34 mg/L; Lepomis macrochirus LC50 96 hr: 1,740 mg/L [static]; Pimephales promelas LC50 96 hr: 45 mg/L [flow-through]; Pimephales promelas LC50 96 hr: 4.1 mg/L

Invertabae: Daphnia magna EC50 48 hr: 0.95 mg/L; Daphnia magna (Water Flea) EL50 48 hr: 3 – 10 mg/L [static]

Algae: Pseudokirchneriella subcapitata (green algae) EL50, 72 hr: 11 mg/L

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Fish: Oncrhynchus mykiss (rainbow trout) LC50 96 hr: 0.0027 mg/L [flow-through]; Lepomis macrochirus (bluegill sunfish) LC50 96 hr: 0.014 mg/L [flow-through];

Invertabae: Daphnia magna (Water Flea) EC50 48 hr: 0.0057 mg/L

Algae: Pseudokirchneriella subcapitata (green algae) ErC50, 72 hr: 0.048 mg/L [static]; Pseudokirchneriella subcapitata (green algae) ErC50, 72 hr: 0.077 mg/L [static];

Bacteria: Activated sludge, Respiration rates EC50; 5.70 mg/L.

2-Ethylhexanol (104-76-7)

Fish: Pimephales promelas (Fathead Minnow) LC50 96 hr: 28.2 mg/L

Invertabae: Daphnia magna (Water flea) EC50 48 hr: 39 mg/L; Daphnia magna (Water Flea) Chronic 21 d: 7.5 ug/L

Persistence and Degradability

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 39 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Considered to be rapidly degradable.

Biodegradation (Aquatic metabolism) CAS # 64359-81-5 t 1/2 anaerobic = < 1hr. CAS #

64359-81-5 t 1/2 aerobic = < 1hr.

Bioaccumulation Potential

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 2.9 - 6.1 Measured

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Partition coefficient: n-octanol/water(log Pow): 2.8 Measured

Bioconcentration factor (BCF): < 13 Fish

Mobility in Soil

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

No relevant data found.

4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one (64359-81-5)

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): 5662 - 7865 Measured

*** Section 13 - DISPOSAL CONSIDERATIONS***

Disposal Methods

Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

Disposal of Contaminated Packaging

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components. Dispose of material according to Local, State, Federal, and Provincial Environmental Regulations.

*** Section 14 - TRANSPORT INFORMATION***

US DOT Information

Shipping Name: Corrosive liquids, n.o.s. (4,5-Dichloro-2-n-octyl-4-isothiazolin-3-on)

UN/NA #: UN1760

Hazard Class: 8 **Packing Group:** III

Emergency Response Guide #: 154



Canada Transportation of Dangerous Goods Information

Shipping Name: Corrosive liquid, n.o.s. (4,5-Dichloro-2-n-octyl-4-isothiazolin-3-on)

UN/NA #: UN1760

Hazard Class: 8 **Packing Group:** III



IMDG

Shipping Name: Corrosive liquids, n.o.s. (4,5-Dichloro-2-n-octyl-4-isothiazolin-3-on)

UN/NA #: UN1760

Hazard Class: 8 **Packing Group:** III

EMS Guide #: F-A, S-B

Marine pollutant: Solvent naphtha (petroleum), heavy aromatic, 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one



*** Section 15 - REGULATORY INFORMATION***

U.S. Federal Regulations

This material does not contain chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4). SARA Section 312 (Tier II) may be applicable depending on onsite storage quantities.

SARA 311/312

Acute Health: Yes **Chronic Health:** No **Fire:** No **Pressure:** No **Reactive:** No

Federal Insecticide, Fungicide, and Rodenticide Act

This material contains the following chemicals present on either the Listing of Pesticide Chemicals (40 CFR 180) or Pesticides Classified for Restricted Use as listed by FIFRA:

Solvent naptha (petroleum), heavy aromatic (64742-94-5)

FIFRA Section number 180.910

Component Marine Pollutants

This material does not contain chemicals required by US DOT to be identified as marine pollutants.

U.S. State Regulations

State Regulations

Other state regulations may apply. Check individual state requirements.

Component Analysis – State

Component	CAS	CA	MA	MN	NJ	PA	RI
Solvent naptha (petroleum), heavy aromatic	64742-94-5	No	No	No	No	No	No
4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one	64359-81-5	No	No	No	No	No	No
2-Ethylhexanol	104-76-7	No	No	No	No	No	No

Component Analysis - WHMIS IDL

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List (IDL). The List is composed of chemicals which must be identified on MSDSs if they are included in products which fall under WHMIS criteria specified in the Controlled Products Regulations and present above the threshold limits listed on the IDL. This product does not contain components listed on the IDL.

WHMIS Classification:

D2A – Very Toxic Material at $\geq 0.1\%$ (Carcinogenicity)

D2B – Very Toxic Material at $\geq 1\%$ (Skin Sensitization, Skin/Eye Irritation)

Component Analysis - Inventory

Component	CAS #	TSCA	DSL	EINECS	AU	MX	JP	PH	KR	CH
Solvent naptha (petroleum), heavy aromatic	64742-94-5	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one	64359-81-5	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
2-Ethylhexanol	104-76-7	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

* * * Section 16 - OTHER INFORMATION * * *

Summary of Changes

New SDS: 09/14/2020 v.1.0;

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; **AU** - Australia; **BOD** - Biochemical Oxygen Demand; **C** - Celsius; **CA** - Canada; **CAS** - Chemical Abstracts Service; **CERCLA** - Comprehensive

Environmental Response, Compensation, and Liability Act; **CFR** - Code of Federal Regulations; **CN** - China; **CNS** - Central Nervous System; **CPR** - Controlled Products Regulations; **cSt** - Centistokes; **DOT** - Department of Transportation; **DSL** - Domestic Substances List; **EbC50** - Acute Endpoint - the concentration of a test substance which results in a 50 percent reduction in biomass growth; **EINECS** - European Inventory of Existing Commercial Chemical Substances; **ELINCS** - European List of Notified Chemical Substances; **EPA** - Environmental Protection Agency; **ERG** - Emergency Response Guide; **ErC50** - EC50 (lethal concentration) in terms of reduction of growth weight; **EU** - European Union; **F** - Fahrenheit; **HEPA** - High Efficiency Particulate Air; **HMIS** - Hazardous Material Information System; **HPV** - High Production Volume Chemical (EU); **IARC** - International Agency for Research on Cancer; **IATA** - International Air Transport Association; **ICL** - In Commerce List (Canada); **IDL** - Ingredient Disclosure List; **IDLH** - Immediately Dangerous to Life and Health; **IMDG** - International Maritime Dangerous Goods; **JP** - Japan; **KR** - Korea; **LL** - Lethal Loading; **LLNA** - Local Lymph Node Assay; **LEL** - Lower Explosive Limit; **LMPE-CT** - Short term exposure limit; **LMPE-PPT** - Límite Máximo Permisible de Exposición Promedio Ponderado en el Tiempo (Mexico TWA equivalent); **MITI** - Japan Ministry of International Trade and Industry; **mg/Kg** - milligrams per Kilogram; **mg/L** - milligrams per Liter; **mg/m³** - milligrams per Cubic Meter; **MSHA** - Mine Safety and Health Administration; **MX** - Mexico; **NA** - Not Applicable or Not Available; **NFPA** - National Fire Protection Association; **NIOSH** - National Institute for Occupational Safety and Health; **NJTSP** - New Jersey Trade Secret Registry; **NTP** - National Toxicology Program; **NZ** - New Zealand; **OSHA** - Occupational Safety and Health Administration; **PH** - Philippines; **RCRA** - Resource Conservation & Recovery Act; **SARA** - Superfund Amendments and Reauthorization Act; **STEL** - Short Term Exposure Limit; **STEV** - Short-term Exposure Values; **TDG** - Transport Dangerous Goods; **TSCA** - Toxic Substances Control Act; **TWA** - Time Weighted Average; **TWAEV** - Time Weighted Average Exposure Values; **UEL** - Upper Explosive Limit; **US** - United States; **VLE-CT** - Short term exposure limit value; **VLE-PPT** - Time weighted average limit value; **WHMIS** - Workplace Hazardous Materials Information System

Other Information

Disclaimer: Supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Read the Material Safety Data Sheet before handling product.

End of Sheet VIA-292