

## APPENDIX 6 – Street Waste Disposal

### Street Waste Liquids General Procedures

**Street waste collection should emphasize retention of solids in preference to liquids.** Street waste solids are the principal objective in street waste collection and are substantially easier to store and treat than liquids.

**Street waste liquids require treatment before their discharge.** Street waste liquids, which include, but are not limited to, eductor and street sweeping truck decant and drainage from piles and containers, usually contain high amounts of suspended and total solids, and absorbed metals. Treatment requirements depend on the discharge location.

**Discharges to sanitary sewer and storm sewer systems must be approved by the entity responsible for operation and maintenance of the system.** Ecology will not generally require waste discharge permits for discharge of stormwater decant to sanitary sewers or to stormwater treatment BMPs constructed and maintained in accordance with Ecology's *Stormwater Management Manual for Western Washington*.

The following order of preference, for disposal of catch basin decant liquid and water removed from stormwater treatment facilities, is **required**.

**1. Discharge of street waste decant liquids to a municipal sanitary sewer connected to a Public Owned Treatment Works (POTW) is the preferred disposal option.** Discharge to a municipal sanitary sewer requires the approval of the sewer authority. Approvals for discharge to a POTW will likely contain pretreatment, quantity, and location conditions to protect the POTW.

**2. Discharge of street waste decant liquids may be allowed into a Basic or Enhanced Stormwater Treatment BMP, if option 1 is not available.** Street waste liquid may be discharged back into the storm sewer system under the following conditions only:

- The preferred disposal option of discharge to sanitary sewer is not reasonably available, **and**
- The discharge is to a Basic or Enhanced Stormwater Treatment Facility. If pretreatment does not remove visible sheen from oils, the treatment facility must be able to prevent the discharge of oils causing a visible sheen, **and**
- The discharge from the educator truck is as near to the inlet of the treatment facility as is practical, to minimize contamination or recontamination of the collection system, **and**
- The storm sewer system owner/operator has granted approval and has determined that the stormwater treatment facility will accommodate the increased loading. Pretreatment conditions to protect the stormwater treatment BMP may be issued as part of the approval process. Following local pretreatment conditions is a requirement of this Permit.

- Flocculants for the pretreatment of street waste liquids must be non-toxic under the circumstances of use and must be approved in advance by the Department of Ecology.

The reasonable availability of sanitary sewer discharge will be determined by the Permittee, by evaluating such factors as distance, time of travel, load restrictions, and capacity of the stormwater treatment facility.

**3. Water removed from stormwater ponds, vaults and oversized catch basins may be returned to the storm sewer system.** Stormwater ponds, vaults, and oversized catch basins contain substantial amounts of liquid, which hampers the collection of solids and pose problems if the removed waste must be hauled away from the site. Water removed from these facilities may be discharged back into the pond, vault, or catch basin provided:

- Clear water removed from a stormwater treatment structure may be discharged directly to a down gradient cell of a treatment pond or into the storm sewer system.
- Turbid water may be discharged back into the structure it was removed from if:
  - The removed water has been stored in a clean container (eductor truck, Baker tank or other appropriate container or facility used specifically for handling stormwater or clean water); **and**
  - There will be no discharge from the treatment structure for at least 24 hours.
- The discharge must be approved by the storm sewer system owner/operator.

### Street Waste Solids

Soils generated from maintenance of the MS4 may be reclaimed, recycled or reused when allowed by local codes and ordinances. Soils that are identified as contaminated, pursuant to Chapter 173-350 WAC, shall be disposed of at a qualified solid waste disposal facility.